

FAMILY OF RECORDERS

IMUX RE/CON™

RECORD, CONVERT, AND PLAYBACK STREAMING TELEMETRY OVER INTERNET PROTOCOL

Parraid's IMUX RE/CON Telemetry Network Recorder leverages over 30 years of telemetry recording and processing experience and provides network recording capability with key features tailored to the needs of the airborne telemetry market. IMUX RE/CON is designed to not only record streaming network telemetry but will also provide on-the-fly conversion of incoming TMoIP streams to a Chapter 10 format. The intuitive software interface is designed specifically for telemetry users and offers features such as automatic telemetry format detection, snapshot viewer, video stream viewer, and descriptive TMoIP channel naming.



IMUX G2e™

THE INDUSTRY STANDARD OF CH10 RECORDERS

The IMUX G2e offers powerful capabilities, including support for all industry-standard telemetry signal types, the ability to record two Chapter 10 files simultaneously—local and/or remote—simultaneous playback, and on-the-fly channel adjustment. Units can be equipped with optional integrated RF receivers, bit synchronizers, best source selection, and real-time decom, processing, and display capabilities. The IMUX G2e can be configured as a rack mount or portable unit, with rack mount options including a compact 2U chassis for up to 4 channels and a robust 4U chassis for up to 24 channels. Touch screen and ruggedized systems for mobile applications, as well as transport cases, are available.



IMUX G2eHYBRID (G2eH™)

DIRECTLY INPUT TMoIP CHANNELS

The IMUX G2e-Hybrid (G2eH) builds on the powerful features of the G2e with the added capability to input TMoIP channels (218-20 or CH10/11 UDP) directly into the recorder. It can record all channels—both TMoIP inputs and PCM signal inputs—in IRIG 106 Chapter 11 PCM format. The G2eH dynamically converts TMoIP 218-20 inputs to Chapter 10 packets while recording, enabling the output of baseband PCM data and clock from the recorded Chapter 10 file. These files are fully compatible with any Chapter 10/11-compliant tool set for processing and analysis, providing a single-box solution to record and reproduce both legacy and modern channel types together.

