School of Computing and Information Systems The University of Melbourne

COMP90042 NATURAL LANGUAGE PROCESSING (Semester 1, 2021)

Workshop exercises: Week 10

Discussion

- 1. What aspects of human language make automatic translation difficult?
- 2. What is **Information Extraction**? What might the "extracted" information look like?
 - (a) What is **Named Entity Recognition** and why is it difficult? What might make it more difficult for persons rather than places, and *vice versa*?
 - (b) What is the **IOB** trick, in a sequence labelling context? Why is it important?
 - (c) What is **Relation Extraction**? How is it similar to NER, and how is it different?
 - (d) Why are hand-written patterns generally inadequate for IE, and what other approaches can we take?

Programming

- 1. In the iPython notebook 11-machine-translation, we provide an example of an encoder-decoder model for machine translation. Just like workshop-07, we'll use colab to run the notebook, as we'll need a GPU to speed up the training. Please refer to workshop-07 if you are looking for instructions to get set up for colab.
 - Modify the code to use GRU instead of LSTM, noting that GRU does not have a memory state (state_c).
 - Modify the code to do translation at the word-level instead of character-level. This will involve:
 - Using a French and English tokeniser (e.g. spaCy);
 - Creating a vocabulary for the input source and target language;
 - Replacing low frequency words with a special UNK token;
 - Changing the corpus reading function to create sequences of words for the training data;
 - Updating the training model and inference model to use the word vocabulary to look up words.

Get ahead

• Extend the encoder-decoder model in 11-machine-translation to incorporate attention mechanism. You can use the formulation described in the lecture: dot product for comparing encoder and decoder hidden states; and concatenating the "context vector" with the decoder hidden state to predict the target word.