

AWS EKS Provisioning using Pulumi

Prerequisites

1. An AWS account with an IAM user having sufficient permissions.
 2. AWS CLI installed and configured with the IAM user.
 3. Pulumi Installed.
 4. Kubectl Installed.
-

Steps

1. Create a Pulumi Project directory.
2. Open the PowerShell.
3. Change the directory to the above-created Pulumi Project.
4. Run the `pulumi new aws-python` command to initialize the *pulumi*.
5. Provide the appropriate values to prompts such as *project-name*, *project-description*, *stack-name*, *toolchain*, *region-name*, etc.
6. This will generate some Pulumi files in this directory.
7. Now we will install predefined Pulumi modules.
8. Activate the *venv* by running `venv\Scripts\activate`.
9. Run `pip install git+https://github.com/sahilphule/pulumi.git` to install the modules.
10. Deactivate the *venv* by running `deactivate`.
11. Now open the directory in the preferred IDE.
12. Create *commons* folder
13. Inside the folder create *init.py* file.
14. Import the following in the *init.py* file:
 - `from inflection_zone_pulumi.modules.aws.vpc import vpc`
 - `from inflection_zone_pulumi.modules.aws.rds import rds`
 - `from inflection_zone_pulumi.modules.aws.eks import eks`
15. Click [code](#) for reference.
16. Definition of *init.py* is complete.
17. Now create the *values.py* file in the root folder of the above-created project directory.
18. Define the following values:
 - `vpc_properties`
 - `rds_properties`
 - `bastion_properties`
 - `eks_properties`
19. Click [code](#) for reference.
20. The definition of *values.py* is complete.
21. Now navigate to the *main.py* file present in the root folder of the above-created project directory.
22. Clear the sample code if present.
23. Import the following:
 - `from commons import vpc, rds, eks`
 - `values`

- 24. Define the following objects and pass the values as an argument:
 - VPC
 - RDS
 - EKS
- 25. Click [code](#) for reference.
- 26. Definition of *main.py* is complete.

Provisioning the Infrastructure

Now we will provision the infrastructure by applying the above-created configuration files.


Ensure AWS CLI is configured with appropriate IAM user credentials and enough permissions.

Steps:


- 1. Open the PowerShell.
- 2. Change the directory to the above-created Pulumi Project.
- 3. Run the `pulumi up` command and if prompted, select `yes` to provision the infrastructure onto the AWS Cloud.
- 4. Head to the AWS Console, and verify the created resources.

Screenshots of Provisioned Infrastructure


VPC Image



RDS Image



EKS Cluster Image



EKS Node Group Image

aws

Services

Search

[Alt+S]

Mumbai

Console Home

Billing and Cost Management

IAM

S3

VPC

RDS

EC2

Elastic Container Registry

Elastic Container Service

Elastic Kubernetes Service

CloudWatch

26, 2025

Overview

Resources

Compute

Networking

Add-ons

Access

Observability

Upgrade insights

Update history

Tags

Nodes (1)

Info

Filter Nodes by property or value

< 1 >

Node name	Instance type	Node group	Created	Status
ip-10-0-1-90.ap-south-1.compute.internal	t2.medium	eks-node-group	Created 3 minutes ago	Ready

Node groups (1)

Info

Edit

Delete

Add node group

Group name	Desired size	AMI release version	Launch template	Status
eks-node-group	1	1.31.0-20241011	-	Active

CloudShell

Feedback

© 2024, Amazon Web Services, Inc. or its affiliates.

Privacy

Terms

Cookie preferences

EKS Nodes Image

aws

Services

Search

[Alt+S]

Mumbai

Console Home

Billing and Cost Management

IAM

S3

VPC

RDS

EC2

Elastic Container Registry

Elastic Container Service

Elastic Kubernetes Service

CloudWatch

Instances (3)

Info

Last updated less than a minute ago

Connect

Instance state

Actions

Launch instances

Find Instance by attribute or tag (case-sensitive)

All states

< 1 >

	Name	Instance ID	Instance state	Instance type	Status check	Alarm status	Availability Zone	Public
<input type="checkbox"/>	ip-10-0-1-90.ap-south-1.compute.internal	i-0152ea65dfc7a636b	Running	t2.micro	2/2 checks passed	View alarms	ap-south-1a	ec2-65
<input type="checkbox"/>	ip-10-0-1-90.ap-south-1.compute.internal	i-0155c8899e2a2cbe4	Running	t2.medium	2/2 checks passed	View alarms	ap-south-1a	ec2-13
<input type="checkbox"/>	ip-10-0-1-90.ap-south-1.compute.internal	i-09e5f3610f8adc35f	Running	t2.medium	2/2 checks passed	View alarms	ap-south-1b	ec2-13

Select an instance

CloudShell

Feedback

© 2024, Amazon Web Services, Inc. or its affiliates.

Privacy

Terms

Cookie preferences

Connect to EKS Cluster from Powershell


1. Open a new Powershell window.
 2. Run the following command to configure local kubectl with eks cluster
`aws eks --region "region-name" update-kubeconfig --name "cluster-name"`
Substitute *region-name* and *cluster-name* with the values defined in the above-created locals.tf file.
 3. Now, apply the Kubernetes manifest files for the application.
 4. To list them all, run `kubectl get all`.
-

Connect to the RDS database through Bastion Host


1. Open MySQL Workbench.
 2. Click Add Connection.
 3. Select connection method as **Standard TCP/IP over SSH**.
 4. In SSH Hostname, enter *bastion-host-ip:22* where *bastion-host-ip* is received from `pulumi stack output bastion-host-ip` command.
 5. In SSH Username, enter *ec2-user*.
 6. In SSH Key File, select *bastion-key.pem* file passed in above *values.py* file from your local computer.
 7. In MySQL Hostname, enter *DB_HOST* where *DB_HOST* is received from `pulumi stack output DB_HOST`.
 8. In the Password section, select *Store in Vault*, and enter the password passed in above-created *values.py* file.
 9. Click *OK* and open the connection.
 10. Now you can run MySQL commands to access databases and verify the successful connection of *eks-nodes*.
-

Screenshots of MySQL Workbench

Connection Page



Commands Page



Destroy the provisioned infrastructure

1. First, delete all the Kubernetes Deployments.
 2. To destroy infrastructure, change the directory to the above-created Pulumi Project.
 3. Run **pulumi destroy** & if prompted, select **yes**.
 4. Infrastructure will be destroyed.
-