



**INERTIA BASE**

N.T.S.




**PIPE PENETRATION SMOKE WALL**

N.T.S.




**PIPE PENETRATION THROUGH FIRE RATED SLAB**

N.T.S.




**PLINTH**

N.T.S.



**INERTIA BASE**


MIN. WEIGHT = 1.5 x EQUIPMENT WEIGHT




**PLINTH**

**PLINTH DETAILS**

N.T.S.




**FORMED PENETRATIONS**




**DRILLED PENETRATIONS**

**PIPE PENETRATING THROUGH SLAB**

N.T.S.



**INSULATED PIPE HANGER DETAIL**



**UN-INSULATED PIPE HANGER DETAIL**

**VIEW A**

**NOTES:**

- CLAMP SIZES PIPES UP TO:  
75mm - 50mm x 8mm  
100mm - 65mm x 10mm  
150mm - 75mm x 10mm
- SPRING ISOLATORS REQUIRED ON HANGERS IN PLANT ROOMS. THEY ARE TO INCORPORATE RUBBER ISOLATORS AS WELL AT THE TOPS AND BOTTOMS OF RISERS WITH A CENTRE ANCHOR. THEY ARE TO BE OF THE CONSTANT SUPPORT TYPE.
- FOR COLD PIPES, SECTIONS OF VAPOUR SEAL MATERIAL ARE TO BE INSTALLED BETWEEN CLAMP AND SPACER BLOCK.

**PIPE HANGER**

N.T.S.

DRG No.

STANDARD DETAILS  
SHEET 3 OF 3

STATUS:

SHEET

(C)

METRO DRG No.

REV.