

EC2X&AG35-QuecOpen

USB Suspend User

Guide

LTE Module Series

Rev. EC2X&AG35-QuecOpen_USB_Suspend_User_Guide

Date: 2018-03-21

Status: Preliminary



Our aim is to provide customers with timely and comprehensive service. For any assistance, please contact our company headquarters:

Quectel Wireless Solutions Co., Ltd.

7th Floor, Hongye Building, No.1801 Hongmei Road, Xuhui District, Shanghai 200233, China

Tel: +86 21 5108 6236

Email: info@quectel.com

Or our local office. For more information, please visit:

<http://quectel.com/support/sales.htm>

For technical support, or to report documentation errors, please visit:

<http://quectel.com/support/technical.htm>

Or email to: support@quectel.com

GENERAL NOTES

QUECTEL OFFERS THE INFORMATION AS A SERVICE TO ITS CUSTOMERS. THE INFORMATION PROVIDED IS BASED UPON CUSTOMERS' REQUIREMENTS. QUECTEL MAKES EVERY EFFORT TO ENSURE THE QUALITY OF THE INFORMATION IT MAKES AVAILABLE. QUECTEL DOES NOT MAKE ANY WARRANTY AS TO THE INFORMATION CONTAINED HEREIN, AND DOES NOT ACCEPT ANY LIABILITY FOR ANY INJURY, LOSS OR DAMAGE OF ANY KIND INCURRED BY USE OF OR RELIANCE UPON THE INFORMATION. ALL INFORMATION SUPPLIED HEREIN IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

COPYRIGHT

THE INFORMATION CONTAINED HERE IS PROPRIETARY TECHNICAL INFORMATION OF QUECTEL WIRELESS SOLUTIONS CO., LTD. TRANSMITTING, REPRODUCTION, DISSEMINATION AND EDITING OF THIS DOCUMENT AS WELL AS UTILIZATION OF THE CONTENT ARE FORBIDDEN WITHOUT PERMISSION. OFFENDERS WILL BE HELD LIABLE FOR PAYMENT OF DAMAGES. ALL RIGHTS ARE RESERVED IN THE EVENT OF A PATENT GRANT OR REGISTRATION OF A UTILITY MODEL OR DESIGN.

Copyright © Quectel Wireless Solutions Co., Ltd. 2018. All rights reserved.

About the Document

History

Revision	Date	Author	Description
1.0	2018-03-21	Gale GAO	Initial

Quectel
Confidential

Contents

	About the Document	2
	Contents	3
	Introduction	4
	USB Suspend Influence Factor	5
	Usb Suspend Feature Testing	6
1	Host Information	6
2	Host Check 4G Module	6
3	Host Informs Module to Go Sleep and Wakeup	7
3.1.	3.3.1. Host inform Module to Go Sleep	7
3.2.	3.3.2. Host inform Module to Wakeup	8
3.3.	Bothway Sleep and Wakeup	8
3.4.	Case	9
3.5.		

Introduction

1 This document introduces the usb suspend function between Quectel module and host which can be another solution for sleep/wakeup. But limitation is some hosts don't support usb suspend which due to operation system kernel version, usb controller and other reasons.

Quectel
Confidential

USB Suspend Influence Factor

2 QuecOpen EC2X&AG35 project enable adb debug mode by default, but usb cannot enter into low power mode causes module cannot go sleep. If users confirm usb suspend feature is required, please close adb and refer to ***QuecOpen_EC2X&AG35_Close_Default_ADB_User_Guide***.

Some hosts don't support usb suspend which due to operation system kernel version, usb controller and other reasons. Specific equipment hardware, software model is not currently doing exact statistics.

Quectel
Confidential

Usb Suspend Feature Testing

Please disable adb feature according to Chapter 2.

3

Host Information

Intel Sandybridge, Ubuntu 14.04, support usb suspend.

3.1.



3.2.

Host Check 4G Module

Through dmesg check find that when 4G module plug in host, registered usb node is 1-1.3, then enter this node.

```
1068748.967934] usb 1-1.3: new high-speed USB device number 100 using ehci-pci
1068749.069949] usb 1-1.3: New USB device found, idVendor=2c7c, idProduct=0125
1068749.069954] usb 1-1.3: New USB device strings: Mfr=1, Product=2, SerialNumber=0
1068749.069957] usb 1-1.3: Product: Android
1068749.069960] usb 1-1.3: Manufacturer: Android
1068749.071104] option 1-1.3:1.0: GSM modem (1-port) converter detected
1068749.071255] usb 1-1.3: GSM modem (1-port) converter now attached to ttyUSB1
1068749.071347] option 1-1.3:1.1: GSM modem (1-port) converter detected
1068749.071437] usb 1-1.3: GSM modem (1-port) converter now attached to ttyUSB2
1068749.071536] option 1-1.3:1.2: GSM modem (1-port) converter detected
1068749.071629] usb 1-1.3: GSM modem (1-port) converter now attached to ttyUSB3
1068749.071712] option 1-1.3:1.3: GSM modem (1-port) converter detected
1068749.071811] usb 1-1.3: GSM modem (1-port) converter now attached to ttyUSB4
1068749.073154] GobiNet 1-1.3:1.4 eth1: register 'GobiNet' at usb-0000:00:1a.0-1.3, Gobi
1068749.075024] creating qcqmi1
oot@roddick-OptiPlex-790:/sys/bus/usb/devices/1-1/1-1.3/power#
```

Host Informs Module to Go Sleep and Wakeup

3.3.3.1. Host inform Module to Go Sleep

Module Terminal:

Module enables autosleep mechanism through API or command line first.

echo mem > /sys/power/autosleep

In order to facilitate debugging, here open the log output:

echo 1 > /sys/module/printk/parameters/perf_mode_console

```
root@mdm9607-perf:~#
root@mdm9607-perf:~# echo 1 > /sys/module/printk/parameters/perf_mode_console
root@mdm9607-perf:~# echo mem > /sys/power/autosleep
root@mdm9607-perf:~#
root@mdm9607-perf:~# [ 82.167304] gser_suspend: Un-supported transport: TTY
[ 82.171415] msm_otg 78d9000.usb: Avail curr from USB = 2
[ 82.176679] msm_hsusb msm_hsusb: CI13XXX_CONTROLLER_SUSPEND_EVENT received
[ 82.183872] android_work: android_work: sent uevent USB_STATE=SUSPENDED
[ 83.188985] PM: suspend entry 2018-03-20 16:07:49.259793253 UTC
[ 83.194077] msm_otg 78d9000.usb: USB in low power mode
[ 83.199114] PM: Syncing filesystems ... done.
[ 83.226391] Freezing user space processes ...
[ 83.231550] Error: returning -512 value
[ 83.238220] mbim_read: Waiting failed
[ 83.255539] (elapsed 0.025 seconds) done.
[ 83.258530] Freezing remaining freezable tasks ... (elapsed 0.002 seconds) done.
[ 83.268083] Suspending console(s) (use no_console_suspend to debug)
```

Host Terminal:

Inform module to allow suspend: echo auto > level

3ms bus will always be idle, then usb device go sleep.


```
root@roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power# ls
active_duration      connected_duration  runtime_active_kids  runtime_suspend
async                control             runtime_active_time  runtime_usage
autosuspend          level              runtime_enabled      wakeup
autosuspend_delay_ms persist             runtime_status       wakeup_abort_co
root@roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power# echo auto > level
root@roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power#
```

3.3.2. Host inform Module to Wakeup

Host Terminal:

Wakeup module, release usb bus suspend state. echo on > level

```
root@roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power# echo auto > level
root@roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power# echo on > level
root@roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power#
```

At this time, module will wake up and hold wakelock.

```
4,1069,6614093872,-;Resume: sysfs_notify wakeup_in
6,1070,6614117033,-;msm_hsusb msm_hsusb: CI13XXX_CONTROLLER_RESUME_EVENT received
SUBSYSTEM=platform
DEVICE=+platform:msm_hsusb
3,1071,6614117139,-;gser_resume: Un-supported transport: TTY
6,1072,6614117217,-;msm_otg 78d9000.usb: Avail curr from USB = 500
SUBSYSTEM=platform
DEVICE=+platform:78d9000.usb
6,1073,6614117471,-;android_work: android_work: sent uevent USB_STATE=RESUMED
6,1074,6614157849,-;PM: resume of devices complete after 74.639 msecs
4,1075,6614159113,-;Restarting tasks ... done.
6,1076,6614168861,-;PM: suspend exit 2017-12-07 09:33:30.736907077 UTC
4,1075,6614159113,-;Restarting tasks ... done.
6,1076,6614168861,-;PM: suspend exit 2017-12-07 09:33:30.736907077 UTC
```

```
root@mdm9607-perf:~#
root@mdm9607-perf:~#
root@mdm9607-perf:~# awk '$6 != 0 {print $1" "$6}' /sys/kernel/debug/wakeup_sou
rces
name active_since
msm_otg 24504
root@mdm9607-perf:~#
```

3.4.

Bothway Sleep and Wakeup

Module also can wakeup host. Configure host to echo enabled > wakeup, when host is in sleep mode, module can wake up host by sending data to bus.

- (1) Enable host remote wakeup function: echo enabled > wakeup

```
root@roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power# cat wakeup
disabled
root@roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power# echo enabled > wakeup
root@roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power#
root@roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power# cat wakeup
enabled
root@roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power#
```

- (2) Host go sleep mode: echo mem > /sys/power/state

```
roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power#
roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power# echo mem > /sys/power/state
roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power#
roddick-OptiPlex-790:/sys/bus/usb/devices/1-1.3/power#
```

- (3) Module terminal send data to bus to wake up host. (/dev/ttyGS0 are usb virtual device)

```
root@mdm9607-perf:~#
root@mdm9607-perf:~# echo df > /dev/ttyGS0
root@mdm9607-perf:~# [ 518.945679] msm_hsusb msm_hsusb: CI13XXX_CONTROLLER_RESUME_EVENT received
[ 518.951545] gser_resume: Un-supported transport: TTY
[ 518.956450] msm_otg 78d9000.usb: Avail curr from USB = 500
[ 518.962361] android_work: android_work: sent uevent USB_STATE=RESUMED
[ 523.310237] gser_suspend: Un-supported transport: TTY
[ 523.314336] msm_otg 78d9000.usb: Avail curr from USB = 2
[ 523.319601] msm_hsusb msm_hsusb: CI13XXX_CONTROLLER_SUSPEND_EVENT received
[ 523.326654] android_work: android_work: sent uevent USB_STATE=SUSPENDED
[ 525.009555] PM: suspend entry 2018-03-20 16:38:00.156767503 UTC
[ 525.014657] msm_otg 78d9000.usb: USB in low power mode
[ 525.019679] PM: Syncing filesystems ... done.
[ 525.047138] Freezing user space processes ...
[ 525.052806] Error: returning -512 value
[ 525.059583] mbim_read: Waiting failed
[ 525.064669] (elapsed 0.013 seconds) done.
[ 525.067662] Freezing remaining freezable tasks ... (elapsed 0.002 seconds) done.
[ 525.076978] Suspending console(s) (use no console suspend to debug)
```

Case

- 3.5.
- (1) Enable module autosleep:
echo mem > /sys/power/autosleep
 - (2) Host informs module prepare to go sleep, and set module remote waking-up host, meantime host go sleep mode.
echo auto > level
echo enabled > wakeup
echo mem > /sys/power/state
 - (3) Then through call, SMS, IP data can wakeup module; app code execute wakelock and send data to usb bus to wake up host.