

CREED TA GREY+

Ultra grade tile adhesive

CREED TA GREY+ is a cement-based adhesive that is modified with high-polymer materials. It is designed for fixing large-format marble, granite, and natural stones on walls and floors in both interior and exterior situations, including swimming pools.

SPECIFICATION

Pot Life	: 2.5 - 3 Hrs
Setting Time	: 24 Hrs
Compressive Strength	: 12N/mm ²
Curing Time	: 10 min

KEY FEATURES

Excellent waterproofing and spreadability characteristic
Good slip resistance
High bond strength with no- shrinkage

Area of Use:-

- This adhesive is suitable for fixing poorly absorbent or non-absorbent materials such as single-fired tiles, split tiles, and refined porcelain stoneware.
- It can be used for outdoor and indoor use on walls and floors.
- It is also suitable for fixing absorbent tiles made of cotto, twice-fired, and single-fired ceramic.
- This adhesive is ideal for high-performance requirements, such as tile fixing in industrial environments, fixing on top of old ceramic tiles, in swimming pools, or on facades.
- It can also be used for spot-gluing insulating panels made of polystyrene, polyurethane foam, rock, or glass wool.
- This adhesive is suitable for fixing natural stone and marble, as long as they are not affected by water.
- It is suitable for tiles and stones weighing less than 60 kg/m². It is also suitable for fixing on heating floors.

APPLICATION



Virtified Tile



Granite



Large formal tile



Marble

AMOUNT REQUIRED:-

TROWEL	8X8 mm	10x10 mm	15 mm
CREED TA GREY+	3 kg/m ²	4 kg/m ²	5 kg/m ²

HOW TO APPLY :-

- CREED TA GREY+ is a non-toxic adhesive that can be used for fixing large format tiles on walls and floors.
- To apply the adhesive, spread it on the surface not more than 2 sq.m. at a time, and then apply it to the wall or floor surface.
- If the thickness of the adhesive is more than 8 mm, apply 50% thickness on tiles and the balance on the wall. The thickness on the wall should not exceed 8 mm.
- To fix the tiles, comb the adhesive to the required depth (between 3 - 6 mm) using a suitable trowel.
- Press the marble firmly into position with a slight twisting action, checking periodically that good contact is maintained with the back of each tile.
- Leave no voids behind tiles when solid-bed fixing.
- Tiles should be fixed within 20 minutes of adhesive being applied, depending on the porosity of the surface and atmospheric conditions.
- Tiles can be adjusted up to 10 - 15 minutes after fixing.
- Touch the adhesive ribs periodically, and if a skin has formed, remove the adhesive and apply a new layer.
- Leave adequate joints between individual wall and floor tiles unless self-spacing tiles are used.
- Clean off surplus adhesive from the tile face and between joints.
- Please note that this adhesive is not suitable for use in damp conditions and temperatures less than 5° C.

Area to cover:-



TO cover an area of 3 to 3.5 m² with a recommended thickness of 4 to 6 mm it will need 20 kg of CREED TA GREY+



Packing:-

20 Kg & 50 Kg

Precautions :-

- CREED TA GREY+ is a non-toxic adhesive. However, if it comes in contact with your skin, wash it well with water. If it comes in contact with your eyes, wash it well with water and seek medical advice

Shelf Life:-:

- CREED TA GREY has a shelf life of 12 months when stored in unopened containers in dry conditions at a temperature between 5°C and 45°C.