

CREED CRACK FILLER

Acrylic Crack Filler Paste

CREED Crack Filler Paste is a white, acrylic polymer-based product composed of a carefully selected blend of graded fillers and additives. This formulation offers a robust bond with flexibility, allowing it to adapt to cracks in plaster. Additionally, it creates a water-resistant surface with an appealing aesthetic.

SPECIFICATION

Color	: Milky White
Consistency	: Viscous Paste Type
Sp. Gravity	: 1.50
Form	: Paste
Water Resistance	: Excellent

KEY FEATURES

- Paint Ability
- Ease of Application
- Flexibility
- Applied on damp surfaces

APPLICATION



Hair-line Crack



Internal Crack



External Crack



Horizontal & Vertical Crack

HOW TO APPLY :-

- Proper surface preparation is essential for optimal adhesion and bonding of CREED Crack Filler Paste.
- Begin by clearing the surface of laitance, loose dust, oil, grease, and other contaminants.
- Firmly press CREED Crack Filler Paste into the crack using a spatula or putty knife, ensuring it is leveled with the surface.
- Take care to prevent the formation of cavities or bubbles during the application process.
- Allow the paste to set for 24 hours, then apply an additional coat of CREED Crack Filler Paste.
- Further applications of POP or painter's putty can be done once it is completely dry. For optimal results, let CREED Crack Filler Paste cure for 7 days.



Area to cover:-

40 - 45 Rft Per Kg / 5 mm Cracks



Packing:-

500 Gms & 1 Kgs

Shelf Life:-:

- Store away from direct sunlight. 12 months from date of manufacture