

EXCEL

Interview Questions

& Answers

Complete Guide — 100 Questions

Easy · Medium · Hard

30 Easy Questions	40 Medium Questions	30 Hard Questions
---	---	---

Covers: Basics · Formulas · Functions · PivotTables · Power Query · VBA · Dynamic Arrays · DAX · Data Analysis

Table of Contents

Easy Level Questions	Q 1–30	Basics, UI, Simple Formulas
Medium Level Questions	Q 31–70	VLOOKUP, PivotTables, Advanced Formulas
Hard Level Questions	Q 71–100	Dynamic Arrays, VBA, Power Query, DAX

EASY LEVEL — Questions 1–30

Q1 What is Microsoft Excel and what is it primarily used for?

Microsoft Excel is a spreadsheet application developed by Microsoft, part of the Microsoft Office suite. It is primarily used for organizing, analyzing, and storing data in tabular form. Common uses include financial modeling, budgeting, data analysis, charts/graphs creation, and performing mathematical calculations.

Q2 What is a cell in Excel?

A cell is the basic unit of a spreadsheet, formed by the intersection of a row and a column. Each cell has a unique address (e.g., A1, B3) and can contain text, numbers, formulas, or dates.

Q3 What is the difference between a workbook and a worksheet?

A workbook is the entire Excel file (with extension .xlsx or .xls). A worksheet (or sheet) is a single tab within a workbook. One workbook can contain multiple worksheets.

Q4 How do you freeze panes in Excel and why would you use it?

Go to View > Freeze Panes and select the desired option (Freeze Top Row, Freeze First Column, or Freeze Panes). Freezing keeps specific rows/columns visible while scrolling through large datasets, making headers always readable.

Q5 What is the shortcut key to insert a new row or column?

Select the entire row or column first (Shift+Space for row, Ctrl+Space for column), then press Ctrl+Shift+Plus (+) to insert. Alternatively, right-click the selection and choose Insert.

Q6 What are the different file formats Excel supports for saving?

Excel supports .xlsx (default), .xls (older format), .xlsm (macro-enabled), .csv (comma-separated values), .pdf, .txt, .xml, .ods (OpenDocument), and .xlsb (binary format). The choice depends on compatibility and purpose.

Q7 How do you use AutoFill in Excel?

Type the initial value(s) in a cell or range, then hover over the bottom-right corner of the selected cell until the cursor becomes a thin black plus sign (Fill Handle). Drag it across or down to fill adjacent cells with a series or copied values.

Q8 What is the SUM function and how do you write it?

SUM adds all numbers in a range. Syntax: =SUM(number1, [number2], ...) or =SUM(A1:A10). You can also use the AutoSum button (Alt+=) to quickly insert SUM for a selected range.

Q9 How do you apply a filter to a dataset in Excel?

Select any cell within the dataset, then go to Data > Filter (or press Ctrl+Shift+L). Drop-down arrows appear in the header row. Click an arrow to filter by specific values, text, numbers, or colors.

Q10 What is Conditional Formatting and how is it useful?

Conditional Formatting automatically applies formatting (colors, icons, data bars) to cells based on their values or formulas. It is useful for highlighting important trends, outliers, duplicates, or meeting specific criteria, making data easier to interpret visually.

Q11 How do you create a simple chart in Excel?

Select the data range you want to visualize, then go to Insert > Charts and choose the desired chart type (Bar, Line, Pie, etc.). Excel inserts the chart as an object on the active sheet. You can then format and customize it.

Q12 What is the difference between relative and absolute cell references?

A relative reference (e.g., A1) changes automatically when a formula is copied to another cell. An absolute reference (e.g., \$A\$1) stays fixed regardless of where the formula is copied. A mixed reference (e.g., \$A1 or A\$1) fixes either the column or row only.

Q13 How do you merge and center cells in Excel?

Select the cells you want to merge, then click Home > Merge & Center. Alternatively, use the drop-down next to it to choose Merge Across or Merge Cells. Note: merging keeps only the upper-left cell's content.

Q14 What is the AVERAGE function?

AVERAGE calculates the arithmetic mean of a range of numbers. Syntax: =AVERAGE(number1, [number2], ...) or =AVERAGE(A1:A10). It ignores text and blank cells but counts cells containing zero.

Q15 How do you sort data in Excel?

Select any cell in the column to sort by, then go to Data > Sort A to Z or Sort Z to A for quick sort. For multi-level sorting, go to Data > Sort, add levels, choose sort-by columns, and select order (ascending/descending).

Q16 What is the MAX and MIN function in Excel?

MAX returns the largest value in a range: =MAX(A1:A10). MIN returns the smallest value: =MIN(A1:A10). Both ignore text and logical values unless used with MAXA/MINA.

Q17	How do you wrap text inside a cell? Select the cell(s), then click Home > Wrap Text. This makes the text display on multiple lines within the same cell, automatically adjusting row height. You can also use Alt+Enter to manually insert a line break within a cell.
Q18	What does the COUNT function do? COUNT counts the number of cells that contain numeric values in a range. Syntax: =COUNT(A1:A10). Related functions: COUNTA (counts non-empty cells), COUNTBLANK (counts empty cells), COUNTIF (counts cells meeting a condition).
Q19	How do you add a comment or note to a cell in Excel? Right-click the cell and select Insert Comment (older Excel) or New Comment (Excel 365). A text box appears; type your note. A small red triangle in the cell corner indicates a comment. In Excel 365, use Notes for persistent annotations and Comments for threaded discussions.
Q20	What is the keyboard shortcut to save an Excel file? Ctrl+S saves the current file. Ctrl+Shift+S (or F12) opens Save As dialog to save with a new name or location. Ctrl+W closes the current workbook.
Q21	What is the purpose of the Name Box in Excel? The Name Box (located to the left of the formula bar) displays the address of the currently selected cell or named range. You can also type a cell address or named range into the Name Box and press Enter to navigate directly to that location.
Q22	How do you use Find & Replace in Excel? Press Ctrl+H to open the Find & Replace dialog. In the Find what field, type the text to search for; in Replace with, type the replacement text. Click Replace or Replace All. Ctrl+F opens just the Find dialog.
Q23	What is the IF function and its syntax? IF tests a logical condition and returns one value if TRUE and another if FALSE. Syntax: =IF(logical_test, value_if_true, value_if_false). Example: =IF(A1>50, "Pass", "Fail").
Q24	What is Flash Fill and when was it introduced? Flash Fill automatically fills data when Excel detects a pattern. Introduced in Excel 2013, it works when you start typing next to a column of data — Excel suggests the fill pattern. Press Ctrl+E or go to Data > Flash Fill to apply it.

Q25	How do you apply number formatting (e.g., currency, percentage) in Excel? Select the cell(s), then use the Number group on the Home tab to choose a format (General, Number, Currency, Accounting, Percentage, etc.). For custom formats, press Ctrl+1 to open Format Cells dialog and enter a custom format code.
Q26	How do you protect a worksheet in Excel? Go to Review > Protect Sheet. Set a password (optional), then check/uncheck the actions users are allowed (selecting locked cells, formatting, etc.). Click OK. To protect the entire workbook structure, use Review > Protect Workbook.
Q27	What is the CONCATENATE function (or & operator)? CONCATENATE joins multiple text strings. Syntax: =CONCATENATE(A1, " ", B1) or the simpler =A1&" "&B1.; In Excel 2016+, use =CONCAT() or =TEXTJOIN() for more flexibility, including a delimiter and the option to ignore empty cells.
Q28	How do you insert a hyperlink in Excel? Select the cell, press Ctrl+K (or Insert > Link). In the dialog, choose the link type: existing file/webpage, place in this document, create new document, or e-mail address. Enter the URL or path and optional display text, then click OK.
Q29	What does Ctrl+Z do in Excel? Ctrl+Z undoes the last action. Excel maintains an undo history of up to 100 actions by default. Ctrl+Y (or Ctrl+Shift+Z) redoes an undone action. Note that some actions (like saving) cannot be undone.
Q30	What is a named range in Excel? A named range assigns a descriptive name to a cell or range of cells (e.g., "SalesData" for A1:A100). Use Formulas > Define Name or type directly in the Name Box. Named ranges make formulas more readable: =SUM(SalesData) instead of =SUM(A1:A100).

MEDIUM LEVEL — Questions 31–70

Q31	What is VLOOKUP and how does it work? VLOOKUP searches for a value in the first column of a range and returns a value in the same row from a specified column. Syntax: =VLOOKUP(lookup_value, table_array, col_index_num, [range_lookup]). Use FALSE for exact match. Limitation: it can only search the leftmost column.
-----	---

Q32 What is HLOOKUP and how does it differ from VLOOKUP?

HLOOKUP searches for a value in the first ROW of a range and returns a value from the same column in a specified row. VLOOKUP searches vertically (down columns), while HLOOKUP searches horizontally (across rows). Syntax: =HLOOKUP(lookup_value, table_array, row_index_num, [range_lookup]).

Q33 What is INDEX MATCH and why is it preferred over VLOOKUP?

INDEX MATCH combines INDEX (returns a cell value given row/col) and MATCH (returns the position of a value). Together: =INDEX(return_range, MATCH(lookup_value, lookup_range, 0)). Advantages: can look left, not affected by inserting/deleting columns, generally faster on large datasets.

Q34 What is a PivotTable and when should you use it?

A PivotTable is an interactive tool to summarize, analyze, explore, and present large datasets. It lets you drag and drop fields to rows, columns, values, and filters areas. Use it when you need to aggregate data quickly — sums, counts, averages — or compare groups without writing formulas.

Q35 How do you refresh a PivotTable?

Right-click anywhere inside the PivotTable and select Refresh, or go to PivotTable Analyze > Refresh > Refresh (or Refresh All). You can also set automatic refresh on file open via PivotTable Options > Data > Refresh data when opening the file.

Q36 What is the COUNTIF function?

COUNTIF counts cells in a range that meet a single condition. Syntax: =COUNTIF(range, criteria). Example: =COUNTIF(A1:A100, ">50") counts cells greater than 50. For multiple conditions, use COUNTIFS.

Q37 What is SUMIF and how does it differ from SUMIFS?

SUMIF sums cells meeting ONE condition: =SUMIF(range, criteria, sum_range). SUMIFS sums cells meeting MULTIPLE conditions: =SUMIFS(sum_range, criteria_range1, criteria1, [criteria_range2, criteria2, ...]). SUMIFS is more versatile and can also replace SUMIF.

Q38 How do you use Data Validation in Excel?

Select the cell(s), go to Data > Data Validation. In the Settings tab, choose Allow (Whole number, Decimal, List, Date, Text length, Custom). For dropdown lists, choose List and enter the source. Use the Error Alert tab to show custom error messages when invalid data is entered.

Q39 What is the TEXT function in Excel?

TEXT converts a numeric value to text using a specified format. Syntax: =TEXT(value, format_text). Example: =TEXT(A1, "DD/MM/YYYY") formats a date, or =TEXT(1234.5, "#,##0.00") gives "1,234.50". Useful for combining numbers with text strings.

Q40 What are the LEFT, RIGHT, and MID text functions?

LEFT extracts characters from the start: =LEFT(text, num_chars). RIGHT extracts from the end: =RIGHT(text, num_chars). MID extracts from a specified position: =MID(text, start_num, num_chars). Example: =MID("Hello World", 7, 5) returns "World".

Q41 What is the IFERROR function and when should you use it?

IFERROR catches errors in a formula and returns an alternative value. Syntax: =IFERROR(value, value_if_error). Example: =IFERROR(VLOOKUP(A1,B:C,2,0), "Not Found"). Use it to prevent error values (#N/A, #DIV/0!, #VALUE!) from displaying in your spreadsheet.

Q42 How does the CHOOSE function work?

CHOOSE returns a value from a list based on an index number. Syntax: =CHOOSE(index_num, value1, value2, ...). Example: =CHOOSE(2, "Red", "Green", "Blue") returns "Green". Useful for mapping numbers to labels without a lookup table.

Q43 What is the difference between ROUND, ROUNDUP, and ROUNDDOWN?

ROUND rounds to the nearest specified decimal (rounds half up): =ROUND(3.456,2) = 3.46. ROUNDUP always rounds away from zero: =ROUNDUP(3.451,2) = 3.46. ROUNDDOWN always rounds toward zero: =ROUNDDOWN(3.456,2) = 3.45.

Q44 How do you use the SUMPRODUCT function?

SUMPRODUCT multiplies corresponding elements in arrays and returns the sum. Syntax: =SUMPRODUCT(array1, [array2], ...). Example: =SUMPRODUCT(B2:B10, C2:C10) calculates total revenue (quantity × price). It can also be used as a powerful alternative to SUMIFS/COUNTIFS with complex criteria.

Q45 What are date functions in Excel? Name five important ones.

Key date functions: TODAY() returns current date; NOW() returns current date and time; DATE(year,month,day) creates a date; DATEDIF(start,end,unit) calculates difference; EOMONTH(start_date, months) returns last day of month; WORKDAY and NETWORKDAYS for working-day calculations.

Q46 What is the TRIM function used for?

TRIM removes all extra spaces from text, leaving only single spaces between words and no leading/trailing spaces. Syntax: =TRIM(text). Very useful when cleaning data imported from external sources where extra spaces cause formula errors.

Q47 How do you use the OFFSET function?

OFFSET returns a reference offset from a starting cell by a number of rows and columns. Syntax: =OFFSET(reference, rows, cols, [height], [width]). It creates dynamic ranges and is often combined with MATCH or COUNTA for dynamic named ranges in charts and data validation lists.

Q48 What is Power Query (Get & Transform) in Excel?

Power Query is a data connection technology that enables you to import, transform, and load data from various sources (Excel, CSV, web, databases, etc.). Available via Data > Get Data, it provides a visual interface to clean, reshape, merge, and prepare data without writing formulas. Steps are recorded and reapplied automatically.

Q49 How do you remove duplicates in Excel?

Select the dataset, then go to Data > Remove Duplicates. Choose which columns to check for duplicates and click OK. Excel removes duplicate rows and reports how many were removed. Always work on a copy, as this action is irreversible after saving.

Q50 What is the purpose of the INDIRECT function?

INDIRECT returns the reference specified by a text string, evaluated dynamically. Syntax: =INDIRECT(ref_text). Example: =INDIRECT("A"&B1;) where B1=5 refers to cell A5. Useful for creating dynamic references that change based on cell values, e.g., referencing different sheets dynamically.

Q51 How do you use nested IF statements?

Nested IFs place IF statements inside each other to handle multiple conditions. Example: =IF(A1>=90,"A",IF(A1>=80,"B",IF(A1>=70,"C","F"))). Excel supports up to 64 levels of nesting. For cleaner code, consider IFS function (Excel 2019+) or SWITCH instead.

Q52 What is the IFS function?

IFS checks multiple conditions and returns the value corresponding to the first TRUE condition. Syntax: =IFS(condition1, value1, condition2, value2, ...). Available in Excel 2019 and Office 365. It replaces nested IFs for improved readability. Example: =IFS(A1>=90,"A",A1>=80,"B",A1>=70,"C",TRUE,"F").

Q53 What is the XLOOKUP function and how does it improve on VLOOKUP?

XLOOKUP (Excel 2019/365) searches a range and returns a matched item. Syntax: =XLOOKUP(lookup_value, lookup_array, return_array, [not_found], [match_mode], [search_mode]). Advantages over VLOOKUP: can look left, returns arrays, handles not-found natively, supports approximate/exact/wildcard matching, and searches from last to first.

Q54 What is Power Pivot and how does it extend Excel's capabilities?

Power Pivot is an Excel add-in that enables advanced data modeling. It can handle millions of rows (unlike regular Excel's ~1M row limit), create relationships between multiple tables, and use DAX (Data Analysis Expressions) formulas. It powers the data model behind PivotTables connected to multiple tables.

Q55 What is the MATCH function?

MATCH searches for a value in a range and returns its relative position. Syntax: =MATCH(lookup_value, lookup_array, [match_type]). Match types: 0 (exact), 1 (largest value <=; sorted ascending), -1 (smallest value >=; sorted descending). Often combined with INDEX for powerful lookups.

Q56 How do you create a drop-down list in Excel?

Select the cell, go to Data > Data Validation > Allow: List. Enter the source as a comma-separated list ("Yes,No,Maybe") or a range reference (=\$A\$1:\$A\$5 or a named range). Check In-cell dropdown. Now users can click the cell and select from the list.

Q57 What does TRANSPOSE do in Excel?

TRANSPOSE converts rows to columns and vice versa. In older Excel, it is entered as an array formula: select the output range, type =TRANSPOSE(A1:C3), and press Ctrl+Shift+Enter. In Excel 365, it is dynamic: just type =TRANSPOSE(A1:C3) and press Enter — it spills automatically.

Q58 How do you calculate the number of working days between two dates?

Use =NETWORKDAYS(start_date, end_date, [holidays]) to count working days (Mon–Fri) between two dates, optionally excluding holidays. For custom weekends use =NETWORKDAYS.INTL(start_date, end_date, [weekend], [holidays]) where the weekend argument lets you specify non-standard work weeks.

Q59 What is Conditional Formatting with formulas?

You can apply conditional formatting based on a custom formula. Go to Home > Conditional Formatting > New Rule > Use a formula to determine which cells to format. Enter a formula that evaluates to TRUE/FALSE (e.g., =\$B1>100). This enables row-level or complex cross-cell highlighting.

Q60 How do you use the SUBTOTAL function and how is it different from SUM?

SUBTOTAL performs calculations on visible cells only (ignoring filtered/hidden rows). Syntax: =SUBTOTAL(function_num, range). Function_num 9 = SUM, 1 = AVERAGE, 2 = COUNT, etc. Use 109 instead of 9 to also ignore manually hidden rows. Regular SUM includes hidden rows.

Q61 What is the EXACT function?

EXACT compares two text strings and returns TRUE if they are identical (case-sensitive), FALSE otherwise. Syntax: =EXACT(text1, text2). Unlike the = operator (which is case-insensitive), EXACT differentiates between "apple" and "Apple".

Q62 How do you link data between worksheets or workbooks in Excel?

Within the same workbook: reference another sheet with SheetName!CellAddress (e.g., =Sheet2!A1). Between workbooks: =[WorkbookName.xlsx]SheetName!\$A\$1. External links update when both files are open; Excel prompts to update when opening a file with external links.

Q63 What are sparklines in Excel?

Sparklines are tiny charts placed within a single cell that show data trends. Insert them via Insert > Sparklines (Line, Column, or Win/Loss). They are useful for showing trends in dashboard reports without taking up chart space. You can customize their color and axis settings.

Q64 What is the purpose of the AGGREGATE function?

AGGREGATE performs 19 different aggregate functions (SUM, AVERAGE, MAX, etc.) with options to ignore hidden rows, errors, or nested SUBTOTAL/AGGREGATE results. Syntax: =AGGREGATE(function_num, options, ref1, [ref2]). It is the most flexible aggregate function in Excel, often replacing SUBTOTAL.

Q65 How do you calculate compound interest in Excel?

Use the formula: =Principal*(1+Rate/n)^(n*t) where Rate is annual interest rate, n is compounding periods per year, and t is years. Alternatively, use the FV (Future Value) function: =FV(rate/n, n*t, 0, -principal) which returns the future value of an investment.

Q66 What is goal seek in Excel and how do you use it?

Goal Seek finds the input value needed to achieve a desired formula result. Go to Data > What-If Analysis > Goal Seek. Set Cell: the formula cell; To value: your target; By changing cell: the input cell. Excel iterates to find the required input. Useful for break-even analysis and target setting.

Q67 What is a Slicer in Excel and how is it used?

Slicers are visual filter controls for PivotTables and Tables. Insert them via PivotTable Analyze > Insert Slicer (or Table Design > Insert Slicer). Click slicer buttons to filter data interactively. Multiple slicers can be connected to multiple PivotTables for dashboard-style interactivity.

Q68 What is the PROPER function?

PROPER capitalizes the first letter of each word in a text string and converts the rest to lowercase. Syntax: =PROPER(text). Example: =PROPER("JOHN DOE") returns "John Doe". Useful for fixing inconsistent name capitalization in datasets.

Q69 How do you use the AND and OR functions in Excel?

AND returns TRUE if all conditions are TRUE: `=AND(A1>0, B1>0)`. OR returns TRUE if at least one condition is TRUE: `=OR(A1="Yes", B1="Yes")`. Both are commonly nested inside IF: `=IF(AND(A1>0,B1>0),"Both positive","Not both positive")`.

Q70 What is the RANK function?

RANK returns the rank of a number in a list. Syntax: `=RANK(number, ref, [order])`. Order 0 (or omitted) ranks in descending order; 1 ranks in ascending order. Use RANK.EQ (same as RANK) or RANK.AVG (averages rank for ties) in Excel 2010+.

HARD LEVEL — Questions 71–100

Q71 What are dynamic array functions in Excel 365 and how do they change formula behavior?

Dynamic array functions (Excel 365/2019) return results that automatically spill into adjacent cells. Key functions: FILTER, SORT, SORTBY, UNIQUE, SEQUENCE, RANDARRAY. Unlike legacy array formulas (Ctrl+Shift+Enter), they enter with just Enter. The spill range is indicated by a blue border; reference it with the spill operator (#): e.g., `=SUM(A1#)`.

Q72 How does the FILTER function work in Excel 365?

FILTER returns only rows/columns of an array that meet specified conditions. Syntax: `=FILTER(array, include, [if_empty])`. Example: `=FILTER(A2:C100, B2:B100="Sales")` returns all rows where column B is "Sales". Multiple conditions: `=FILTER(A2:C100, (B2:B100="Sales")*(C2:C100>1000))` uses multiplication for AND logic, addition for OR logic.

Q73 Explain how to create a dynamic dashboard in Excel.

A dynamic dashboard combines: (1) structured Table as data source, (2) PivotTables for aggregation, (3) Slicers and Timelines for filtering, (4) Charts linked to PivotTables, (5) dynamic formulas (INDIRECT, OFFSET, or dynamic arrays) for KPI cards. Use Form Controls or ActiveX for additional interactivity. A single Slicer can control multiple PivotTables via Report Connections.

Q74 What is a CSE (Ctrl+Shift+Enter) array formula and how does it differ from regular formulas?

Legacy array formulas perform calculations on arrays and return multiple results or a single summarized result. They are entered with Ctrl+Shift+Enter instead of just Enter, and Excel wraps them in {} braces. Example: `{=SUM(IF(A1:A10>5, B1:B10, 0))}` sums B values where A>5. In Excel 365, most CSE formulas are replaced by dynamic array functions.

Q75 How do you build a two-way lookup using INDEX-MATCH-MATCH?

Two-way lookup finds a value by matching both a row and column header. Formula: `=INDEX(data_range, MATCH(row_value, row_headers, 0), MATCH(col_value, col_headers, 0))`. The first MATCH finds the row position; the second finds the column position. INDEX then returns the intersecting value. More powerful than nested VLOOKUP/HLOOKUP.

Q76 What is DAX in Power Pivot and give examples of common DAX measures?

DAX (Data Analysis Expressions) is a formula language used in Power Pivot, Power BI, and Analysis Services. It works on tables and columns rather than cell ranges. Common measures: Total Sales = `SUM(Sales[Amount])`; Sales YTD = `TOTALYTD([Total Sales], Dates[Date])`; % of Total = `DIVIDE([Total Sales], CALCULATE([Total Sales], ALL(Sales)))`. DAX supports time intelligence, filter context, and row context.

Q77 How do you create a Macro in Excel using VBA?

Press Alt+F11 to open the VBA Editor. Insert a Module (Insert > Module), then write a Sub procedure: `Sub MyMacro() ... End Sub`. You can record macros via Developer > Record Macro and review/edit the generated VBA code. Macros can automate repetitive tasks: formatting, data manipulation, sending emails. Save as .xlsm to preserve macros.

Q78 What is the LAMBDA function in Excel 365?

LAMBDA allows you to define reusable custom functions without VBA. Syntax: `=LAMBDA([parameter1, ...], formula)`. To make it reusable, assign it a name in Name Manager. Example: Define 'CELSIUSTOFAHRENHEIT' as `=LAMBDA(c, c*9/5+32)` then use `=CELSIUSTOFAHRENHEIT(100)` anywhere in the workbook. Supports recursion for iterative calculations.

Q79 How does Excel handle circular references and how can you enable iterative calculation?

A circular reference occurs when a formula refers (directly or indirectly) to its own cell, causing an infinite loop. By default, Excel warns and stops calculation. Enable iterative calculation at File > Options > Formulas > Enable iterative calculation. Set Maximum Iterations and Maximum Change. Useful for loan payoff schedules or convergence calculations.

Q80 What is Solver in Excel and how does it differ from Goal Seek?

Solver is an optimization add-in that finds the optimal value (minimum, maximum, or specific target) by adjusting multiple input cells subject to constraints. Goal Seek changes only ONE input to hit ONE target. Solver supports multiple variable cells and multiple constraints, making it suitable for linear programming, portfolio optimization, and scheduling problems.

Q81 How do you perform a sensitivity analysis using a Data Table in Excel?

A one-variable data table tests how one input affects results: lay out input values in a column/row, reference your formula in the corner cell, select the table, go to Data > What-If Analysis > Data Table, enter row/column input cell. A two-variable data table tests two inputs simultaneously. Data Tables recalculate automatically and are ideal for mortgage payment or scenario analysis.

Q82 What are Excel Tables (Ctrl+T) and what are their advantages?

Excel Tables are structured data ranges with automatic features: (1) auto-expanding formulas and formatting when new rows are added; (2) structured references (e.g., Table1[Amount]); (3) auto-filter dropdowns; (4) Total Row for quick aggregation; (5) automatic naming; (6) seamless integration with PivotTables and Power Query. Structured references update automatically as data changes.

Q83 How do you connect Excel to an external database or web data source?

Via Power Query (Data > Get Data): connect to SQL Server, Azure, Oracle, MySQL, Access, OData feeds, SharePoint, web pages, JSON, XML, etc. Enter connection details and credentials, then select tables and transform data. The query can be refreshed on demand or on schedule. Connection strings can be managed via Data > Queries & Connections.

Q84 Explain the difference between SUMPRODUCT and regular array formulas for weighted averages.

Weighted average with SUMPRODUCT: `=SUMPRODUCT(values, weights)/SUM(weights)`. No Ctrl+Shift+Enter needed. Equivalent array formula: `{=SUM(values*weights)/SUM(weights)}`. SUMPRODUCT is cleaner, doesn't require CSE, and handles errors differently. It also works with additional conditions: `=SUMPRODUCT((criteria_range="X")*values*weights)/SUMPRODUCT((criteria_range="X")*weights)`.

Q85 How do you use the GETPIVOTDATA function and when should you avoid it?

GETPIVOTDATA extracts specific data from a PivotTable using field names and items. It is automatically inserted when you click a PivotTable cell in a formula. Syntax: `=GETPIVOTDATA("Sales", pivot_ref, "Region", "North", "Year", 2024)`. Avoid it when you need formulas to adjust dynamically as PivotTable layout changes, or when building dynamic reports. Disable auto-generation in PivotTable Analyze options.

Q86 What is M language in Power Query and how does it extend data transformation?

M (Mashup Query Formula Language) is the functional, case-sensitive language underlying all Power Query transformations. Each transformation step generates M code visible in the Advanced Editor. You can write custom M to: create custom columns, apply conditional logic, call web APIs, handle errors with try/otherwise, loop with List.Generate, and apply transformations not available in the GUI.

Q87 How do you implement error handling in VBA Excel macros?

Use On Error statements: On Error GoTo ErrorHandler (jumps to a label on error), On Error Resume Next (ignores errors — use with caution), On Error GoTo 0 (resets error handling). The Err object provides error number (Err.Number) and description (Err.Description). Always include cleanup code in the ErrorHandler section and use Resume or Resume Next to continue execution after handling.

Q88 What are structured references in Excel Tables and how do they work?

Structured references use table and column names instead of cell addresses: =Table1[Amount] refers to all cells in the Amount column; [@Amount] refers to the current row's Amount; Table1[[Sales]:[Profit]] refers to multiple columns; Table1[#Headers] refers to header row; Table1[#Totals] refers to total row. They update automatically when columns are added/renamed.

Q89 How do you build a rolling 12-month average using dynamic formulas?

Using OFFSET: =AVERAGE(OFFSET(data_start, COUNT(data_range)-12, 0, 12, 1)) dynamically references the last 12 months. In Excel 365, use: =AVERAGE(TAKE(FILTER(data,month_col=...), -12)) or combine OFFSET+MATCH to anchor to a specific month. Alternatively, define a dynamic named range using OFFSET+COUNTA and use it in a chart for auto-updating rolling averages.

Q90 What are the LET function's advantages in Excel 365?

LET assigns names to calculation results within a formula, improving readability and performance. Syntax: =LET(name1, value1, name2, value2, ..., calculation). Example: =LET(x, A1*B1, y, C1+D1, x+y). Benefits: (1) avoids repeating complex sub-expressions; (2) each sub-expression is calculated once (performance); (3) makes long formulas self-documenting.

Q91 How do you merge queries in Power Query and what join types are available?

In Power Query: Home > Merge Queries. Select the two tables and the join key columns. Join types: Left Outer (all from left, matching from right), Right Outer, Full Outer (all rows from both), Inner (only matching rows), Left Anti (non-matching from left), Right Anti. After merging, expand the resulting column to access fields from the joined table.

Q92 What is the MAKEARRAY function and how does it enable programmatic array creation?

MAKEARRAY (Excel 365) creates an array of specified dimensions by applying a LAMBDA to each position. Syntax: =MAKEARRAY(rows, cols, LAMBDA(r,c, calculation)). Example: =MAKEARRAY(5,5,LAMBDA(r,c,r*c)) creates a 5x5 multiplication table. It enables generating arrays based on index positions without external data, useful for creating calendar grids or mathematical tables.

Q93

How do you automate report generation across multiple sheets using VBA?

Use a VBA loop: For Each ws In ThisWorkbook.Worksheets ... Next ws. Inside the loop, reference ws.Range("A1") to work with each sheet's data. Use Application.ScreenUpdating = False for performance, Application.DisplayAlerts = False to suppress dialogs. Consolidate data with arrays or write to a summary sheet. Use Workbooks.Open and SaveAs for multi-file processing.

Q94

What is the difference between OLAP and flat-file PivotTables, and how does this affect MDX?

Flat-file PivotTables source data from Excel ranges or Power Pivot data models. OLAP PivotTables connect to Analysis Services, SQL Server OLAP cubes, or other MDX-compliant sources. OLAP PivotTables use MDX (Multidimensional Expressions) for calculated members/measures and support cube functions (CUBEMEMBER, CUBEVALUE, CUBESET) for extracting OLAP data directly into cells without PivotTable structure.

Q95

How do you use the BYROW and BYCOL functions in Excel 365?

BYROW applies a LAMBDA to each row of an array and returns a column of results: =BYROW(A1:D5, LAMBDA(row, SUM(row))). BYCOL applies a LAMBDA to each column: =BYCOL(A1:D5, LAMBDA(col, AVERAGE(col))). They are used for row-wise or column-wise aggregations across a range, eliminating the need for helper columns or complex array formulas.

Q96

What is a UserForm in VBA and how do you build a data entry form with it?

A UserForm is a custom dialog box built in VBA. Insert it via VBA Editor: Insert > UserForm. Add controls (TextBoxes, ComboBoxes, Buttons, Labels) from the Toolbox. Write event handlers: Private Sub CommandButton1_Click() reads TextBox values and writes them to the worksheet (e.g., Cells(nextRow, 1) = TextBox1.Value). Show with UserForm1.Show from a macro.

Q97

How do you implement a Monte Carlo simulation in Excel?

Monte Carlo simulation uses random sampling to model uncertainty. In Excel: (1) Define input distributions using NORM.INV(RAND(), mean, sd) or equivalent. (2) Build a model formula that uses these random inputs. (3) Use a Data Table (one-variable, with blank row input cell) to run 1000+ iterations capturing output values. (4) Analyze the distribution of results with histograms, PERCENTILE, and AVERAGE functions.

Q98

How do you optimize VBA macro performance for large datasets?

Key optimizations: (1) Application.ScreenUpdating = False; (2) Application.Calculation = xlCalculationManual then restore to xlAutomatic; (3) Application.EnableEvents = False; (4) Read/write entire arrays at once (Dim arr = range.Value, process, range.Value = arr) instead of looping cell-by-cell; (5) Avoid Select/Activate; (6) Use With statements; (7) Minimize worksheet interactions inside loops.

Q99 What are cube functions in Excel and how do they enable flexible OLAP reporting?

Cube functions query OLAP data sources or Power Pivot data models directly without PivotTable structure. Key functions: CUBEMEMBER (retrieves a member from a cube), CUBEVALUE (retrieves an aggregated value), CUBESET (creates a set of members), CUBESETCOUNT, CUBERANKEDMEMBER, CUBEMEMBERPROPERTY. They allow freeform report layouts, conditional formatting on specific OLAP values, and fully dynamic off-PivotTable dashboards.

Q100 How do you implement a recursive LAMBDA function in Excel 365?

Recursive LAMBDA uses the LAMBDA helper function to call itself. Use LET to name the LAMBDA, then reference that name inside the body. Example — factorial: =LET(FACT, LAMBDA(n, IF(n<=1, 1, n * FACT(n-1))), FACT(5)) returns 120. The REDUCE, SCAN, and MAP helper functions also enable iteration without true recursion: =REDUCE(0, SEQUENCE(5), LAMBDA(acc,x, acc+x)) sums 1 to 5.

■ **You've covered all 100 questions!**

Practice regularly, build sample spreadsheets, and apply these concepts on real datasets to ace your Excel interview!