


# LOGICAL AGENTS

## CHAPTER 7

# Outline

- ◇ Knowledge-based agents
- ◇ Wumpus world
- ◇ Logic in general—models and entailment
- ◇ Propositional (Boolean) logic
- ◇ Equivalence, validity, satisfiability
- ◇ Inference rules and theorem proving
  - forward chaining
  - backward chaining
  - resolution



Knowledge base = set of sentences in a **formal** language

**Declarative** approach to building an agent (or other system):

**TELL** it what it needs to know

Then it can **ASK** itself what to do—answers should follow from the KB

Agents can be viewed at the **knowledge level**

i.e., **what they know**, regardless of how implemented

Or at the **implementation level**

i.e., data structures in KB and algorithms that manipulate them

# Logic in general

**Logics** are formal languages for representing information such that conclusions can be drawn

**Syntax** defines the sentences in the language

**Semantics** define the “meaning” of sentences;  
i.e., define **truth** of a sentence in a world

E.g., the language of arithmetic

$x + 2 \geq y$  is a sentence;  $x^2 + y >$  is not a sentence

$x + 2 \geq y$  is true iff the number  $x + 2$  is no less than the number  $y$

$x + 2 \geq y$  is true in a world where  $x = 7$ ,  $y = 1$

$x + 2 \geq y$  is false in a world where  $x = 0$ ,  $y = 6$

# Entailment

Entailment means that one thing **follows from** another:

$$KB \models \alpha$$

Knowledge base  $KB$  entails sentence  $\alpha$

if and only if

$\alpha$  is true in all worlds where  $KB$  is true

E.g., the KB containing “the Giants won” and “the Reds won” entails “Either the Giants won or the Reds won”

E.g.,  $x + y = 4$  entails  $4 = x + y$

Entailment is a relationship between sentences (i.e., **syntax**) that is based on **semantics**

Note: brains process **syntax** (of some sort)

# Models


Logicians typically think in terms of **models**, which are formally structured worlds with respect to which truth can be evaluated

We say  $m$  is a model of a sentence  $\alpha$  if  $\alpha$  is true in  $m$

$M(\alpha)$  is the set of all models of  $\alpha$

Then  $KB \models \alpha$  if and only if  $M(KB) \subseteq M(\alpha)$

E.g.  $KB = \text{Giants won and Reds won}$   
 $\alpha = \text{Giants won}$



# Inference

$KB \vdash_i \alpha$  = sentence  $\alpha$  can be derived from  $KB$  by procedure  $i$

Consequences of  $KB$  are a haystack;  $\alpha$  is a needle.

Entailment = needle in haystack; inference = finding it

**Soundness:**  $i$  is sound if

whenever  $KB \vdash_i \alpha$ , it is also true that  $KB \models \alpha$

**Completeness:**  $i$  is complete if

whenever  $KB \models \alpha$ , it is also true that  $KB \vdash_i \alpha$

Preview: we will define a logic (first-order logic) which is expressive enough to say almost anything of interest, and for which there exists a sound and complete inference procedure.

That is, the procedure will answer any question whose answer follows from what is known by the  $KB$ .

## Propositional logic: Syntax

Propositional logic is the simplest logic—illustrates basic ideas

The proposition symbols  $P_1$ ,  $P_2$  etc are sentences

If  $S$  is a sentence,  $\neg S$  is a sentence (negation)

If  $S_1$  and  $S_2$  are sentences,  $S_1 \wedge S_2$  is a sentence (conjunction)

If  $S_1$  and  $S_2$  are sentences,  $S_1 \vee S_2$  is a sentence (disjunction)

If  $S_1$  and  $S_2$  are sentences,  $S_1 \Rightarrow S_2$  is a sentence (implication)

If  $S_1$  and  $S_2$  are sentences,  $S_1 \Leftrightarrow S_2$  is a sentence (biconditional)



# Propositional logic: Semantics

Each model specifies true/false for each proposition symbol

E.g.  $P_{1,2}$   $P_{2,2}$   $P_{3,1}$   
*true true false*

(With these symbols, 8 possible models, can be enumerated automatically.)

Rules for evaluating truth with respect to a model  $m$ :

$\neg S$	is true iff	$S$	is false
$S_1 \wedge S_2$	is true iff	$S_1$	is true <b>and</b> $S_2$ is true
$S_1 \vee S_2$	is true iff	$S_1$	is true <b>or</b> $S_2$ is true
$S_1 \Rightarrow S_2$	is true iff	$S_1$	is false <b>or</b> $S_2$ is true
i.e.,	is false iff	$S_1$	is true <b>and</b> $S_2$ is false
$S_1 \Leftrightarrow S_2$	is true iff	$S_1 \Rightarrow S_2$ is true <b>and</b> $S_2 \Rightarrow S_1$ is true	

Simple recursive process evaluates an arbitrary sentence, e.g.,

$\neg P_{1,2} \wedge (P_{2,2} \vee P_{3,1}) = \textit{true} \wedge (\textit{false} \vee \textit{true}) = \textit{true} \wedge \textit{true} = \textit{true}$

## Truth tables for connectives

$P$	$Q$	$\neg P$	$P \wedge Q$	$P \vee Q$	$P \Rightarrow Q$	$P \Leftrightarrow Q$
<i>false</i>	<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>true</i>
<i>false</i>	<i>true</i>	<i>true</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>false</i>
<i>true</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>
<i>true</i>	<i>true</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>

# Inference by enumeration

Depth-first enumeration of all models is sound and complete

```
function TT-ENTAILS?(KB,  $\alpha$ ) returns true or false
  inputs: KB, the knowledge base, a sentence in propositional logic
          $\alpha$ , the query, a sentence in propositional logic
  symbols  $\leftarrow$  a list of the proposition symbols in KB and  $\alpha$ 
  return TT-CHECK-ALL(KB,  $\alpha$ , symbols, [])
```

---

```
function TT-CHECK-ALL(KB,  $\alpha$ , symbols, model) returns true or false
  if EMPTY?(symbols) then
    if PL-TRUE?(KB, model) then return PL-TRUE?( $\alpha$ , model)
    else return true
  else do
    P  $\leftarrow$  FIRST(symbols); rest  $\leftarrow$  REST(symbols)
    return TT-CHECK-ALL(KB,  $\alpha$ , rest, EXTEND(P, true, model)) and
      TT-CHECK-ALL(KB,  $\alpha$ , rest, EXTEND(P, false, model))
```

$O(2^n)$  for  $n$  symbols; problem is **co-NP-complete**

# Logical equivalence

Two sentences are **logically equivalent** iff true in same models:

$\alpha \equiv \beta$  if and only if  $\alpha \models \beta$  and  $\beta \models \alpha$

$(\alpha \wedge \beta) \equiv (\beta \wedge \alpha)$	commutativity of $\wedge$
$(\alpha \vee \beta) \equiv (\beta \vee \alpha)$	commutativity of $\vee$
$((\alpha \wedge \beta) \wedge \gamma) \equiv (\alpha \wedge (\beta \wedge \gamma))$	associativity of $\wedge$
$((\alpha \vee \beta) \vee \gamma) \equiv (\alpha \vee (\beta \vee \gamma))$	associativity of $\vee$
$\neg(\neg\alpha) \equiv \alpha$	double-negation elimination
$(\alpha \Rightarrow \beta) \equiv (\neg\beta \Rightarrow \neg\alpha)$	contraposition
$(\alpha \Rightarrow \beta) \equiv (\neg\alpha \vee \beta)$	implication elimination
$(\alpha \Leftrightarrow \beta) \equiv ((\alpha \Rightarrow \beta) \wedge (\beta \Rightarrow \alpha))$	biconditional elimination
$\neg(\alpha \wedge \beta) \equiv (\neg\alpha \vee \neg\beta)$	De Morgan
$\neg(\alpha \vee \beta) \equiv (\neg\alpha \wedge \neg\beta)$	De Morgan
$(\alpha \wedge (\beta \vee \gamma)) \equiv ((\alpha \wedge \beta) \vee (\alpha \wedge \gamma))$	distributivity of $\wedge$ over $\vee$
$(\alpha \vee (\beta \wedge \gamma)) \equiv ((\alpha \vee \beta) \wedge (\alpha \vee \gamma))$	distributivity of $\vee$ over $\wedge$

# Validity and satisfiability

A sentence is **valid** if it is true in **all** models,

e.g.,  $True$ ,  $A \vee \neg A$ ,  $A \Rightarrow A$ ,  $(A \wedge (A \Rightarrow B)) \Rightarrow B$

Validity is connected to inference via the **Deduction Theorem**:

$KB \models \alpha$  if and only if  $(KB \Rightarrow \alpha)$  is valid

A sentence is **satisfiable** if it is true in **some** model

e.g.,  $A \vee B$ ,  $C$

A sentence is **unsatisfiable** if it is true in **no** models

e.g.,  $A \wedge \neg A$

Satisfiability is connected to inference via the following:

$KB \models \alpha$  if and only if  $(KB \wedge \neg \alpha)$  is unsatisfiable

i.e., prove  $\alpha$  by *reductio ad absurdum*

# Proof methods

Proof methods divide into (roughly) two kinds:

## Application of inference rules

- Legitimate (sound) generation of new sentences from old
- **Proof** = a sequence of inference rule applications
  - Can use inference rules as operators in a standard search alg.
- Typically require translation of sentences into a **normal form**

## Model checking

- truth table enumeration (always exponential in  $n$ )
- improved backtracking, e.g., Davis–Putnam–Logemann–Loveland
- heuristic search in model space (sound but incomplete)
  - e.g., min-conflicts-like hill-climbing algorithms

# Forward and backward chaining

Horn Form (restricted)

KB = **conjunction** of **Horn clauses**

Horn clause =

◇ proposition symbol; or

◇ (conjunction of symbols)  $\Rightarrow$  symbol

E.g.,  $C \wedge (B \Rightarrow A) \wedge (C \wedge D \Rightarrow B)$

Modus Ponens (for Horn Form): complete for Horn KBs

$$\frac{\alpha_1, \dots, \alpha_n, \quad \alpha_1 \wedge \dots \wedge \alpha_n \Rightarrow \beta}{\beta}$$

Can be used with forward chaining or backward chaining.

These algorithms are very natural and run in **linear** time

# Forward chaining

Idea: fire any rule whose premises are satisfied in the *KB*,  
add its conclusion to the *KB*, until query is found

$$P \Rightarrow Q$$

$$L \wedge M \Rightarrow P$$


$$B \wedge L \Rightarrow M$$

$$A \wedge P \Rightarrow L$$

$$A \wedge B \Rightarrow L$$

*A*

*B*






# Forward chaining algorithm

```
function PL-FC-ENTAILS?(KB, q) returns true or false
  inputs: KB, the knowledge base, a set of propositional Horn clauses
         q, the query, a proposition symbol
  local variables: count, a table, indexed by clause, initially the number of premises
                  inferred, a table, indexed by symbol, each entry initially false
                  agenda, a list of symbols, initially the symbols known in KB


  while agenda is not empty do
    p ← POP(agenda)
    unless inferred[p] do
      inferred[p] ← true
      for each Horn clause c in whose premise p appears do
        decrement count[c]
        if count[c] = 0 then do
          if HEAD[c] = q then return true
          PUSH(HEAD[c], agenda)

  return false
```


# Forward chaining example




# Forward chaining example




# Forward chaining example




# Forward chaining example




# Forward chaining example



# Forward chaining example




# Forward chaining example





# Forward chaining example



# Backward chaining

Idea: work backwards from the query  $q$ :

- to prove  $q$  by BC,

- check if  $q$  is known already, or

- prove by BC all premises of some rule concluding  $q$


Avoid loops: check if new subgoal is already on the goal stack

Avoid repeated work: check if new subgoal


- 1) has already been proved true, or

- 2) has already failed


## Backward chaining example




## Backward chaining example




## Backward chaining example




## Backward chaining example



## Backward chaining example




## Backward chaining example







## Backward chaining example




## Backward chaining example




## Backward chaining example



## Backward chaining example



## Backward chaining example



## Forward vs. backward chaining

FC is **data-driven**, cf. automatic, unconscious processing,  
e.g., object recognition, routine decisions

May do lots of work that is irrelevant to the goal

BC is **goal-driven**, appropriate for problem-solving,  
e.g., Where are my keys? How do I get into a PhD program?

Complexity of BC can be **much less** than linear in size of KB

# Resolution

Conjunctive Normal Form (CNF—universal)

**conjunction** of **disjunctions** of **literals**  
}  
**clauses**

E.g.,  $(A \vee \neg B) \wedge (B \vee \neg C \vee \neg D)$


**Resolution** inference rule (for CNF): complete for propositional logic

$$\frac{\ell_1 \vee \cdots \vee \ell_k, \quad m_1 \vee \cdots \vee m_n}{\ell_1 \vee \cdots \vee \ell_{i-1} \vee \ell_{i+1} \vee \cdots \vee \ell_k \vee m_1 \vee \cdots \vee m_{j-1} \vee m_{j+1} \vee \cdots \vee m_n}$$

where  $\ell_i$  and  $m_j$  are complementary literals. E.g.,

$$\frac{P_{1,3} \vee P_{2,2}, \quad \neg P_{2,2}}{P_{1,3}}$$

Resolution is sound and complete for propositional logic



## Conversion to CNF

$$B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})$$

1. Eliminate  $\Leftrightarrow$ , replacing  $\alpha \Leftrightarrow \beta$  with  $(\alpha \Rightarrow \beta) \wedge (\beta \Rightarrow \alpha)$ .

$$(B_{1,1} \Rightarrow (P_{1,2} \vee P_{2,1})) \wedge ((P_{1,2} \vee P_{2,1}) \Rightarrow B_{1,1})$$

2. Eliminate  $\Rightarrow$ , replacing  $\alpha \Rightarrow \beta$  with  $\neg\alpha \vee \beta$ .

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge (\neg(P_{1,2} \vee P_{2,1}) \vee B_{1,1})$$

3. Move  $\neg$  inwards using de Morgan's rules and double-negation:

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge ((\neg P_{1,2} \wedge \neg P_{2,1}) \vee B_{1,1})$$

4. Apply distributivity law ( $\vee$  over  $\wedge$ ) and flatten:

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge (\neg P_{1,2} \vee B_{1,1}) \wedge (\neg P_{2,1} \vee B_{1,1})$$



# Resolution algorithm


Proof by contradiction, i.e., show  $KB \wedge \neg\alpha$  unsatisfiable

```
function PL-RESOLUTION( $KB, \alpha$ ) returns true or false
  inputs:  $KB$ , the knowledge base, a sentence in propositional logic
          $\alpha$ , the query, a sentence in propositional logic

   $clauses \leftarrow$  the set of clauses in the CNF representation of  $KB \wedge \neg\alpha$ 
   $new \leftarrow \{ \}$ 
  loop do
    for each  $C_i, C_j$  in  $clauses$  do
       $resolvents \leftarrow$  PL-RESOLVE( $C_i, C_j$ )
      if  $resolvents$  contains the empty clause then return true
       $new \leftarrow new \cup resolvents$ 
  if  $new \subseteq clauses$  then return false
   $clauses \leftarrow clauses \cup new$ 
```

# Resolution example

$$KB = (B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})) \wedge \neg B_{1,1} \quad \alpha = \neg P_{1,2}$$



## Summary

Logical agents apply **inference** to a **knowledge base** to derive new information and make decisions

Basic concepts of logic:

- **syntax**: formal structure of **sentences**
- **semantics**: **truth** of sentences wrt **models**
- **entailment**: necessary truth of one sentence given another
- **inference**: deriving sentences from other sentences
- **soundness**: derivations produce only entailed sentences
- **completeness**: derivations can produce all entailed sentences

Wumpus world requires the ability to represent partial and negated information, reason by cases, etc.

Forward, backward chaining are linear-time, complete for Horn clauses  
Resolution is complete for propositional logic

Propositional logic lacks expressive power