



# Constraint Relationships

Step-by-Step Enhancing a MiniZinc Model

We will ...

- start with an **n-queens model** in MiniZinc
- add some additional soft constraints (e.g. one queen should be placed in the **center**)
- prioritize these soft constraints using **constraint relationships**
- switch dominance properties (SPD, TPD)
- and **solve** with: Branch-and-Bound (BaB), Large Neighborhood Search (LNS)

<http://isse-augsburg.github.io/constraint-relationships/>

```
include "globals.mzn";
int: n; array[1..n] of var 1..n: queens; n = 8;

solve :: int_search(queens, first_fail, indomain_median, complete)
satisfy;

constraint all_different(queens);
constraint all_different([queens[i]+i | i in 1..n]);
constraint all_different([queens[i]-i | i in 1..n]);

queens = array1d(1..8 ,[4, 6, 1, 5, 2, 8, 3, 7]);
-----
```

© Hakan Kjellerstrand, <http://www.hakank.org/minizinc>

# Step 1: Add Soft Constraint Support

```
include "globals.mzn";  
include "soft_constraints/soft_constraints.mzn";  
int: n; array[1..n] of var 1..n: queens; n = 8;  
  
solve :: int_search(queens, first_fail, indomain_median, complete)  
satisfy;  
  
constraint all_different(queens);  
constraint all_different([queens[i]+i | i in 1..n]);  
constraint all_different([queens[i]-i | i in 1..n]);
```

- Adds nScs (a new parameter) boolean variables, one for each soft constraint
- Adds parameter penalties (use [1 | i in 1..nScs] if not relevant)
- Intuition: The cost of violating soft constraint i should be penalties[i]

```
include "link_set_to_booleans.mzn";  
% MODEL-SPECIFIC parameters: nScs and penalties  
int: nScs; set of int: SOFTCONSTRAINTS = 1..nScs;  
  
% reified variables for each soft constraint  
array[SOFTCONSTRAINTS] of var bool: satisfied;  
array[SOFTCONSTRAINTS] of var bool: violated =  
    [not satisfied[sc] | sc in SOFTCONSTRAINTS] ;  
  
array[SOFTCONSTRAINTS] of int: penalties;  
var int: penSum = sum(sc in SOFTCONSTRAINTS)  
    (bool2int(not satisfied[sc]) * penalties[sc]);  
  
var set of SOFTCONSTRAINTS: violatedScs;  
constraint link_set_to_booleans(violatedScs,violated);
```

- Using *satisfied* *and* *violated* is done for convenience in expressing soft constraints
- There is also a variant without *violatedScs* for solvers that do not support set variables (e.g. MIP): `soft_constraints_noset.mzn`

```
% find the sorted permutation of soft constraint instances
array[SOFTCONSTRAINTS] of SOFTCONSTRAINTS: sortPermScs =
    arg_sort(penalties);
% invert, since arg_sort use <= and we need decreasing order
array[SOFTCONSTRAINTS] of SOFTCONSTRAINTS: mostImpFirst =
    [ sortPermScs[nScs-s+1] | s in SOFTCONSTRAINTS];
```

- mostImpFirst gives an array of soft constraint indices in decreasing order (start with most important ones)
- Used later as a (generic) labeling strategy

## Step 2: Add Soft Constraints

```
include "globals.mzn";
include "soft_constraints/soft_constraints.mzn";
int: n; array[1..n] of var 1..n: queens; n = 8;

solve :: int_search(queens, first_fail, indomain_median, complete)
minimize penSum;

constraint all_different(queens);
constraint all_different([queens[i]+i | i in 1..n]);
constraint all_different([queens[i]-i | i in 1..n]);
% soft constraint business
nScs = 3; penalties = [1 | i in SOFTCONSTRAINTS];
constraint queens[n div 2] = n div 2 <-> satisfied[1] ;
constraint queens[2] = queens[1] + 2 <-> satisfied[2];
constraint queens[3] = queens[2] + 2 <-> satisfied[3];
```

- Just tie reified soft constraint variables to actual soft constraints
- `[1 | i in 1..nScs]` makes it a Max-CSP when minimizing `penSum`

## Step 2: What about Globals?

What if want to use global constraints as soft constraints? Consider (reified.mzn):

```
include "globals.mzn";
include "soft_constraints/soft_constraints.mzn";
array[1..5] of var 0..5: x;
constraint alldifferent(x); % hard constraint

% but it would be nice to have x increase ...
nScs = 1; penalties = [1];
constraint increasing(x) <-> satisfied[1];

solve maximize bool2int(satisfied[1]);
output["satisfied[1] = \(satisfied[1]), x = \(x)"];
```

Solved with Gecode:

MiniZinc: flattening error: 'increasing\_int' is used in a reified context but no reified version is available



## Step 2: What about Globals?

- a) Use a solver that has the reified global, e.g., here:
  - G12-FD
  - JaCoP
- b) Use a decomposition from the MiniZinc standard library (reified\_fix.mzn)

```
include "globals.mzn";
include "soft_constraints/soft_constraints.mzn";
array[1..5] of var 0..5: x;
constraint alldifferent(x); % hard constraint
nScs = 1; penalties = [1];
% copied from share/minizinc/std/increasing_int.mzn
predicate my_increasing_int(array[int] of var int: x) =
    forall(i in index_set(x) diff { min(index_set(x)) })
        (x[i-1] <= x[i]);

constraint my_increasing_int(x) <-> satisfied[1];
solve maximize bool2int(satisfied[1]);
output["satisfied[1] = \"(satisfied[1])\", x = \"(x)\""];
```

## Step 2: What about Globals?

Solved `reified_fix.mzn` with Gecode (same as `reified.mzn` solved with JaCoP or G12-FD):

```
satisfied[1] = false, x = [4, 1, 3, 0, 2]
-----
satisfied[1] = true, x = [0, 1, 2, 3, 4]
-----
=====
```

We do not get the performance benefits of globals (in a decomposition) but at least their conciseness.

## Step 3: Prioritize Soft Constraints (Weights)

```
include "globals.mzn";
include "soft_constraints/soft_constraints.mzn";
int: n; array[1..n] of var 1..n: queens; n = 8;

solve :: int_search(queens, first_fail, indomain_median, complete)
minimize penSum; output["penSum = \(penSum), queens = \(queens)"];

constraint all_different(queens);
constraint all_different([queens[i]+i | i in 1..n]);
constraint all_different([queens[i]-i | i in 1..n]);
% soft constraint business
nScs = 3; penalties = [2, 1, 1];
constraint queens[n div 2] = n div 2 <-> satisfied[1] ;
constraint queens[2] = queens[1] + 2 <-> satisfied[2];
constraint queens[3] = queens[2] + 2 <-> satisfied[3];
```

- If you manually set weights, just add them
- Switch from [1 | i in 1..nScs] to [2, 1, 1]

## Step 3: Prioritize Soft Constraints (Relations)

```
include "globals.mzn";
include "soft_constraints/soft_constraints.mzn";
include "soft_constraints/cr_types.mzn"; % graph types
include "soft_constraints/cr_weighting.mzn"; % weighting functions
int: n; array[1..n] of var 1..n: queens; n = 8;


solve :: int_search(queens, first_fail, indomain_median, complete)
minimize penSum; output["penSum = \(penSum), queens = \(queens)"];
constraint all_different(queens);
constraint all_different([queens[i]+i | i in 1..n]);
constraint all_different([queens[i]-i | i in 1..n]);
% soft constraint business
nScs = 3;
penalties = [weighting(s, SOFTCONSTRAINTS, crEdges, true)
              | s in SOFTCONSTRAINTS];
constraint queens[n div 2] = n div 2 <-> satisfied[1] ;
constraint queens[2] = queens[1] + 2 <-> satisfied[2];
constraint queens[3] = queens[2] + 2 <-> satisfied[3];
```

## Step 3: Prioritize Soft Constraints (Relations)

```
include "soft_constraints/cr_types.mzn"; % graph types
[... inside cr_types.mzn]
% constraint-relationship-types
int: nCrEdges;
array[1..nCrEdges, 1..2] of SOFTCONSTRAINTS: crEdges;
```

### Concrete instantiation


```
% data file for soft edges,
% constraint c1 is more important than c2 and c3
nCrEdges = 2;
crEdges = [| 2, 1 | 3, 1 |];
```



## Step 3: Prioritize Soft Constraints (Relations)

```
include "soft_constraints/cr_weighting.mzn"; % graph types
[... inside cr_weighting.mzn]
function int: weighting(int: s, set of int: softConstraints,
                        array[int, 1..2] of int: edges,
                        bool: useSPD);
% weigh each constraint higher than the largest child
function int: weightingSPD(int: s, set of int: softConstraints,
                           array[int] of set of int: dominees) = (
1 + max(s_ in dominees[s])(weightingSPD(s_, softConstraints, dominees)));

% weighting(s, SOFTCONSTRAINTS, crEdges, true)
[2, 1, 1]
% weighting(s, SOFTCONSTRAINTS, crEdges, false) more than chi. together
[3, 1, 1]
```



## Step 4: Switch to PVS Architecture

```
include "globals.mzn";
include "soft_constraints/soft_constraints.mzn";
include "soft_constraints/spd_worse.mzn"; % solution ordering
include "soft_constraints/pvs_spd.mzn"; % concrete PVS
int: n; array[1..n] of var 1..n: queens; n = 8; nScs = 3;

solve :: int_search(queens, first_fail, indomain_median, complete)
minimize penSum; output["penSum = \(penSum), queens = \(queens)"];
constraint all_different(queens);
constraint all_different([queens[i]+i | i in 1..n]);
constraint all_different([queens[i]-i | i in 1..n]);

constraint queens[n div 2] = n div 2 <-> satisfied[1] ;
constraint queens[2] = queens[1] + 2 <-> satisfied[2];
constraint queens[3] = queens[2] + 2 <-> satisfied[3];
```

- Defines *single-predecessor-dominance* as solution ordering with predicate `spd_worse`
- Hides the weight calculation in `pvs_spd.mzn`

**Idea** Many soft constraint formalisms are generalized by **partial valuation structures** that give the codomain of the objective function an *algebraic structure*.

- Defines *single-predecessor-dominance* as solution ordering with predicate `spd_worse`
- Hides the weight calculation in `pvs_spd.mzn`



