



Department of Informatics
King's College London
United Kingdom

7CCSMPRJ - Individual Project

Explainable Deep Learning for Portfolio Optimisation

Name: **Ingrid Pérez Aguilera**

Student Number: K24087939

Course: Computational Finance M.Sc.

Supervisor: **Riaz Ahmad**

Abstract

It is a précis of the report (normally in one page), which should include:

- A brief introduction to the project objectives
- A brief description of the main work of the project
- A brief description of the contributions, major findings, results achieved and principal conclusion of the project

Acknowledgements

It is a short paragraph to thank those who have contributed to the project work.

Table of Contents

1	Introduction	1
1.1	Objectives	3
1.2	Report Structure	4
2	Background	6
2.1	Portfolio Optimisation	6
2.1.1	Modern Portfolio Theory	7
2.2	Deep Reinforcement Learning	9
2.2.1	Reinforcement Learning	11
3	Methodology	16
4	Results	17
5	Legal, Social, Ethical and Professional Issues	18
6	Conclusion	19
	References	i
A	Appendix	iv

List of Figures

2.1	Efficient Frontier in Risk-Return Space. [1]	9
2.2	Agent interaction with environment	11
2.3	Markov Decision Process with policy, transition, and reward functions	13

List of Tables

Nomenclature

c Speed of light in a vacuum

h Planck constant

Glossary

Advantage Actor-Critic Algorithm that uses both an actor (policy) and a critic (value function) to learn optimal policies by estimating the advantage of actions taken. ix, 3

Algorithmic Trading Use of computer algorithms to automate trading decisions and execute trades in financial markets. 1

Artificial Intelligence Simulation of human intelligence processes by machines, especially computer systems, enabling them to perform tasks that typically require human intelligence, such as visual perception, speech recognition, decision-making, and language translation. ix, 2, 10

Bellman Equations Set of equations that describe the relationship between the value of a state or action and the values of subsequent states or actions in dynamic programming and reinforcement learning, used to compute optimal policies. 14

Deep Deterministic Policy Gradient Algorithm that uses deep neural networks to learn policies for continuous action spaces, combining the benefits of deep learning and policy gradient methods. viii, ix, 3

Deep Learning Subset of machine learning that uses neural networks with many layers to learn from large amounts of data, enabling the model to automatically learn complex patterns and representations. ix, 2, 4, 6, 9, 10

Deep Neural Network Type of artificial neural network with multiple layers that can learn complex representations and patterns in data. ix, 10

Deep Reinforcement Learning Combination of deep learning and reinforcement learning, where deep neural networks are used to approximate the value function or policy in reinforcement learning tasks. ix, 3, 6, 9

Efficient Frontier Set of optimal portfolios that offer the highest expected return for a given level of risk, or the lowest risk for a given level of expected return, in the context of portfolio optimisation. 8

Explainable Artificial Intelligence Methods and techniques in the application of artificial intelligence that make the results of the models understandable by humans, providing insights into how decisions are made. x, 2

Feature Importance Technique for determining the contribution of each feature in a machine learning model to its predictions, helping to identify which features are most influential. 4, 6

Financial Markets Marketplaces where people trade financial securities, commodities, and other fungible items of value at low transaction costs and at prices that reflect supply and demand. 1

Hyper-parameter Parameter that is set before the learning process begins and control the learning process of a machine learning model, such as learning rate, batch size, and number of layers in a neural network. 2

Local Interpretable Model-agnostic Explanations Technique for explaining the predictions of any machine learning model by approximating it with a locally interpretable model, allowing users to understand the model's behaviour in a specific instance. ix, 4–6

Machine Learning Subset of artificial intelligence that enables systems to learn from data and improve their performance over time without being explicitly programmed.

ix, 1, 6, 10

Markov Decision Process Mathematical framework for modelling decision-making in situations where outcomes are partly random and partly under the control of a decision maker, characterised by states, actions, rewards, and transition probabilities.

vii, ix, 11–13

Modern Portfolio Theory Investment theory that aims to construct a portfolio of assets that maximises expected return for a given level of risk, or minimises risk for a given level of expected return, through diversification. ix, 7

Partially Observable Markov Decision Process Extension of Markov Decision Process where the agent does not have access to the complete state information, requiring the use of belief states or observations to make decisions. ix, 13

Portfolio Optimisation Process of selecting the best distribution of assets in a portfolio to achieve specific investment goals, such as maximising returns or minimising risk, while considering constraints and preferences. 1, 6

Proximal Policy Optimization Algorithm that optimises policies by ensuring that updates to the policy are not too large, maintaining a balance between exploration and exploitation. ix, 3

Reinforcement Learning Subset of machine learning where an agent learns to make decisions by taking actions in an environment to maximise cumulative reward. ix, 2, 4, 6, 9, 10

Reward Function Function that defines the feedback signal received by an agent in reinforcement learning, guiding the agent’s learning process by providing rewards

or penalties based on its actions. 2

SHapley Additive exPlanations Method for interpreting machine learning models by assigning each feature an importance value for a particular prediction, based on cooperative game theory. x, 4, 6

Soft Actor-Critic Algorithm that combines the benefits of off-policy learning and entropy regularisation, allowing for more exploration and better stability in learning policies for continuous action spaces. x, 3

Supervised Learning Machine learning task where a model is trained on labelled data to learn a mapping from inputs to outputs. 10

Twin Delayed Deep Deterministic Policy Gradient Extension of Deep Deterministic Policy Gradient that addresses the overestimation bias in value function estimation by using two critic networks and delaying policy updates. x, 3

Unsupervised Learning Machine learning task where a model learns patterns or structures in unlabelled data without explicit supervision. 10

Acronyms

A2C Advantage Actor-Critic. 3, 4

AI Artificial Intelligence. 2, 10

DDPG Deep Deterministic Policy Gradient. 3, 4

DL Deep Learning. 2, 4, 6, 9, 10

DNN Deep neural network. 10

DRL Deep Reinforcement Learning. 3–6, 9

LIME Local Interpretable Model-agnostic Explanations. 4–6

MDP Markov Decision Process. 11–14

ML Machine Learning. 1–6, 10, 11

MPT Modern Portfolio Theory. 7, 9

POMDP Partially Observable Markov Decision Process. 13

PPO Proximal Policy Optimization. 3, 4

RL Reinforcement Learning. 2, 4, 6, 9–11, 15

SAC Soft Actor-Critic. 3, 4

SHAP SHapley Additive exPlanations. 4–6

TD3 Twin Delayed Deep Deterministic Policy Gradient. 3, 4

XAI Explainable Artificial Intelligence. 2

Chapter 1

Introduction

Financial markets are highly complex systems influenced by numerous factors, including financial and political events, social trends and technological advancements. Moreover, their evolving and stochastic nature requires using the most advance computational developments to model the financial environment. The tasks of financial time series prediction and Portfolio optimisation are considerably intricate, due to the semi-strong form of market efficiency and the high level of noise. [2]

Algorithmic trading focuses on the application of analytical methods to automatically execute trading actions based on an algorithm without human intervention. In its early days, the field mainly studied the usage of a computer program to follow a predefined strategy [3]. Nonetheless, in recent years, algorithmic trading has evolved to a problem in which environment perception entails learning feature representation from highly non-stationary and noisy financial time series data and decision-making requires the algorithm to explore the environment and simultaneously make correct decisions in an online manner without supervision [4].

Machine Learning (ML) is at an advantage for the task given its capability to learn from

historical data and make predictions about the future state of an environment. In the past years, research has explored the application of Deep Learning (DL) in future price prediction of financial assets [2, 5, 6, 7]. However, its main disadvantage is the inability to directly deal with trading, requiring an additional step to convert the predictions into actionable strategies. In contrast, Reinforcement Learning (RL) would allow the algorithm to learn a trading strategy directly from the environment, without the need for a separate step [8, 9]. In this case, there are two main approaches: first, the algorithm can learn the amount of assets to buy, sell or hold at each time step [10], or second, the algorithm can learn the optimal portfolio allocation and automatically rebalance the portfolio weights at each time step [11].

Despite the potential of RL in portfolio optimisation, its widespread adoption in the financial industry remains limited. This is primarily due to following challenges [12]:

1. difficulty in finding the appropriate algorithm with a suitable reward function and hyper-parameters to ensure efficiency and performance,
2. challenge of testing the algorithm in a real-world environment, and
3. lack of transparency of ML models, often referred to as black boxes, making it increasingly complex to interpret the algorithm's decisions.

In recent years, the rise in popularity of Artificial Intelligence (AI) and its widespread use have led to concerns regarding its decisions due to its black-box nature. The concept of explainability in AI, known as Explainable Artificial Intelligence (XAI), refers to a model's ability to provide details and reasons to make itself understandable [13]. The term was first coined in 2016 to describe the need for users to effectively understand, trust and manage artificial intelligence applications [14]. The need for explainability becomes particularly relevant in the context of financial usage, where the regulatory framework requires transparency and accountability in automated decision-making. Various relevant

applications, including volatility models [15], credit risk assessment [16] and portfolio construction [12] have explored the concept of explainability in financial applications. This highlights its importance and the need to explore its advantages in more complex models, without inadvertently increasing the complexity of the overall methodology.

Consequently, this thesis will focus on addressing the aforementioned challenges by exploring the application of Deep Reinforcement Learning (DRL) to portfolio optimisation and implementing post-hoc explainability techniques.

1.1 Objectives

The objective of this thesis is to develop an explainable Deep Reinforcement Learning model for portfolio optimisation. A DRL model has the ability to leverage historical financial data to learn an investment strategy that efficiently allocates financial assets while maximising expected returns and minimising risk. Moreover, the incorporation of advanced explainability techniques enhances the interpretability and transparency of the model’s decision-making. This project aims to bridge the gap between cutting-edge machine learning techniques and their practical application in finance by addressing the challenges of algorithm selection, simulation of real-world scenarios, and black box nature of ML models.

First, DRL models, such as Advantage Actor-Critic (A2C), Proximal Policy Optimization (PPO), Deep Deterministic Policy Gradient (DDPG), Twin Delayed Deep Deterministic Policy Gradient (TD3) and Soft Actor-Critic (SAC), will be implemented to learn the optimal portfolio allocation from high-dimensional environment representations. The algorithms will be trained on historical financial data, including technical and macroeconomic indicators, with the goal of capturing the complex market dynamics. Each of the algorithms is better suited to a particular scenario, for instance, DDPG

encourages maximum returns, while A2C reduces the variance.

Second, post-hoc explainability techniques: Feature Importance, SHapley Additive explanations (SHAP) values and Local Interpretable Model-agnostic Explanations (LIME) analysis, will be applied to interpret the model’s decisions. The goal of these is to understand which market conditions, represented by financial data, lead to the actions/decisions, encoded as portfolio weights.

Finally, the performance of the DRL models will be analysed in different scenarios, including the impact of a larger financial environment representation, portfolio size and asset composition. The results will be compared with traditional portfolio optimisation methods to evaluate the effectiveness of the proposed approach.

1.2 Report Structure

This report is organised into six chapters, each of which focuses on a concrete area related to the problem. Additional material, together with source code, is included in the appendices.

The current chapter, 1, presents the motivation and the objectives of this thesis. It gives an overview of the potential of DRL in portfolio optimisation and its main challenges, particularly the lack of transparency of ML models.

Chapter 2 provides an overview of the theoretical background of the project, including financial markets and machine learning concepts. The problem of portfolio optimisation in the financial domain is outlined and the potential of DRL in this context is discussed. The chapter provides a comprehensive background explanation of the fundamentals of Deep Learning and Reinforcement Learning, including the main algorithms (A2C, PPO, DDPG, TD3, SAC) and techniques in their intersection, DRL. In addition, it gives an overview of the post-hoc explainability techniques: feature importance, SHapley Addi-

tive exPlanations (SHAP) values and Local Interpretable Model-agnostic Explanations (LIME) analysis, which will be used to interpret the model's decisions. Finally, it includes a comprehensive in-depth literature review on the topics of ML applied to portfolio optimisation and relevant applications of explainability techniques.

The methodology chapter 3 describes the techniques and methods used to solve the problem and outlines the implementation of the proposed solution. The chapter provides a detailed explanation of the architecture and components of the proposed DRL model, including the state representation, reward function, and training process.

The results of the experiments are presented in chapter 4, which analyses and evaluates the results obtained from the proposed implementation, while critically discussing the findings. It provides a detailed comparison of the proposed DRL strategies with traditional portfolio optimisation methods. Furthermore, it consists of an in-depth analysis of the model's decisions using post-hoc explainability techniques, in particular, SHAP values, feature importance and LIME analysis.

Chapter 5 discusses the legal, social, ethical and professional implications within the context of the project. By addressing these issues, the project aims to ensure that the proposed solution adheres to industry standards, while considering the implications of the technology.

Finally, the report concludes with a summary of the main points of the work, the contributions made, the results achieved as well as potential applications and future work in chapter 6.

Chapter 2

Background

This chapter provides an overview of the problem of portfolio optimisation in the financial domain, followed by a comprehensive explanation of the fundamentals of Deep Learning (DL) and Reinforcement Learning (RL), including the relevant algorithms in the field of Deep Reinforcement Learning (DRL). In addition, it discusses the need for explainability in Machine Learning (ML) and the main techniques used to achieve it: SHapley Additive exPlanations (SHAP), Local Interpretable Model-agnostic Explanations (LIME) and Feature Importance. Finally, it presents the state of the art in portfolio optimisation using DRL and the recent advancements in explainability techniques in the field.

2.1 Portfolio Optimisation

Portfolio optimisation is the process of selecting optimal weights for a portfolio of assets in order to maximise expected returns for a given level of risk, or conversely, to minimise risk for a given level of expected returns [17]. In mathematical terms, the problem requires finding a solution to the specified objective function, which is typically a function of the expected returns and the risk associated with the portfolio [18]. The task becomes

further complicated if a time dimension is introduced, as the portfolio weights need to be adjusted over time to capture the changes in market conditions and asset prices [19].

2.1.1 Modern Portfolio Theory

There exist several traditional frameworks that formalise the problem of portfolio allocation. Markowitz's Modern Portfolio Theory (MPT) was proposed in 1952 [20] and it provides a mathematical framework where investors choose optimal portfolios based on risk and return, by either minimising the risk given a specified return or, maximising the return given a specified risk [21]. The theory extends the concept of diversification by suggesting that owning financial assets of different kinds is less risky than owning assets of the same kind, due to the correlations between assets.

The main assumptions in MPT are:

- investors are risk-averse, rational, and seek to maximise return for a given risk;
- returns are normally distributed;
- markets are frictionless, meaning there are no transaction costs; and
- assets are infinitely divisible.

Under these assumptions, portfolio risk and return can be modelled as an optimisation problem. Let $\mathbf{w} = (w_1, w_2, \dots, w_N)^T$ denote the portfolio weight vector, where each w_i indicates the proportion of capital allocated to asset i , subject to the budget constraint:

$$\sum_{i=1}^N w_i = 1 \quad \Leftrightarrow \quad \mathbf{w}^T \mathbf{1} = 1 \quad (2.1)$$

with $\mathbf{1} \in \mathbb{R}^N$ being a vector of ones, and subject to the non-negativity constraint,

meaning that short-selling is not allowed:

$$w_i \geq 0 \quad \forall i = 1, 2, \dots, N. \quad (2.2)$$

Let $\boldsymbol{\mu} = (R_1, R_2, \dots, R_N)^T$ represent the vector of expected returns, and $\Sigma \in \mathbb{R}^{N \times N}$ the covariance matrix of asset returns. The expected return of the portfolio is then given by:

$$R_p = \mathbf{w}^T \boldsymbol{\mu}, \quad (2.3)$$

and the portfolio risk is quantified by the variance of returns:

$$\sigma_p^2 = \mathbf{w}^T \Sigma \mathbf{w}. \quad (2.4)$$

This formulation provides the foundation for solving the mean-variance optimisation problem, by either:

- minimising portfolio variance σ_p^2 subject to a target expected return R_p , or
- maximising expected return R_p subject to a risk constraint σ_p .

The Markowitz mean-variance optimisation problem can be expressed as:

$$\begin{aligned} \min_{\mathbf{w}} \quad & \mathbf{w}^T \Sigma \mathbf{w} \\ \text{subject to} \quad & \begin{cases} \mathbf{w}^T \boldsymbol{\mu} = R_p \\ \mathbf{w}^T \mathbf{1} = 1 \\ \mathbf{w} \geq 0 \end{cases} \end{aligned} \quad (2.5)$$

Solving the mean-variance optimisation problem for varying levels of target return leads to a set of optimal portfolios that form the efficient frontier. It is typically visualised

in a risk-return space, where the x-axis represents the risk (standard deviation) and the y-axis represents the expected return, as shown in Figure 2.1. Portfolios below the curve are suboptimal, while those on the frontier represent the best achievable combinations of risk and return.




Figure 2.1: Efficient Frontier in Risk-Return Space. [1]

Despite the simplicity in the formulation of MPT, its assumptions do not reflect the behaviour of real markets. Moreover, modern markets are dynamic, non-stationary, and feature non-linear relationships, which have driven research into other approaches better suited to capture the complexities of modern financial markets.

2.2 Deep Reinforcement Learning

Deep Reinforcement Learning (DRL) is a sub-field of Deep Learning (DL) that combines Deep Learning (DL) and Reinforcement Learning (RL) to solve sequential decision-making problems with high-dimensionality in the environment representation. This ap-

proach has gained significant attention in recent years due to its success in various applications, including robotics, game playing, and finance.

ADD CITA-
TION

Machine Learning is a branch of Artificial Intelligence (AI) that focuses on the use of data and algorithms to imitate the way humans learn, gradually improving their accuracy over time. There are three main tasks in ML:

15

16

- **Supervised Learning:** Task of inferring a classification or regression from labelled training data, where the model learns to map inputs to outputs based on examples.
- **Unsupervised Learning:** Task of drawing inferences from datasets consisting of unlabelled input data, where the model learns to identify patterns or structures in the data.
- **Reinforcement Learning:** Task of training an agent to sequentially make decisions by taking actions in an environment with the goal of maximising cumulative reward, using feedback from the environment to learn.

Consequently, RL emerges as a framework for solving complex decision-making problems, where an agent continuously interacts with an environment, receiving observations about its states and rewards based on the actions taken. The agent's objective is to learn a policy that maximises the expected cumulative reward over time.

Conversely, Deep Learning is not a ML task, but rather a set of methods and techniques to solve such ML tasks, specially in supervised and unsupervised learning. DL focuses on the use of Deep neural network (DNN), which are characterised by a succession of layers of non-linear transformation that allow the model to learn a representation of the data with various levels of abstraction.

17

2.2.1 Reinforcement Learning

As mentioned, RL is a type of ML that solves the problem of sequential decision-making through continuous interaction with an environment. The agent learns to take actions given a representation of the environment's state with the goal of optimising a pre-defined notion of reward. The agent learns by successively adjusting its policy based on its observations and interactions with the environment.

The RL problem can be formalised as a discrete-time stochastic control process where an agent interacts with the environment. At each time step t , the agent observes the state of the environment $s_t \in \mathcal{S}$, takes an action $a_t \in \mathcal{A}$ to obtain a reward $r_t \in \mathbb{R}$ and transition to a new state $s_{t+1} \in \mathcal{S}$, where \mathcal{S} is the state space and \mathcal{A} is the action space. The agent's interaction with the environment is visually represented in Figure 2.2.1.




Figure 2.2: Agent interaction with environment

A discrete time stochastic control process can be formalised as a Markov Decision Process (MDP), if it fulfils the Markov Property.

Definition 2.2.1 (Markov Property). A discrete time stochastic control process satisfies

the Markov Property if:

$$P(s_{t+1}|s_t, a_t) = P(s_{t+1}|s_t, a_t, s_{t-1}, a_{t-1}, \dots, s_0, a_0) \quad (2.6)$$

$$P(r_t|s_t, a_t) = P(r_t|s_t, a_t, s_{t-1}, a_{t-1}, \dots, s_0, a_0) \quad (2.7)$$

where $P(s_{t+1}|s_t, a_t)$ is the transition probability of moving to state s_{t+1} given the current state s_t and action a_t , and $P(r_t|s_t, a_t)$ is the reward function that defines the expected reward received at time t given the current state and action.

This implies that the state s_{t+1} at a future time step $t + 1$ only depends on the current state s_t and action a_t . Similarly, the reward r_t at time step t only depends on the current state and action and not on the history of previous states and actions. Consequently, a Markov Decision Process is a discrete time stochastic control process defined as:

Definition 2.2.2 (Markov Decision Process). An MDP is a tuple $\mathcal{M} = (\mathcal{S}, \mathcal{A}, T, R, \gamma)$, where:

- \mathcal{S} is the state space: $s_t \in \mathcal{S}$,
- \mathcal{A} is the action space: $a_t \in \mathcal{A}$,
- $T : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \rightarrow [0, 1]$ is the transition function,
- $R : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \rightarrow \mathcal{R}$ is the reward function, where $\mathcal{R} \in [0, R_{max}]$ is the set of all possible rewards bounded by $R_{max} \in \mathbb{R}^+$, and
- $\gamma \in [0, 1)$ is the discount factor.

At each time step, the probability of advancing to the next state s_{t+1} is given by the transition function $T(s_t, a_t, s_{t+1})$ and the reward r_t is given by the reward function $R(s_t, a_t, s_{t+1})$. This can be visualised in Figure 2.2.1.




Figure 2.3: Markov Decision Process with policy, transition, and reward functions

The agent's objective is to learn a policy $\pi : \mathcal{S} \rightarrow \mathcal{A}$ that maps states to actions, in order to maximise the expected cumulative reward over time. In the case of a stochastic policy, it describes the probability that action a_t is taken in state s_t .

Markov Decision Process are based on the idea that the current state is fully representative of the environment. However, in most real world scenarios, the agent does not have access to the complete state. In such cases, Partially Observable Markov Decision Process (POMDP) can be used to model the uncertainty in the agent's observations and actions.

The goal of the agent is maximise the cumulative long-term reward G_t , which is defined as the sum of discounted rewards over time:

$$G_t = r_{t+1} + \gamma r_{t+2} + \gamma^2 r_{t+3} + \dots = r_{t+1} + \gamma G_{t+1} \quad (2.8)$$

where $\gamma \in [0, 1)$ is the discount factor and is used to balance the importance between immediate and future rewards. If the discount factor is set to 0, the agent is myopic and only maximises the immediate reward; whereas, as γ approaches 1, the agent becomes more far-sighted and places greater importance on future rewards.

The expected cumulative reward is defined as the state value function $V^\pi(s) : \mathcal{S} \rightarrow \mathbb{R}$,

which is the expected return when starting from state s and following policy π :

$$V^\pi(s) = \mathbb{E}_\pi [G_t | s_t = s] \quad (2.9)$$

where \mathbb{E}_π denotes the expectation over the policy π .

Similarly, the state-action value function $Q^\pi(s, a) : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$ is defined as the expected return when starting from state s , taking action a , and then following policy π :

$$Q^\pi(s, a) = \mathbb{E}_\pi [G_t | s_t = s, a_t = a] \quad (2.10)$$

The state value function $V^\pi(s)$ and the state-action value function $Q^\pi(s, a)$ are related as follows:

$$V^\pi(s) = \sum_{a \in \mathcal{A}} \pi(a|s) Q^\pi(s, a) = \mathbb{E}_\pi [Q^\pi(s, a) | s_t = s] \quad (2.11)$$

A policy π is said to be optimal if the policy's value function is the optimal value function of the MDP, defined as:

$$V^*(s) = \max_{\pi'} V^{\pi'}(s), \forall s \in \mathcal{S} \quad (2.12)$$

$$Q^*(s, a) = \max_{\pi'} Q^{\pi'}(s, a), \forall s \in \mathcal{S}, a \in \mathcal{A} \quad (2.13)$$

The optimal policy π^* is:

$$\pi^*(s) = \arg \max_{a \in \mathcal{A}} Q^*(s, a) \quad (2.14)$$

As a result, the optimal policy is the greedy policy that performs the optimal actions at each time step as determined by the optimal value functions. This enables the agent to determine optimal actions that maximise long-term returns by evaluating immediate information, without requiring knowledge of the values of future states and actions.

The Bellman equations provide a recursive relation between the value functions in terms

Bellman 1957

of the future state/action values. There are four main Bellman equations, classified in two groups: the Bellman expectation equations and the Bellman optimality equations. The Bellman expectation equations are defined as follows:

$$V^\pi(s) = \sum_{a \in \mathcal{A}} \pi(a | s) \sum_{s' \in \mathcal{S}} T(s, a, s') [R(s, a) + \gamma V^\pi(s')] \quad (2.15)$$

$$Q^\pi(s, a) = \sum_{s' \in \mathcal{S}} T(s, a, s') \left[R(s, a) + \gamma \sum_{a' \in \mathcal{A}} \pi(a' | s') Q^\pi(s', a') \right] \quad (2.16)$$

and the Bellman optimality equations are defined as:

$$V^*(s) = \max_{a \in \mathcal{A}} \sum_{s' \in \mathcal{S}} T(s, a, s') [R(s, a) + \gamma V^*(s')] \quad (2.17)$$

$$Q^*(s, a) = \sum_{s' \in \mathcal{S}} T(s, a, s') \left[R(s, a) + \gamma \max_{a' \in \mathcal{A}} Q^*(s', a') \right] \quad (2.18)$$

Although explicitly solving the Bellman equations would lead to the optimal policy, it is often intractable due to the size of the state and action spaces. Therefore, in RL algorithms, the goal is to learn an approximation of the optimal value functions, which can be used to derive the optimal policy. Another problem that arises is that of balancing exploration and exploitation. Theoretically, following the greedy action yields the optimal policy, but this is only true if the action values are known. In practice, the agent at each time step and given state chooses either an action whose value is higher, thus exploiting the current knowledge, or picks an action at random, thus exploring the environment and gaining more information about the state-action space, leading to potentially discovering a better action than the greedy one.

Chapter 3

Methodology

Chapter 4

Results

Chapter 5

Legal, Social, Ethical and Professional Issues

Chapter 6

Conclusion

References

- [1] Z. Bodie, A. Kane, and A. J. Marcus, *Investments*. McGraw-Hill Education, 10 ed., 2014.
- [2] J. Shen and M. O. Shafiq, “Short-term stock market price trend prediction using a comprehensive deep learning system,” *Journal of Big Data*, vol. 7, pp. 1–33, 12 2020.
- [3] K. Lei, B. Zhang, Y. Li, M. Yang, and Y. Shen, “Time-driven feature-aware jointly deep reinforcement learning for financial signal representation and algorithmic trading,” *Expert Systems with Applications*, vol. 140, p. 112872, 2 2020.
- [4] C. Ma, J. Zhang, J. Liu, L. Ji, and F. Gao, “A parallel multi-module deep reinforcement learning algorithm for stock trading,” *Neurocomputing*, vol. 449, pp. 290–302, 8 2021.
- [5] I. K. Nti, A. F. Adekoya, and B. A. Weyori, “A comprehensive evaluation of ensemble learning for stock-market prediction,” *Journal of Big Data*, vol. 7, pp. 1–40, 12 2020.
- [6] J. M. T. Wu, Z. Li, N. Herencsar, B. Vo, and J. C. W. Lin, “A graph-based cnn-lstm stock price prediction algorithm with leading indicators,” *Multimedia Systems*, vol. 29, pp. 1751–1770, 6 2023.

- [7] M. Hasan, M. Z. Abedin, P. Hajek, K. Coussement, M. N. Sultan, and B. Lucey, “A blending ensemble learning model for crude oil price forecasting,” *Annals of Operations Research*, pp. 1–31, 1 2024.
- [8] J. Moody and M. Saffell, “Learning to trade via direct reinforcement,” *IEEE Transactions on Neural Networks*, vol. 12, pp. 875–889, 7 2001.
- [9] H. Yang, X. Y. Liu, S. Zhong, and A. Walid, “Deep reinforcement learning for automated stock trading: An ensemble strategy,” *ICAIF 2020 - 1st ACM International Conference on AI in Finance*, 10 2020.
- [10] X.-Y. Liu, Z. Xiong, S. Zhong, H. Yang, and A. Walid, “Practical deep reinforcement learning approach for stock trading,” *NeurIPS 2018 AI in Finance Workshop.*, 11 2018.
- [11] M. Guan and X. Y. Liu, “Explainable deep reinforcement learning for portfolio management: An empirical approach,” *ICAIF 2021 - 2nd ACM International Conference on AI in Finance*, 11 2021.
- [12] D. G. Cortés, E. Onieva, I. Pastor, L. Trinchera, and J. Wu, “Portfolio construction using explainable reinforcement learning,” *Expert Systems*, vol. 41, p. e13667, 11 2024.
- [13] A. B. Arrieta, N. Díaz-Rodríguez, J. D. Ser, A. Bennetot, S. Tabik, A. Barbado, S. Garcia, S. Gil-Lopez, D. Molina, R. Benjamins, R. Chatila, and F. Herrera, “Explainable artificial intelligence (xai): Concepts, taxonomies, opportunities and challenges toward responsible ai,” *Information Fusion*, vol. 58, pp. 82–115, 10 2019.
- [14] D. Gunning, M. Stefik, J. Choi, T. Miller, S. Stumpf, and G. Z. Yang, “Xai—explainable artificial intelligence,” *Science Robotics*, vol. 4, 12 2019.

- [15] D. Brigo, X. Huang, A. Pallavicini, and H. S. de Ocariz Borde, “Interpretability in deep learning for finance: a case study for the heston model,” *SSRN Electronic Journal*, 4 2021.
- [16] R. García-Céspedes, F. J. Alias-Carrascosa, and M. Moreno, “On machine learning models explainability in the banking sector: the case of shap,” *Journal of the Operational Research Society*, 2025.
- [17] Y. Sato, “Model-free reinforcement learning for financial portfolios: A brief survey,” *arXiv preprint arXiv:1904.04973*, 4 2019.
- [18] B. Bruce and J. Greene, *Chapter 4 - Portfolio Construction*, pp. 133–178. Academic Press, 2014.
- [19] X. Li, Y. Li, Y. Zhan, and X.-Y. Liu, “Optimistic bull or pessimistic bear: Adaptive deep reinforcement learning for stock portfolio allocation,” *arXiv preprint arXiv:1907.01503*, 6 2019.
- [20] H. Markowitz, “Portfolio selection,” *The Journal of Finance*, vol. 7, pp. 77–91, 3 1952.
- [21] F. M. Clinic, “Mean variance portfolio theory.”

Appendix A

Appendix