

Simple, highly reliable network communication system



ISE5010D Industrial Switch

· Plug-and-play

· DIN-rail

· Fanless

· IP40

1. Product Overview

ISE5010D is designed specifically for power, transportation, industrial control, and other demanding industrial environments.


Features:

- **Robust design:** Robust metal casing, fanless design, and industrial-grade power supply design.
- **Wide adaptability:** Wide-temperature (-40 ~ +75°C) and wide-voltage design (18-60VDC).
- **International standard:** Complies with FCC, CE, ROHS standards and Excellent EMC.
- **Flexible uplink:** 2 x SFP fiber ports plus 8 x Gigabit RJ45 ports for versatile networking.
- **Easy deployment:** Plug-and-play, DIN rail mountable, compact size for quick deployment.

Key Technical Specifications

Parameter	Specification
Type	Layer 2 Unmanaged Industrial Ethernet Switch
Ports	2 x 100/1000BaseX SFP + 8 x 10/100/1000BaseT
Switching Performance	20 Gbps backplane, Store-and-Forward, 4K MAC
Dimensions / Weight	52 x 140 x 110 mm / 0.7 kg
Power	18-60 VDC, Redundant dual inputs
Environment	-40 to +75 C operating; IP40
EMC	IEC 61000-4-2/3/4/5/6 Class 3-4, IEC 61000-4-9 Class 5
Certifications	CE, FCC

2. Product Dimensions



ISE5010D

Note:

- 1. All dimensions are in millimeters (mm).
- 2. All dimensions are approximate and **for reference only**.
- 3. The dimensions shown in the figure **shall not be used for production or processing**.
- 4. Dimensions must comply with part and manufacturing tolerance requirements.
- 5. Dimensions are subject to change without notice.

3. Hardware Specifications

Category/Parameter	Specification
Physical Performance	
Enclosure	Fully enclosed seamless metal enclosure
Dimensions (W × D × H)	52 mm × 140 mm × 110 mm
Weight	0.7 kg

Category/Parameter	Specification
Mounting Method	DIN-rail mounting
Cooling Method	Fanless cooling
Protection Grade	IP40
Storage Temperature	-40 °C ~ +85 °C
Operating Temperature	-40 °C ~ +75 °C
Humidity	5 ~ 95% (non-condensing)
Hardware Performance	
Backplane Bandwidth	20 Gbps
Processing Type	Store-and-Forward
MAC Table Size	4K
Packet Buffer Size	1.5 Mbits
Exchange Rate	148,800 pps / 100M ports; 1,488,000 pps / 1000M ports
Power Parameters	
Operating Voltage	18-60 VDC, Redundant dual inputs
Protection	Overload Current Protection, Reverse Polarity Protection
Electromagnetic Characteristics	
EMS	IEC(EN)61000-4-2, Class 4; IEC(EN)61000-4-3, Class 3 IEC(EN)61000-4-4, Class 4; IEC(EN)61000-4-5, Class 4 IEC(EN)61000-4-6, Class 3; IEC(EN)61000-4-9, Class 5

Category/Parameter	Specification
Certifications	
Certifications	CE, FCC
Quality Assurance	
Warranty Period	5 years
MTBF	35 years

4. Ordering Guide

Model	Description
ISE5010D-P-2GSFP-8GT-24	Layer 2 unmanaged Industrial Switch. 2 <i>100/1000BaseX SFP Ports (SFP module not included)</i> , 8 10/ 100/ 1000 BaseT Ports. IP40 Protection Class, Operating Temperature from -40°C to +75°C. Isolated Dual 18-60VDC Power Inputs.

5. Contact Us

- Website: [InHand Networks](https://www.inhandnetworks.com)
- Copyright: ©InHand Networks All rights reserved