IR602

5G RedCap for Industrial IoT

5G RedCap • Dual-Band Wi-Fi 6 • 2.5GbE • Cloud-Managed



Built for space-conscious industrial installations.

- 3.87 × 3.62 × 0.94 in*
- DIN-rail or wall mounting
- Fanless metal housing · IP30
- –40°F to +158°F operation*




223 Mbps
DOWNLINK
IR602
INDUSTRIAL 5G ROUTER
123 Mbps
UPLINK
5G NR SA • LTE FDD/TDD


5 GHz
IR602
INDUSTRIAL 5G ROUTER
DC 9-48V
WAN/LAN1
LAN2
SIM 1
SIM 2
Reset
2.4 GHz
5 GHz:
up to 2402 Mbps*
2.4 GHz:
up to 574 Mbps*
Up to 64
connected devices*



IPsec · L2TP · WireGuard · OpenVPN

Stateful firewall and access control

SNAT/DNAT and port forwarding

Policy-based routing and QoS

1 × 2.5GbE (WAN/LAN) + 1 × 1GbE LAN

2 × DI/DO

12 V DC / 2 A industrial input

Power consumption ≤15 W





Dual-SIM
hot backup

Ethernet,
cellular &
Wi-Fi STA

ICMP/TCP
health checks

Priority failover
& multi-WAN

Embedded
watchdog

Device Live


Device Live
Overview
Devices
Groups
Alerts
Reports
Settings
Total Devices
1,000
Online / Offline
600 / 300
Inactive
100
Current Rate
10%
Configuration Status
60%
Synced 600
Pending 300
Failed 100
Device Health
96.7%
96.7%
Healthy
Offline Devices
Alerts (Top 5)
Today
Device Distribution


Device Live
Factory Site
Remoto Cabinet
Field Device


Cellular1
Cellular2
Wi-Fi
Wi-Fi



Smart Manufacturing



Smart Energy



Municipal Infrastructure



Transport Infrastructure



Environmental & Chemical Safety



Industrial Cabinet Deployment



IR602

5G RedCap