

3rd Generation Partnership Project;
Technical Specification Group Radio Access Network;
NR;
Requirements for support of radio resource management
(Release 15)



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP..

The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented.

This Specification is provided for future development work within 3GPP only. The Organizational

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia

Antipolis

Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65
47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2022, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP
Organizational Partners

Contents

Foreword	30
1 Scope	31
2 References	31
3 Definitions, symbols and abbreviations	32
3.1 Definitions.....	32
3.2 Symbols.....	33
3.3 Abbreviations	34
3.4 Test tolerances	36
3.5 Frequency bands grouping	36
3.5.1 Introduction	36
3.5.2 NR operating bands in FR1	36
3.5.3 NR operating bands in FR2.....	36
3.6 Applicability of requirements in this specification version	37
3.6.1 RRC connected state requirements in DRX.....	37
3.6.2 Number of serving carriers	38
3.6.2.1 Number of serving carriers for SA.....	38
3.6.2.2 Number of serving carriers for EN-DC.....	38
3.6.2.3 Number of serving carriers for NE-DC.....	38
3.6.2.4 Number of serving carriers for NR-DC	38
3.6.3 Applicability for intra-band FR2	38
3.6.4 Applicability for FR2 UE power classes.....	39
3.6.5 Applicability for SDL bands	39
3.6.6 Applicability of requirements for NGEN-DC operation	39
3.6.7 Applicability of QCL	39
4 SA: RRC_IDLE state mobility.....	39
4.1 Cell Selection	39
4.2 Cell Re-selection	39
4.2.1 Introduction.....	39
4.2.2 Requirements	40
4.2.2.1 UE measurement capability	40
4.2.2.2 Measurement and evaluation of serving cell	40
4.2.2.3 Measurements of intra-frequency NR cells	40
4.2.2.4 Measurements of inter-frequency NR cells	41
4.2.2.5 Measurements of inter-RAT E-UTRAN cells.....	43
4.2.2.6 Maximum interruption in paging reception	44
4.2.2.7 General requirements.....	44
5 SA: RRC_INACTIVE state mobility	45
5.1 Cell Re-selection	45
5.1.1 Introduction.....	45
5.1.2 Requirements	45
5.1.2.1 UE measurement capability	45
5.1.2.2 Measurement and evaluation of serving cell	45
5.1.2.3 Measurements of intra-frequency NR cells	45
5.1.2.4 Measurements of inter-frequency NR cells.....	45

5.1.2.5	Measurements of inter-RAT E-UTRAN cells.....	45
5.1.2.6	Maximum interruption in paging reception	45
5.1.2.7	General requirements	45
5.2	Void	46
6	RRC_CONNECTED state mobility	46
6.1	Handover	46
6.1.1	NR Handover.....	46
6.1.1.1	Introduction	46
6.1.1.2	NR FR1 - NR FR1 Handover.....	46
6.1.1.2.1	Handover delay	46
6.1.1.2.2	Interruption time.....	46
6.1.1.3	NR FR2- NR FR1 Handover	47
6.1.1.3.1	Handover delay	47
6.1.1.3.2	Interruption time.....	47
6.1.1.4	NR FR2- NR FR2 Handover.....	48
6.1.1.4.1	Handover delay	48
6.1.1.4.2	Interruption time.....	48
6.1.1.5	NR FR1- NR FR2 Handover	49
6.1.1.5.1	Handover delay	49
6.1.1.5.2	Interruption time.....	49
6.1.2	NR Handover to other RATs.....	50
6.1.2.1	NR – E-UTRAN Handover.....	50
6.1.2.1.1	Introduction.....	50
6.1.2.1.2	Handover delay	50
6.1.2.1.3	Interruption time.....	50
6.2	RRC Connection Mobility Control.....	51
6.2.1	SA: RRC Re-establishment.....	51
6.2.1.1	Introduction	51
6.2.1.2	Requirements.....	51
6.2.1.2.1	UE Re-establishment delay requirement	51
6.2.2	Random access	52
6.2.2.1	Introduction	52
6.2.2.2	Requirements.....	52
6.2.2.2.1	Contention based random access	53
6.2.2.2.2	Non-Contention based random access	54
6.2.2.2.3	UE behaviour when configured with supplementary UL.....	55
6.2.3	SA: RRC Connection Release with Redirection	55
6.2.3.1	Introduction	55
6.2.3.2	Requirements.....	55
6.2.3.2.1	RRC connection release with redirection to NR	55
6.2.3.2.2	RRC connection release with redirection to E-UTRAN.....	56
7	Timing	56
7.1	UE transmit timing	56
7.1.1	Introduction	56
7.1.2	Requirements	56
7.1.2.1	Gradual timing adjustment.....	57
7.1.2.2	Void.....	58

7.2	UE timer accuracy.....	58
7.2.1	Introduction.....	58
7.2.2	Requirements	58
7.3	Timing advance.....	58
7.3.1	Introduction.....	58
7.3.2	Requirements	59
7.3.2.1	Timing Advance adjustment delay	59
7.3.2.2	Timing Advance adjustment accuracy	59
7.4	Cell phase synchronization accuracy.....	59
7.4.1	Definition.....	59
7.4.2	Minimum requirements.....	59
7.5	Maximum Transmission Timing Difference.....	59
7.5.1	Introduction.....	59
7.5.2	Minimum Requirements for inter-band EN-DC	59
7.5.2.1	Minimum Requirements for inter-band synchronous EN-DC	60
7.5.3	Minimum Requirements for intra-band EN-DC	60
7.5.4	Minimum Requirements for NR Carrier Aggregation	61
7.5.5	Minimum Requirements for inter-band NE-DC	61
7.5.5.1	Minimum Requirements for inter-band synchronous NE-DC	61
7.5.6	Minimum Requirements for inter-band NR DC	62
7.6	Maximum Receive Timing Difference	62
7.6.1	Introduction.....	62
7.6.2	Minimum Requirements for inter-band EN-DC	62
7.6.2.1	Minimum Requirements for inter-band synchronous EN-DC	63
7.6.3	Minimum Requirements for intra-band EN-DC	63
7.6.4	Minimum Requirements for NR Carrier Aggregation	64
7.6.5	Minimum Requirements for inter-band NE-DC	64
7.6.5.1	Minimum Requirements for inter-band synchronous NE-DC	65
7.6.6	Minimum Requirements for inter-band NR DC	65
7.7	deriveSSB-IndexFromCell tolerance.....	65
7.7.1	Minimum requirements.....	65
7.8	Void	66
8	Signalling characteristics	66
8.1	Radio Link Monitoring.....	66
8.1.1	Introduction	66
8.1.2	Requirements for SSB based radio link monitoring.....	67
8.1.2.1	Introduction	67
8.1.2.2	Minimum requirement.....	68
8.1.2.3	Measurement restrictions for SSB based RLM	69
8.1.3	Requirements for CSI-RS based radio link monitoring	70
8.1.3.1	Introduction	70
8.1.3.2	Minimum requirement.....	70
8.1.3.3	Measurement restrictions for CSI-RS based RLM	72
8.1.4	Minimum requirement at transitions	73
8.1.5	Minimum requirement for UE turning off the transmitter.....	73
8.1.6	Minimum requirement for L1 indication	73
8.1.7	Scheduling availability of UE during radio link monitoring.....	74

8.1.7.1	Scheduling availability of UE performing radio link monitoring with a same subcarrier spacing as PDSCH/PDCCH on FR1	74
8.1.7.2	Scheduling availability of UE performing radio link monitoring with a different subcarrier spacing than PDSCH/PDCCH on FR1.....	74
8.1.7.3	Scheduling availability of UE performing radio link monitoring on FR2	74
8.1.7.4	Scheduling availability of UE performing radio link monitoring on FR1 or FR2 in case of FR1-FR2 inter-band CA and NR-DC	75
8.2	Interruption	75
8.2.1	EN-DC Interruption	75
8.2.1.1	Introduction	75
8.2.1.2	Requirements.....	76
8.2.1.2.1	Interruptions at transitions between active and non-active during DRX.....	76
8.2.1.2.2	Interruptions at transitions from non-DRX to DRX	76
8.2.1.2.3	Interruptions at SCell addition/release	76
8.2.1.2.4	Interruptions at SCell activation/deactivation	77
8.2.1.2.5	Interruptions during measurements on SCC	78
8.2.1.2.6	Interruptions at UL carrier RRC reconfiguration	79
8.2.1.2.7	Interruptions due to Active BWP switching Requirement.....	79
8.2.2	SA: Interruptions with Standalone NR Carrier Aggregation	80
8.2.2.1	Introduction	80
8.2.2.2	Requirements.....	80
8.2.2.2.1	Interruptions at SCell addition/release	80
8.2.2.2.2	Interruptions at SCell activation/deactivation	81
8.2.2.2.3	Interruptions during measurements on deactivated SCC.....	82
8.2.2.2.4	Interruptions at UL carrier RRC reconfiguration	82
8.2.2.2.5	Interruptions due to Active BWP switching Requirement.....	83
8.2.2.2.6	Interruptions at inter-frequency SFTD measurement.....	84
8.2.3	NE-DC Interruptions	85
8.2.3.1	Introduction	85
8.2.3.2	Requirements.....	85
8.2.3.2.1	Interruptions at transitions between active and non-active during DRX.....	85
8.2.3.2.2	Interruptions at transitions from non-DRX to DRX	86
8.2.3.2.3	Interruptions at PSCell/SCell addition/release	86
8.2.3.2.4	Interruptions at SCell activation/deactivation	87
8.2.3.2.5	Interruptions during measurements on SCC	88
8.2.3.2.6	Interruptions at UL carrier RRC reconfiguration	89
8.2.3.2.7	Interruptions due to Active BWP switching Requirement.....	89
8.2.4	NR-DC: Interruptions	89
8.2.4.1	Introduction	89
8.2.4.2	Requirements.....	90
8.2.4.2.1	Interruptions at PSCell/SCell addition/release	90
8.2.4.2.2	Interruptions at SCell activation/deactivation	90
8.2.4.2.3	Interruptions during measurements on SCC	91
8.2.4.2.4	Interruptions at UL carrier RRC reconfiguration	91
8.2.4.2.5	Interruptions due to Active BWP switching Requirement.....	92
8.2.4.2.6	Interruptions at transitions between active and non-active during DRX.....	92
8.2.4.2.7	Interruptions at transitions from non-DRX to DRX	92
8.3	SCell Activation and Deactivation Delay	92

8.3.1	Introduction	92
8.3.2	SCell Activation Delay Requirement for Deactivated SCell	93
8.3.3	SCell Deactivation Delay Requirement for Activated SCell	96
8.4	UE UL carrier RRC reconfiguration delay	97
8.4.1	Introduction	97
8.4.2	UE UL carrier configuration delay requirement	97
8.4.3	UE UL carrier deconfiguration delay requirement.....	97
8.5	Link Recovery Procedures	97
8.5.1	Introduction	97
8.5.2	Requirements for SSB based beam failure detection.....	98
8.5.2.1	Introduction	98
8.5.2.2	Minimum requirement.....	98
8.5.2.3	Measurement restriction for SSB based beam failure detection	100
8.5.3	Requirements for CSI-RS based beam failure detection	100
8.5.3.1	Introduction	100
8.5.3.2	Minimum requirement.....	101
8.5.3.3	Measurement restrictions for CSI-RS beam failure detection.....	103
8.5.4	Minimum requirement for L1 indication	103
8.5.5	Requirements for SSB based candidate beam detection.....	104
8.5.5.1	Introduction	104
8.5.5.2	Minimum requirement.....	104
8.5.5.3	Measurement restriction for SSB based candidate beam detection	106
8.5.6	Requirements for CSI-RS based candidate beam detection	106
8.5.6.1	Introduction	106
8.5.6.2	Minimum requirement.....	106
8.5.6.3	Measurement restriction for CSI-RS based candidate beam detection.....	108
8.5.7	Scheduling availability of UE during beam failure detection.....	109
8.5.7.1	Scheduling availability of UE performing beam failure detection with a same subcarrier spacing as PDSCH/PDCCH on FR1	109
8.5.7.2	Scheduling availability of UE performing beam failure detection with a different subcarrier spacing than PDSCH/PDCCH on FR1.....	109
8.5.7.3	Scheduling availability of UE performing beam failure detection on FR2	109
8.5.7.4	Scheduling availability of UE performing beam failure detection on FR1 or FR2 in case of FR1-FR2 inter-band CA and NR DC	110
8.5.8	Scheduling availability of UE during candidate beam detection.....	110
8.5.8.1	Scheduling availability of UE performing L1-RSRP measurement with a same subcarrier spacing as PDSCH/PDCCH on FR1	110
8.5.8.2	Scheduling availability of UE performing L1-RSRP measurement with a different subcarrier spacing than PDSCH/PDCCH on FR1.....	110
8.5.8.3	Scheduling availability of UE performing L1-RSRP measurement on FR2	110
8.5.8.4	Scheduling availability of UE performing L1-RSRP measurement on FR1 or FR2 in case of FR1-FR2 inter-band CA and NR-DC	111
8.5.9	Minimum requirement at transitions for beam failure detection.....	111
8.6	Active BWP switch delay.....	111
8.6.1	Introduction	111
8.6.2	DCI and timer based BWP switch delay	111
8.6.3	RRC based BWP switch delay.....	112
8.7	Void	113

8.8	NE-DC: E-UTRAN PSCell Addition and Release Delay	113
8.8.1	Introduction	113
8.8.2	E-UTRAN PSCell Addition Delay Requirement	113
8.8.3	E-UTRAN PSCell Release Delay Requirement.....	114
8.9	NR-DC: PSCell Addition and Release Delay	114
8.9.1	Introduction	114
8.9.2	PSCell Addition Delay Requirement.....	114
8.9.3	PSCell Release Delay Requirement	115
8.10	Active TCI state switching delay	115
8.10.6	Active TCI state list update delay.....	117
8.11	PSCell Change	117
9	Measurement Procedure.....	118
9.1	General measurement requirement.....	118
9.1.1	Introduction	118
9.1.2	Measurement gap	118
9.1.2.1	EN-DC: Measurement Gap Sharing	125
9.1.2.1a	SA: Measurement Gap Sharing	126
9.1.2.1b	NE-DC: Measurement Gap Sharing	127
9.1.2.1c	NR-DC: Measurement Gap Sharing	127
9.1.3	UE Measurement capability	128
9.1.3.1	EN-DC: Monitoring of multiple layers using gaps	128
9.1.3.1a	SA: Monitoring of multiple layers using gaps	129
9.1.3.1b	NE-DC: Monitoring of multiple layers using gaps	129
9.1.3.1c	NR-DC: Monitoring of multiple layers using gaps	129
9.1.3.2	EN-DC: Maximum allowed layers for multiple monitoring	130
9.1.3.2a	SA: Maximum allowed layers for multiple monitoring	130
9.1.3.2b	NE-DC: Maximum allowed layers for multiple monitoring	131
9.1.3.2c	NR-DC: Maximum allowed layers for multiple monitoring	131
9.1.4	Capabilities for Support of Event Triggering and Reporting Criteria	132
9.1.4.1	Introduction	132
9.1.4.2	Requirements.....	132
9.1.5	Carrier-specific scaling factor.....	133
9.1.5.1	Monitoring of multiple layers outside gaps.....	133
9.1.5.1.1	EN-DC mode: carrier-specific scaling factor for SSB-based measurements performed outside gaps	134
9.1.5.1.2	SA mode: carrier-specific scaling factor for SSB-based measurements performed outside gaps	135
9.1.5.1.3	NR-DC mode: carrier-specific scaling factor for SSB-based measurements performed outside gaps	136
9.1.5.1.4	NE-DC mode: carrier-specific scaling factor for SSB-based measurements performed outside gaps	136
9.1.5.2	Monitoring of multiple layers within gaps.....	136
9.1.5.2.1	EN-DC mode: carrier-specific scaling factor for SSB-based measurements performed within gaps	137
9.1.5.2.2	SA mode: carrier-specific scaling factor for SSB-based measurements performed within gaps	138
9.1.5.2.3	NE-DC: carrier-specific scaling factor for SSB-based measurements performed within gaps	139

9.1.5.2.4	NR-DC: carrier-specific scaling factor for SSB-based measurements performed within gaps	141
9.1.6	Minimum requirement at transitions	142
9.2	NR intra-frequency measurements	142
9.2.1	Introduction	142
9.2.2	Requirements applicability.....	143
9.2.3	Number of cells and number of SSB	143
9.2.3.1	Requirements for FR1	143
9.2.3.2	Requirements for FR2	143
9.2.4	Measurement Reporting Requirements	144
9.2.4.1	Periodic Reporting	144
9.2.4.2	Event-triggered Periodic Reporting	144
9.2.4.3	Event Triggered Reporting	144
9.2.5	Intrafrequency measurements without measurement gaps	144
9.2.5.1	Intrafrequency cell identification	144
9.2.5.2	Measurement period	147
9.2.5.3	Scheduling availability of UE during intra-frequency measurements	148
9.2.5.3.1	Scheduling availability of UE performing measurements in TDD bands on FR1	148
9.2.5.3.2	Scheduling availability of UE performing measurements with a different subcarrier spacing than PDSCH/PDCCH on FR1.....	148
9.2.5.3.3	Scheduling availability of UE performing measurements on FR2.....	149
9.2.5.3.4	Scheduling availability of UE performing measurements on FR1 or FR2 in case of FR1-FR2 inter-band CA	150
9.2.5.4	SFTD Measurements between PCell and PSCell.....	150
9.2.5.4.1	Introduction.....	150
9.2.5.4.2	SFTD Measurement delay	150
9.2.5.4.3	SFTD Measurement Reporting Delay	151
9.2.6	Intra-frequency measurements with measurement gaps.....	151
9.2.6.1	Void.....	151
9.2.6.2	Intra-frequency cell identification.....	151
9.2.6.3	Intra-frequency Measurement Period	152
9.3	NR inter-frequency measurements	153
9.3.1	Introduction	153
9.3.2	Requirements applicability.....	153
9.3.2.1	Void	154
9.3.2.2	Void	154
9.3.3	Number of cells and number of SSB	154
9.3.3.1	Requirements for FR1	154
9.3.3.2	Requirements for FR2	154
9.3.4	Inter-frequency cell identification	154
9.3.4.1	Void	155
9.3.4.2	Void	155
9.3.5	Inter-frequency measurements	155
9.3.5.1	Void	156
9.3.5.2	Void	156
9.3.5.3	Void	156
9.3.6	Inter-frequency measurements reporting requirements.....	156

9.3.6.1	Periodic Reporting	156
9.3.6.2	Event-triggered Periodic Reporting	156
9.3.6.3	Event-triggered Reporting	156
9.3.7	Void	157
9.3.8	Inter-frequency SFTD measurement requirements	157
9.3.8.1	Introduction	157
9.3.8.2	SFTD Measurement delay	157
9.3.8.3	SFTD Measurement reporting delay	158
9.4	Inter-RAT measurements	158
9.4.1	Introduction	158
9.4.2	NR – E-UTRAN FDD measurements	159
9.4.2.1	Introduction	159
9.4.2.2	Requirements when no DRX is used	160
9.4.2.3	Requirements when DRX is used	160
9.4.2.4	Measurement reporting requirements	161
9.4.2.4.1	Periodic Reporting	161
9.4.2.4.2	Event-Triggered Periodic Reporting	161
9.4.2.4.3	Event-Triggered Reporting	161
9.4.3	NR – E-UTRAN TDD measurements	162
9.4.3.1	Introduction	162
9.4.3.2	Requirements when no DRX is used	162
9.4.3.3	Requirements when DRX is used	163
9.4.3.4	Measurement reporting requirements	164
9.4.3.4.1	Periodic Reporting	164
9.4.3.4.2	Event-Triggered Periodic Reporting	164
9.4.3.4.3	Event-Triggered Reporting	164
9.4.4	Inter-RAT RSTD measurements	164
9.4.4.1	NR – E-UTRAN FDD RSTD measurements	164
9.4.4.1.1	Introduction	164
9.4.4.1.2	Requirements	165
9.4.4.2	NR – E-UTRAN TDD RSTD measurements	168
9.4.4.2.1	Introduction	168
9.4.4.2.2	Requirements	169
9.4.5	Inter-RAT E-CID measurements	172
9.4.5.1	NR–E-UTRAN FDD E-CID RSRP and RSRQ measurements	172
9.4.5.1.1	Introduction	172
9.4.5.1.2	Requirements	172
9.4.5.1.3	Measurement Reporting Delay	172
9.4.5.2	NR–E-UTRAN TDD E-CID RSRP and RSRQ measurements	172
9.4.5.2.1	Introduction	172
9.4.5.2.2	Requirements	172
9.4.5.2.3	Measurement Reporting Delay	173
9.5	L1-RSRP measurements for Reporting	173
9.5.1	Introduction	173
9.5.2	Requirements applicability	173
9.5.3	Measurement Reporting Requirements	173
9.5.3.1	Periodic Reporting	174
9.5.3.2	Semi-Persistent Reporting	174

9.5.3.3	Aperiodic Reporting.....	174
9.5.4	L1-RSRP measurement requirements	174
9.5.4.1	SSB based L1-RSRP Reporting	174
9.5.4.2	CSI-RS based L1-RSRP Reporting	176
9.5.5	Measurement restriction for CSI-RS and SSB for L1-RSRP measurement	178
9.5.5.1	Measurement restriction for SSB based L1-RSRP.....	179
9.5.5.2	Measurement restriction for CSI-RS based L1-RSRP	179
9.5.6	Scheduling availability of UE during L1-RSRP measurement.....	180
9.5.6.1	Scheduling availability of UE performing L1-RSRP measurement with a same subcarrier spacing as PDSCH/PDCCH on FR1	180
9.5.6.2	Scheduling availability of UE performing L1-RSRP measurement with a different subcarrier spacing than PDSCH/PDCCH on FR1.....	180
9.5.6.3	Scheduling availability of UE performing L1-RSRP measurement on FR2.....	180
9.5.6.4	Scheduling availability of UE performing L1-RSRP measurement on FR1 or FR2 in case of FR1-FR2 inter-band CA	181
9.6	NE-DC: Measurements	181
9.6.1	Introduction	181
9.6.2	SFTD Measurements	181
9.6.2.1	Introduction	181
9.6.2.2	SFTD Measurement requirements	181
10	Measurement Performance requirements.....	182
10.1	NR measurements.....	182
10.1.1	Introduction	182
10.1.2	Intra-frequency RSRP accuracy requirements for FR1.....	183
10.1.2.1	Intra-frequency SS-RSRP accuracy requirements	183
10.1.2.1.1	Absolute SS-RSRP Accuracy.....	183
10.1.2.1.2	Relative SS-RSRP Accuracy	183
10.1.2.2	Void.....	184
10.1.3	Intra-frequency RSRP accuracy requirements for FR2	184
10.1.3.1	Intra-frequency SS-RSRP accuracy requirements	184
10.1.3.1.1	Absolute SS-RSRP Accuracy.....	184
10.1.3.1.2	Relative SS-RSRP Accuracy	185
10.1.3.2	Void.....	186
10.1.4	Inter-frequency RSRP accuracy requirements for FR1.....	186
10.1.4.1	Inter-frequency SS-RSRP accuracy requirements	186
10.1.4.1.1	Absolute Accuracy of SS-RSRP in FR1.....	186
10.1.4.1.2	Relative Accuracy of SS-RSRP in FR1	186
10.1.4.2	Void.....	187
10.1.5	Inter-frequency RSRP accuracy requirements for FR2	187
10.1.5.1	Inter-frequency SS-RSRP accuracy requirements	187
10.1.5.1.1	Absolute SS-RSRP Accuracy.....	187
10.1.5.1.2	Relative SS-RSRP Accuracy	188
10.1.5.2	Void.....	189
10.1.6	RSRP Measurement Report Mapping	189
10.1.7	Intra-frequency RSRQ accuracy requirements for FR1	191
10.1.7.1	Intra-frequency SS-RSRQ accuracy requirements in FR1	191
10.1.7.1.1	Absolute SS-RSRQ Accuracy in FR1.....	191
10.1.8	Intra-frequency RSRQ accuracy requirements for FR2.....	192

10.1.8.1	Intra-frequency SS-RSRQ accuracy requirements in FR2	192
10.1.8.1.1	Absolute SS-RSRQ Accuracy in FR2	192
10.1.9	Inter-frequency RSRQ accuracy requirements for FR1	193
10.1.9.1	Inter-frequency SS-RSRQ accuracy requirements in FR1	193
10.1.9.1.1	Absolute Accuracy of SS-RSRQ in FR1	193
10.1.9.1.2	Relative Accuracy of SS-RSRQ in FR1.....	194
10.1.10	Inter-frequency RSRQ accuracy requirements for FR2.....	194
10.1.11	RSRQ report mapping	196
10.1.12	Intra-frequency SINR accuracy requirements for FR1.....	196
10.1.13	Intra-frequency SINR accuracy requirements for FR2	197
10.1.14	Inter-frequency SINR accuracy requirements for FR1	198
10.1.15	Inter-frequency SINR accuracy requirements for FR2	199
10.1.16	SINR report mapping.....	201
10.1.17	Power Headroom	201
10.1.18	$P_{\text{CMAX},c,f}$	202
10.1.19	L1-RSRP accuracy requirements for FR1	202
10.1.20	L1-RSRP accuracy requirements for FR2	206
10.1.21	SFTD accuracy requirements	209
10.2	E-UTRAN measurements	213
10.2.1	Introduction	213
10.2.2	E-UTRAN RSRP measurements	213
10.2.3	E-UTRAN RSRQ measurements	214
10.2.4	E-UTRAN RSTD measurements	214
10.2.5	E-UTRAN RS-SINR measurements	214
11	Void.....	214
Annex A (normative): Test Cases		212
A.1	Purpose of annex	212
A.2	Requirement classification for statistical testing	212
A.2.1	Types of requirements in TS 38.133	212
A.2.1.1	Time and delay requirements on UE higher layer actions	212
A.2.1.2	Measurements of power levels, relative powers and time	213
A.2.1.3	Implementation requirements.....	213
A.2.1.4	Physical layer timing requirements.....	213
A.3	RRM test configurations.....	214
A.3.1	Reference measurement channels.....	214
A.3.1.1	PDSCH	214
A.3.1.1.1	FDD	214
A.3.1.1.2	TDD	215
A.3.1.2	CORESET for RMSI scheduling.....	218
A.3.1.2.1	FDD	218
A.3.1.2.2	TDD	219
A.3.1.3	CORESET for RMC scheduling.....	222
A.3.1.3.1	FDD	222
A.3.1.3.2	TDD	223
A.3.1.4	TDD UL/DL configuration	226
A.3.2	OFDMA channel noise generator (OCNG)	227

A.3.2.1	Generic OFDMA Channel Noise Generator (OCNG).....	227
A.3.2.1.1	OCNG pattern 1: Generic OCNG pattern for all unused REs.....	227
A.3.2.1.2	OCNG pattern 2: Generic OCNG pattern for all unused REs for 2AoA setup.....	228
A.3.2.1.3	OCNG pattern 3: Generic OCNG pattern for unused REs in the same bandwidth as CORESET	228
A.3.2.1.4	OCNG pattern 4: Generic OCNG pattern for all unused REs outside SSB slot(s).....	229
A.3.2.2	Void.....	230
A.3.3	Reference DRX configurations	230
A.3.3.1	DRX Configuration 1: DRX cycle = 40 ms and TAT = 500 ms	230
A.3.3.2	DRX Configuration 2: DRX cycle = 640 ms and TAT = 500 ms.....	230
A.3.3.3	DRX Configuration 3: DRX cycle = 40 ms and TAT = Infinity	231
A.3.3.4	DRX Configuration 4: DRX cycle = 160 ms and TAT = Infinity	231
A.3.3.5	DRX Configuration 5: DRX cycle = 320 ms and TAT = Infinity	231
A.3.3.6	DRX Configuration 6: DRX cycle = 320 ms and TAT = 500 ms.....	232
A.3.3.7	DRX Configuration 7: DRX cycle = 640 ms and TAT = Infinity	232
A.3.3.8	DRX Configuration 8: DRX cycle = 320 ms and TAT = Infinity	232
A.3.3.9	DRX Configuration 9: DRX cycle = 40 ms and TAT = 500 ms.....	233
A.3.3.10	DRX Configuration 10: DRX cycle = 640 ms and TAT = 500 ms.....	233
A.3.3.11	DRX Configuration 11: DRX cycle = 20 ms and TAT = Infinity.....	233
A.3.3.12	DRX Configuration 12: DRX cycle = 640 ms and TAT = Infinity.....	234
A.3.4	Test Cases with Different Channel Bandwidths.....	234
A.3.4.1	Test Cases with Different E-UTRA Channel Bandwidths	234
A.3.4.1.1	Introduction	234
A.3.4.1.2	Principle of testing.....	234
A.3.5	Test Cases for Synchronous and Asynchronous DC Operations.....	234
A.3.5.1	EN-DC Test Cases for Synchronous and Asynchronous EN-DC Operations	234
A.3.5.1.1	Introduction	234
A.3.5.1.2	Principle of Testing	235
A.3.6	Antenna configurations	235
A.3.6.1	Antenna configurations for FR1.....	235
A.3.6.1.1	Antenna connection for 4 Rx capable UEs	235
A.3.6.1.1.1	Introduction.....	235
A.3.6.1.1.2	Principle of testing	235
A.3.6.2	Antenna configurations for FR2.....	238
A.3.7	EN-DC test setup	238
A.3.7.1	Introduction.....	238
A.3.7.2	E-UTRAN Serving Cell Parameters	238
A.3.7.2.1	E-UTRAN Serving Cell Parameters for Tests with NR Cell(s) in FR1.....	238
A.3.7.2.2	E-UTRAN Serving Cell Parameters for Tests with NR Cell(s) in FR2	239
A.3.7A	NR FR1-FR2 test setup	240
A.3.7B	Void	240
A.3.7C	LTE-FR1/FR2 test setup	241
A.3.7D	NE-DC test setup	241
A.3.7D.1	Introduction.....	241
A.3.7D.2	E-UTRAN Serving Cell Parameters	241
A.3.7D.2.1	E-UTRAN Serving Cell Parameters for Tests with NR Cell(s) in FR1.....	241
A.3.7D.2.2	E-UTRAN Serving Cell Parameters for Tests with NR Cell(s) in FR2	241
A.3.8	PRACH configurations.....	241

A.3.8.1	Introduction	241
A.3.8.2	PRACH configurations in FR1.....	241
A.3.8.2.1	FR1 PRACH configuration 1	241
A.3.8.2.2	FR1 PRACH configuration 2.....	242
A.3.8.2.3	FR1 PRACH configuration 3.....	243
A.3.8.2.4	FR1 PRACH configuration 4	244
A.3.8.3	PRACH configurations in FR2	245
A.3.8.3.1	FR2 PRACH configuration 1.....	245
A.3.8.3.2	FR2 PRACH configuration 2	246
A.3.8.3.3	FR2 PRACH configuration 3	247
A.3.8.3.4	FR2 PRACH configuration 4	248
A.3.9	BWP configurations	249
A.3.9.1	Introduction	249
A.3.9.2	Downlink BWP configurations	250
A.3.9.2.1	Initial BWP	250
A.3.9.2.2	Dedicated BWP	250
A.3.9.3	Uplink BWP configurations	250
A.3.9.3.1	Initial BWP	250
A.3.9.3.2	Dedicated BWP	251
A.3.10	SSB Configurations.....	251
A.3.10.1	SSB Configurations for FR1.....	251
A.3.10.1.1	SSB pattern 1 in FR1: SSB allocation for SSB SCS=15 kHz in 10 MHz.....	251
A.3.10.1.2	SSB pattern 2 in FR1: SSB allocation for SSB SCS=30 kHz in 40 MHz.....	252
A.3.10.1.3	SSB pattern 3 in FR1: SSB allocation for SSB SCS=15 kHz in 10 MHz	252
A.3.10.1.4	SSB pattern 4 in FR1: SSB allocation for SSB SCS=30 kHz in 40 MHz	253
A.3.10.1.5	SSB pattern 5 in FR1: SSB allocation for SSB SCS=15 kHz starting from odd SFN in 10 MHz.....	254
A.3.10.1.6	SSB pattern 6 in FR1: SSB allocation for SSB SCS=30 kHz starting from odd SFN in 40 MHz	254
A.3.10.2	SSB Configurations for FR2	255
A.3.10.2.1	SSB pattern 1 in FR2: SSB allocation for SSB SCS=120 kHz in 100 MHz	255
A.3.10.2.2	SSB pattern 2 in FR2: SSB allocation for SSB SCS=240 kHz in 100 MHz.....	255
A.3.10.2.3	SSB pattern 3 in FR2: SSB allocation for SSB SCS=120 kHz in 100 MHz	256
A.3.10.2.4	SSB pattern 4 in FR2: SSB allocation for SSB SCS=240 kHz in 100 MHz	256
A.3.10.2.5	SSB pattern 5 in FR2: SSB allocation for SSB SCS=120 kHz in 100 MHz	257
A.3.10.2.6	SSB pattern 6 in FR2: SSB allocation for SSB SCS=240 kHz in 100 MHz	257
A.3.10.2.7	SSB pattern 7 in FR2: SSB allocation for SSB SCS=120 kHz in 100 MHz	258
A.3.10.2.8	SSB pattern 8 in FR2: SSB allocation for SSB SCS=240 kHz in 100 MHz	258
A.3.11	SMTC Configurations	258
A.3.11.1	SMTC pattern 1: SMTC period = 20 ms with SMTC duration = 1 ms	258
A.3.11.2	SMTC pattern 2: SMTC period = 20 ms with SMTC duration = 5 ms	259
A.3.11.3	SMTC pattern 3: SMTC period = 160 ms with SMTC duration = 1 ms.....	259
A.3.11.4	SMTC pattern 4: SMTC period = 20 ms with SMTC duration = 1 ms	259
A.3.11.5	SMTC pattern 5: SMTC period = 20 ms with SMTC duration = 5 ms.....	259
A.3.11.6	SMTC pattern 6: SMTC period = 20 ms with SMTC duration = 5 ms.....	260
A.3.12	Test Cases with Different CC Configurations	260
A.3.12.1	EN-DC Test Cases with Different EN-DC Configurations	260
A.3.12.1.1	Introduction	260

A.3.12.1.2	Principle of testing.....	260
A.3.12.2	Carrier Aggregation Test Cases with Different CA Configurations	260
A.3.12.2.1	Introduction	260
A.3.12.2.2	Principle of testing.....	260
A.3.13	Test Cases in SA and EN-DC Operations	261
A.3.13.1	Introduction	261
A.3.13.2	Principle of Testing.....	261
A.3.13A	Test Cases involving E-UTRA/FR1 and FR2 carriers	261
A.3.13A.1	Introduction.....	261
A.3.13A.2	Principle of Testing in EN-DC.....	261
A.3.13A.3	Principle of Testing in SA.....	262
A.3.13A.4	Principle of Testing in E-UTRA.....	262
A.3.13B	Test Cases for EN-DC and NE-DC Operations	263
A.3.13B.1	Active BWP switch Test Cases for EN-DC and NE-DC Operations	263
A.3.13B.1.1	Introduction	263
A.3.13B.1.2	Principle of Testing	263
A.3.13B.2	SFTD accuracy Test Cases for EN-DC and NE-DC Operations	263
A.3.13B.2.1	Introduction	263
A.3.13B.2.2	Principle of Testing	263
A.3.14	CSI-RS configurations.....	263
A.3.14.1	FDD.....	263
A.3.14.2	TDD.....	264
A.3.15	Angle of Arrival (AoA) for FR2 RRM test cases.....	267
A.3.15.1	Setup 1: Single AoA in Rx beam peak direction.....	267
A.3.15.2	Setup 2: Single AoA in non Rx beam peak direction.....	267
A.3.15.2.1	Setup 2a: Single AoA in non Rx beam peak direction without change in direction	267
A.3.15.2.2	Setup 2b: Single AoA in non Rx beam peak direction with change in direction ..	267
A.3.15.3	Setup 3: 2 AoAs	267
A.3.15.4	Setup 4: 2 AoAs, 1 AoA in Rx beam peak direction, 1 in non Rx beam peak	268
A.3.15.4.1	Setup 4a: 2 AoAs, 1 AoA in Rx beam peak direction, 1 in non Rx beam peak without change in direction	268
A.3.15.4.2	Setup 4b: 2 AoAs, 1 AoA in Rx beam peak direction, 1 in non Rx beam peak with change in direction	268
A.3.16	TCI State Configuration.....	268
A.3.16.1	Introduction.....	268
A.3.16.2	TCI states.....	269
A.3.17	Configurations of CSI-RS for tracking.....	269
A.3.17.1	Configuration of CSI-RS for tracking for FR1	269
A.3.17.1.1	FDD	269
A.3.17.1.2	TDD	270
A.3.17.2	Configuration of CSI-RS for tracking for FR2.....	271
A.3.17.2.1	TDD	271
A.3.18	Additional definitions related to OTA testing for FR2 RRM test cases.....	272
A.3.18.1	Introduction	272
A.3.18.2	PRACH Power Measurement	272
A.4	EN-DC tests with all NR cells in FR1	273
A.4.1	Void	273

A.4.2	Void	273
A.4.3	RRC_CONNECTED state mobility.....	273
A.4.3.1	Void.....	273
A.4.3.2	RRC Connection Mobility Control	273
A.4.3.2.1	Void.....	273
A.4.3.2.2	Random Access	273
A.4.3.2.2.1	Contention based random access test in FR1 for PSCell in EN-DC	273
A.4.3.2.2.1.1	Test Purpose and Environment	273
A.4.3.2.2.2	Non-contention based random access test in FR1 for PSCell in EN-DC	276
A.4.3.2.3	Void.....	279
A.4.4	Timing	279
A.4.4.1	UE transmit timing.....	279
A.4.4.1.1	NR UE Transmit Timing Test for FR1	279
A.4.4.1.1.1	Test Purpose and environment	279
A.4.4.1.1.2	Test requirements	282
A.4.4.2	UE timer accuracy.....	283
A.4.4.3	Timing advance.....	283
A.4.4.3.1	EN-DC FR1 timing advance adjustment accuracy	283
A.4.4.3.1.1	Test Purpose and Environment	283
A.4.4.3.1.2	Test Parameters	283
A.4.4.3.1.3	Test Requirements	286
A.4.5	Signaling characteristics	286
A.4.5.1	Radio link Monitoring.....	286
A.4.5.1.1	Radio Link Monitoring Out-of-sync Test for FR1 PSCell configured with SSB- based RLM RS in non-DRX mode	287
A.4.5.1.1.1	Test Purpose and Environment	287
A.4.5.1.1.2	Test Requirements	290
A.4.5.1.2	Radio Link Monitoring In-sync Test for FR1 PSCell configured with SSB-based RLM RS in non-DRX mode	290
A.4.5.1.2.2	Test Requirements	294
A.4.5.1.3	Radio Link Monitoring Out-of-sync Test for FR1 PSCell configured with SSB- based RLM RS in DRX mode	294
A.4.5.1.3.1	Test Purpose and Environment	294
A.4.5.1.3.2	Test Requirements	297
A.4.5.1.4	Radio Link Monitoring In-sync Test for FR1 PSCell configured with SSB-based RLM RS in DRX mode.....	298
A.4.5.1.4.1	Test Purpose and Environment	298
A.4.5.1.4.2	Test Requirements	301
A.4.5.1.5	EN-DC Radio Link Monitoring Out-of-sync Test for FR1 PSCell configured with CSI-RS-based RLM in non-DRX mode	302
A.4.5.1.5.1	Test Purpose and Environment	302
A.4.5.1.5.2	Test Requirements	305
A.4.5.1.6	EN-DC Radio Link Monitoring In-sync Test for FR1 PSCell configured with CSI- RS-based RLM in non-DRX mode	305
A.4.5.1.6.1	Test Purpose and Environment	305
A.4.5.1.6.2	Test Requirements	309
A.4.5.1.7	EN-DC Radio Link Monitoring Out-of-sync Test for FR1 PSCell configured with CSI-RS-based RLM in DRX mode	309

A.4.5.1.7.1	Test Purpose and Environment	309
A.4.5.1.7.2	Test Requirements	313
A.4.5.1.8	EN-DC Radio Link Monitoring In-sync Test for FR1 PSCell configured with CSI- RS-based RLM in DRX mode	313
A.4.5.1.8.1	Test Purpose and Environment	313
A.4.5.1.8.2	Test Requirements	317
A.4.5.2	Interruption	317
A.4.5.2.1	E-UTRAN – NR FR1 interruptions at transitions between active and non-active during DRX in synchronous EN-DC	317
A.4.5.2.1.1	Test Purpose and Environment	317
A.4.5.2.1.2	Test Requirements	320
A.4.5.2.2	E-UTRAN – NR FR1 interruptions at transitions between active and non-active during DRX in asynchronous EN-DC	320
A.4.5.2.2.1	Test Purpose and Environment	320
A.4.5.2.2.2	Test Requirements	323
A.4.5.2.3	E-UTRAN – NR FR1 interruptions during measurements on deactivated NR SCC in synchronous EN-DC	323
A.4.5.2.3.1	Test Purpose and Environment	323
A.4.5.2.3.2	Test Requirements	328
A.4.5.2.4	E-UTRAN – NR FR1 interruptions during measurements on deactivated NR SCC in asynchronous EN-DC	329
A.4.5.2.4.1	Test Purpose and Environment	329
A.4.5.2.4.2	Test Requirements	333
A.4.5.2.5	E-UTRAN – NR FR1 interruptions during measurements on deactivated E- UTRAN SCC in synchronous EN-DC	334
A.4.5.2.5.1	Test Purpose and Environment	334
A.4.5.2.5.2	Test Requirements	337
A.4.5.2.6	E-UTRAN – NR FR1 interruptions during measurements on deactivated E- UTRAN SCC in asynchronous EN-DC	337
A.4.5.2.6.1	Test Purpose and Environment	337
A.4.5.2.6.2	Test Requirements	340
A.4.5.2.7	Void	341
A.4.5.3.1	SCell Activation and deactivation of known SCell in FR1 for 160ms SCell measurement cycle	341
A.4.5.3.1.1	Test Purpose and Environment	341
A.4.5.3.1.2	Test Requirements	347
A.4.5.3.2	SCell Activation and deactivation of known SCell in FR1 for 640ms SCell measurement cycle	347
A.4.5.3.2.1	Test Purpose and Environment	347
A.4.5.3.2.2	Test Requirements	347
A.4.5.3.3	SCell Activation and deactivation of unknown SCell in FR1	348
A.4.5.3.3.1	Test Purpose and Environment	348
A.4.5.3.3.2	Test Requirements	349
A.4.5.4	UE UL carrier RRC reconfiguration Delay	349
A.4.5.4.1	UE UL carrier RRC reconfiguration Delay	349
A.4.5.4.1.1	Test Purpose and Environment	349
A.4.5.4.1.2	Test Requirements	355
A.4.5.5	Beam Failure Detection and Link recovery procedures	355

A.4.5.5.1	EN-DC Beam Failure Detection and Link Recovery Test for FR1 PSCell configured with SSB-based BFD and LR in non-DRX mode	355
A.4.5.5.1.1	Test Purpose and Environment	355
A.4.5.5.1.2	Test Requirements	361
A.4.5.5.2	EN-DC Beam Failure Detection and Link Recovery Test for FR1 PSCell configured with SSB-based BFD and LR in DRX mode	361
A.4.5.5.2.1	Test Purpose and Environment	361
A.4.5.5.2.2	Test Requirements	368
A.4.5.5.3	EN-DC Beam Failure Detection and Link Recovery Test for FR1 PSCell configured with CSI-RS-based BFD and LR in non-DRX mode	368
A.4.5.5.3.1	Test Purpose and Environment	368
A.4.5.5.3.2	Test Requirements	374
A.4.5.5.4	EN-DC Beam Failure Detection and Link Recovery Test for FR1 PSCell configured with CSI-RS-based BFD and LR in DRX mode	374
A.4.5.5.4.1	Test Purpose and Environment	374
A.4.5.5.4.2	Test Requirements	379
A.4.5.6.1	DCI-based and Timer-based Active BWP Switch	380
A.4.5.6.1.1	E-UTRAN – NR PSCell FR1 DL active BWP switch in non-DRX in synchronous EN-DC	380
A.4.5.6.1.1.1	Test Purpose and Environment	380
A.4.5.6.1.1.2	Test Requirements	383
A.4.5.6.1.2	E-UTRAN – NR PSCell FR1 DL active BWP switch with FR1 SCell in non-DRX in synchronous EN-DC	384
A.4.5.6.1.2.1	Test Purpose and Environment	384
A.4.5.6.1.2.2	Test Requirements	389
A.4.5.6.2	RRC-based Active BWP Switch	390
A.4.5.6.2.1.1	Test Purpose and Environment	390
A.4.5.6.2.1.2	Test Requirements	394
A.4.5.7	PSCell addition and release delay	395
A.4.5.7.1	Addition and Release Delay of known NR PSCell	395
A.4.5.7.1.1	Test purpose and environment	395
A.4.5.7.1.2	Test Requirements	398
A.4.6	Measurement procedure	399
A.4.6.1	Intra-frequency Measurements	399
A.4.6.1.1	EN-DC event triggered reporting tests without gap under non-DRX	399
A.4.6.1.1.1	Test purpose and Environment	399
A.4.6.1.1.2	Test parameters	399
A.4.6.1.1.3	Test Requirements	403
A.4.6.1.2	EN-DC event triggered reporting tests without gap under DRX	403
A.4.6.1.2.1	Test purpose and Environment	403
A.4.6.1.2.2	Test parameters	403
A.4.6.1.2.2	Test Requirements	407
A.4.6.1.3	EN-DC event triggered reporting tests with per-UE gaps under non-DRX	407
A.4.6.1.3.1	Test purpose and Environment	407
A.4.6.1.3.2	Test parameters	407
A.4.6.1.3.3	Test Requirements	411
A.4.6.1.4	EN-DC event triggered reporting tests with per-UE gaps under DRX	411
A.4.6.1.4.1	Test purpose and Environment	411

A.4.6.1.4.2	Test parameters	411
A.4.6.1.4.3	Test Requirements	415
A.4.6.1.5	EN-DC event triggered reporting tests without gap under non-DRX with SSB index reading	415
A.4.6.1.5.1	Test purpose and Environment	415
A.4.6.1.5.2	Test parameters	415
A.4.6.1.5.3	Test Requirements	417
A.4.6.1.6	EN-DC event triggered reporting tests with SSB index reading with per-UE gaps	418
A.4.6.1.6.1	Test purpose and Environment	418
A.4.6.1.6.2	Test parameters	418
A.4.6.1.6.3	Test Requirements	420
A.4.6.2	Inter-frequency Measurements	421
A.4.6.2.1	EN-DC event triggered reporting tests for FR1 cell without SSB time index detection when DRX is not used	421
A.4.6.2.1.1	Test Purpose and Environment	421
A.4.6.2.1.2	Test Requirements	424
A.4.6.2.2	EN-DC event triggered reporting tests for FR1 cell without SSB time index detection when DRX is used	424
A.4.6.2.2.1	Test Purpose and Environment	424
A.4.6.2.2.2	Test Requirements	428
A.4.6.2.3	Void	428
A.4.6.2.4	Void	428
A.4.6.2.5	EN-DC event triggered reporting tests for FR1 cell with SSB time index detection when DRX is not used	428
A.4.6.2.5.1	Test Purpose and Environment	428
A.4.6.2.5.2	Test Requirements	431
A.4.6.2.6	EN-DC event triggered reporting tests for FR1 cell with SSB time index detection when DRX is used	432
A.4.6.2.6.1	Test Purpose and Environment	432
A.4.6.2.6.2	Test Requirements	435
A.4.6.2.7	Void	436
A.4.6.2.8	Void	436
A.4.6.3	Void	436
A.4.6.4	L1-RSRP measurement for beam reporting	436
A.4.6.4.1	SSB based L1-RSRP measurement when DRX is not used	436
A.4.6.4.1.1	Test Purpose and Environment	436
A.4.6.4.1.2	Test parameters	436
A.4.6.4.1.3	Test Requirements	438
A.4.6.4.2	SSB based L1-RSRP measurement when DRX is used	438
A.4.6.4.2.1	Test Purpose and Environment	438
A.4.6.4.2.2	Test parameters	439
A.4.6.4.2.3	Test Requirements	441
A.4.6.4.3	CSI-RS based L1-RSRP measurement when DRX is not used	441
A.4.6.4.3.1	Test Purpose and Environment	441
A.4.6.4.3.2	Test parameters	442
A.4.6.4.3.3	Test Requirements	444
A.4.6.4.4	CSI-RS based L1-RSRP measurement when DRX is used	444

A.4.6.4.4.1	Test Purpose and Environment	444
A.4.6.4.4.2	Test parameters	444
A.4.6.4.4.3	Test Requirements	447
A.4.7	Measurement Performance requirements	447
A.4.7.1	SS-RSRP	448
A.4.7.1.1	EN-DC Intra-frequency measurement accuracy with FR1 serving cell and FR1 target cell	448
A.4.7.1.1.1	Test Purpose and Environment	448
A.4.7.1.1.2	Test parameters	448
A.4.7.1.1.3	Test Requirements	451
A.4.7.1.2	EN-DC inter-frequency measurement accuracy with FR1 serving cell and FR1 target cell	451
A.4.7.1.2.1	Test Purpose and Environment	451
A.4.7.1.2.2	Test parameters	451
A.4.7.1.2.3	Test Requirements	454
A.4.7.1.3	Void.....	454
A.4.7.2	SS-RSRQ	454
A.4.7.2.1	EN-DC Intra-frequency measurement accuracy with FR1 serving cell and FR1 target cell	454
A.4.7.2.1.1	Test Purpose and Environment	454
A.4.7.2.1.2	Test Parameters	454
A.4.7.2.1.3	Test Requirements	458
A.4.7.2.2	EN-DC Inter-frequency measurement accuracy with FR1 serving cell and FR1 target cell	458
A.4.7.2.2.1	Test Purpose and Environment	458
A.4.7.2.2.2	Test Parameters	458
A.4.7.2.2.3	Test Requirements	461
A.4.7.3	SS-SINR.....	462
A.4.7.3.1	EN-DC Intra-frequency measurement accuracy with FR1 serving cell and FR1 target cell	462
A.4.7.3.1.1	Test Purpose and Environment	462
A.4.7.3.1.2	Test Parameters	462
A.4.7.3.1.3	Test Requirements	465
A.4.7.3.2	EN-DC Inter-frequency measurement accuracy with FR1 serving cell and FR1 target cell	465
A.4.7.3.2.1	Test Purpose and Environment	465
A.4.7.3.2.2	Test Parameters	465
A.4.7.3.2.3	Test Requirements	469
A.4.7.4	L1-RSRP measurement for beam reporting.....	470
A.4.7.4.1	SSB based L1-RSRP measurement.....	470
A.4.7.4.1.1	Test Purpose and Environment	470
A.4.7.4.1.2	Test parameters	470
A.4.7.4.1.3	Test Requirements	473
A.4.7.4.2	CSI-RS based L1-RSRP measurement on resource set with repetition off.....	473
A.4.7.4.2.1	Test Purpose and Environment	473
A.4.7.4.2.2	Test parameters	473
A.4.7.4.2.3	Test Requirements	476
A.4.7.5	SFTD accuracy	476

A.4.7.5.1	SFTD accuracy	476
A.4.7.5.1.1	Test Purpose and Environment	476
A.4.7.5.1.2	Test Parameters	476
A.4.7.5.1.3	Test Requirements	479
A.4.7.5.2	Void	479
A.4.7.5.3	Void	479
A.4.8	Void	479
A.4A	NE-DC test with all NR cells in FR1	480
A.4A.1	Signaling characteristics	480
A.4A.1.1	E-UTRAN PSCell addition	480
A.4A.1.1.1	Test purpose and environment	480
A.4A.1.1.2	Test Requirements	484
A.4A.1.2	Active BWP switch	485
A.4A.1.2.1	E-UTRAN PSCell – NR PCell FR1 DCI-based and Timer-based DL active BWP switch in non-DRX in synchronous NE-DC	485
A.4A.1.2.1.1	Test Purpose and Environment	485
A.4A.2	Measurement performance	490
A.4A.2.1	SFTD accuracy	490
A.4A.2.1.1	SFTD accuracy	490
A.4A.2.1.1.1	Test Purpose	490
A.4A.2.1.1.2	Test Environment	490
A.4A.2.1.1.3	Test Requirements	493
A.5	EN-DC tests with one or more NR cells in FR2	494
A.5.1	Void	494
A.5.2	Void	494
A.5.3	RRC_CONNECTED state mobility	494
A.5.3.1	Void	494
A.5.3.2	RRC Connection Mobility Control	494
A.5.3.2.1	Void	494
A.5.3.2.2	Random Access	494
A.5.3.2.2.1	Contention based random access test in FR2 for PSCell/SCell in EN-DC	494
A.5.3.2.2.2	Non-contention based random access test in FR2 for PSCell/SCell in EN-DC	498
A.5.3.2.3	Void	503
A.5.4	Timing	503
A.5.4.1	UE transmit timing	503
A.5.4.1.1	NR UE Transmit Timing Test for FR2	503
A.5.4.1.1.1	Test Purpose and environment	503
A.5.4.1.1.2	Test requirements	506
A.5.4.2	UE timer accuracy	506
A.5.4.3	Timing advance	506
A.5.4.3.1	EN-DC FR2 timing advance adjustment accuracy	506
A.5.4.3.1.1	Test Purpose and Environment	506
A.5.4.3.1.2	Test Parameters	507
A.5.4.3.1.3	Test Requirements	510
A.5.5	Signaling characteristics	510
A.5.5.1	Radio link Monitoring	510

A.5.5.1.1	Radio Link Monitoring Out-of-sync Test for FR2 PSCell configured with SSB-based RLM RS in non-DRX mode	510
A.5.5.1.1.1	Test Purpose and Environment	510
A.5.5.1.1.2	Test Requirements	514
A.5.5.1.2	Radio Link Monitoring In-sync Test for FR2 PSCell configured with SSB-based RLM RS in non-DRX mode	515
A.5.5.1.2.1	Test Purpose and Environment	515
A.5.5.1.2.2	Test Requirements	518
A.5.5.1.3	Radio Link Monitoring Out-of-sync Test for FR2 PSCell configured with SSB-based RLM RS in DRX mode	518
A.5.5.1.3.1	Test Purpose and Environment	518
A.5.5.1.3.2	Test Requirements	523
A.5.5.1.4	Radio Link Monitoring In-sync Test for FR2 PSCell configured with SSB-based RLM RS in DRX mode	523
A.5.5.1.4.1	Test Purpose and Environment	523
A.5.5.1.4.2	Test Requirements	527
A.5.5.1.5	EN-DC Radio Link Monitoring Out-of-sync Test for FR2 PSCell configured with CSI-RS-based RLM in non-DRX mode	527
A.5.5.1.6	EN-DC Radio Link Monitoring In-sync Test for FR2 PSCell configured with CSI-RS-based RLM in non-DRX mode	531
A.5.5.1.6.1	Test Purpose and Environment	531
A.5.5.1.6.2	Test Requirements	535
A.5.5.1.7	EN-DC Radio Link Monitoring Out-of-sync Test for FR2 PSCell configured with CSI-RS-based RLM in DRX mode	535
A.5.5.1.7.1	Test Purpose and Environment	535
A.5.5.1.7.2	Test Requirements	540
A.5.5.1.8	EN-DC Radio Link Monitoring In-sync Test for FR2 PSCell configured with CSI-RS-based RLM in DRX mode	540
A.5.5.1.8.1	Test Purpose and Environment	540
A.5.5.1.8.2	Test Requirements	544
A.5.5.1.9	EN-DC Radio Link Monitoring UE Scheduling Restrictions on FR2	545
A.5.5.1.9.1	Test Purpose and Environment	545
A.5.5.1.9.2	Test Requirements	547
A.5.5.2	Interruption	547
A.5.5.2.1	E-UTRAN – NR FR2 interruptions at transitions between active and non-active during DRX in synchronous EN-DC	547
A.5.5.2.1.1	Test Purpose and Environment	547
A.5.5.2.1.2	Test Requirements	550
A.5.5.2.2	E-UTRAN – NR FR2 interruptions at transitions between active and non-active during DRX in asynchronous EN-DC	550
A.5.5.2.2.1	Test Purpose and Environment	550
A.5.5.2.2.2	Test Requirements	553
A.5.5.2.3	E-UTRAN – NR FR2 interruptions during measurements on deactivated NR SCC in synchronous EN-DC	553
A.5.5.2.3.1	Test Purpose and Environment	553
A.5.5.2.3.2	Test Requirements	556
A.5.5.2.4	E-UTRAN – NR FR2 interruptions during measurements on deactivated NR SCC in asynchronous EN-DC	557

A.5.5.2.4.1	Test Purpose and Environment	557
A.5.5.2.4.2	Test Requirements	560
A.5.5.2.5	E-UTRAN – NR FR2 interruptions during measurements on deactivated E-UTRAN SCC in synchronous EN-DC	561
A.5.5.2.5.1	Test Purpose and Environment	561
A.5.5.2.5.2	Test Requirements	564
A.5.5.2.6	E-UTRAN – NR FR2 interruptions during measurements on deactivated E-UTRAN SCC in asynchronous EN-DC	565
A.5.5.2.6.1	Test Purpose and Environment	565
A.5.5.2.6.2	Test Requirements	567
A.5.5.3.1	SCell Activation and deactivation of SCell in FR2 intra-band	568
A.5.5.3.1.1	Test Purpose and Environment	568
A.5.5.3.1.2	Test Requirements	570
A.5.5.3.2	SCell Activation and deactivation of known SCell in FR1 for 160ms SCell measurement cycle.....	570
A.5.5.3.2.1	Test Purpose and Environment	570
A.5.5.3.2.2	Test Requirements	573
A.5.5.3.3	Void.....	573
A.5.5.3.4	Void.....	573
A.5.5.3.5	SCell Activation and deactivation of SCell in FR2	573
A.5.5.3.5.1	Test Purpose and Environment	573
A.5.5.3.5.2	Test Requirements	576
A.5.5.4	Void.....	577
A.5.5.5	Beam Failure Detection and Link recovery procedures.....	577
A.5.5.5.1	EN-DC Beam Failure Detection and Link Recovery Test for FR2 PSCell configured with SSB-based BFD and LR in non-DRX mode	577
A.5.5.5.1.1	Test Purpose and Environment	577
A.5.5.5.1.2	Test Requirements	581
A.5.5.5.2	EN-DC Beam Failure Detection and Link Recovery Test for FR2 PSCell configured with SSB-based BFD and LR in DRX mode	581
A.5.5.5.2.1	Test Purpose and Environment	581
A.5.5.5.2.2	Test Requirements	585
A.5.5.5.3	EN-DC Beam Failure Detection and Link Recovery Test for FR2 PSCell configured with CSI-RS-based BFD and LR in non-DRX mode	585
A.5.5.5.3.1	Test Purpose and Environment	585
A.5.5.5.3.2	Test Requirements	589
A.5.5.5.4	EN-DC Beam Failure Detection and Link Recovery Test for FR2 PSCell configured with CSI-RS-based BFD and LR in DRX mode.....	589
A.5.5.5.4.1	Test Purpose and Environment	589
A.5.5.5.4.2	Test Requirements	593
A.5.5.5.5	EN-DC scheduling availability restriction during Beam Failure Detection and Link Recovery for FR2 PSCell configured with SSB-based BFD and LR in non-DRX mode.....	593
A.5.5.5.5.1	Test Purpose and Environment	593
A.5.5.5.5.2	Test Requirements	597
A.5.5.6	Active BWP switch.....	597
A.5.5.6.1	DCI-based and Timer-based Active BWP Switch	597

A.5.5.6.1.1	E-UTRAN – NR PSCell FR2 DL active BWP switch with non-DRX in synchronous EN-DC.....	597
A.5.5.6.1.1.1	Test Purpose and Environment	597
A.5.5.6.1.1.2	Test Requirements	601
A.5.5.6.1.2	E-UTRAN – NR PSCell FR2 with FR2 SCell DL active BWP switch in non-DRX in synchronous EN-DC.....	602
A.5.5.6.1.2.1	Test Purpose and Environment	602
A.5.5.6.1.2.2	Test Requirements	605
A.5.5.6.2	RRC-based Active BWP Switch.....	606
A.5.5.6.2.1	E-UTRAN – NR PSCell FR2 DL active BWP switch with non-DRX in synchronous EN-DC.....	606
A.5.5.6.2.1.1	Test Purpose and Environment	606
A.5.5.6.2.1.2	Test Requirements	609
A.5.5.7	PSCell addition and release delay	610
A.5.5.7.1	Addition and Release Delay of NR PSCell	610
A.5.5.7.1.1	Test purpose and environment	610
A.5.5.7.1.2	Test Requirements	613
A.5.5.8	Active TCI state switch delay	614
A.5.5.8.1	MAC-CE based active TCI state switch	614
A.5.5.8.1.1	E-UTRAN – NR PSCell FR2 active TCI state switch for a known TCI state.....	614
A.5.5.8.1.1.1	Test Purpose and Environment	614
A.5.5.8.1.1.2	Test Requirements	617
A.5.5.8.2	RRC based active TCI state switch	617
A.5.5.8.2.1	E-UTRAN – NR PSCell FR2 active TCI state switch for a known TCI state.....	617
A.5.5.8.2.1.1	Test Purpose and Environment	617
A.5.5.8.2.1.2	Test Requirements	621
A.5.6	Measurement procedure.....	621
A.5.6.1	Intra-frequency Measurements	621
A.5.6.1.1	EN-DC event triggered reporting test without gap under non-DRX	621
A.5.6.1.1.1	Test purpose and Environment	621
A.5.6.1.1.2	Test Requirements	625
A.5.6.1.2	EN-DC event triggered reporting test without gap under DRX.....	625
A.5.6.1.2.1	Test purpose and Environment	625
A.5.6.1.2.2	Test Requirements	627
A.5.6.1.3	EN-DC event triggered reporting test with per-UE gaps under non-DRX	628
A.5.6.1.3.1	Test purpose and Environment	628
A.5.6.1.3.2	Test Requirements	632
A.5.6.1.4	EN-DC event triggered reporting test with per-UE gaps under DRX.....	632
A.5.6.1.4.1	Test purpose and Environment	632
A.5.6.1.4.2	Test Requirements	635
A.5.6.2	Inter-frequency Measurements.....	636
A.5.6.2.1	EN-DC event triggered reporting tests for FR2 cell without SSB time index detection when DRX is not used	636
A.5.6.2.1.1	Test Purpose and Environment	636
A.5.6.2.1.2	Test Requirements	639
A.5.6.2.2	EN-DC event triggered reporting tests for FR2 cell without SSB time index detection when DRX is used.....	639
A.5.6.2.2.1	Test Purpose and Environment	639

A.5.6.2.2.2	Test Requirements	642
A.5.6.2.3	EN-DC event triggered reporting tests for FR2 cell with SSB time index detection when DRX is not used	642
A.5.6.2.3.1	Test Purpose and Environment	642
A.5.6.2.3.2	Test Requirements	646
A.5.6.2.4	EN-DC event triggered reporting tests for FR2 cell with SSB time index detection when DRX is used	646
A.5.6.2.4.1	Test Purpose and Environment	646
A.5.6.2.5	EN-DC event triggered reporting tests for FR2 cell without SSB time index detection when DRX is not used	650
A.5.6.2.5.1	Test Purpose and Environment	650
A.5.6.2.5.2	Test Requirements	653
A.5.6.2.6	EN-DC event triggered reporting tests for FR2 cell without SSB time index detection when DRX is used	654
A.5.6.2.6.1	Test Purpose and Environment	654
A.5.6.2.6.2	Test Requirements	658
A.5.6.2.7	EN-DC event triggered reporting tests for FR2 cell with SSB time index detection when DRX is not used	658
A.5.6.2.7.1	Test Purpose and Environment	658
A.5.6.2.7.2	Test Requirements	662
A.5.6.2.8	EN-DC event triggered reporting tests for FR2 cell with SSB time index detection when DRX is used	663
A.5.6.2.8.1	Test Purpose and Environment	663
A.5.6.2.8.2	Test Requirements	667
A.5.6.3	L1-RSRP measurement for beam reporting	668
A.5.6.3.1	SSB based L1-RSRP measurement when DRX is not used	668
A.5.6.3.1.1	Test Purpose and Environment	668
A.5.6.3.1.2	Test parameters	668
A.5.6.3.1.3	Test Requirements	670
A.5.6.3.1.3	Test Requirements	670
A.5.6.3.2	SSB based L1-RSRP measurement when DRX is used	671
A.5.6.3.2.1	Test Purpose and Environment	671
A.5.6.3.2.2	Test parameters	671
A.5.6.3.2.3	Test Requirements	673
A.5.6.3.3	CSI-RS based L1-RSRP measurement when DRX is not used	673
A.5.6.3.3.1	Test Purpose and Environment	673
A.5.6.3.3.2	Test parameters	674
A.5.6.3.3.3	Test Requirements	675
A.5.6.3.4	CSI-RS based L1-RSRP measurement when DRX is used	676
A.5.6.3.4.1	Test Purpose and Environment	676
A.5.6.3.4.2	Test parameters	676
A.5.6.3.4.3	Test Requirements	678
A.5.7	Measurement Performance requirements	679
A.5.7.1	SS-RSRP	679
A.5.7.1.1	EN-DC intra-frequency case measurement accuracy with FR2 serving cell and FR2 target cell	679
A.5.7.1.1.1	Test Purpose and Environment	679
A.5.7.1.1.2	Test parameters	679

A.5.7.1.1.3	Test Requirements	681
A.5.7.1.2	EN-DC inter-frequency case measurement accuracy with FR2 serving cell and FR2 target cell	682
A.5.7.1.2.1	Test Purpose and Environment	682
A.5.7.1.2.2	Test parameters	682
A.5.7.1.2.3	Test Requirements	687
A.5.7.1.3	EN-DC inter-frequency measurement accuracy with FR1 serving cell and FR2 target cell	688
A.5.7.1.3.1	Test Purpose and Environment	688
A.5.7.1.3.2	Test parameters	688
A.5.7.1.3.3	Test Requirements	691
A.5.7.2	SS-RSRQ	691
A.5.7.2.1	EN-DC Intra-frequency measurement accuracy with FR2 serving cell and FR2 TDD target cell	691
A.5.7.2.1.1	Test Purpose and Environment	691
A.5.7.2.1.2	Test Parameters.....	691
A.5.7.2.1.3	Test Requirements	693
A.5.7.2.2	EN-DC Inter-frequency measurement accuracy with FR2 serving cell and FR2 TDD target cell	693
A.5.7.2.2.1	Test Purpose and Environment	693
A.5.7.2.2.2	Test Parameters	694
A.5.7.2.2.3	Test Requirements	696
A.5.7.3	SS-SINR.....	696
A.5.7.3.1	EN-DC Intra-frequency measurement accuracy with FR2 serving cell and FR2 TDD target cell	696
A.5.7.3.1.1	Test Purpose and Environment	696
A.5.7.3.1.2	Test Parameters	697
A.5.7.3.1.3	Test Requirements	699
A.5.7.3.2	EN-DC Inter-frequency measurement accuracy with FR2 serving cell and FR2 TDD target cell	700
A.5.7.3.2.1	Test Purpose and Environment	700
A.5.7.3.2.2	Test Parameters	700
A.5.7.3.2.3	Test Requirements	702
A.5.7.4	L1-RSRP measurement for beam reporting.....	702
A.5.7.4.1	SSB based L1-RSRP measurement.....	702
A.5.7.4.1.1	Test Purpose and Environment	702
A.5.7.4.1.2	Test parameters	703
A.5.7.4.1.3	Test Requirements	705
A.5.7.4.2	CSI-RS based L1-RSRP measurement on resource set with repetition off.....	706
A.5.7.4.2.1	Test Purpose and Environment	706
A.5.7.4.2.2	Test parameters	706
A.5.7.4.2.3	Test Requirements	708
A.5.8	Void	709
A.6	NR standalone tests with all NR cells in FR1	674
A.6.1	SA: RRC_IDLE state mobility	674
A.6.1.1	Cell re-selection to NR	674
A.6.1.1.1	Cell reselection to FR1 intra-frequency NR case.....	674
A.6.1.1.1.1	Test Purpose and Environment	674

A.6.1.1.1.2	Test Parameters	674
A.6.1.1.1.3	Test Requirements	678
A.6.1.1.2	Cell reselection to FR1 inter-frequency NR case	678
A.6.1.1.2.1	Test Purpose and Environment	678
A.6.1.1.2.2	Test Parameters	678
A.6.1.1.2.3	Test Requirements	682
A.6.1.2.1	Cell reselection to higher priority E-UTRAN	682
A.6.1.2.1.1	Test Purpose and Environment	682
A.6.1.2.1.2	Test Parameters	682
A.6.1.2.1.3	Test Requirements	685
A.6.1.2.2	Cell reselection to lower priority E-UTRAN.....	686
A.6.1.2.2.1	Test Purpose and Environment	686
A.6.1.2.2.2	Test Parameters	686
A.6.1.2.2.3	Test Requirements	688
A.6.2	SA: RRC_INACTIVE state mobility.....	689
A.6.3	RRC_CONNECTED state mobility.....	689
A.6.3.1.1	Intra-frequency handover from FR1 to FR1; known target cell.....	689
A.6.3.1.1.1	Test Purpose and Environment	689
A.6.3.1.1.2	Test Parameters	689
A.6.3.1.1.3	Test Requirements	691
A.6.3.1.2	Intra-frequency handover from FR1 to FR1; unknown target cell	691
A.6.3.1.2.1	Test Purpose and Environment	691
A.6.3.1.2.2	Test Parameters	691
A.6.3.1.2.3	Test Requirements	693
A.6.3.1.3	Inter-frequency handover from FR1 to FR1; unknown target cell	693
A.6.3.1.3.1	Test Purpose and Environment	693
A.6.3.1.3.2	Test Parameters	693
A.6.3.1.3.3	Test Requirements	695
A.6.3.1.4	SA NR - E-UTRAN handover	695
A.6.3.1.4.1	Test Purpose and Environment	695
A.6.3.1.4.2	Test Requirements	699
A.6.3.1.5	SA NR - E-UTRAN handover with unknown target cell	699
A.6.3.1.5.1	Test Purpose and Environment	699
A.6.3.1.5.2	Test Requirements	702
A.6.3.2.1	SA: RRC Re-establishment	703
A.6.3.2.1.1	Intra-frequency RRC Re-establishment in FR1	703
A.6.3.2.1.2	Inter-frequency RRC Re-establishment in FR1	706
A.6.3.2.1.3	Intra-frequency RRC Re-establishment in FR1 without serving cell timing	709
A.6.3.2.2	Random Access	712
A.6.3.2.2.1	Contention based random access test in FR1 for NR standalone	712
A.6.3.2.2.2	Non-Contention based random access test in FR1 for NR standalone	716
A.6.3.2.3.1	Redirection from NR in FR1 to NR in FR1	719
A.6.3.2.3.2	Redirection from NR in FR1 to E-UTRAN	722
A.6.4	Timing	726
A.6.4.1.1	NR UE Transmit Timing Test for FR1	726
A.6.4.1.1.1	Test Purpose and environment	726
A.6.4.1.1.2	Test requirements	728
A.6.4.3.1	SA FR1 timing advance adjustment accuracy	729

A.6.4.3.1.1	Test Purpose and Environment	729
A.6.4.3.1.2	Test Parameters	729
A.6.4.3.1.3	Test Requirements	732
A.6.5	Signalling characteristics.....	732
A.6.5.1.1	Radio Link Monitoring Out-of-sync Test for FR1 PCell configured with SSB-based RLM RS in non-DRX mode	733
A.6.5.1.1.1	Test Purpose and Environment	733
A.6.5.1.1.2	Test Requirements	736
A.6.5.1.2	Radio Link Monitoring In-sync Test for FR1 PCell configured with SSB-based RLM RS in non-DRX mode	736
A.6.5.1.2.1	Test Purpose and Environment	736
A.6.5.1.2.2	Test Requirements	740
A.6.5.1.3	Radio Link Monitoring Out-of-sync Test for FR1 PCell configured with SSB-based RLM RS in DRX mode	740
A.6.5.1.3.1	Test Purpose and Environment	740
A.6.5.1.3.2	Test Requirements	744
A.6.5.1.4	Radio Link Monitoring In-sync Test for FR1 PCell configured with SSB-based RLM RS in DRX mode.....	744
A.6.5.1.4.1	Test Purpose and Environment	744
A.6.5.1.4.2	Test Requirements	748
A.6.5.1.5	Radio Link Monitoring Out-of-sync Test for FR1 PCell configured with CSI-RS-based RLM in non-DRX mode.....	748
A.6.5.1.5.1	Test Purpose and Environment	748
A.6.5.1.5.2	Test Requirements	753
A.6.5.1.6	Radio Link Monitoring In-sync Test for FR1 PCell configured with CSI-RS-based RLM in non-DRX mode.....	753
A.6.5.1.6.1	Test Purpose and Environment	753
A.6.5.1.6.2	Test Requirements	757
A.6.5.1.7	Radio Link Monitoring Out-of-sync Test for FR1 PCell configured with CSI-RS-based RLM in DRX mode	757
A.6.5.1.7.1	Test Purpose and Environment	757
A.6.5.1.7.2	Test Requirements	761
A.6.5.1.8	Radio Link Monitoring In-sync Test for FR1 PCell configured with CSI-RS-based RLM in DRX mode	761
A.6.5.1.8.1	Test Purpose and Environment	761
A.6.5.1.8.2	Test Requirements	765
A.6.5.2.1	Interruptions during measurements on deactivated NR SCC in FR1	765
A.6.5.3.1	SCell Activation and deactivation of known SCell in FR1 in non-DRX for 160ms SCell measurement cycle.....	770
A.6.5.3.1.1	Test Purpose and Environment	770
A.6.5.3.1.2	Test Requirements	775
A.6.5.3.2	SCell Activation and deactivation of known SCell in FR1 in non-DRX for 640 ms SCell measurement cycle	776
A.6.5.3.2.1	Test Purpose and Environment	776
A.6.5.3.2.2	Test Requirements	776
A.6.5.3.3	SCell Activation and deactivation of unknown SCell in FR1 in non-DRX.....	776
A.6.5.3.3.1	Test Purpose and Environment	776
A.6.5.3.3.2	Test Requirements	777

A.6.5.4.1	UE UL carrier RRC reconfiguration Delay	777
A.6.5.4.1.1	Test Purpose and Environment	777
A.6.5.4.1.2	Test Requirements	784
A.6.5.4.2	Void	785
A.6.5.5.1	Beam Failure Detection and Link Recovery Test for FR1 PCell configured with SSB-based BFD and LR in non-DRX mode	785
A.6.5.5.1.1	Test Purpose and Environment	785
A.6.5.5.1.2	Test Requirements	789
A.6.5.5.2	Beam Failure Detection and Link Recovery Test for FR1 PCell configured with SSB-based BFD and LR in DRX mode	789
A.6.5.5.2.1	Test Purpose and Environment	789
A.6.5.5.2.2	Test Requirements	794
A.6.5.5.3	Beam Failure Detection and Link Recovery Test for FR1 PCell configured with CSI-RS-based BFD and LR in non-DRX mode	794
A.6.5.5.3.1	Test Purpose and Environment	794
A.6.5.5.3.2	Test Requirements	800
A.6.5.5.4	Beam Failure Detection and Link Recovery Test for FR1 PCell configured with CSI-RS-based BFD and LR in DRX mode	800
A.6.5.5.4.1	Test Purpose and Environment	800
A.6.5.5.4.2	Test Requirements	805
A.6.5.6.1	DCI-based and Timer-based Active BWP Switch	805
A.6.5.6.1.1	NR FR1- NR FR1 DL active BWP switch of SCell with non-DRX in SA	805
A.6.5.6.1.2	NR FR1 DL active BWP switch with non-DRX in SA	812
A.6.5.6.2	RRC-based Active BWP Switch	816
A.6.5.6.2.1	NR FR1 DL active BWP switch of Cell with non-DRX in SA	816
A.6.6	Measurement procedure	819
A.6.6.1.1	SA event triggered reporting tests without gap under non-DRX	819
A.6.6.1.1.1	Test purpose and Environment	819
A.6.6.1.1.2	Test parameters	819
A.6.6.1.1.3	Test Requirements	821
A.6.6.1.2	SA event triggered reporting tests without gap under DRX	821
A.6.6.1.2.1	Test purpose and Environment	821
A.6.6.1.2.2	Test parameters	822
A.6.6.1.2.3	Test Requirements	823
A.6.6.1.3	SA event triggered reporting tests with per-UE gaps under non-DRX	824
A.6.6.1.3.1	Test purpose and Environment	824
A.6.6.1.3.2	Test parameters	824
A.6.6.1.3.3	Test Requirements	828
A.6.6.1.4	SA event triggered reporting tests with per-UE gaps under DRX	828
A.6.6.1.4.1	Test purpose and Environment	828
A.6.6.1.4.2	Test parameters	828
A.6.6.1.4.3	Test Requirements	831
A.6.6.1.5	SA event triggered reporting tests without gap under non-DRX with SSB index reading	831
A.6.6.1.5.1	Test purpose and Environment	831
A.6.6.1.5.2	Test parameters	831
A.6.6.1.5.3	Test Requirements	833

A.6.6.1.6	SA event triggered reporting tests with per-UE gaps under non-DRX with SSB index reading	833
A.6.6.1.6.1	Test purpose and Environment	833
A.6.6.1.6.2	Test parameters	833
A.6.6.1.6.3	Test Requirements	835
A.6.6.2.1	SA event triggered reporting tests for FR1 without SSB time index detection when DRX is not used	835
A.6.6.2.1.1	Test Purpose and Environment	835
A.6.6.2.1.2	Test Requirements	838
A.6.6.2.2	SA event triggered reporting tests for FR1 without SSB time index detection when DRX is used.....	838
A.6.6.2.2.1	Test Purpose and Environment	838
A.6.6.2.2.2	Test Requirements	841
A.6.6.2.3	Void.....	842
A.6.6.2.4	Void.....	842
A.6.6.2.5	SA event triggered reporting tests for FR1 with SSB time index detection when DRX is not used	842
A.6.6.2.5.1	Test Purpose and Environment	842
A.6.6.2.5.2	Test Requirements	846
A.6.6.2.6	SA event triggered reporting tests for FR1 with SSB time index detection when DRX is used.....	846
A.6.6.2.6.1	Test Purpose and Environment	846
A.6.6.2.6.2	Test Requirements	849
A.6.6.2.7	Void.....	850
A.6.6.2.8	Void.....	850
A.6.6.3	Inter-RAT Measurements	850
A.6.6.3.1	SA NR - E-UTRAN event-triggered reporting in non-DRX in FR1	850
A.6.6.3.1.1	Test Purpose and Environment	850
A.6.6.3.1.2	Test Requirements	853
A.6.6.3.2	SA NR - E-UTRAN event-triggered reporting in DRX in FR1.....	854
A.6.6.3.2.1	Test Purpose and Environment	854
A.6.6.3.2.2	Test Requirements	857
A.6.6.4	L1-RSRP measurement for beam reporting.....	858
A.6.6.4.1	SSB based L1-RSRP measurement when DRX is not used	858
A.6.6.4.1.1	Test Purpose and Environment	858
A.6.6.4.1.2	Test parameters	858
A.6.6.4.1.3	Test Requirements	860
A.6.6.4.2	SSB based L1-RSRP measurement when DRX is used	860
A.6.6.4.2.1	Test Purpose and Environment	860
A.6.6.4.2.2	Test parameters	860
A.6.6.4.2.3	Test Requirements	863
A.6.6.4.3	CSI-RS based L1-RSRP measurement when DRX is not used	863
A.6.6.4.3.1	Test Purpose and Environment	863
A.6.6.4.3.2	Test parameters	863
A.6.6.4.3.3	Test Requirements	865
A.6.6.4.4	CSI-RS based L1-RSRP measurement when DRX is used.....	865
A.6.6.4.4.1	Test Purpose and Environment	865
A.6.6.4.4.2	Test parameters	865

A.6.6.4.4.3	Test Requirements	867
A.6.7	Measurement Performance requirements	868
A.6.7.1.1	SA: intra-frequency case measurement accuracy with FR1 serving cell and FR1 target cell	868
A.6.7.1.1.1	Test Purpose and Environment	868
A.6.7.1.1.2	Test parameters	868
A.6.7.1.1.3	Test Requirements	873
A.6.7.1.2	SA inter-frequency case measurement accuracy with FR1 serving cell and FR1 target cell	873
A.6.7.1.2.1	Test Purpose and Environment	873
A.6.7.1.2.2	Test parameters	873
A.6.7.1.2.3	Test Requirements	876
A.6.7.1.3	Void	876
A.6.7.2	SS-RSRQ	876
A.6.7.2.1	SA: Intra-frequency measurement accuracy with FR1 serving cell and FR1 target cell	876
A.6.7.2.1.1	Test Purpose and Environment	876
A.6.7.2.1.2	Test Parameters	876
A.6.7.2.1.3	Test Requirements	880
A.6.7.2.2	SA Inter-frequency measurement accuracy with FR1 serving cell and FR1 target cell	880
A.6.7.2.2.1	Test Purpose and Environment	880
A.6.7.2.2.2	Test Parameters	880
A.6.7.2.2.3	Test Requirements	884
A.6.7.3.1	SA intra-frequency measurement accuracy with FR1 serving cell and FR1 target cell	884
A.6.7.3.1.1	Test Purpose and Environment	884
A.6.7.3.1.2	Test Parameters	884
A.6.7.3.1.3	Test Requirements	887
A.6.7.3.2	SA Inter-frequency measurement accuracy with FR1 serving cell and FR1 target cell	888
A.6.7.3.2.1	Test Purpose and Environment	888
A.6.7.3.2.2	Test Parameters	888
A.6.7.3.2.3	Test Requirements	891
A.6.7.4.1	SSB based L1-RSRP measurement.....	891
A.6.7.4.1.1	Test Purpose and Environment	891
A.6.7.4.1.2	Test parameters	891
A.6.7.4.1.3	Test Requirements	894
A.6.7.4.2	CSI-RS based L1-RSRP measurement on resource set with repetition off.....	894
A.6.7.4.2.1	Test Purpose and Environment	894
A.6.7.4.2.2	Test parameters	894
A.6.7.4.2.3	Test Requirements	897
A.6.7.5.1	SA: inter-RAT measurement accuracy with FR1 serving cell	897
A.6.7.5.1.1	Test Purpose and Environment	897
A.6.7.5.1.2	Test parameters	897
A.6.7.5.1.3	Test Requirements	902
A.6.7.6.1	SA: inter-RAT measurement accuracy with FR1 serving cell	903
A.6.7.6.1.1	Test Purpose and Environment	903

A.6.7.6.1.2	Test parameters	903
A.6.7.6.1.3	Test Requirements	908
A.6.7.7.1	SA: inter-RAT measurement accuracy with FR1 serving cell	908
A.6.7.7.1.1	Test Purpose and Environment	908
A.6.7.7.1.2	Test parameters	908
A.6.7.7.1.3	Test Requirements	913
A.7	NR standalone tests with one or more NR cells in FR2	913
A.7.1	SA: RRC_IDLE state mobility	913
A.7.1.1.1	Cell reselection to FR2 intra-frequency NR case	913
A.7.1.1.1.1	Test Purpose and Environment	913
A.7.1.1.1.2	Test Parameters	913
A.7.1.1.1.3	Test Requirements	916
A.7.1.1.2	Cell reselection to FR2 inter-frequency NR case	916
A.7.1.1.2.1	Test Purpose and Environment	916
A.7.1.1.2.2	Test Parameters	917
A.7.1.1.2.3	Test Requirements	919
A.7.2	SA: RRC_INACTIVE state mobility	919
A.7.3	RRC_CONNECTED state mobility	919
A.7.3.1	Handover	919
A.7.3.1.1	Inter-frequency handover from FR1 to FR2; unknown target cell	919
A.7.3.1.1.1	Test Purpose and Environment	919
A.7.3.1.1.2	Test Parameters	919
A.7.3.1.1.3	Test Requirements	922
A.7.3.1.2	Intra-frequency handover from FR2 to FR2; unknown target cell	923
A.7.3.1.2.1	Test Purpose and Environment	923
A.7.3.1.2.2	Test Parameters	923
A.7.3.1.2.3	Test Requirements	925
A.7.3.1.3	Inter-frequency handover from FR2 to FR2; unknown target cell	925
A.7.3.1.3.1	Test Purpose and Environment	925
A.7.3.1.3.2	Test Parameters	925
A.7.3.1.3.3	Test Requirements	927
A.7.3.2.1	SA: RRC Re-establishment	927
A.7.3.2.1.1	Intra-frequency RRC Re-establishment in FR2	927
A.7.3.2.1.2	Inter-frequency RRC Re-establishment in FR2	930
A.7.3.2.1.3	Intra-frequency RRC Re-establishment in FR2 without serving cell timing	933
A.7.3.2.1.3.1	Test Purpose and Environment	933
A.7.3.2.1.3.2	Test Requirements	935
A.7.3.2.2	Random Access	936
A.7.3.2.2.1	Contention based random access test in FR2 for NR Standalone	936
A.7.3.2.2.2	Non-contention based random access test in FR2 for NR Standalone	940
A.7.3.2.3	SA: RRC Connection Release with Redirection	944
A.7.3.2.3.1	Redirection from NR in FR2 to NR in FR2	944
A.7.4	Timing	946
A.7.4.1.1	NR UE Transmit Timing Test for FR2	946
A.7.4.1.1.1	Test Purpose and environment	946
A.7.4.1.1.2	Test requirements	949
A.7.4.3.1	SA FR2 timing advance adjustment accuracy	950
A.7.4.3.1.1	Test Purpose and Environment	950

A.7.4.3.1.2	Test Parameters	950
A.7.4.3.1.3	Test Requirements	954
A.7.5	Signaling characteristics	954
A.7.5.1.1	Radio Link Monitoring Out-of-sync Test for FR2 PCell configured with SSB-based RLM RS in non-DRX mode	954
A.7.5.1.1.1	Test Purpose and Environment	954
A.7.5.1.1.2	Test Requirements	957
A.7.5.1.2	Radio Link Monitoring In-sync Test for FR2 PCell configured with SSB-based RLM RS in non-DRX mode	958
A.7.5.1.2.1	Test Purpose and Environment	958
A.7.5.1.2.2	Test Requirements	962
A.7.5.1.3	Radio Link Monitoring Out-of-sync Test for FR2 PCell configured with SSB-based RLM RS in DRX mode	963
A.7.5.1.3.1	Test Purpose and Environment	963
A.7.5.1.3.2	Test Requirements	967
A.7.5.1.4	Radio Link Monitoring In-sync Test for FR2 PCell configured with SSB-based RLM RS in DRX mode	967
A.7.5.1.4.1	Test Purpose and Environment	967
A.7.5.1.4.2	Test Requirements	972
A.7.5.1.5	Radio Link Monitoring Out-of-sync Test for FR2 PCell configured with CSI-RS-based RLM in non-DRX mode	972
A.7.5.1.5.1	Test Purpose and Environment	972
A.7.5.1.5.2	Test Requirements	977
A.7.5.1.6	Radio Link Monitoring In-sync Test for FR2 PCell configured with CSI-RS-based RLM in non-DRX mode	977
A.7.5.1.6.1	Test Purpose and Environment	977
A.7.5.1.6.2	Test Requirements	981
A.7.5.1.7	Radio Link Monitoring Out-of-sync Test for FR2 PCell configured with CSI-RS-based RLM in DRX mode	981
A.7.5.1.7.1	Test Purpose and Environment	981
A.7.5.1.7.2	Test Requirements	985
A.7.5.1.8	Radio Link Monitoring In-sync Test for FR2 PCell configured with CSI-RS-based RLM in DRX mode	985
A.7.5.1.8.1	Test Purpose and Environment	985
A.7.5.1.8.2	Test Requirements	990
A.7.5.1.9	UE Radio Link Monitoring Scheduling Restrictions on FR2	990
A.7.5.1.9.1	Test Purpose and Environment	990
A.7.5.1.9.2	Test Requirements	993
A.7.5.2.1	Interruptions during measurements on deactivated NR SCC in FR2	993
A.7.5.3.1	SCell Activation and deactivation for SCell in FR2 intra-band in non-DRX	997
A.7.5.3.1.1	Test Purpose and Environment	997
A.7.5.3.1.2	Test Requirements	999
A.7.5.3.2	SCell Activation and deactivation for FR1+FR2 inter-band with target SCell in FR2	999
A.7.5.3.2.1	Test Purpose and Environment	999
A.7.5.3.2.2	Test Requirements	1003
A.7.5.5.1	Beam Failure Detection and Link Recovery Test for FR2 PCell configured with SSB-based BFD and LR in non-DRX mode	1004

A.7.5.5.1.1	Test Purpose and Environment	1004
A.7.5.5.1.2	Test Requirements	1008
A.7.5.5.2	Beam Failure Detection and Link Recovery Test for FR2 PCell configured with SSB-based BFD and LR in DRX mode	1008
A.7.5.5.2.1	Test Purpose and Environment	1008
A.7.5.5.2.2	Test Requirements	1012
A.7.5.5.3	Beam Failure Detection and Link Recovery Test for FR2 PCell configured with CSI-RS-based BFD and LR in non-DRX mode.....	1012
A.7.5.5.3.1	Test Purpose and Environment	1012
A.7.5.5.3.2	Test Requirements	1015
A.7.5.5.4	Beam Failure Detection and Link Recovery Test for FR2 PCell configured with CSI-RS-based BFD and LR in DRX mode	1016
A.7.5.5.4.1	Test Purpose and Environment	1016
A.7.5.5.4.2	Test Requirements	1019
A.7.5.5.5	Scheduling availability restriction during Beam Failure Detection and Link Recovery for FR2 PCell configured with SSB-based BFD and LR in non-DRX mode.....	1020
A.7.5.5.5.1	Test Purpose and Environment	1020
A.7.5.5.5.2	Test Requirements	1024
A.7.5.6.1	DCI-based and Timer-based Active BWP Switch	1024
A.7.5.6.1.1	NR FR2- NR FR2 DL active BWP switch of SCell with non-DRX in SA	1024
A.7.5.6.1.2	NR FR1- NR FR2 DL active BWP switch of SCell with non-DRX in SA.....	1029
A.7.5.6.1.3	NR FR2 DL active BWP switch with non-DRX in SA.....	1033
A.7.5.6.1.3.1	Test Purpose and Environment	1033
A.7.5.6.1.3.2	Test Requirements	1036
A.7.5.6.2	RRC-based Active BWP Switch.....	1036
A.7.5.7.1	Addition and Release Delay of known NR PSCell	1040
A.7.5.7.1.1	Test Purpose and Environment	1040
A.7.5.7.2	Addition and Release Delay of unknown NR PSCell.....	1043
A.7.5.7.2.1	Test Purpose and Environment	1043
A.7.5.8.1	MAC-CE based active TCI state switch	1046
A.7.5.8.2	RRC based active TCI state switch	1050
A.7.6	Measurement procedure	1054
A.7.6.1.1	SA event triggered reporting test without gap under non-DRX	1054
A.7.6.1.1.1	Test purpose and Environment	1054
A.7.6.1.1.2	Test Requirements	1057
A.7.6.1.2	SA event triggered reporting test without gap under DRX.....	1058
A.7.6.1.2.1	Test purpose and Environment	1058
A.7.6.1.2.2	Test Requirements	1061
A.7.6.1.3	SA event triggered reporting test with per-UE gaps under non-DRX	1061
A.7.6.1.3.1	Test purpose and Environment	1061
A.7.6.1.3.2	Test Requirements	1064
A.7.6.1.4	SA event triggered reporting test with per-UE gaps under DRX.....	1065
A.7.6.1.4.1	Test purpose and Environment	1065
A.7.6.1.4.2	Test Requirements	1068
A.7.6.2.1	SA event triggered reporting tests For FR2 without SSB time index detection when DRX is not used (PCell in FR2)	1068
A.7.6.2.1.1	Test Purpose and Environment	1068

A.7.6.2.1.2	Test Requirements	1072
A.7.6.2.2	SA event triggered reporting tests For FR2 without SSB time index detection when DRX is used (PCell in FR2)	1072
A.7.6.2.2.1	Test Purpose and Environment	1072
A.7.6.2.2.2	Test Requirements	1075
A.7.6.2.3	SA event triggered reporting tests For FR2 with SSB time index detection when DRX is not used (PCell in FR2)	1075
A.7.6.2.3.1	Test Purpose and Environment	1075
A.7.6.2.3.2	Test Requirements	1079
A.7.6.2.4	SA event triggered reporting tests For FR2 with SSB time index detection when DRX is used (PCell in FR2)	1079
A.7.6.2.4.1	Test Purpose and Environment	1079
A.7.6.2.4.2	Test Requirements	1082
A.7.6.2.5	SA event triggered reporting tests for FR2 without SSB time index detection when DRX is not used (PCell in FR1)	1082
A.7.6.2.5.1	Test Purpose and Environment	1082
A.7.6.2.5.2	Test Requirements	1085
A.7.6.2.6	SA event triggered reporting tests for FR2 without SSB time index detection when DRX is used (PCell in FR1)	1086
A.7.6.2.6.1	Test Purpose and Environment	1086
A.7.6.2.6.2	Test Requirements	1089
A.7.6.2.7	SA event triggered reporting tests for FR2 with SSB time index detection when DRX is not used (PCell in FR1)	1090
A.7.6.2.7.1	Test Purpose and Environment	1090
A.7.6.2.7.2	Test Requirements	1093
A.7.6.2.8	SA event triggered reporting tests for FR2 with SSB time index detection when DRX is used (PCell in FR1)	1093
A.7.6.2.8.1	Test Purpose and Environment	1093
A.7.6.2.8.2	Test Requirements	1097
A.7.6.3	L1-RSRP measurement for beam reporting	1098
A.7.6.3.1	SSB based L1-RSRP measurement when DRX is not used	1098
A.7.6.3.1.1	Test Purpose and Environment	1098
A.7.6.3.1.2	Test parameters	1098
A.7.6.3.1.3	Test Requirements	1100
A.7.6.3.2	SSB based L1-RSRP measurement when DRX is used	1100
A.7.6.3.2.1	Test Purpose and Environment	1100
A.7.6.3.2.2	Test parameters	1101
A.7.6.3.2.3	Test Requirements	1103
A.7.6.3.3	CSI-RS based L1-RSRP measurement when DRX is not used	1103
A.7.6.3.3.1	Test Purpose and Environment	1103
A.7.6.3.3.2	Test parameters	1104
A.7.6.3.3.3	Test Requirements	1106
A.7.6.3.4	CSI-RS based L1-RSRP measurement when DRX is used	1107
A.7.6.3.4.1	Test Purpose and Environment	1107
A.7.6.3.4.2	Test parameters	1107
A.7.6.3.4.3	Test Requirements	1109
A.7.7	Measurement Performance requirements	1110

A.7.7.1.1	SA intra-frequency case measurement accuracy with FR2 serving cell and FR2 target cell	1110
A.7.7.1.1.1	Test Purpose and Environment	1110
A.7.7.1.1.2	Test parameters	1110
A.7.7.1.1.3	Test Requirements	1113
A.7.7.1.2	SA inter-frequency case measurement accuracy with FR2 serving cell and FR2 target cell	1113
A.7.7.1.2.1	Test Purpose and Environment	1113
A.7.7.1.2.2	Test parameters	1114
A.7.7.1.2.3	Test Requirements	1118
A.7.7.1.3	SA inter-frequency measurement accuracy with FR1 serving cell and FR2 target cell	1119
A.7.7.1.3.1	Test Purpose and Environment	1119
A.7.7.1.3.2	Test parameters	1119
A.7.7.1.3.3	Test Requirements	1121
A.7.7.2	SS-RSRQ	1122
A.7.7.2.1	SA intra-frequency measurement accuracy with FR2 serving cell and FR2 target cell	1122
A.7.7.2.1.1	Test Purpose and Environment	1122
A.7.7.2.1.2	Test Parameters	1122
A.7.7.2.1.3	Test Requirements	1124
A.7.7.2.2	SA Inter-frequency measurement accuracy with FR2 serving cell and FR2 TDD target cell	1124
A.7.7.2.2.1	Test Purpose and Environment	1124
A.7.7.2.2.2	Test Parameters	1124
A.7.7.2.2.3	Test Requirements	1126
A.7.7.3.1	SA intra-frequency case measurement accuracy with FR2 serving cell and FR2 target cell	1126
A.7.7.3.1.1	Test Purpose and Environment	1126
A.7.7.3.1.2	Test Parameters	1127
A.7.7.3.1.3	Test Requirements	1128
A.7.7.3.2	SA Inter-frequency measurement accuracy with FR2 serving cell and FR2 TDD target cell	1128
A.7.7.3.2.1	Test Purpose and Environment	1128
A.7.7.3.2.2	Test Parameters	1128
A.7.7.3.2.3	Test Requirements	1130
A.7.7.4.1	SSB based L1-RSRP measurement.....	1130
A.7.7.4.1.1	Test Purpose and Environment	1130
A.7.7.4.1.2	Test parameters	1131
A.7.7.4.1.3	Test Requirements	1133
A.7.7.4.2	CSI-RS based L1-RSRP measurement on resource set with repetition off.....	1134
A.7.7.4.2.1	Test Purpose and Environment	1134
A.7.7.4.2.2	Test parameters	1134
A.7.7.4.2.3	Test Requirements	1136
A.8	E-UTRA standalone tests for NR RRM	1137
A.8.1	Void	1137
A.8.2	RRC_IDLE state mobility	1137
A.8.2.1	Inter-RAT NR Cell re-selection.....	1137

A.8.2.1.1	E-UTRA Cell reselection to higher priority NR target Cell in FR1.....	1137
A.8.2.1.1.1	Test Purpose and Environment	1137
A.8.2.1.1.2	Test Requirements	1140
A.8.3	RRC_CONNECTED state mobility.....	1141
A.8.3.1	Handover.....	1141
A.8.3.1.1	E-UTRAN - NR handover in FR1.....	1141
A.8.3.1.1.1	Test Purpose and Environment	1141
A.8.3.1.1.2	Test Requirements	1146
A.8.4	Measurement procedure.....	1146
A.8.4.1.1	E-UTRA – NR Inter-RAT SFTD Measurement Delay in non-DRX.....	1146
A.8.4.1.1.1	Test Purpose and Environment	1146
A.8.4.1.1.2	Test Requirements	1148
A.8.4.1.2	E-UTRA – NR Inter-RAT SFTD Measurement Delay in DRX	1149
A.8.4.1.2.1	Test Purpose and Environment	1149
A.8.4.1.2.2	Test Requirements	1150
A.8.4.2	E-UTRA – NR Inter-RAT Measurements.....	1150
A.8.4.2.1	NR Inter-RAT event triggered reporting tests for FR1 without SSB time index detection when DRX is not used	1150
A.8.4.2.1.1	Test Purpose and Environment	1150
A.8.4.2.1.2	Test Requirements	1154
A.8.4.2.2	NR Inter-RAT event triggered reporting tests for FR1 without SSB time index detection when DRX is used.....	1155
A.8.4.2.2.1	Test Purpose and Environment	1155
A.8.4.2.2.2	Test Requirements	1158
A.8.4.2.3	NR Inter-RAT event triggered reporting tests for FR1 with SSB time index detection when DRX is not used	1159
A.8.4.2.3.1	Test Purpose and Environment	1159
A.8.4.2.3.2	Test Requirements	1162
A.8.4.2.4	NR Inter-RAT event triggered reporting tests for FR1 with SSB time index detection when DRX is used.....	1163
A.8.4.2.4.1	Test Purpose and Environment	1163
A.8.4.2.4.2	Test Requirements	1168
A.8.4.2.5	NR Inter-RAT event triggered reporting tests for FR2 without SSB time index detection when DRX is not used	1169
A.8.4.2.5.1	Test Purpose and Environment	1169
A.8.4.2.5.2	Test Requirements	1171
A.8.4.2.6	NR Inter-RAT event triggered reporting tests for FR2 without SSB time index detection when DRX is used.....	1172
A.8.4.2.6.1	Test Purpose and Environment	1172
A.8.4.2.6.2	Test Requirements	1174
A.8.4.2.7	NR Inter-RAT event triggered reporting tests for FR2 with SSB time index detection when DRX is not used	1175
A.8.4.2.7.1	Test Purpose and Environment	1175
A.8.4.2.7.2	Test Requirements	1177
A.8.4.2.8	NR Inter-RAT event triggered reporting tests for FR2 with SSB time index detection when DRX is used.....	1178
A.8.4.2.8.1	Test Purpose and Environment	1178
A.8.4.2.8.2	Test Requirements	1180

A.8.5	Measurement performance.....	1181
A.8.5.1.1	SFTD accuracy	1181
A.8.5.1.1.1	Test Purpose.....	1181
A.8.5.1.1.2	Test Environment.....	1181
A.8.5.1.1.3	Test Requirements	1185
A.8.5.2	E-UTRA – NR Inter-RAT Measurement Performance requirements	1185
A.8.5.2.1	SS-RSRP	1185
A.8.5.2.1.1	E-UTRAN – NR inter-RAT measurements with FR1 target cell	1185
A.8.5.2.1.2	E-UTRAN – NR inter-RAT measurements with FR2 target cell.....	1189
A.8.5.2.1.2.1	Test Purpose and Environment	1189
A.8.5.2.1.2.2	Test Parameters.....	1189
A.8.5.2.1.2.3	Test Requirements	1191
A.8.5.2.2	SS-RSRQ.....	1192
A.8.5.2.2.1	E-UTRAN – NR inter-RAT measurements with FR1 target cell	1192
A.8.5.2.2.2	E-UTRAN – NR inter-RAT measurements with FR2 target cell.....	1195
A.8.5.2.2.2.1	Test Purpose and Environment	1195
A.8.5.2.2.2.2	Test Parameters.....	1195
A.8.5.2.2.2.3	Test Requirements	1197
A.8.5.2.3	SS-SINR	1198
A.8.5.2.3.1	E-UTRAN – NR inter-RAT measurements with FR1 target cell	1198
A.8.5.2.3.2	E-UTRAN – NR inter-RAT measurements with FR2 target cell.....	1201
A.8.5.2.3.2.1	Test Purpose and Environment	1201
A.8.5.2.3.2.2	Test Parameters.....	1201
A.8.5.2.3.2.3	Test Requirements	1202
Annex B (normative): Conditions for RRM requirements applicability for operating bands		1186
B.1	Conditions for NR RRC_IDLE state mobility	1186
B.1.1	Introduction.....	1186
B.1.2	Conditions for measurements on NR intra-frequency cells for cell re-selection	1186
B.1.3	Conditions for measurements on NR inter-frequency cells for cell re-selection	1187
B.2	Conditions for UE measurements procedures and performance requirements in RRC_CONNECTED state.....	1188
B.2.1	Introduction.....	1188
B.2.1.1	General.....	1188
B.2.1.2	Derivation of Minimum SSB_RP values for FR1.....	1188
B.2.1.3	Derivation of Minimum SSB_RP values for FR2	1188
B.2.1.3.1	Minimum SSB_RP values for Rx Beam Peak angle of arrival	1188
B.2.1.4	Gain to SS-RSRP measurement point for FR1.....	1190
B.2.1.5	Gain to SS-RSRP measurement point for FR2	1190
B.2.1.5.1	Gain to SS-RSRP measurement point for Rx Beam Peak angle of arrival	1190
B.2.1.5.2	Gain to SS-RSRP measurement point for different frequency	1190
B.2.1.5.3	Alignment of Rough beam to Rx beam Peak	1191
B.2.2	Conditions for NR intra-frequency measurements.....	1191
B.2.3	Conditions for NR inter-frequency measurements	1192
B.2.4	Conditions for NR L1-RSRP reporting.....	1193
B.2.4.1	Conditions for SSB based L1-RSRP reporting	1193
B.2.4.2	Conditions for CSI-RS based L1-RSRP reporting.....	1194
B.2.5	Conditions for RRC connection release with redirection to NR	1196

B.2.6	Void	1197
B.2.6.1	Void.....	1197
B.2.6.2	Void.....	1197
B.3	RRM Requirements Exceptions	1197
B.3.1	Introduction.....	1197
B.3.2	Receiver sensitivity relaxation for CA.....	1197
B.3.2.1	Receiver sensitivity relaxation for UE supporting CA in FR1	1197
B.3.2.2	Receiver sensitivity relaxation for UE configured with CA in FR1	1197
B.3.2.2.1	Inter-band carrier aggregation.....	1197
B.3.2.2.2	Reference sensitivity exceptions due to UL harmonic interference for CA	1197
B.3.2.2.3	Reference sensitivity exceptions due to intermodulation interference due to 2UL CA	1198
B.3.2.3	Receiver sensitivity relaxation for UE supporting CA in FR2	1198
B.3.2.4	Receiver sensitivity relaxation for UE configured with CA in FR2.....	1198
B.3.2.4.1	Intra-band contiguous carrier aggregation	1198
B.3.2.4.2	Intra-band non-contiguous carrier aggregation.....	1198
B.3.3	Receiver sensitivity relaxation for DC	1198
B.3.3.1	Receiver sensitivity relaxation for EN-DC	1198
B.3.3.2	Receiver sensitivity relaxation for NE-DC	1198
B.3.4	Receiver sensitivity relaxation for SUL	1198
B.3.4.1	Receiver sensitivity relaxation for UE supporting SUL in FR1	1198
B.3.4.2	Receiver sensitivity relaxation for UE configured with SUL in FR1	1198
B.3.4.2.1	Reference sensitivity exceptions due to UL harmonic interference for SUL	1198
Annex C (informative):	Change history	1200