

The Java Environment



SoftEng
<http://softeng.polito.it>

© Maurizio Morisio, Marco Torchiano, 2015






This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

To view a copy of this license, visit

<http://creativecommons.org/licenses/by-nc-nd/4.0/>.

You are free: to copy, distribute, display, and perform the work

Under the following conditions:

-  **Attribution.** You must attribute the work in the manner specified by the author or licensor.
-  **Non-commercial.** You may not use this work for commercial purposes.
-  **No Derivative Works.** You may not alter, transform, or build upon this work.
 - For any reuse or distribution, you must make clear to others the license terms of this work.
 - Any of these conditions can be waived if you get permission from the copyright holder.

Your fair use and other rights are in no way affected by the above.

Learning objectives

- Understand the basic features of Java
 - ♦ What are portability and robustness?
- Understand the concepts of bytecode and interpreter
 - ♦ What is the JVM?
- Learn few coding conventions
 - ♦ How shall I name identifiers?

Java Timeline


- 1991: SUN develops a programming language for cable TV set-top boxes
- Simple, OO, platform independent
- 1994: Java-based web browser (HotJava), the idea of “applet” comes out
- 1996: first version of Java (1.0)

See also: <http://oracle.com.edgesuite.net/timeline/java/>

Java timeline (cont' d)

- 1996: Netscape supports Java
 - ♦ Popularity grows
 - ♦ Java 1.02 released, followed by many updated releases in close rounds
- 1997: Java 1.1 released, major leap over for the language
- 1998: Java 2 platform (v. 1.2) released (libraries)
- 2000: J2SE 1.3 (platform enhancements, HotSpot)
- 2002: J2SE 1.4 (several new APIs), e.g.
 - ♦ XML
 - ♦ Logging

Java timeline (cont' d)

- 2005: J2SE 5.0 (Language enhancements)
 - ♦ Generics
- 2006: Java SE 6 (Faster Graphics),
 - ♦ goes open source
- 2011: Java SE 7 (I/O improvements)
- 2014: Java SE 8 (Language evolution)
 - ♦ Lambda expressions
 - ♦ Functional paradigm
 - ♦ New features marked with 

OO language features

- OO language provides constructs to:
 - ♦ Define classes (types) in a hierarchic way (inheritance)
 - ♦ Create/destroy objects dynamically
 - ♦ Send messages (w/ dynamic binding)
- No procedural constructs (pure OO language)
 - ♦ no functions, class methods only
 - ♦ no global vars, class attributes only

Java features

- Platform independence (portability)
 - ♦ Write once, run everywhere
 - ♦ Translated to intermediate language (bytecode)
 - ♦ Interpreted (with optimizations, e.g. JIT)
- High dynamicity
 - ♦ Run time loading and linking
 - ♦ Dynamic array sizes
- Automatic garbage collection

Java features (cont' d)

- Robust language, i.e. less error prone
 - ♦ Strong type model and no explicit pointers
 - Compile-time checks
 - ♦ Run-time checks
 - No array overflow
 - ♦ Garbage collection
 - No memory leaks
 - ♦ Exceptions as a pervasive mechanism to check errors

Java features (cont' d)

- Shares many syntax elements w/ C++
 - ♦ Learning curve is less steep for C/C++ programmers
- Quasi-pure OO language
 - ♦ Only classes and objects (no functions, pointers, and so on)
- Basic types deviates from pure OO...
- Easy to use

Java features – Classes

- There is only one first level concept: the **class**

```
public class First {  
}
```

- The source code of a class sits in a *.java* file having the *same name*
 - ♦ Rule: one file per class
 - ♦ Enforced automatically by IDEs
 - ♦ Case-wise name correspondence

Java features – Methods

- In Java there are no functions, but only methods within classes
- The execution of a Java program starts from a special method:

```
public static void main(String[] args)
```


- Note

In C we find the function:


```
int main(int argc, char* argv[])
```

- ♦ return type is **void**
- ♦ **args**[0] is the first argument on the command line (after the program name)

Build and run



Building and running



Java Ecosystem

- Java language
- Java platform
 - ♦ JVM
 - ♦ Class libraries (API)
 - ♦ SDK

Dynamic class loading

- JVM loading is based on the **classpath**:
 - ♦ list of locations whence classes can be loaded
- When class X is required:
 - ♦ For each location in the classpath:
 - Look for file X.class
 - If present load the class
 - Otherwise move to next location

Example

- File: First.java:

```
public class First {  
    public static void main(String[] args) {  
        int a;  
        a = 3;  
        System.out.println(a);  
    }  
}
```

Java features (cont' d)

- Supports “programming in the large”
 - ♦ JavaDoc
 - ♦ Class libraries (Packages)
- Lots of standard utilities included
 - ♦ Concurrency (thread)
 - ♦ Graphics (GUI) (library)
 - ♦ Network programming (library)
 - socket, RMI
 - applet (client side programming)

Types of Java programs

- **Application**

- ♦ It's a common program, similarly to C executable programs
- ♦ Runs through the Java interpreter (**java**) of the installed Java Virtual Machine

```
public class HelloWorld {  
    public static void main(String args[]){  
        System.out.println("Hello world!");  
    }  
}
```

Types of Java programs

- **Applet** (client browser)
 - ♦ Java code dynamically downloaded
 - ♦ Execution is limited by “sandbox”
- **Servlet** (web server)
 - ♦ In J2EE (Java 2 Enterprise Edition)
- **Midlet** (mobile devices)
 - ♦ In J2ME (Java 2 Micro Edition)
- **Android App** (Android device)
 - ♦ Java

Java development environment

- Java SE 8
(<http://www.oracle.com/technetwork/java/javase>)
 - ♦ javac compiler
 - ♦ jdb debugger
 - ♦ JRE (Java Run Time Environment)
 - JVM
 - Native packages (awt, swing, system, etc)
- Docs
 - ♦ <http://docs.oracle.com/javase/>
- Eclipse:
 - ♦ Integrated development environment (IDE)
 - ♦ <http://www.eclipse.org/>

Coding conventions

- Use **camelBackCapitalization** for compound names, not underscore
- Class name must be capitalized
- Method names, object instance names, attributes, method variables must all start in lowercase
- Constants must be all uppercases (w/ underscore)
- Indent properly

Coding conventions (example)

```
class ClassName {  
  
    final static double PI = 3.14;  
  
    private int attributeName;  
  
    public void methodName {  
        int var;  
        if ( var==0 ) {  
        }  
    }  
}
```

Deployment – Jar

- Java programs are packaged and deployed in **jar** files.
- Jar files are compressed archives
 - ♦ Like zip files
 - ♦ Contain additional meta-information
- It is possible to directly execute the contents of a jar file from a JVM
 - ♦ JVM can load classes from within a JAR

Jar command

- A jar file can be created using:
`jar cvf my.jar *.class`
- The contents can be seen with:
`jar tf my.jar`
- To run a class included in a jar:
`java -cp my.jar First`
 - ♦ The “-cp my.jar” option adds the jar to the JVM classpath

Jar Main class

- When a main class for a jar is defined, it can be executed simply by:
`java -jar my.jar`
- To define a main class, a manifest file must be added to the jar with:
`jar cvfm my.jar manifest.txt`



Main-Class: First

FAQ

- Which is more “powerfull”: Java or C?
 - ♦ Performance: C is better though non that much better (JIT)
 - ♦ Ease of use: Java
 - ♦ Error containment: Java
- How can I generate an “.exe” file?
 - ♦ You cannot. Use an installed JVM to execute the program
 - ♦ GCJ: <http://gcc.gnu.org/java/>

FAQ

- I downloaded Java on my PC but I cannot compile Java programs:
 - ♦ Check you downloaded Java SDK (including the compiler) not Java RTE or JRE (just the JVM)
 - ♦ Check the path includes *pathToJava/bin*
- Note: Eclipse uses a different compiler than javac

FAQ

- Java cannot find a class (ClassNotFoundException)
 - ♦ The name of the class must not include the extension .class:
 - Es. java First
 - ♦ Check you are in the right place in your file system
 - java looks for classes starting from the current working directory

Wrap-up session

- Java is a quasi-pure OO language
- Java is interpreted
- Java is robust (no explicit pointers, static/dynamic checks, garbage collection)
- Java provides many utilities (data types, threads, networking, graphics)
- Java can be used for different types of programs
- Coding conventions are not “just aesthetic”