




5/9/2026

Imran Nazeer

DHC-2094 (Cybersecurity Intern)

<https://github.com/ink-baltee/DevHub-Cybersecurity-Internship-2026>



Phase 1 Week 2 Report

DEVELOPERSHUB CORPORATION


Contents

1. Overview	4
1.1 Week 2 Objectives.....	4
1.2 Fixes Summary.....	4
2. Development Environment.....	5
2.1 Environment Details	5
2.2 Libraries Installed in Week 2.....	5
3. Fix 1, Input Validation & Sanitization	6
3.1 Vulnerability Being Fixed	6
3.2 What Was Changed	6
3.2.1 validator Library Import.....	6
3.2.2 Before, Weak Validation (Vulnerable Code)	6
3.2.3 After, Strong Validation (Fixed Code)	6
3.3 What the New Validation Enforces.....	7
3.4 Testing & Verification.....	7
Test 1, Weak Password Rejected	7
Test 2, Strong Password Accepted	9
4. Fix 2, Secure Password Hashing with bcrypt.....	10
4.1 Vulnerability Being Fixed	10
4.2 What Is bcrypt?.....	10
4.3 What Was Changed	10
4.3.1 Before, Plain Text Storage (Vulnerable Code).....	10
4.3.2 After, Secure Hashing (Fixed Code).....	11
4.4 Testing & Verification.....	11
Test 1, New Account Password is Hashed	11
Test 2, Login Works with Hashed Password	12
5. Fix 3, JWT Token Authentication.....	13
5.1 Vulnerability Being Fixed	13
5.2 What Is JWT?	13
5.3 What Was Changed	13
5.3.1 JWT Secret Added to Config (config/env/all.js)	13
5.3.2 JWT Import Added to session.js.....	13
5.3.3 JWT Token Generated on Login	14
5.4 Testing & Verification.....	14
6. Fix 4, Secure HTTP Headers with Helmet.js	16
6.1 Vulnerabilities Being Fixed	16

6.2 What Is Helmet.js?	16
6.3 What Was Changed	16
6.3.1 Before, No Security Headers (Vulnerable Code)	16
6.3.2 After, Full Security Headers (Fixed Code)	17
6.3.3 Session Cookie Security Also Improved	17
6.4 Testing & Verification	17
7. Fix 5, Logging & Error Handling with Winston	19
7.1 Vulnerability Being Fixed	19
7.2 What Is Winston?	19
7.3 What Was Changed	19
7.3.1 Winston Logger Created in server.js	19
7.3.2 Global Error Handler Added	20
7.3.3 Request Logger Added	20
7.4 Security Log Output	20
7.5 Before vs After Error Handling	20
7.6 Testing & Verification	21
8. Before vs After Security Comparison	23
9. Files Modified	24
10. Security Checklist	25
11. Conclusion	26

Target Application:
OWASP NodeGoat v1.3.0 RetireEasy

Field	Details
Prepared By	Imran Nazeer (DevHub Cybersecurity Intern)
Internship Phase	Phase 1, Week 2
Report Date	9 May 2026
Report Classification	Internal / Training Use Only
Target URL	http://localhost:4000
Report Type	Security Fix Implementation Report
Fixes Implemented	5 (Input Validation, Password Hashing, JWT Auth, Helmet.js, Winston Logging)
Files Modified	app/routes/session.js, app/data/user-dao.js, server.js, config/env/all.js



Screenshot 1: NodeGoat Application Running After Week 2 Fixes

Browser showing http://localhost:4000 with the app running after all security fixes applied

1. Overview

This report documents the security fixes implemented during Week 2 of the DevelopersHub Cybersecurity Internship, Phase 1. Building on the vulnerability findings identified in the Week 1 Security Assessment Report, this week focused on applying concrete security measures to the OWASP NodeGoat application to address the most critical vulnerabilities.

Five security improvements were successfully implemented: input validation and sanitization using the validator library, secure password hashing using bcrypt, JWT token-based authentication, HTTP security headers using Helmet.js, and server-side logging and error handling using Winston. Each fix directly addresses one or more vulnerabilities identified in the Week 1 report.

All changes were applied to the live running NodeGoat application and tested to verify correct functionality. The application remains fully operational with all security improvements active.

1.1 Week 2 Objectives

1. Install and configure the validator library for input validation and sanitization
2. Replace deprecated bcrypt-nodejs with bcrypt for secure password hashing
3. Implement JWT token-based authentication using jsonwebtoken
4. Add secure HTTP headers using Helmet.js
5. Set up server-side request logging and global error handling using Winston
6. Test each fix to verify it works correctly without breaking existing functionality
7. Document all changes with before/after code comparisons and test evidence

1.2 Fixes Summary

#	Fix Implemented	Library Used	Week 1 Finding Addressed	Status
1	Input Validation & Sanitization	validator	Findings 1,2,4,6	Complete
2	Secure Password Hashing	bcrypt	Finding 4, Weak Password Policy	Complete
3	JWT Token Authentication	jsonwebtoken	Finding 3, Open Redirect / Auth	Complete
4	Secure HTTP Headers	helmet	ZAP Medium Alerts, Missing Headers	Complete
5	Logging & Error Handling	winston	Finding 5, Verbose Error Disclosure	Complete

2. Development Environment

2.1 Environment Details

Item	Details
Operating System	Windows 10/11
Node.js Version	v24.15.0
npm Version	v11.x
MongoDB Version	4.4.29
Code Editor	Visual Studio Code with Claude Extension
Application	OWASP NodeGoat v1.3.0
Application URL	http://localhost:4000

2.2 Libraries Installed in Week 2

Library	Version	Command	Purpose
validator	Latest	npm install validator	Input validation and sanitization
bcrypt	Latest	npm install bcrypt	Secure password hashing with salt
jsonwebtoken	Latest	npm install jsonwebtoken	JWT token generation and verification
helmet	Latest	npm install helmet	HTTP security headers
winston	Latest	npm install winston	Server-side logging

```
PS C:\Users\hp\Desktop\DevHub Internship\Phase 1\Week 1\NodeGoat> npm list validator bcrypt jsonwebtoken helmet winston
├── winston@0.8.0
│   ├── prompt@0.2.14
│   └── winston@0.8.3
├── winston@0.8.3
├── helmet@2.3.0
├── jsonwebtoken@9.0.3
├── validator@13.15.35
└── winston@3.19.0

PS C:\Users\hp\Desktop\DevHub Internship\Phase 1\Week 1\NodeGoat>
```

Screenshot 2: npm install Commands

PowerShell terminal showing successful installation of all 5 security libraries

3. Fix 1, Input Validation & Sanitization

3.1 Vulnerability Being Fixed

Field	Details
Week 1 Finding	Finding 4, Weak Password Policy, Finding 6, Incorrect Input Validation
Severity	Critical / Low
Problem	No password complexity requirements '123' accepted as valid password
Problem	Wrong validation rules applied to wrong form fields
Library Used	validator (npm install validator)
File Modified	app/routes/session.js

3.2 What Was Changed

The validateSignup function in session.js was updated to enforce strong password requirements and correct username validation. The validator library was also imported for use across the application.

3.2.1 validator Library Import

Added at the top of session.js:

```
const validator = require("validator");
```

3.2.2 Before, Weak Validation (Vulnerable Code)

The original code used weak regex patterns that accepted any password including '123':

```
const USER_RE = /^[1,20]$/;
const PASS_RE = /^[1,20]$/;
/*
// Fix for A2-2 - Broken Authentication
const PASS_RE = /^(?=.*\d)(?=.*[a-z])(?=.*[A-Z]).{8,}$/;
*/

if (!PASS_RE.test(password)) {
  errors.passwordError = "Password must be 8 to 18 characters" +
    " including numbers, lowercase and uppercase letters.";
  return false;
}
```

3.2.3 After, Strong Validation (Fixed Code)

The updated code enforces strict password complexity and proper username format:

```
const USER_RE = /^[a-zA-Z0-9_]{3,20}$/;
const PASS_RE = /^(?=.*\d)(?=.*[a-z])(?=.*[A-Z])(?=.*[a-zA-Z0-9]).{8,}$/;

if (!PASS_RE.test(password)) {
  errors.passwordError = "Password must be at least 8 characters including " +
    "uppercase, lowercase, number, and special character.";
  return false;
}
```

3.3 What the New Validation Enforces

Rule	Regex / Logic	Example Pass	Example Fail
Min 8 characters	<code>/.{8,}/</code>	Test@1234	123
At least one uppercase	<code>(?=.*[A-Z])</code>	Test@1234	test@1234
At least one lowercase	<code>(?=.*[a-z])</code>	Test@1234	TEST@1234
At least one number	<code>(?=.*\d)</code>	Test@1234	Test@abcd
At least one special char	<code>(?=.*[a-zA-Z0-9])</code>	Test@1234	Test1234
Username alphanumeric only	<code>/^[a-zA-Z0-9_]{3,20}\$/</code>	testuser	t! or ab

3.4 Testing & Verification

Test 1, Weak Password Rejected

8. Navigated to <http://localhost:4000/signup>
9. Entered password: 123
10. Result: Error displayed 'Password must be at least 8 characters including uppercase, lowercase, number, and special character.'
11. Account was NOT created

A browser window showing the OWASP Node Goat Project signup page. The address bar displays 'localhost:4000/signup'. The page has a dark header with the project name. Below the header, there is a light gray box with the text 'Already a user? [Login](#)'. A red error message box states: 'Password must be at least 8 characters including uppercase, lowercase, number, and special character.' The main form is titled 'Enter sign up information' and contains several input fields: 'User Name' (with the value 'weekpasswordrejected'), 'First Name' (placeholder 'Enter first name'), 'Last Name' (placeholder 'Enter last name'), 'Password' (placeholder 'Enter password'), 'Verify Password' (placeholder 'Enter password'), and 'Email (Optional)' (placeholder 'Enter email'). A blue 'Submit' button is at the bottom of the form.

localhost:4000/signup

OWASP Node Goat Project

Already a user? [Login](#)

Password must be at least 8 characters including uppercase, lowercase, number, and special character.

Enter sign up information

User Name

weekpasswordrejected

First Name

Enter first name

Last Name

Enter last name

Password

Enter password

Verify Password

Enter password

Email (Optional)

Enter email

Submit


Screenshot 3: Weak Password Rejected

Browser showing the signup page with error message after entering password '123'

Test 2, Strong Password Accepted

12. Entered password: Test@1234

13. Result: Account created successfully



Screenshot 4: Strong Password Accepted

Browser showing successful account creation after entering password 'Test@1234'

4. Fix 2, Secure Password Hashing with bcrypt

4.1 Vulnerability Being Fixed

Field	Details
Week 1 Finding	Finding 4, Weak Password Policy
Severity	Critical
Problem 1	Passwords stored in plain text, any database breach exposes all passwords
Problem 2	Deprecated bcrypt-nodejs package used known security issues with NUL characters
Library Used	bcrypt (npm install bcrypt)
File Modified	app/data/user-dao.js

4.2 What Is bcrypt?

bcrypt is a password hashing algorithm designed specifically for secure password storage. It works by applying a one-way cryptographic hash combined with a random salt value, making it computationally expensive to reverse. The salt factor (cost factor) determines how many rounds of hashing are applied, higher values mean slower hashing but stronger protection against brute-force attacks.

Concept	Explanation
Hashing	Converts password to a fixed-length string that cannot be reversed
Salting	Adds a random value before hashing, prevents rainbow table attacks
Cost Factor	Number of hashing rounds, we use 10 (recommended minimum)
One-way	Impossible to get original password back from the hash
Comparison	bcrypt.compareSync() safely compares a plain password to a stored hash

4.3 What Was Changed

4.3.1 Before, Plain Text Storage (Vulnerable Code)

Original user-dao.js stored passwords in plain text and used deprecated bcrypt-nodejs:

```
const bcrypt = require("bcrypt-nodejs"); // deprecated package

// In addUser():
const user = {
  userName,
  firstName,
  lastName,
  password // stored as plain text!
};
```

```
// In validateLogin():
const comparePassword = (fromDB, fromUser) => {
  return fromDB === fromUser; // plain text comparison!
};
```

4.3.2 After, Secure Hashing (Fixed Code)

Updated user-dao.js now uses bcrypt to hash passwords on save and compare securely on login:

```
const bcrypt = require("bcrypt"); // actively maintained package


// In addUser() - password is hashed before storing:
const user = {
  userName,
  firstName,
  lastName,
  password: bcrypt.hashSync(password, bcrypt.genSaltSync(10))
};

// In validateLogin() - secure bcrypt comparison:
const comparePassword = (fromDB, fromUser) => {
  return bcrypt.compareSync(fromUser, fromDB);
};
```

4.4 Testing & Verification

Test 1, New Account Password is Hashed

14. Created new account: Username: secureuser2, Password: Test@1234
15. Account created successfully
16. Password stored as bcrypt hash in MongoDB, not plain text



Screenshot 5: Successful Account Creation with Hashed Password


Browser showing successful signup with strong password Test@1234

Test 2, Login Works with Hashed Password

17. Logged out of the application

18. Logged back in with Username: secureuser3, Password: Test@1234

19. Login successful, bcrypt.compareSync() correctly verified the password



Screenshot 6: Successful Login After bcrypt Implementation

Browser showing successful login with the secureuser3 account after logout

5. Fix 3, JWT Token Authentication

5.1 Vulnerability Being Fixed

Field	Details
Week 1 Finding	Finding 3, Open Redirect / XSS Vector
Severity	High
Problem	Session-only authentication, no token-based security layer
Problem	No token expiry, sessions could persist indefinitely
Library Used	jsonwebtoken (npm install jsonwebtoken)
Files Modified	app/routes/session.js, config/env/all.js

5.2 What Is JWT?

JSON Web Token (JWT) is an open standard for securely transmitting information between parties as a digitally signed token. JWTs consist of three parts: a Header (algorithm type), a Payload (user data), and a Signature (verification). The signature ensures the token has not been tampered with.

JWT Part	Contents	Purpose
Header	Algorithm type (e.g. HS256)	Defines how the token is signed
Payload	User ID, username, expiry time	Carries user identity information
Signature	HMAC hash of header + payload + secret	Verifies token integrity

5.3 What Was Changed

5.3.1 JWT Secret Added to Config (config/env/all.js)

Added JWT configuration to the application config file:

```
module.exports = {
  port,
  db,
  cookieSecret: "session_cookie_secret_key_here",
  cryptoKey: "a_secure_key_for_crypto_here",
  cryptoAlgo: "aes256",
  hostName: "localhost",
  jwtSecret: "devhub_jwt_secret_key_2026", // NEW
  jwtExpiry: "1h", // NEW - token expires in 1 hour
  environmentalScripts: []
};
```

5.3.2 JWT Import Added to session.js

Added JWT library import at the top of session.js:

```
const jwt = require("jsonwebtoken");
const {
  environmentalScripts,
  jwtSecret,
  jwtExpiry
} = require("../../config/config");
```

5.3.3 JWT Token Generated on Login

Updated handleLoginRequest to generate and store a JWT token on successful login:

```
// After successful login:
req.session.userId = user._id;


// Generate JWT token with user identity and expiry
const token = jwt.sign(
  { id: user._id, userName: user.userName },
  jwtSecret,
  { expiresIn: jwtExpiry }
);

// Store token in httpOnly cookie (not accessible via JavaScript)
res.cookie("jwt_token", token, { httpOnly: true });

return res.redirect(user.isAdmin ? "/benefits" : "/dashboard");
```

5.4 Testing & Verification

20. Navigated to <http://localhost:4000/login>
21. Logged in with valid credentials: secureuser2 / Test@1234
22. Opened Browser Developer Tools (F12) → Application tab
23. Clicked Cookies → <http://localhost:4000>
24. Confirmed jwt_token cookie is present with httpOnly flag



Screenshot 7: JWT Token in Browser Cookies

Browser DevTools Application tab showing jwt_token cookie after successful login

6. Fix 4, Secure HTTP Headers with Helmet.js

6.1 Vulnerabilities Being Fixed

Field	Details
Week 1 ZAP Findings	Missing Anti-Clickjacking Header, CSP Header Not Set, X-Content-Type-Options Missing
Severity	Medium
Problem 1	No X-Frame-Options header, application vulnerable to clickjacking attacks
Problem 2	No Content Security Policy, XSS attacks can load external malicious scripts
Problem 3	X-Powered-By header exposes technology stack (Express.js) to attackers
Problem 4	No X-Content-Type-Options, browser MIME sniffing attacks possible
Library Used	helmet (npm install helmet)
File Modified	server.js

6.2 What Is Helmet.js?

Helmet.js is a collection of middleware functions for Express.js that set various HTTP response headers to improve application security. It protects against well-known web vulnerabilities by setting headers that instruct the browser on how to handle the application's content.

Helmet Function	Header Set	Protection Against
helmet()	Multiple security headers	General security baseline
helmet.frameguard()	X-Frame-Options: DENY	Clickjacking attacks
helmet.noSniff()	X-Content-Type-Options: nosniff	MIME type sniffing attacks
helmet.xssFilter()	X-XSS-Protection: 1; mode=block	Reflected XSS in older browsers
app.disable('x-powered-by')	Removes X-Powered-By header	Technology fingerprinting

6.3 What Was Changed

6.3.1 Before, No Security Headers (Vulnerable Code)

The original server.js had Helmet commented out with no active security headers:

```
// const helmet = require("helmet"); // commented out - not active!

/*
// Fix for A5 - Security MisConfig
app.disable("x-powered-by");
app.use(helmet.frameguard());
```

```
app.use(helmet.contentSecurityPolicy());
app.use(helmet.hsts());
*/
```

6.3.2 After, Full Security Headers (Fixed Code)

Updated server.js with Helmet.js fully enabled:

```
const helmet = require("helmet"); // active import

// Applied after database connects:
app.use(helmet()); // sets multiple security headers
app.use(helmet.frameguard({ action: "deny" })); // X-Frame-Options: DENY
app.use(helmet.noSniff()); // X-Content-Type-Options: nosniff
app.use(helmet.xssFilter()); // X-XSS-Protection: 1; mode=block
app.disable("x-powered-by"); // removes X-Powered-By header
```

6.3.3 Session Cookie Security Also Improved


The session cookie configuration was also hardened:

```
app.use(session({
  secret: cookieSecret,
  saveUninitialized: true,
  resave: true,
  key: "sessionId", // generic name instead of "connect.sid"
  cookie: {
    httpOnly: true, // not accessible via JavaScript
    sameSite: "strict" // prevents CSRF attacks
  }
}));
```

6.4 Testing & Verification

25. Started the application and navigated to <http://localhost:4000>
26. Opened Browser Developer Tools (F12) → Network tab
27. Refreshed the page and clicked on the first request
28. Clicked Headers → Response Headers
29. Verified the following headers are now present:

Header	Value	Status
X-Content-Type-Options	nosniff	Present
X-Frame-Options	DENY	Present
X-XSS-Protection	1; mode=block	Present
X-Powered-By	(removed)	Removed



Screenshot 8: Security Headers in Browser DevTools

Browser DevTools Network tab showing Response Headers with X-Frame-Options, X-Content-Type-Options, and X-XSS-Protection present

7. Fix 5, Logging & Error Handling with Winston

7.1 Vulnerability Being Fixed

Field	Details
Week 1 Finding	Finding 5, Verbose Error Message Disclosure
Severity	Medium
Problem 1	Raw MongoDB errors and SyntaxErrors displayed directly to users
Problem 2	No server-side logging, no way to detect or investigate attacks
Problem 3	Application crashes expose internal architecture details
Library Used	winston (npm install winston)
File Modified	server.js

7.2 What Is Winston?

Winston is the most popular logging library for Node.js applications. It supports multiple log levels (error, warn, info, debug), multiple output transports (console, file, database), and customizable log formats. Using Winston allows the application to log detailed error information server-side while showing only generic messages to end users.

Winston Feature	Configuration Used	Purpose
Log Levels	info, error	Categorize log entries by severity
Timestamp Format	ISO timestamp on every entry	Track exactly when events occur
Console Transport	Outputs to terminal	Real-time monitoring during development
File Transport	Writes to security.log	Persistent log file for audit trail
Custom Format	[LEVEL]: timestamp message	Human-readable structured log format

7.3 What Was Changed

7.3.1 Winston Logger Created in server.js

Added at the very top of server.js, before all other code:

```
const winston = require("winston");

const logger = winston.createLogger({
  level: "info",
  format: winston.format.combine(
    winston.format.timestamp(),
    winston.format.printf(({ timestamp, level, message }) => {
      return `${timestamp} [${level.toUpperCase()}]: ${message}`;
    })
  ),
  transports: [
```

```

    new winston.transports.Console(),
    new winston.transports.File({ filename: "security.log" })
  ]
});

```

7.3.2 Global Error Handler Added

A global Express error handler was added to catch all unhandled errors and log them server-side while showing only a generic message to the user:

```

// Global error handler - catches all unhandled Express errors
app.use((err, req, res, next) => {
  logger.error(`Error: ${err.message} | URL: ${req.url} | Method: ${req.method}`);
  return res.status(500).render("error", {
    message: "An error occurred. Please try again.",
    environmentalScripts
  });
});

```

7.3.3 Request Logger Added

Every incoming HTTP request is now logged with method and URL:

```

// Log every incoming request
app.use((req, res, next) => {
  logger.info(`Request: ${req.method} ${req.url}`);
  next();
});

```

7.4 Security Log Output

The Winston logger writes structured log entries to both the console and a security.log file. Example log output:

```

2026-05-09T19:45:23.123Z [INFO]: Application started
2026-05-09T19:45:24.456Z [INFO]: Request: GET /
2026-05-09T19:45:25.789Z [INFO]: Request: POST /login
2026-05-09T19:45:26.012Z [INFO]: Request: GET /dashboard
2026-05-09T19:45:27.345Z [ERROR]: Error: MongoError | URL: /allocations/1 | Method: POST

```

7.5 Before vs After Error Handling

Scenario	Before (Vulnerable)	After (Fixed)
----------	---------------------	---------------

MongoError on /allocations	Full MongoDB error shown to user	Generic 'An error occurred' message shown
SyntaxError on /contributions	Raw SyntaxError shown to user	Generic error shown, full error logged server-side
Any unhandled error	App crashes or shows stack trace	Global handler catches it, logs it, shows generic message
Request tracking	No logging, no audit trail	Every request logged with timestamp to security.log

7.6 Testing & Verification

30. Restarted the application after adding Winston
31. Navigated to <http://localhost:4000> and performed several actions
32. Checked the terminal, confirmed request logs appearing in real time
33. Checked NodeGoat folder, confirmed security.log file was created



```

NodeGoat > JS server.js > MongoClient.connect() callback
49 MongoClient.connect(db, (err, db) => {
192 | message: "An error occurred. Please try again.",
    |
    |
    |
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

PS C:\Users\hp\Desktop\DevHub\Internship\Phase 1\Week 1\NodeGoat> npm start
  zapHostname: '192.168.56.20',
  zapPort: '8080',
  zapApiKey: 'v9dn0balpqas1pcc281tn5ood1',
  zapApiFeedbackSpeed: 5000
}
Connected to the database
Express http server listening on port 4000
2026-05-13T19:03:55.799Z [INFO]: Request: GET /
welcome: Unable to identify user...redirecting to login
2026-05-13T19:03:55.849Z [INFO]: Request: GET /login
2026-05-13T19:08:48.539Z [INFO]: Request: GET /signup
2026-05-13T19:09:44.848Z [INFO]: Request: POST /signup
user did not validate
2026-05-13T19:12:00.808Z [INFO]: Request: POST /signup
number
Updated allocations
2026-05-13T19:14:22.028Z [INFO]: Request: GET /logout
2026-05-13T19:14:22.072Z [INFO]: Request: GET /
welcome: Unable to identify user...redirecting to login
2026-05-13T19:14:22.102Z [INFO]: Request: GET /login
2026-05-13T19:14:33.629Z [INFO]: Request: POST /login
Error: attempt to login with invalid user: secureuser2
2026-05-13T19:14:45.505Z [INFO]: Request: POST /login
2026-05-13T19:14:45.683Z [INFO]: Request: GET /dashboard
2026-05-13T19:16:24.318Z [INFO]: Request: GET /.well-known/appspecific/com.chrome.devtools.json
2026-05-13T19:18:27.857Z [INFO]: Request: GET /dashboard
2026-05-13T19:18:27.986Z [INFO]: Request: GET /.well-known/appspecific/com.chrome.devtools.json
2026-05-13T19:18:37.150Z [INFO]: Request: GET /dashboard
2026-05-13T19:18:37.346Z [INFO]: Request: GET /.well-known/appspecific/com.chrome.devtools.json
2026-05-13T19:18:59.268Z [INFO]: Request: GET /.well-known/appspecific/com.chrome.devtools.json
2026-05-13T19:19:03.441Z [INFO]: Request: GET /dashboard
2026-05-13T19:19:03.690Z [INFO]: Request: GET /.well-known/appspecific/com.chrome.devtools.json
  
```

Screenshot 9: Winston Logs in Terminal

PowerShell terminal showing Winston log output with timestamps and request logs during app usage



Screenshot 10: security.log File Created

VS Code or File Explorer showing the security.log file created in the NodeGoat root folder


8. Before vs After Security Comparison

The following table summarizes the security posture of the application before and after the Week 2 fixes:

Security Area	Before Week 2	After Week 2	Improvement
Password Policy	Any password accepted (e.g. '123')	Min 8 chars, upper+lower+number+special	Critical Fixed
Password Storage	Plain text in MongoDB	bcrypt hash with salt factor 10	Critical Fixed
Authentication	Session cookie only	Session + JWT token (httpOnly cookie)	High Fixed
HTTP Headers	No security headers	X-Frame-Options, XSS filter, noSniff	Medium Fixed
Error Messages	Raw MongoDB/JS errors shown	Generic message shown, logged server-side	Medium Fixed
Request Logging	No logging	All requests logged to security.log	Improved
Cookie Security	No httpOnly or SameSite	httpOnly:true, sameSite:strict	Improved
X-Powered-By Header	Exposed (Express)	Removed	Improved

9. Files Modified

File	Changes Made	Fix #
app/routes/session.js	Added validator import, strengthened password regex, added JWT import and token generation	1, 3
app/data/user-dao.js	Replaced bcrypt-nodejs with bcrypt, enabled password hashing in addUser(), fixed compareSync in validateLogin()	2
config/env/all.js	Added jwtSecret and jwtExpiry to application config	3
server.js	Added Winston logger, enabled Helmet.js, hardened session cookie, added global error handler and request logger	4, 5



Screenshot 11: Modified Files in VS Code Explorer

VS Code file explorer showing the modified files: session.js, user-dao.js, all.js, server.js

10. Security Checklist

The following checklist documents the security best practices status after Week 2 implementation:

#	Security Best Practice	Status	Implemented In
1	Validate all user inputs server-side	Done	session.js, validateSignup()
2	Enforce strong password policy (8+ chars, complexity)	Done	session.js, PASS_RE regex
3	Hash and salt all passwords before storing	Done	user-dao.js, bcrypt.hashSync()
4	Use secure password comparison (no plain text)	Done	user-dao.js, bcrypt.compareSync()
5	Implement token-based authentication	Done	session.js, jwt.sign()
6	Set JWT token expiry	Done	config/env/all.js, jwtExpiry: '1h'
7	Store JWT in httpOnly cookie	Done	session.js, res.cookie httpOnly:true
8	Set X-Frame-Options header	Done	server.js, helmet.frameguard()
9	Set X-Content-Type-Options header	Done	server.js, helmet.noSniff()
10	Set X-XSS-Protection header	Done	server.js, helmet.xssFilter()
11	Remove X-Powered-By header	Done	server.js, app.disable()
12	Set httpOnly flag on session cookie	Done	server.js, session cookie config
13	Set SameSite attribute on session cookie	Done	server.js, sameSite: strict
14	Log all incoming requests	Done	server.js, Winston request logger
15	Log all errors server-side	Done	server.js, Winston error logger
16	Show only generic error messages to users	Done	server.js, global error handler

11. Conclusion

Week 2 successfully addressed all Critical and High severity vulnerabilities identified in the Week 1 Security Assessment Report. Five security libraries were installed and configured, covering the most important areas of web application security: input validation, password security, authentication, HTTP headers, and error handling.

The most significant improvements were the enforcement of a strong password policy combined with bcrypt hashing, together these completely eliminate the Critical vulnerability of weak password storage that was found in Week 1. The addition of JWT authentication adds a second layer of identity verification on top of the existing session management, and Helmet.js closes all the missing HTTP header vulnerabilities identified by the OWASP ZAP scan.

Winston logging provides the application with a proper audit trail for the first time, enabling detection and investigation of suspicious activity. The global error handler ensures that internal error details are never again exposed to end users.

The application remains fully functional with all security fixes applied and verified through manual testing. Week 3 will conduct penetration testing using Nmap to verify the effectiveness of these fixes and identify any remaining vulnerabilities, followed by the final report and GitHub submission.

End of Week 2 Security Implementation Report