inkledger design system

How inkledger looks, feels and is built: for the people and the AI agents who change it. Colours and type in the plates are read from the code.

Contents

1. How to use this document
2. Principles
3. Colour
4. Type, density and spacing
5. Surfaces, elevation and motion
6. Components
7. Layout and overflow
8. Interaction
9. Copy and languages
10. Special surfaces
11. For AI agents: hard rules
12. Checklist before a PR
13. Plates: colour and type

How inkledger looks, feels and is built, for the people and the AI agents who change it.

The rules here are not wishes: `pnpm lint` enforces most of them, and an e2e test guards the others. Where a rule exists because of a past mistake, its **why** is given; keep it when you are tempted to "simplify" it away.

A printable version with live colour swatches and the type scale is in `docs/design-system.pdf`. It is regenerated from the code with `pnpm docs:design-system`.

1. How to use this document

You are…	Read	Then
Building a new page	§2, §5, §6, §8	Copy `src/pages/Dashboard.tsx`'s structure
Adding a component	§3, §4, §6, §7	Check §12 before you open a PR
Changing colours or type	§3 and the token sources	Run `pnpm theme:tokens`, `pnpm lint`, the e2e
An AI agent	All of it, §11 first	Never invent a token, size or colour

Sources of truth. When this document and the code disagree, the code wins: fix the document.

- `src/index.css`: tokens and base styles.
- `tailwind.config.js`: the scale and how tokens map to classes.
- `src/components/ui/*`: low-level primitives (shadcn/Radix).
- `src/components/app/*`: the app's own building blocks.
- `scripts/check-design.mjs`: the enforced rules.
- `docs/dev/ux-patterns.md`: interaction conventions, each guarded by an e2e test.

2. Principles

1. **Calm, warm, data first.** Warm neutrals with one terracotta accent (the user's colour, §3.2). Colour carries data and state, never decoration. The reference is a time-tracker dashboard: one white panel divided by hairlines, not a wall of boxed cards.
2. **Pastel and tone on tone.** Every colour derives from one base hue. Saturated fills were rejected as "too loud", and hue jumps towards pink or lilac as "a costume party".
3. **Minimal is not anonymous.** Character comes from texture (the grain on covers and paper) and one accent, **never from motion**. Hover animations and "fun" movement were rejected; a flat, toneless version was called "anonymous".
4. **Compact by default.** The root font is 14 px (§4.2). Density is a choice the user makes, not a page's.
5. **Everything is the app.** No page, pane or screen with its own look. A separate server page was called "awful and inconsistent". The Outlook pane is a page of the app's build for this reason (§10).
6. **Every screen has a way back**, and going back returns to where you were (state and scroll).
7. **Say what happens.** Copy describes what will happen and how to undo it, never the internals (§9).

3. Colour

3.1 Tokens, never values

Colours are CSS variables holding HSL triples (`--primary: 16.5 71.7% 78%`). Tailwind maps each one to a class with alpha support: `bg-primary` , `bg-primary/40` , `text-muted-foreground` .

Never	Use
Hex in components (`#B5562F`)	A token class (`text-primary-strong`)
Tailwind's palette (`bg-red-500` , `text-gray-600`)	A semantic token (`bg-danger-soft text-danger`)
`bg-white` , `text-black`	`bg-card` , `text-foreground`
A new CSS variable used directly	Register it in `tailwind.config.js` with `token("name")` , or the class generates nothing (the lint checks this)

3.2 The palette is derived

The user picks one base colour (Settings → Appearance, stored as `settings.theme_color` ; the default is terracotta `#B5562F`).

- `src/lib/theme/derive.ts` derives the whole light and dark palette from it in OKLCH, staying within 12° of its hue.
- `src/lib/theme/apply.ts` writes it at run time.
- The defaults in `src/index.css` between `@theme-derived:start` and `@theme-derived:end` are generated with `pnpm theme:tokens` . Never edit that block by hand.

`src/lib/theme/derive.test.ts` checks the contrast of every pair that matters, for many base colours: AA text, and focus rings ≥ 3:1. A colour change that breaks contrast fails the unit tests.

3.3 Roles

Token	Role	Typical classes
`canvas`	Behind everything (the page's ground)	`bg-canvas`
`background` , `card` , `popover`	Panels, cards, floating layers	`bg-card`
`foreground`	Main text	`text-foreground`
`muted` / `muted-foreground`	Quiet fills / secondary text (AA on card)	`bg-muted` , `text-muted-foreground`
`accent`	Hover and selected rows	`hover:bg-accent`
`border` , `input`	Hairlines, field borders	`border` , `border-input`
`action` / `action-foreground`	The one main action on a screen (the default `Button`)	via `Button`
`primary` , `primary-soft` , `primary-strong`	Brand tint, soft fills, accent text and dots	`text-primary-strong`

Token	Role	Typical classes
`ring`	Focus ring, always full strength	`focus-visible:ring-2 ring-ring`
`success`, `warning`, `danger`, `info` (+ `-soft`)	State: text on its soft fill	`bg-success-soft text-success`
`chart-*`, `project-1..6`	Data only: charts, project colours	`bg-chart-focus`
`paper`, `tape-1..5`, `string`	The pinboard's notes, washi tape, the red string	pinboard only
`cover-*`, `sunset-*`	Grainy covers: focus mode, avatars, illustrations, the sign-in page (never on a page's figures)	`cover-sunset`

3.4 Rules that came from mistakes

- **Project colours are stable per project.** A hash of the project key picks one of `--project-1..6`, never the project's rank in a period, which made colours jump around.
- **Hatched stripes mean one thing only:** tracked but not yet logged (a live timer). Never use them for logged data.
- **No decorative covers** on cards, figures or the issue page. A page's figures are a `StatStrip` (the stat card with a cover and tiles was retired on 3 Nov, as a favourite-card banner was before it: wasted space).
- **No gradients** except the theme's own sunset band on covers and the brand mark. No purple, blue or "AI" gradients.
- **Dark mode is not inverted light.** It has its own derived values. Check both themes, every time.

4. Type, density and spacing

4.1 Fonts

- **Inter Variable** for text. Its features `cv11`, `ss01`, `ss03` and `calt` give a single-storey a, open digits and a curved l.
- **Inter Tight Variable** (`font-display`) for titles and numbers that headline.
- **No monospace anywhere in the UI**, keys and codes included; the lint refuses `font-mono`. Use `tabular-nums` where digits must line up.

4.2 Type scale (the only sizes)

Class	Size	Use
`text-display`	2.75 rem, 600	One per page at most (big stats)
`text-title`	1.75 rem, 600	Page titles (`PageHeader`)
`text-heading`	1.375 rem, 600	Section and dialog headlines
`text-body`	1 rem	Body text
`text-body-sm`	0.875 rem	Dense lists, tables, most UI text
`text-caption`	0.8125 rem	Secondary lines, labels, hints
`text-overline`	≥ 11 px, 600, tracked	Small uppercase labels
`text-2xs`	≥ 11 px, 600	Counters in pills

Tailwind's `text-xs`, `text-sm`, `text-lg`... and arbitrary sizes such as `text-[13px]` are refused by the lint. Nothing is ever smaller than 11 px.

4.3 Density

Every size is in rem, so density scales the root: compact is 14 px (the default), comfortable is 16 px (`html[data-density]`). Never fix a size in px to "escape" density. The exceptions are hairlines and the 44 px touch target.

4.4 Spacing and radius

- **Spacing.** Tailwind's 4 px scale.
- Gap `2` by default; gap `1` only for dense chip groups.
- Sections use `p-5 md:p-6` (`PanelSection`).
- `touch` (44 px) and `target` (24 px) are named spacings for hit areas.
- **Radius.** It comes from `--radius` (0.5 rem):
- `rounded-sm`, `md`, `lg`, `xl` and `2xl` only;
- `rounded-3xl` and arbitrary radii are refused.
- Cards use `rounded-lg`; fields and buttons use `rounded-md`.

5. Surfaces, elevation and motion

5.1 Surfaces

Every element that stands out from what is under it declares what it is, with `{...surface(kind)}` from `src/components/app/surface.ts`. Never write `data-surface` by hand.

Kind	What it is
`control`	A button, switch, segmented option or nav box standing on the page
`chip`	A chip, badge or count pill
`picture`	An avatar, project picture or mark (its own silhouette)
`note`	A paper note on the pinboard (its shadow is part of the drawing)
`bar`	A data bar, block or meter on a chart or timeline
`card`	A card or a group of controls
`panel`	The main panel over the page
`nav`	A navigation item (stands out only while current)
`menu`	A menu, popover or list floating over the page
`dialog`	A dialog or sheet floating over the page
`ground`	What surfaces stand on (receives shadows, casts none)
`glass`	See-through by design (casts no shadow)

A box with a border or a fill and no `surface()` fails the lint, unless the line above says why: `// surface: none — <why>`.

This catalogue is what lets a module that draws light and shadow (the Shadow mod) reach every page without guessing from the DOM.

5.2 Elevation

The shadows are `shadow-xs`, `sm`, `md`, `lg` and `xl`: two soft layers tinted with `--shadow-color`.

- Pages and cards use `xs` or `sm` at most.
- `md` and above are for popovers and dialogs, inside `components/ui` only (the lint enforces it).
- Prefer hairlines to shadows for separating sections.

5.3 Motion

- The durations are 180 ms (`DEFAULT`), `fast` (120 ms) and `slow` (260 ms), with ease `cubic-bezier(.2,.8,.2,1)`.
- Motion explains a change: a page appears, a panel opens. **It never decorates**: no hover lifts, no bouncing, no animated gradients.
- `prefers-reduced-motion: reduce` stops all animations and transitions app-wide.

- **Smoothness first.** Nothing may cause jank. Writes to `:root` cost a frame, and modules are measured on GPU and on software rendering.

5.4 Icons

- Use lucide icons only, with one stroke weight everywhere (1.75, set in `index.css`).
- Icons sit at `h-4 w-4`, or `h-3.5 w-3.5` in captions.
- An icon that carries meaning without text has an `aria-label` on its button; one that only decorates is `aria-hidden`.

6. Components

6.1 Use what exists

Before writing a component, look in `src/components/app/` and `src/components/ui/`.

Need	Use	Not
Page title row	`PageHeader` (breadcrumb, h1, description, actions; sets the tab title)	A custom `<h1>` row
A block of the page panel	`PanelSection` / `PanelRow` (hairlines, not boxes)	Nested cards
A page's figures	`StatStrip` (one row divided by hairlines, three to a row under lg (two for four figures), the cover's grainy sunset as a faint wash behind the row; the figure looked for first is `lead`: a step larger, in the primary colour; a figure can be a filter or carry a `meter` towards its target; `busy` while another period loads; variants compact/default/expanded)	A card with a cover and tiles (retired)
A collection (recent issues, a board column's cards, a day's entries, attachments)	`Collection` (§7.1): a bounded adaptive grid of its container's width, a row budget, then "Show all N" (the same total at every width), expanded in place or on the full page	A rail scrolled sideways, a column clipped by a mask, a list that grows the page, a `slice` with no way to the rest
▶ on an issue shown as a card or tile	`StartIssueButton` (`controlId` for FlowMap; none while its timer runs; never the card's drag or link)	A per-page start button
A date typed or picked to jump to	`DateJump` (the picker jumps at once, typing on Enter or blur)	An `onChange` on a date input (typing "2" jumped to the 2nd)
A block that adapts to its own width	`region` (a container) and the `@m:` / `@l:` / `@xl:` variants: 28 / 56 / 80rem (`src/lib/layout/regions.ts`, shared with desk panes)	Viewport breakpoints (`md:`, `xl:`) inside a page's blocks
A header's controls	`Toolbar` (at most 3 groups; an item with a `menu` form folds behind ⋯ as the header's region narrows)	A row of controls that wraps the title
A row in a list	`ListRow` (lead, title, second line, trail; `min-h-target`, `coarse:min-h-touch`, never a fixed height)	A row with its own paddings
A card in a column or a grid	`ItemCard` (raised, `p-2.5`, `rounded-xl`)	A card with its own paddings
A board column's head, a folded column	`ColumnHeader`, `CollapsedColumn` (`components/app/Columns.tsx`)	A copy per board
A page's own controls under its header	`PageToolbar` (sticks under the sticky header on desktop, publishes `--page-toolbar-h`, opaque, wraps)	A search or filter row that scrolls away

Need	Use	Not
Sections of a page shown one at a time	`Tabs` + `TabPanel` (`components/ui/tabs.tsx`: one Tab stop, arrows without modifiers, value kept by the caller in the URL)	A long stack of sections
A secondary part folded under its title	`Disclosure` (title and count; content drawn only while open)	Always-open blocks of detail
Text with actions on a row	`ActionRow` (content `minmax(0,1fr)`, actions `shrink-0`)	Ad-hoc flex rows
A button	`Button`: variants `default` (the one main action), `outline`, `ghost`, `secondary`, `link`, `destructive`; sizes `sm`, `default`, `lg`, `icon`, `icon-sm`, `icon-lg`	Raw `<button>` with its own styling
A small label	`Chip`: tone `neutral`, `info`, `success`, `warning` or `danger`; variant `soft` for alerts, `dot` for status in lists	Coloured spans
Two to five exclusive choices	`SegmentedControl` (one radio group, arrows move)	A row of toggled buttons
Text typed in a field	`Input` / `Textarea` (their type is `text-field`: never under 16 px on a phone, where iOS would zoom in)	A field's own smaller text size
A choice from a list	`Select` (Radix, themed)	`<select>` or `<datalist>` (they ignore the theme; datalist is refused)
Picking an issue	`IssuePicker`	A custom search list
A link to another site	`ExternalLink` (asks before opening an unknown domain)	`<a target="_blank">`
Copying text	`CopyButton`	Hand-written clipboard code
Loading, empty, error	`PageSpinner`, `EmptyState`, `ErrorState` (with Retry)	Bare text
A meter or progress bar	`Meter`	Divs with widths
The brand	`BrandMark` (follows the theme)	The favicon image
A dialog	`Dialog` with title and description (named in every state)	Custom overlays
A dialog's body	`lazyPart` keeps it out of the first load	Importing heavy parts eagerly

6.2 States every component handles

1. **Loading.** One status per region: the spinner is decorative, its region says "Loading"; skeletons are `aria-hidden`.
2. **Empty.** It says what to do next (`EmptyState`), never only "No data".
3. **Error.** It says what failed and offers Retry (`ErrorState`, `toastError(e, { action })`). A failed action keeps what was typed.

4. **Busy.** While an action runs, its button is disabled and the result is announced (`role="status"` or a toast).
5. **Long content.**
6. User text wraps with `[overflow-wrap:anywhere]` (not `break-words`, which the lint refuses).
7. Single lines truncate with `truncate` inside a `min-w-0` parent.

7. Layout and overflow

- **One panel, hairlines inside.** Pages are one rounded panel over the canvas, divided by hairlines. On desktop the panel stays put and scrolls inside. Pages driven by controls (Dashboard, Timesheet, Issues) keep the header and their toolbar fixed and solid, with no blur.
- **Intrinsic sizing is the usual bug.**
- A grid track that holds text is `minmax(0,1fr)` (or `grid-cols-[minmax(0,1fr)]`).
- Flexible flex children get `min-w-0`.
- Never hide an overflowing child with the parent's `overflow`, and never add a global `overflow-x-hidden` to mask it.
- **No long lists, no white space beside them.** Every collection is bounded (§7.1). Sections side by side share one height and the shorter one fills it; the row's hairline is the row's own, never a section's in mid-air.
- **The sidebar never scrolls and is the same open and closed.**
- From top to bottom: brand (always visible), search, notifications, the sections, favorites (the only part that shrinks), then the foot.
- Sections: where the day is spent (Dashboard, Board, Issues, Desk, Timesheet) are rows; every other entry is a tile, icon over its whole name, 3 columns open and 2 closed, in the same order. Every entry stays inside the navigation block (FlowMap measures a click on the block it is drawn in).
- Icon-only tiles are 28–32 px with a 44 px touch area (`coarse:after:size-touch`), a tooltip and an accessible name.
- Foot: "Now" (the timer card, with Start timer always its last line), a hairline, the account, then the quick tiles (theme, screensaver, sync) with the sidebar's toggle last.
- Open, the timer card has every control on two lines (pause and stop by the time; move, discard and focus by the note). Closed, the ring opens a small player beside the rail with the same lines.
- Open, the quick tiles are one row; closed, a 2×2 block. No feature leaves the sidebar to save room, and no control is shown on hover only.
- Checked at 700–1000 px high, open and closed.
- **Horizontal scroll only inside a declared scroller** (a table, the Board). The page itself never scrolls sideways, at 320 px included.
- **Phones.**
- The tab bar is Home, Board, ⏱, Issues and More, and `--bottom-nav-h` reserves its space.
- Rows and tab items are `min-h-touch`.
- Icon buttons get a 44 px tap area on touch screens (`coarse:`) without changing their look.
- **At 320 px controls wrap** instead of overflowing. Tables that hide on a phone keep their sorting through a native control.

7.1 Spatial system

Grounded in Material 3 (window classes, canonical layouts), Apple HIG (split views, toolbars), Fluent 2 (responsive techniques), WCAG 2.2 and NN/g research.

Container first: regions. A block lays itself out by its own width, not the window's.

- The sizes are in rem, so density moves them: `@s` < 28rem ≤ `@m` < 56rem ≤ `@l` < 80rem ≤ `@xl`. They are the same thresholds as a desk pane's.
- Viewport breakpoints are only for the shell (sidebar, phone tab bar).

Three page layouts, nothing ad hoc.

Layout	For	Rule
Overview (bento)	Dashboard, Team	Regions in rows of one height.
List-detail	Issues, Notes, Settings	Two panes from `@xl`. On a narrower container a choice replaces the list and Back returns. The selection stays highlighted. An empty selection shows a placeholder.
Supporting pane	Issue detail, a Team person, a report drill-in	About 70/30 from `@l`. Below that, the supporting part goes under the main one or into a sheet.

Collections are bounded, and nothing is hidden for good.

- A row budget, then "Show all N". Expanding happens in place (focus moves to the first new item, and the button becomes "Show fewer") or on the page that holds them all.
- Never sideways: horizontal scroll is only for declared boards (Board, Ideas) and data tables (WCAG 1.4.10's two-dimensional exceptions). Their headings and filters still reflow.
- Never a mask over focusable items, never an item off screen.

Budgets (checked by `e2e/space-budget.test.mjs`).

	Desktop (≥ 1024)	Phone (390)
Chrome (header + toolbar)	≤ 15% of the viewport's height	≤ 20%
Primary block	starts in the first screen	starts in the first screen, above the tab bar
Overview pages	≤ 1.5 screens	≤ 3 screens
Working pages (Timesheet, issue detail)	≤ 1.5 screens	≤ 2.5 screens

Toolbars. A header toolbar has at most three groups: what the page shows, where it goes, its main action. Lower priorities fold into ⋯ as the container narrows, and the title never wraps because of controls.

One datum, one place. A value is shown once per view: the timer, favorites, an issue's key, status and assignee.

Stability. Expanding never moves what is above it. Open and closed states keep their footprint. No primary control appears on hover only.

Never remove to save space. Budgets and variants change density and how much shows at once. What is folded stays one step away: "Show all N", ⋯, or Peek.

Accessibility is measured, not assumed.

- Focus is never covered, at the top or the bottom (2.4.11). The bars that stay put mark themselves (`usePublishChromeHeight` , `data-chrome`), and `useFocusClearOfBars` scrolls a covered control into view. Not CSS `scroll-padding` : with it Chrome treated the bars' own controls as covered and scrolled the page.
- Targets are 24 px (2.5.8), and 44 px on coarse pointers, as the catalog's `minTouchTargetPx` declares.
- Reflow at 320 px (1.4.10).
- Text spacing (1.4.12): `min-height` , never a fixed row height.
- Forced colors: the focus outline survives.
- Both densities.

8. Interaction

These conventions are in `docs/dev/ux-patterns.md`, each with its e2e test. The essentials:

- **Drafts are safe.** A dialog holding typed work asks before closing (`useDirtyClose`).
- **One target per action.** An action started from a day acts on that day, never on "today" by accident. Switching a view keeps the period you were looking at.
- **Forms.**
- A field the server refused takes the focus, with its message tied by `aria-describedby`.
- A form-wide error is `role="alert"`.
- **Keyboard.**
- A choice group is one Tab stop; arrows move within it.
- Lists that pick one thing are buttons with `aria-pressed`.
- Shortcuts are written per platform (`MOD_KEY`: ⌘ on Apple, Ctrl elsewhere).
- **Focus.** Rings use the full `ring-ring` colour; faded rings (`ring-ring/40`) are refused.
- **Toasts.** Every toast and notification can be closed without opening it. Errors use `toastError`, which explains and offers Retry.

9. Copy and languages

- **No hard-coded text.** Every string is a typed key in `contracts/i18n/{en,it}` (`t("ui.mail.pinTitle")`).
- English and Italian are both required, and their key sets must match.
- `pnpm parity:update` records the change.
- **Say what happens**, in the user's words: "a deleted worklog stays in Recently deleted for 30 days", not "can't be undone".
- **Labels are short;** the panel or section title gives context, so a button inside "TODO" says "Add TODO".
- **Settings search** finds localized synonyms: add the words a user would type to `settings.categories.*.keywords`.
- **The repo is public:** English in code, comments, docs and commit messages; no personal data, hosts or company names.

10. Special surfaces

- **The pinboard.**
- One warm grainy paper for every note (`--paper` , with the covers' grain).
- The colour sits on a washi-tape strip (`--tape-1..5`), with a tiny static tilt.
- Titles use the display font.
- No hover movement.
- **Covers** (focus mode, avatars, illustrations): grainy, with the sunset band derived from the theme.
- **The Outlook add-in's pane** is a page of the app's build: `outlook.html` and `src/outlook/` .
- It uses the same components, tokens, fonts, theme colour and language as the app, and nothing hand-styled.
- Outlook's panes are narrow (320–480 px), so a section puts its selector and its short action button on one row; nothing may need a sideways scroll.
- The e2e checks both widths.
- **Modules** draw only through the host APIs and the surface catalogue (§5.1). They never style the app's elements directly, and they keep their own licence and version (they stay at 1.0.0 until told otherwise).

11. For AI agents: hard rules

Do:

- Read the component you are changing and its neighbours first, and copy their idiom: naming, comment density, structure.
- Use only the tokens, sizes, radii and shadows listed here.
- If a value is missing, say so; do not invent one.
- Reuse the components in §6.1.
- Mark every standing box with `surface()`.
- Give long text `[overflow-wrap:anywhere]` and its grid tracks `minmax(0,1fr)`.
- Add English and Italian keys together.
- Check light and dark, at 320 px and on desktop.
- Add an e2e test for any interaction you fix or add.
- Run `pnpm lint` and `pnpm check` before you say you are done.

Never:

- Hex colours, Tailwind palette colours, `text-xs` / `sm` / `lg`, `font-mono`, `break-words`, `<datalist>`, `rounded-3xl`, or shadows above `sm` outside `components/ui`.
- Hover animations, gradients, glassmorphism or decorative covers.
- A global `overflow-x-hidden`, `!important`, or inline `style` for colours or sizes.
- A page, pane or dialog with its own look.
- Text that is not an i18n key.
- Silencing the lint without a `design-ok` comment explaining the reviewed exception.

12. Checklist before a PR

- □ Tokens only. `node scripts/check-design.mjs` prints no violations.
- □ `pnpm lint && pnpm check` pass.
- □ Light and dark both look right.
- □ Compact and comfortable density both look right.
- □ At 320 px: nothing overflows, controls wrap, touch targets are 44 px.
- □ Loading, empty, error and busy states exist and are announced.
- □ Keyboard only: reachable, visible focus, Esc closes, no traps.
- □ English and Italian keys added; `pnpm parity:update` run.
- □ Every new or fixed interaction has an e2e test in `e2e/` (run it with `PROVIDERS_READ_ONLY=1`).
- □ No new component where §6.1 already has one.

Plates: colour and type

The default palette (base colour #B5562F), from `src/index.css`. A user's own base colour derives every value again (§3.2).

Light

Surfaces and text

canvas
hsl(16.2 11.5% 95.1%)

background
hsl(0 0% 100%)

card
hsl(0 0% 100%)

popover
hsl(0 0% 100%)

foreground
hsl(16.3 7% 8.7%)

muted
hsl(16.2 13.8% 95.9%)

muted-foreground
hsl(16.3 4.6% 41.9%)

accent
hsl(16.3 12.7% 92.9%)

border
hsl(16.3 10.7% 91.6%)

input
hsl(16.3 9% 85.2%)

Brand and action

primary
hsl(16.5 71.7% 78%)

primary-soft
hsl(16.3 100% 94.7%)

primary-strong
hsl(16.6 26% 43.5%)

primary-foreground
hsl(16.8 46% 22%)

action
hsl(16.6 37% 20.2%)

action-foreground
hsl(16.3 45.9% 97.5%)

ring
hsl(16.6 26% 43.5%)

State

success
hsl(140 32% 31%)

success-soft
hsl(135 32% 94%)

warning
hsl(36 60% 30%)

warning-soft
hsl(40 72% 93%)

danger
hsl(4 46% 45%)

danger-soft
hsl(6 60% 95%)

info
hsl(214 36% 43%)

info-soft
hsl(214 48% 95%)

Data

chart-focus
hsl(20 84.5% 79.3%)

chart-other
hsl(16.4 63% 87.8%)

chart-break
hsl(16.3 11.9% 74.7%)

chart-ink
hsl(16.3 7% 8.7%)

project-1
hsl(20 67% 74.2%)

project-2
hsl(11.6 83.9% 85.5%)

project-3
hsl(22.1 34% 65.3%)

project-4
hsl(15.3 82.1% 80.9%)

project-5
hsl(10.3 28.3% 72.4%)

project-6
hsl(23 70.4% 84%)

Pinboard

paper
hsl(38 45% 96%)

tape-1
hsl(18 52% 70%)

tape-2
hsl(42 58% 66%)

tape-3
hsl(140 18% 62%)

tape-4
hsl(208 26% 66%)

tape-5
hsl(322 18% 68%)

string
hsl(355 62% 40%)

Dark

Surfaces and text

canvas
hsl(16.3 10.9% 5.2%)

background
hsl(16.3 8.7% 8.7%)

card
hsl(16.3 8.7% 8.7%)

popover
hsl(16.3 8.8% 10.5%)

foreground
hsl(16.3 14% 93.6%)

muted
hsl(16.3 6.4% 12.3%)

muted-foreground
hsl(16.3 4.8% 57.5%)

accent
hsl(16.3 6.8% 14.2%)

border
hsl(16.3 6.5% 15.2%)

input
hsl(16.3 6.3% 22.1%)

Brand and action

primary
hsl(16.5 37.6% 65.4%)

primary-soft
hsl(16.6 31.2% 15.3%)

primary-strong
hsl(16.5 35.5% 65.4%)

primary-foreground
hsl(16.7 43.2% 18.1%)

action
hsl(16.4 51.7% 85.2%)

action-foreground
hsl(16.4 17.1% 8.8%)

ring
hsl(16.5 35.5% 65.4%)

State

success
hsl(140 30% 66%)

success-soft
hsl(138 16% 16%)

warning
hsl(40 55% 68%)

warning-soft
hsl(40 22% 16%)

danger
hsl(5 55% 72%)

danger-soft
hsl(4 22% 18%)

info
hsl(214 45% 74%)

info-soft
hsl(214 22% 18%)

Data

chart-focus
hsl(20 41.4% 64.4%)

chart-other
hsl(16.4 14% 50.9%)

chart-break
hsl(16.3 6.8% 39.2%)

chart-ink
hsl(16.3 14% 93.6%)

project-1
hsl(20 32.7% 57.1%)

project-2
hsl(11.6 30.6% 67.6%)

project-3
hsl(22.1 19.5% 48.7%)

project-4
hsl(15.3 34.7% 63.3%)

project-5
hsl(10.3 14.1% 55.1%)

project-6
hsl(23 27.5% 66.5%)

Pinboard

paper
hsl(28 12% 20%)

tape-1
hsl(18 32% 48%)

tape-2
hsl(40 36% 46%)

tape-3
hsl(140 14% 42%)

tape-4
hsl(208 18% 46%)

tape-5
hsl(322 12% 46%)

string
hsl(355 55% 55%)

Type scale

From `tailwind.config.js`, at the compact density (root 14 px).

`text-display` 2.75rem	Your time, from every tracker
`text-title` 1.75rem	Your time, from every tracker
`text-heading` 1.375rem	Your time, from every tracker
`text-body` 1rem	Your time, from every tracker
`text-body-sm` 0.875rem	Your time, from every tracker
`text-caption` 0.8125rem	Your time, from every tracker
`text-field` max(1rem, 16px)	Your time, from every tracker
`text-2xs` max(11px, 0.625rem)	**Your time, from every tracker**
`text-overline` max(11px, 0.6875rem)	**Your time, from every tracker**