

Dynamic State Estimation and Threat Trajectory Prediction for Low-RCS Counter-UAS via Interacting Multiple Model EKF and Decision-Level EO/IR Sensor Fusion

Kobe Illana A. Atanacio*

September 14, 2026

Abstract

Autonomous tracking and 3D trajectory estimation of small Uncrewed Aerial Systems (sUAS) present severe operational challenges for Counter-UAS (C-UAS) air defense architectures due to low radar cross-sections (RCS), complex background clutter, and non-linear evasive maneuvers [8, 9, 10]. Conventional tracking pipelines relying on single-sensor feeds or global spherical coordinate models struggle with extreme resolution mismatches (4K RGB vs. 640×512 Thermal IR) and severe latency constraints on tactical edge hardware [10, 11, 12].

This paper presents an integrated, defense-grade state estimation framework operating in a Local Tangent Plane (LTP) North-East-Down (NED) Cartesian space. Dual independent deep learning detectors process electro-optical (EO) and infrared (IR) streams, extracting 2D bounding centroids that are mathematically validated via a Mahalanobis distance gate ($\chi^2 \leq 9.21$) and associated via the Hungarian Algorithm. The fused range and angular observations are ingested into an Interacting Multiple Model Extended Kalman Filter (IMM-EKF) combining Constant Velocity (CV) and bidirectional Coordinated Turn (CT+, CT-) kinematic models.

Rather than claiming a novel filtering algorithm, our core contribution lies in the complete system integration and empirical edge benchmarking of this multi-modal pipeline for 0–200 m fire-control tracking. Evaluated across 100 Monte Carlo simulation runs on the LRDDv3 dataset and evasive flight telemetry, the proposed architecture achieves a mean 3D position Root Mean Square Error (RMSE) of 1.245 ± 0.082 m (an 88% error reduction compared to standard CV filters) and a velocity RMSE of 1.390 ± 0.065 m/s. During complete 3-second visual occlusions, the IMM-EKF maintains trajectory lock with a recovery RMSE of 4.180 ± 0.312 m. A composite latency budget assembled from measured filter execution (0.437 ms) and published sequential dual-stream Jetson-class detector benchmarks indicates real-time feasibility (~ 24.4 ms / ~ 41 FPS); physical hardware validation remains outstanding.

Keywords—Counter-UAS, Interacting Multiple Model EKF, Sensor Fusion, Data Association, Local Tangent Plane, Threat Trajectory Prediction, Edge AI, SWaP-C.

1 Introduction

The rapid proliferation of low-cost, high-agility small uncrewed aerial systems (sUAS) has fundamentally transformed modern air defense requirements [8, 9]. Defensive systems deployed by military and security agencies require resilient, low-latency Counter-UAS (C-UAS) capabilities to counter multiple simultaneous evasive reconnaissance platforms [10].

Detecting and tracking sUAS platforms is technically demanding due to low radar cross-sections (RCS), adverse visual conditions, and erratic, high- g evasive flight maneuvers [9, 10]. While modern deep learning detectors excel at 2D object localization in camera frames [4, 5], physical kinetic interceptors and direct energy weapons require exact 3D position and velocity vectors ($\mathbf{x}, \mathbf{v}$) in local physical coordinates.

Furthermore, traditional algorithms that rely on global spherical models (e.g., Haversine great-circle formulas) incur unnecessary mathematical overhead over short 0–200 meter tactical engagement zones. Over localized tactical distances, Earth’s curvature is mathematically negligible, making Cartesian transformations significantly more efficient and directly actionable for fire-control hardware.

We explicitly define the scope boundary of this work: our system assumes that wide-area surveillance sensors (e.g., long-range search radar or RF scanners) have cued the target into the narrow Field-of-View (FOV) of the optical tracking payload. Once cued, our pipeline provides high-precision 3D threat state estimation and dynamic trajectory prediction in local Cartesian coordinates.

2 Related Work

Target tracking and maneuvering threat estimation have a rich literature in aerospace systems. Interacting Mul-

*Independent Researcher. Applied Mathematics - Data Science, Far Eastern University, Manila, Philippines.

tuple Model (IMM) filtering combining Constant Velocity (CV) and Coordinated Turn (CT) models represents the classic paradigm for maneuvering target tracking [2, 3]. Standard data association architectures heavily leverage Mahalanobis distance gating combined with Hungarian optimal assignment [6, 7].

In multi-sensor air defense, fusing electro-optical (EO) and thermal infrared (IR) feeds with ranging sensors has been explored in patents and specialized guidance literature [15, 16]. Recent studies have investigated deep learning target classification [12, 11], vision-Kalman tracking frameworks [14], and disturbance-observer-enhanced trajectory prediction for non-cooperative UAVs [13].

Our work differs from existing literature not by proposing new theoretical filtering equations, but by presenting a fully integrated, open-source C-UAS software pipeline¹ that bridges 4K/IR visual detectors, Mahalanobis clutter gating, and IMM-EKF state estimation, supported by composite latency and SWaP-C deployment profiling.

3 Coordinate Reference Frames & Kinematics

3.1 Local Tangent Plane (NED) Transformation

Target measurements from sensor ground stations (or airborne sensor platforms whose own position $\mathbf{p}_{\text{sensor},k}$ is updated per frame) are transformed into a Local Tangent Plane (LTP) North-East-Down (NED) Cartesian coordinate system. Let $\mathbf{p}_{\text{sensor}}$ denote the local radar/camera position in Earth-Centered, Earth-Fixed (ECEF) coordinates. The local target position $\mathbf{p}_{\text{LTP}} = [x, y, z]^T$ is obtained via:

$$\mathbf{p}_{\text{LTP}} = \mathbf{R}_{\text{ECEF} \rightarrow \text{NED}} (\mathbf{p}_{\text{target, ECEF}} - \mathbf{p}_{\text{sensor, ECEF}}) \quad (1)$$

where $\mathbf{R}_{\text{ECEF} \rightarrow \text{NED}}$ is the standard rotation matrix parameterized by sensor geodetic latitude ϕ_0 and longitude λ_0 .

Note on Evaluation Data: While the LRDDv3 validation dataset utilized an airborne sensor platform to collect telemetry, this framework mathematically projects that data onto a synthetic, stationary ground-station coordinate ($\mathbf{p}_{\text{sensor}}$) to strictly validate the filter’s performance for fixed-site SHORAD (Short-Range Air Defense) architectures.

The 6-DOF system state vector $\mathbf{x}_k$ is formulated in local Cartesian space as:

$$\mathbf{x}_k = [x_k, y_k, z_k, \dot{x}_k, \dot{y}_k, \dot{z}_k]^T \quad (2)$$

¹Our complete Python simulation, Mahalanobis gating logic, and IMM-EKF architecture are open-sourced under an MIT License at: <https://github.com/inline-illana/DSETTPLRCSC-UAS.git>

3.2 Kinematic Motion Engine

To track both steady cruising and bidirectional evasive high- g tactical turns, $M = 3$ distinct motion models are defined within the tracking filter:

1. **Constant Velocity (CV):** Captures non-maneuvering trajectories with state transition matrix $\mathbf{F}_{\text{CV}}(\Delta t)$.
2. **Left Coordinated Turn (CT+):** Incorporates a dynamic turn rate to capture aggressive left-lateral evasion maneuvers, where $\omega = +0.35$ rad/s.
3. **Right Coordinated Turn (CT-):** Captures aggressive right-lateral evasion maneuvers, where $\omega = -0.35$ rad/s.

The Coordinated Turn state transition matrix $\mathbf{F}_{\text{CT}}(\Delta t, \omega)$ is generalized as:

$$\mathbf{F}_{\text{CT}}(\Delta t, \omega) = \begin{bmatrix} 1 & 0 & 0 & \frac{\sin(\omega \Delta t)}{\omega} & -\frac{1 - \cos(\omega \Delta t)}{\omega} & 0 \\ 0 & 1 & 0 & \frac{1 - \cos(\omega \Delta t)}{\omega} & \frac{\sin(\omega \Delta t)}{\omega} & 0 \\ 0 & 0 & 1 & 0 & 0 & \Delta t \\ 0 & 0 & 0 & \cos(\omega \Delta t) & -\sin(\omega \Delta t) & 0 \\ 0 & 0 & 0 & \sin(\omega \Delta t) & \cos(\omega \Delta t) & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 \end{bmatrix} \quad (3)$$

4 Decision-Level EO/IR Fusion Pipeline

We adopt a decision-level (late) fusion architecture [11, 12] using dual YOLOv11-Nano feature extractors [4, 5]:

4.1 Mahalanobis Distance Validation Gating & Association

Before data association, incoming candidate detections are filtered through a Chi-Square (χ^2) validation gate [7]:

$$D_M^2 = \mathbf{y}_{\text{ang}}^T \mathbf{S}_{\text{ang}}^{-1} \mathbf{y}_{\text{ang}} \leq \gamma \quad (4)$$

where $\gamma = 9.21$ corresponds to a 99% confidence threshold for a 2-DOF angular distribution. Candidates exceeding γ are discarded as background clutter before applying the Hungarian algorithm [6, 7].

4.2 Observation Vector Assembly & Measurement Function

To resolve the range ambiguity inherent in monocular cameras [12], the measurement vector $\mathbf{z}_k = [r_k, \theta_k, \phi_k]^T$ combines angular coordinates (θ, ϕ) from the fused EO/IR centroids with range telemetry (r) modeled with a noise variance $\sigma_r^2 = 1.0 \text{ m}^2$.

The non-linear measurement mapping function $h(\mathbf{x}_k)$ is explicitly defined as:

$$h(\mathbf{x}_k) = \begin{bmatrix} \sqrt{x_k^2 + y_k^2 + z_k^2} \\ \arctan 2(y_k, x_k) \\ \arcsin \left(\frac{-z_k}{\max(\sqrt{x_k^2 + y_k^2 + z_k^2}, \epsilon)} \right) \end{bmatrix} \quad (5)$$

with the analytical measurement Jacobian matrix evaluated at each update step:

$$\mathbf{H}_k = \left. \frac{\partial h}{\partial \mathbf{x}} \right|_{\hat{\mathbf{x}}_{k|k-1}} \quad (6)$$

5 Interacting Multiple Model EKF

The IMM algorithm operates $M = 3$ parallel EKFs representing the CV, CT+, and CT- flight modes [2, 3].

5.1 Filter Hyperparameters & Setup

To ensure complete reproducibility, the exact filter tuning parameters for the 3-Model IMM are configured as follows:

- **Markov Transition Matrix:**

$$\mathbf{\Pi} = \begin{bmatrix} 0.90 & 0.05 & 0.05 \\ 0.05 & 0.90 & 0.05 \\ 0.05 & 0.05 & 0.90 \end{bmatrix} \quad (7)$$

- **Initial Mode Probabilities:** $\boldsymbol{\mu}_0 = [0.8, 0.1, 0.1]^T$ ($\mu_{CV}, \mu_{CT+}, \mu_{CT-}$).
- **Process Noise Intensities:** $q_{CV} = 0.3 \text{ m/s}^{3/2}$ and $q_{CT} = 0.8 \text{ m/s}^{3/2}$.
- **Measurement Noise Covariance:** $\mathbf{R} = \text{diag}(1.0 \text{ m}^2, (0.005 \text{ rad})^2, (0.005 \text{ rad})^2)$.

5.2 IMM Execution Cycle

At each time step k :

1. **Interaction / Mixing:** Initial states $\mathbf{x}_{0j,k-1}$ and covariances $\mathbf{P}_{0j,k-1}$ are computed using Markov transition probabilities $\mathbf{\Pi}$.
2. **Model-Specific Filtering:** Each EKF updates its state estimate $\hat{\mathbf{x}}_{j,k}$ and innovation residual $\mathbf{y}_{j,k} = \mathbf{z}_k - h(\hat{\mathbf{x}}_{j,k|k-1})$.
3. **Mode Probability Update:** Mode likelihood $\Lambda_j(k)$ is calculated from Gaussian innovation PDF:

$$\Lambda_j(k) = \frac{1}{\sqrt{|2\pi\mathbf{S}_{j,k}|}} \exp \left(-\frac{1}{2} \mathbf{y}_{j,k}^T \mathbf{S}_{j,k}^{-1} \mathbf{y}_{j,k} \right) \quad (8)$$

Mode probabilities $\mu_j(k)$ are updated dynamically.

4. **Combination:** The final target state estimate $\hat{\mathbf{x}}_k$ and covariance $\mathbf{P}_k$ are computed as the probability-weighted sum.




Figure 1: Dynamic Markov mode probability updates (μ_{CV} vs. μ_{CT+} vs. μ_{CT-}) during target evasive turns.

6 Experimental Results & Benchmarks

Validation is conducted on LRDDv3 synchronized 4K RGB, Thermal IR, and differential GPS range telemetry [1]. To evaluate statistical consistency, benchmarks are aggregated over 100 Monte Carlo simulation runs across evasive flight trajectories.

Counter-UAS 3D Threat Trajectory Estimation in LTP NED Frame




Figure 2: Representative single-trial 3D threat trajectory estimation in local NED Cartesian coordinates. Aggregate performance across 100 randomized flight profiles is detailed in Table 1.

Table 1: Defense Tracking Metrics & Computational Latency (100-Run Monte Carlo)

Model	3D Pos RMSE	Vel RMSE	Occlusion RMSE	Measured Filter Latency
Single CV EKF Ablation	10.215 $\pm$ 0.410 m	7.802 $\pm$ 0.220 m/s	33.450 $\pm$ 1.105 m	0.110 ms
Single CT EKF Ablation	1.622 $\pm$ 0.105 m	3.890 $\pm$ 0.145 m/s	6.855 $\pm$ 0.420 m	0.125 ms
Proposed 3-Model IMM-EKF	1.245 $\pm$ 0.082 m	1.390 $\pm$ 0.065 m/s	4.180 $\pm$ 0.312 m	0.437 ms




Figure 3: Representative single-trial temporal 3D position error comparison highlighting tracking stability during evasive turns and complete optical occlusion.

6.1 Kinematic Performance Summary

As shown in Table 1, the internal ablation study compares the Proposed IMM-EKF against single-model CV and CT variants. The IMM-EKF maintains track lock during visual occlusions with a recovery RMSE of 4.180 $\pm$ 0.312 m.

6.2 Composite Latency & SWaP-C Deployment Profile

To validate edge deployment feasibility beyond pure mathematical accuracy, a composite latency budget was established. Deep learning detection utilizing YOLO-Nano optimized via TensorRT INT8 on an NVIDIA Jetson Orin Nano is benchmarked at ~ 12.0 ms per forward pass. Processing the dual EO and IR streams sequentially yields a ~ 24.0 ms detection phase. Combined with our empirically measured 0.437 ms IMM-EKF execution step, the complete multi-modal pipeline operates in ~ 24.4 ms (~ 41 FPS throughput). This budget indicates computational feasibility within real-time constraints, though physical hardware validation is outstanding.

Table 2: Estimated Tactical SWaP-C Profile

Module	Size (mm)	Weight	Power	Est. Cost
Compute Edge (Orin Nano)*	100 $\times$ 79 $\times$ 21	250 g	7–15 W	\$249–399
Sensor (FLIR Hadron 640R)**	35 $\times$ 49 $\times$ 45	56 g	1.8 W	$\sim$ \$3,900–4,330
Total Est. Package	—	~ 306 g	8.8–16.8 W	$\sim$\$4,150–4,730

*Derived from NVIDIA published hardware specifications.

**Derived from Teledyne FLIR published specifications.

Furthermore, Table 2 verifies that the combined hard-

ware architecture is well within typical seeker/payload mass allowances for man-portable interceptor systems, which carry 10–20 kg of total missile mass.

6.3 Clutter Rejection & Multi-Target Association

To assess operational data association robustness against thermal glare and background clutter, synthetic spurious detections were injected into the measurement stream. Sweeping the Mahalanobis threshold (γ) yielded a false-accept rate of 6.7% and a false-reject rate of 0.9% at the optimal $\gamma = 9.21$. Similarly, multi-target testing with $N = 3$ overlapping drone trajectories maintained track fidelity with a track-swap rate of only 3.98%.

7 Discussion & Limitations

While the experimental results demonstrate strong sub-2-meter 3D position tracking and rapid occlusion recovery, several operational limitations warrant discussion:

- Turn Rate Capacity:** The current CT models utilize fixed nominal turn rates ($\omega = \pm 0.35$ rad/s). For extreme multi- g acrobatics, the model bank can be expanded to $M = 5$ models (CV, CT_{slow}^+ , CT_{fast}^+ , CT_{slow}^- , CT_{fast}^-).
- Cueing Dependency:** As noted in Section 1, the pipeline requires an external wide-area cueing sensor to bring the target into the narrow EO/IR optical cone.
- Sim-to-Real Considerations:** While the composite latency budget indicates feasibility, real-world deployment requires profiling sequential memory transfer overheads between optical payloads and the Tensor Cores.

8 Conclusion

By combining local NED Cartesian transformations, Mahalanobis validation gating, decision-level EO/IR fusion, and 3-Model IMM-EKF filtering, the system achieves sub-2-meter 3D position tracking operating well within real-time edge computational latency budgets for forward-deployed defense applications.

References

- [1] LRDDv3 Research Consortium, “LRDDv3: High-Resolution Long-Range Drone Detection Dataset with Range Information and Thermal Data,” *arXiv preprint arXiv:2605.25942*, 2026.
- [2] Y. Bar-Shalom, X. R. Li, and T. Kirubarajan, *Estimation with Applications to Tracking and Navigation*, John Wiley & Sons, 2001.
- [3] X. R. Li and V. P. Jilkov, “Survey of maneuvering target tracking. Part V. Multiple-model methods,” *IEEE Transactions on Aerospace and Electronic Systems*, vol. 41, no. 4, pp. 1255–1321, 2005.
- [4] G. Jocher, J. Chaurasia, and J. Qiu, “Ultralytics YOLO,” GitHub repository, Ultralytics, 2023. [Online]. Available: <https://github.com/ultralytics/ultralytics>
- [5] J. Redmon, S. Divvala, R. Girshick, and A. Farhadi, “You Only Look Once: Unified, Real-Time Object Detection,” in *Proc. IEEE Conf. Comput. Vis. Pattern Recog. (CVPR)*, Las Vegas, NV, USA, 2016, pp. 779–788.
- [6] H. W. Kuhn, “The Hungarian method for the assignment problem,” *Naval Research Logistics Quarterly*, vol. 2, no. 1-2, pp. 83–97, 1955.
- [7] S. Blackman and R. Popoli, *Design and Analysis of Modern Tracking Systems*, Norwood, MA, USA: Artech House, 1999.
- [8] U.S. Department of Defense, “Counter-Small Unmanned Aircraft Systems Strategy,” Washington, D.C., USA, Jan. 2021.
- [9] J. Park, L. S. Briceno, C. Kim, and S. K. Kim, “A Survey of Anti-Drone Systems: Sensors, Detection, and Tracking,” *IEEE Access*, vol. 9, pp. 100721–100742, 2021.
- [10] M. Ezuma, F. Erden, C. K. Anjinappa, O. A. Dobre, and I. Guvenc, “Micro-UAV Detection and Classification from RF Fingerprints Using Machine Learning Techniques,” *IEEE Transactions on Aerospace and Electronic Systems*, vol. 56, no. 4, pp. 3013–3031, Aug. 2020.
- [11] C. Liu, Y. Cao, and M. Al-Qizwini, “Deep Learning-Based Small Target Detection in Infrared and Visible Images: A Review,” *IEEE Sensors Journal*, vol. 22, no. 13, pp. 12613–12629, 2022.
- [12] A. Schumann, L. Sommer, J. Teutsch, and J. Beyrer, “Deep cross-domain flying object classification for robust UAV detection,” in *14th IEEE Int. Conf. Adv. Video Signal Based Surveillance (AVSS)*, Lecce, Italy, 2017, pp. 1–6.
- [13] H. Zhu et al., “An Interference Observation-Enhanced Trajectory Prediction Method for Non-Cooperative UAVs,” in *Proc. 5th Int. Conf. Autonomous Unmanned Systems (ICAUS 2025)*, Springer, 2026, pp. 511–524.
- [14] M. Alshaer, R. Abdelfatah, T. Ismail, and H. Mahmoud, “Vision-Based UAV Detection and Tracking Using Deep Learning and Kalman Filter,” *Computational Intelligence*, 2025.
- [15] R. J. Smith et al., “EOIR and RF sensors fusion and tracking using a dual EKF’s system,” U.S. Patent 11 199 379 B1, Dec. 14, 2021.
- [16] P. Wu, X. Li, J. Kong, and J. Liu, “Heterogeneous Multiple Sensors Joint Tracking of Maneuvering Target in Clutter,” *Sensors*, vol. 15, no. 7, pp. 17350–17365, 2015.