



Threagile

Agile Threat Modeling

Threat Model Report

OWASP Juice Shop — Local Lab Threat Model

7 September 2025

Student Name

Table of Contents

Results Overview

| | |
|--|----|
| Management Summary | 4 |
| Impact Analysis of 23 Initial Risks in 15 Categories | 5 |
| Risk Mitigation | 7 |
| Impact Analysis of 23 Remaining Risks in 15 Categories | 8 |
| Application Overview | 10 |
| Data-Flow Diagram | 11 |
| Security Requirements | 12 |
| Abuse Cases | 13 |
| Tag Listing | 14 |
| STRIDE Classification of Identified Risks | 16 |
| Assignment by Function | 19 |
| RAA Analysis | 22 |
| Data Mapping | 23 |
| Out-of-Scope Assets: 2 Assets | 24 |
| Potential Model Failures: 7 / 7 Risks | 25 |
| Questions: 4 / 4 Questions | 26 |

Risks by Vulnerability Category

| | |
|--|----|
| Identified Risks by Vulnerability Category | 27 |
| Cross-Site Scripting (XSS): 1 / 1 Risk | 28 |
| Missing Authentication: 1 / 1 Risk | 30 |
| Unencrypted Communication: 3 / 3 Risks | 32 |
| Container Base Image Backdooring: 1 / 1 Risk | 34 |
| Cross-Site Request Forgery (CSRF): 2 / 2 Risks | 36 |
| Missing Build Infrastructure: 1 / 1 Risk | 38 |
| Missing Hardening: 1 / 1 Risk | 40 |
| Missing Identity Store: 1 / 1 Risk | 42 |
| Missing Two-Factor Authentication (2FA): 2 / 2 Risks | 44 |
| Missing Vault (Secret Storage): 1 / 1 Risk | 46 |
| Server-Side Request Forgery (SSRF): 3 / 3 Risks | 48 |
| Unencrypted Technical Assets: 1 / 1 Risk | 50 |
| Missing Web Application Firewall (WAF): 1 / 1 Risk | 52 |
| Unnecessary Data Transfer: 2 / 2 Risks | 54 |
| Unnecessary Technical Asset: 2 / 2 Risks | 56 |

Risks by Technical Asset

| | |
|-------------------------------------|----|
| Identified Risks by Technical Asset | 58 |
| Juice Shop: 13 / 13 Risks | 59 |
| Reverse Proxy: 3 / 3 Risks | 64 |
| User Browser: 5 / 5 Risks | 67 |
| Persistent Storage: 1 / 1 Risk | 70 |
| Email/SMS Provider: out-of-scope | 72 |
| Webhook Endpoint: out-of-scope | 74 |

Data Breach Probabilities by Data Asset

| | |
|--|----|
| Identified Data Breach Probabilities by Data Asset | 76 |
| Logs: 15 / 15 Risks | 77 |
| Orders: 14 / 14 Risks | 78 |
| Product Catalog: 16 / 16 Risks | 79 |
| Tokens & Sessions: 16 / 16 Risks | 80 |
| User Accounts: 14 / 14 Risks | 81 |

Trust Boundaries

| | |
|-------------------|----|
| Container Network | 82 |
| Host | 82 |
| Internet | 82 |

Shared Runtime

| | |
|-------------|----|
| Docker Host | 83 |
|-------------|----|

About Threagile


| | |
|---------------------------------|----|
| Risk Rules Checked by Threagile | 84 |
| Disclaimer | 97 |

Management Summary

Threagile toolkit was used to model the architecture of "OWASP Juice Shop — Local Lab Threat Model" and derive risks by analyzing the components and data flows. The risks identified during this analysis are shown in the following chapters. Identified risks during threat modeling do not necessarily mean that the vulnerability associated with this risk actually exists: it is more to be seen as a list of potential risks and threats, which should be individually reviewed and reduced by removing false positives. For the remaining risks it should be checked in the design and implementation of "OWASP Juice Shop — Local Lab Threat Model" whether the mitigation advices have been applied or not.

Each risk finding references a chapter of the OWASP ASVS (Application Security Verification Standard) audit checklist. The OWASP ASVS checklist should be considered as an inspiration by architects and developers to further harden the application in a Defense-in-Depth approach. Additionally, for each risk finding a link towards a matching OWASP Cheat Sheet or similar with technical details about how to implement a mitigation is given.

In total **23 initial risks** in **15 categories** have been identified during the threat modeling process:



Threat model for a local OWASP Juice Shop setup. Users access the app either directly on HTTP 3000/tcp or via an optional reverse proxy that terminates TLS and adds security headers. The app runs in a container and may write to a host-mounted volume. Optional outbound notifications use an external Email/SMS provider or generic webhook endpoints.

Impact Analysis of 23 Initial Risks in 15 Categories

The most prevalent impacts of the **23 initial risks** (distributed over **15 risk categories**) are (taking the severity ratings into account and using the highest for each category):

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated: [Cross-Site Scripting \(XSS\)](#): 1 Initial Risk - Exploitation likelihood is *Likely with Medium impact*.

If this risk remains unmitigated, attackers might be able to access individual victim sessions and steal or modify user data.

Elevated: [Missing Authentication](#): 1 Initial Risk - Exploitation likelihood is *Likely with Medium impact*.

If this risk is unmitigated, attackers might be able to access or modify sensitive data in an unauthenticated way.

Elevated: [Unencrypted Communication](#): 3 Initial Risks - Exploitation likelihood is *Likely with High impact*.

If this risk is unmitigated, network attackers might be able to eavesdrop on unencrypted sensitive data sent between components.

Medium: [Container Base Image Backdooring](#): 1 Initial Risk - Exploitation likelihood is *Unlikely with Medium impact*.

If this risk is unmitigated, attackers might be able to deeply persist in the target system by executing code in deployed containers.

Medium: [Cross-Site Request Forgery \(CSRF\)](#): 2 Initial Risks - Exploitation likelihood is *Very Likely with Low impact*.

If this risk remains unmitigated, attackers might be able to trick logged-in victim users into unwanted actions within the web application by visiting an attacker controlled web site.

Medium: [Missing Build Infrastructure](#): 1 Initial Risk - Exploitation likelihood is *Unlikely with Medium impact*.

If this risk is unmitigated, attackers might be able to exploit risks unseen in this threat model due to critical build infrastructure components missing in the model.

Medium: [Missing Hardening](#): 1 Initial Risk - Exploitation likelihood is *Likely with Low impact*.

If this risk remains unmitigated, attackers might be able to easier attack high-value targets.

Medium: [Missing Identity Store](#): 1 Initial Risk - Exploitation likelihood is *Unlikely with Medium impact*.

If this risk is unmitigated, attackers might be able to exploit risks unseen in this threat model in the identity provider/store that is currently missing in the model.

Medium: [Missing Two-Factor Authentication \(2FA\)](#): 2 Initial Risks - Exploitation likelihood is *Unlikely with Medium impact*.

If this risk is unmitigated, attackers might be able to access or modify highly sensitive data without strong authentication.

Medium: Missing Vault (Secret Storage): 1 Initial Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

If this risk is unmitigated, attackers might be able to easier steal config secrets (like credentials, private keys, client certificates, etc.) once a vulnerability to access files is present and exploited.

Medium: Server-Side Request Forgery (SSRF): 3 Initial Risks - Exploitation likelihood is *Likely* with *Low* impact.

If this risk is unmitigated, attackers might be able to access sensitive services or files of network-reachable components by modifying outgoing calls of affected components.

Medium: Unencrypted Technical Assets: 1 Initial Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

If this risk is unmitigated, attackers might be able to access unencrypted data when successfully compromising sensitive components.

Low: Missing Web Application Firewall (WAF): 1 Initial Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

If this risk is unmitigated, attackers might be able to apply standard attack pattern tests at great speed without any filtering.

Low: Unnecessary Data Transfer: 2 Initial Risks - Exploitation likelihood is *Unlikely* with *Low* impact.


If this risk is unmitigated, attackers might be able to target unnecessarily transferred data.

Low: Unnecessary Technical Asset: 2 Initial Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

If this risk is unmitigated, attackers might be able to target unnecessary technical assets.

Risk Mitigation



The following chart gives a high-level overview of the risk tracking status (including mitigated risks):



After removal of risks with status *mitigated* and *false positive* the following 23 remain unmitigated:

0 unmitigated critical risk
0 unmitigated high risk
5 unmitigated elevated risk
13 unmitigated medium risk
5 unmitigated low risk

2 business side related
8 architecture related
6 development related
7 operations related



Impact Analysis of 23 Remaining Risks in 15 Categories

The most prevalent impacts of the **23 remaining risks** (distributed over **15 risk categories**) are (taking the severity ratings into account and using the highest for each category):

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated: [Cross-Site Scripting \(XSS\)](#): 1 Remaining Risk - Exploitation likelihood is *Likely* with *Medium* impact.

If this risk remains unmitigated, attackers might be able to access individual victim sessions and steal or modify user data.

Elevated: [Missing Authentication](#): 1 Remaining Risk - Exploitation likelihood is *Likely* with *Medium* impact.

If this risk is unmitigated, attackers might be able to access or modify sensitive data in an unauthenticated way.

Elevated: [Unencrypted Communication](#): 3 Remaining Risks - Exploitation likelihood is *Likely* with *High* impact.

If this risk is unmitigated, network attackers might be able to eavesdrop on unencrypted sensitive data sent between components.

Medium: [Container Base Image Backdooring](#): 1 Remaining Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

If this risk is unmitigated, attackers might be able to deeply persist in the target system by executing code in deployed containers.

Medium: [Cross-Site Request Forgery \(CSRF\)](#): 2 Remaining Risks - Exploitation likelihood is *Very Likely* with *Low* impact.

If this risk remains unmitigated, attackers might be able to trick logged-in victim users into unwanted actions within the web application by visiting an attacker controlled web site.

Medium: [Missing Build Infrastructure](#): 1 Remaining Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

If this risk is unmitigated, attackers might be able to exploit risks unseen in this threat model due to critical build infrastructure components missing in the model.

Medium: [Missing Hardening](#): 1 Remaining Risk - Exploitation likelihood is *Likely* with *Low* impact.

If this risk remains unmitigated, attackers might be able to easier attack high-value targets.

Medium: [Missing Identity Store](#): 1 Remaining Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

If this risk is unmitigated, attackers might be able to exploit risks unseen in this threat model in the identity provider/store that is currently missing in the model.

Medium: [Missing Two-Factor Authentication \(2FA\)](#): 2 Remaining Risks - Exploitation likelihood is *Unlikely* with *Medium* impact.

If this risk is unmitigated, attackers might be able to access or modify highly sensitive data without strong authentication.

Medium: Missing Vault (Secret Storage): 1 Remaining Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

If this risk is unmitigated, attackers might be able to easier steal config secrets (like credentials, private keys, client certificates, etc.) once a vulnerability to access files is present and exploited.

Medium: Server-Side Request Forgery (SSRF): 3 Remaining Risks - Exploitation likelihood is *Likely* with *Low* impact.

If this risk is unmitigated, attackers might be able to access sensitive services or files of network-reachable components by modifying outgoing calls of affected components.

Medium: Unencrypted Technical Assets: 1 Remaining Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

If this risk is unmitigated, attackers might be able to access unencrypted data when successfully compromising sensitive components.

Low: Missing Web Application Firewall (WAF): 1 Remaining Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

If this risk is unmitigated, attackers might be able to apply standard attack pattern tests at great speed without any filtering.

Low: Unnecessary Data Transfer: 2 Remaining Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

If this risk is unmitigated, attackers might be able to target unnecessarily transferred data.

Low: Unnecessary Technical Asset: 2 Remaining Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

If this risk is unmitigated, attackers might be able to target unnecessary technical assets.

Application Overview

Business Criticality

The overall business criticality of "OWASP Juice Shop — Local Lab Threat Model" was rated as:

(archive | operational | **IMPORTANT** | critical | mission-critical)

Business Overview


Training environment for DevSecOps. The goal is to model risks for a deliberately vulnerable web app (OWASP Juice Shop) running locally in a container. Focus on minimal architecture, STRIDE thinking, and actionable mitigations.

Technical Overview

Browser (user) connects to Juice Shop (Node.js) on localhost:3000 or via a reverse proxy on 443/80. Juice Shop can call external services (Email/SMS provider, webhooks). Logs and files may persist on a host volume. Trust boundaries: Internet . Host . Container network.

Data-Flow Diagram

The following diagram was generated by Threatgile based on the model input and gives a high-level overview of the data-flow between technical assets. The RAA value is the calculated *Relative Attacker Attractiveness* in percent. For a full high-resolution version of this diagram please refer to the PNG image file alongside this report.



Security Requirements

This chapter lists the custom security requirements which have been defined for the modeled target.

AuthZ on sensitive routes

Enforce role/permission checks server-side.

Rate limiting & lockouts

Prevent brute force/login abuse; protect expensive endpoints.

Secrets management

Keep tokens/credentials out of repo and logs.

Secure headers

Add HSTS, CSP, X-Frame-Options, X-Content-Type-Options at proxy.

TLS in transit

Enforce HTTPS for user traffic via reverse proxy with strong ciphers.

This list is not complete and regulatory or law relevant security requirements have to be taken into account as well. Also custom individual security requirements might exist for the project.

Abuse Cases

This chapter lists the custom abuse cases which have been defined for the modeled target.

Credential Stuffing / Brute Force

Attackers attempt repeated logins to exhaust resources or guess valid credentials.

SSRF via Webhook Targets

Outbound webhooks abused to pivot to internal endpoints.

Stored XSS via Product Reviews

Malicious payloads stored and executed in other users' browsers.

This list is not complete and regulatory or law relevant abuse cases have to be taken into account as well. Also custom individual abuse cases might exist for the project.

Tag Listing

This chapter lists what tags are used by which elements.

actor

User Browser

app

Juice Shop

auth

Tokens & Sessions, User Accounts

direct

Direct To App (no proxy)

docker

Docker Host

egress

To Webhook Endpoint, To Email/SMS Provider

logs

Logs

nodejs

Juice Shop

notifications

Email/SMS Provider

optional

Reverse Proxy

pii

Orders, User Accounts

primary

To Reverse Proxy (preferred)

proxy

Reverse Proxy

public

Product Catalog

saas

Email/SMS Provider, Webhook Endpoint

storage

Persistent Storage

tokens

Tokens & Sessions

user

User Browser

volume

Persistent Storage

webhook

Webhook Endpoint

STRIDE Classification of Identified Risks

This chapter clusters and classifies the risks by STRIDE categories: In total **23 potential risks** have been identified during the threat modeling process of which **3 in the Spoofing** category, **5 in the Tampering** category, **0 in the Repudiation** category, **8 in the Information Disclosure** category, **0 in the Denial of Service** category, and **7 in the Elevation of Privilege** category.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Spoofing

Medium: **Cross-Site Request Forgery (CSRF)**: 2 / 2 Risks - Exploitation likelihood is *Very Likely* with *Low* impact.

When a web application is accessed via web protocols Cross-Site Request Forgery (CSRF) risks might arise.

Medium: **Missing Identity Store**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

The modeled architecture does not contain an identity store, which might be the risk of a model missing critical assets (and thus not seeing their risks).

Tampering

Elevated: **Cross-Site Scripting (XSS)**: 1 / 1 Risk - Exploitation likelihood is *Likely* with *Medium* impact.

For each web application Cross-Site Scripting (XSS) risks might arise. In terms of the overall risk level take other applications running on the same domain into account as well.

Medium: **Container Base Image Backdooring**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

When a technical asset is built using container technologies, Base Image Backdooring risks might arise where base images and other layers used contain vulnerable components or backdoors.

Medium: **Missing Build Infrastructure**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

The modeled architecture does not contain a build infrastructure (devops-client, sourcecode-repo, build-pipeline, etc.), which might be the risk of a model missing critical assets (and thus not seeing their risks). If the architecture contains custom-developed parts, the pipeline where code gets developed and built needs to be part of the model.

Medium: **Missing Hardening**: 1 / 1 Risk - Exploitation likelihood is *Likely* with *Low* impact.

Technical assets with a Relative Attacker Attractiveness (RAA) value of 55 % or higher should be explicitly hardened taking best practices and vendor hardening guides into account.

Low: Missing Web Application Firewall (WAF): 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

To have a first line of filtering defense, security architectures with web-services or web-applications should include a WAF in front of them. Even though a WAF is not a replacement for security (all components must be secure even without a WAF) it adds another layer of defense to the overall system by delaying some attacks and having easier attack alerting through it.

Repudiation

n/a

Information Disclosure

Elevated: Unencrypted Communication: 3 / 3 Risks - Exploitation likelihood is *Likely* with *High* impact.

Due to the confidentiality and/or integrity rating of the data assets transferred over the communication link this connection must be encrypted.

Medium: Missing Vault (Secret Storage): 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

In order to avoid the risk of secret leakage via config files (when attacked through vulnerabilities being able to read files like Path-Traversal and others), it is best practice to use a separate hardened process with proper authentication, authorization, and audit logging to access config secrets (like credentials, private keys, client certificates, etc.). This component is usually some kind of Vault.

Medium: Server-Side Request Forgery (SSRF): 3 / 3 Risks - Exploitation likelihood is *Likely* with *Low* impact.

When a server system (i.e. not a client) is accessing other server systems via typical web protocols Server-Side Request Forgery (SSRF) or Local-File-Inclusion (LFI) or Remote-File-Inclusion (RFI) risks might arise.

Medium: Unencrypted Technical Assets: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

Due to the confidentiality rating of the technical asset itself and/or the processed data assets this technical asset must be encrypted. The risk rating depends on the sensitivity technical asset itself and of the data assets stored.

Denial of Service

n/a

Elevation of Privilege

Elevated: **Missing Authentication: 1 / 1 Risk** - Exploitation likelihood is *Likely* with *Medium* impact.

Technical assets (especially multi-tenant systems) should authenticate incoming requests when the asset processes or stores sensitive data.

Medium: **Missing Two-Factor Authentication (2FA): 2 / 2 Risks** - Exploitation likelihood is *Unlikely* with *Medium* impact.

Technical assets (especially multi-tenant systems) should authenticate incoming requests with two-factor (2FA) authentication when the asset processes or stores highly sensitive data (in terms of confidentiality, integrity, and availability) and is accessed by humans.

Low: **Unnecessary Data Transfer: 2 / 2 Risks** - Exploitation likelihood is *Unlikely* with *Low* impact.

When a technical asset sends or receives data assets, which it neither processes or stores this is an indicator for unnecessarily transferred data (or for an incomplete model). When the unnecessarily transferred data assets are sensitive, this poses an unnecessary risk of an increased attack surface.

Low: **Unnecessary Technical Asset: 2 / 2 Risks** - Exploitation likelihood is *Unlikely* with *Low* impact.

When a technical asset does not process or store any data assets, this is an indicator for an unnecessary technical asset (or for an incomplete model). This is also the case if the asset has no communication links (either outgoing or incoming).

Assignment by Function

This chapter clusters and assigns the risks by functions which are most likely able to check and mitigate them: In total **23 potential risks** have been identified during the threat modeling process of which **2 should be checked by Business Side**, **8 should be checked by Architecture**, **6 should be checked by Development**, and **7 should be checked by Operations**.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Business Side

Medium: **Missing Two-Factor Authentication (2FA)**: 2 / 2 Risks - Exploitation likelihood is *Unlikely with Medium impact*.

Apply an authentication method to the technical asset protecting highly sensitive data via two-factor authentication for human users.

Architecture

Elevated: **Missing Authentication**: 1 / 1 Risk - Exploitation likelihood is *Likely with Medium impact*.

Apply an authentication method to the technical asset. To protect highly sensitive data consider the use of two-factor authentication for human users.

Medium: **Missing Build Infrastructure**: 1 / 1 Risk - Exploitation likelihood is *Unlikely with Medium impact*.

Include the build infrastructure in the model.

Medium: **Missing Identity Store**: 1 / 1 Risk - Exploitation likelihood is *Unlikely with Medium impact*.

Include an identity store in the model if the application has a login.

Medium: **Missing Vault (Secret Storage)**: 1 / 1 Risk - Exploitation likelihood is *Unlikely with Medium impact*.

Consider using a Vault (Secret Storage) to securely store and access config secrets (like credentials, private keys, client certificates, etc.).

Low: **Unnecessary Data Transfer**: 2 / 2 Risks - Exploitation likelihood is *Unlikely with Low impact*.

Try to avoid sending or receiving sensitive data assets which are not required (i.e. neither processed or stored) by the involved technical asset.

Low: **Unnecessary Technical Asset**: 2 / 2 Risks - Exploitation likelihood is *Unlikely with Low impact*.

Try to avoid using technical assets that do not process or store anything.

Development

Elevated: **Cross-Site Scripting (XSS)**: 1 / 1 Risk - Exploitation likelihood is *Likely* with *Medium* impact.

Try to encode all values sent back to the browser and also handle DOM-manipulations in a safe way to avoid DOM-based XSS. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

Medium: **Cross-Site Request Forgery (CSRF)**: 2 / 2 Risks - Exploitation likelihood is *Very Likely* with *Low* impact.

Try to use anti-CSRF tokens or the double-submit patterns (at least for logged-in requests). When your authentication scheme depends on cookies (like session or token cookies), consider marking them with the same-site flag. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

Medium: **Server-Side Request Forgery (SSRF)**: 3 / 3 Risks - Exploitation likelihood is *Likely* with *Low* impact.

Try to avoid constructing the outgoing target URL with caller controllable values. Alternatively use a mapping (whitelist) when accessing outgoing URLs instead of creating them including caller controllable values. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

Operations

Elevated: **Unencrypted Communication**: 3 / 3 Risks - Exploitation likelihood is *Likely* with *High* impact.

Apply transport layer encryption to the communication link.

Medium: **Container Base Image Backdooring**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

Apply hardening of all container infrastructures (see for example the *CIS-Benchmarks for Docker and Kubernetes* and the *Docker Bench for Security*). Use only trusted base images of the original vendors, verify digital signatures and apply image creation best practices. Also consider using Google's *Distroless* base images or otherwise very small base images. Regularly execute container image scans with tools checking the layers for vulnerable components.

Medium: **Missing Hardening**: 1 / 1 Risk - Exploitation likelihood is *Likely* with *Low* impact.

Try to apply all hardening best practices (like CIS benchmarks, OWASP recommendations, vendor recommendations, DevSec Hardening Framework, DBSAT for Oracle databases, and others).

Medium: **Unencrypted Technical Assets**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

Apply encryption to the technical asset.

Low: **Missing Web Application Firewall (WAF)**: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Low* impact.

Consider placing a Web Application Firewall (WAF) in front of the web-services and/or web-applications. For cloud environments many cloud providers offer pre-configured WAFs. Even reverse proxies can be enhanced by a WAF component via ModSecurity plugins.

RAA Analysis

For each technical asset the "**Relative Attacker Attractiveness**" (RAA) value was calculated in percent. The higher the RAA, the more interesting it is for an attacker to compromise the asset. The calculation algorithm takes the sensitivity ratings and quantities of stored and processed data into account as well as the communication links of the technical asset. Neighbouring assets to high-value RAA targets might receive an increase in their RAA value when they have a communication link towards that target ("Pivoting-Factor").

The following lists all technical assets sorted by their RAA value from highest (most attacker attractive) to lowest. This list can be used to prioritize on efforts relevant for the most attacker-attractive technical assets:

Technical asset paragraphs are clickable and link to the corresponding chapter.

Juice Shop: RAA 100%

OWASP Juice Shop application (Node.js, v19.0.0).

Persistent Storage: RAA 33%

Host-mounted volume for logs/uploads.

User Browser: RAA 32%


End-user web browser.

Reverse Proxy: RAA 13%

Optional reverse proxy with TLS termination & security headers.

Data Mapping

The following diagram was generated by Threagile based on the model input and gives a high-level distribution of data assets across technical assets. The color matches the identified data breach probability and risk level (see the "Data Breach Probabilities" chapter for more details). A solid line stands for *data is stored by the asset* and a dashed one means *data is processed by the asset*. For a full high-resolution version of this diagram please refer to the PNG image file alongside this report.



Out-of-Scope Assets: 2 Assets

This chapter lists all technical assets that have been defined as out-of-scope. Each one should be checked in the model whether it should better be included in the overall risk analysis:

Technical asset paragraphs are clickable and link to the corresponding chapter.

Email/SMS Provider: out-of-scope
Third-party service.

Webhook Endpoint: out-of-scope
Third-party sink.

Potential Model Failures: 7 / 7 Risks

This chapter lists potential model failures where not all relevant assets have been modeled or the model might itself contain inconsistencies. Each potential model failure should be checked in the model against the architecture design:

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium: Missing Build Infrastructure: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

The modeled architecture does not contain a build infrastructure (devops-client, sourcecode-repo, build-pipeline, etc.), which might be the risk of a model missing critical assets (and thus not seeing their risks). If the architecture contains custom-developed parts, the pipeline where code gets developed and built needs to be part of the model.

Medium: Missing Identity Store: 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

The modeled architecture does not contain an identity store, which might be the risk of a model missing critical assets (and thus not seeing their risks).

Medium: Missing Vault (Secret Storage): 1 / 1 Risk - Exploitation likelihood is *Unlikely* with *Medium* impact.

In order to avoid the risk of secret leakage via config files (when attacked through vulnerabilities being able to read files like Path-Traversal and others), it is best practice to use a separate hardened process with proper authentication, authorization, and audit logging to access config secrets (like credentials, private keys, client certificates, etc.). This component is usually some kind of Vault.

Low: Unnecessary Data Transfer: 2 / 2 Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

When a technical asset sends or receives data assets, which it neither processes or stores this is an indicator for unnecessarily transferred data (or for an incomplete model). When the unnecessarily transferred data assets are sensitive, this poses an unnecessary risk of an increased attack surface.

Low: Unnecessary Technical Asset: 2 / 2 Risks - Exploitation likelihood is *Unlikely* with *Low* impact.

When a technical asset does not process or store any data assets, this is an indicator for an unnecessary technical asset (or for an incomplete model). This is also the case if the asset has no communication links (either outgoing or incoming).

Questions: 4 / 4 Questions

This chapter lists custom questions that arose during the threat modeling process.

Are outbound notifications (email/webhook) configured?

- answer pending -

Do you expose port 3000 beyond localhost?

- answer pending -

Do you use a reverse proxy with TLS and security headers?

- answer pending -

Is any sensitive data stored in logs or files?

- answer pending -

Identified Risks by Vulnerability Category

In total **23 potential risks** have been identified during the threat modeling process of which **0 are rated as critical, 0 as high, 5 as elevated, 13 as medium, and 5 as low.**

These risks are distributed across **15 vulnerability categories**. The following sub-chapters of this section describe each identified risk category.

Cross-Site Scripting (XSS): 1 / 1 Risk

Description (Tampering): [CWE 79](#)

For each web application Cross-Site Scripting (XSS) risks might arise. In terms of the overall risk level take other applications running on the same domain into account as well.

Impact

If this risk remains unmitigated, attackers might be able to access individual victim sessions and steal or modify user data.

Detection Logic

In-scope web applications.

Risk Rating

The risk rating depends on the sensitivity of the data processed or stored in the web application.

False Positives

When the technical asset is not accessed via a browser-like component (i.e not by a human user initiating the request that gets passed through all components until it reaches the web application) this can be considered a false positive.

Mitigation (Development): XSS Prevention

Try to encode all values sent back to the browser and also handle DOM-manipulations in a safe way to avoid DOM-based XSS. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

ASVS Chapter: [V5 - Validation, Sanitization and Encoding Verification Requirements](#)

Cheat Sheet: [Cross Site Scripting Prevention Cheat Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Cross-Site Scripting (XSS)** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

Cross-Site Scripting (XSS) risk at **Juice Shop**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@juice-shop](#)

Unchecked

Missing Authentication: 1 / 1 Risk

Description (Elevation of Privilege): [CWE 306](#)

Technical assets (especially multi-tenant systems) should authenticate incoming requests when the asset processes or stores sensitive data.

Impact

If this risk is unmitigated, attackers might be able to access or modify sensitive data in an unauthenticated way.

Detection Logic

In-scope technical assets (except load-balancer, reverse-proxy, service-registry, waf, ids, and ips and in-process calls) should authenticate incoming requests when the asset processes or stores sensitive data. This is especially the case for all multi-tenant assets (there even non-sensitive ones).

Risk Rating

The risk rating (medium or high) depends on the sensitivity of the data sent across the communication link. Monitoring callers are exempted from this risk.

False Positives

Technical assets which do not process requests regarding functionality or data linked to end-users (customers) can be considered as false positives after individual review.

Mitigation (Architecture): Authentication of Incoming Requests

Apply an authentication method to the technical asset. To protect highly sensitive data consider the use of two-factor authentication for human users.

ASVS Chapter: [V2 - Authentication Verification Requirements](#)

Cheat Sheet: [Authentication Cheat Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Missing Authentication** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

Missing Authentication covering communication link **To App** from **Reverse Proxy** to **Juice Shop**: Exploitation likelihood is *Likely* with *Medium* impact.

[missing-authentication@reverse-proxy>to-app@reverse-proxy@juice-shop](#)

Unchecked

Unencrypted Communication: 3 / 3 Risks

Description (Information Disclosure): [CWE 319](#)

Due to the confidentiality and/or integrity rating of the data assets transferred over the communication link this connection must be encrypted.

Impact

If this risk is unmitigated, network attackers might be able to to eavesdrop on unencrypted sensitive data sent between components.

Detection Logic

Unencrypted technical communication links of in-scope technical assets (excluding monitoring traffic as well as local-file-access and in-process-library-call) transferring sensitive data.

Risk Rating

Depending on the confidentiality rating of the transferred data-assets either medium or high risk.

False Positives

When all sensitive data sent over the communication link is already fully encrypted on document or data level. Also intra-container/pod communication can be considered false positive when container orchestration platform handles encryption.

Mitigation (Operations): Encryption of Communication Links

Apply transport layer encryption to the communication link.

ASVS Chapter: [V9 - Communication Verification Requirements](#)

Cheat Sheet: [Transport Layer Protection Cheat Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Unencrypted Communication** was found **3 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

Unencrypted Communication named **Direct To App (no proxy)** between **User Browser** and **Juice Shop** transferring authentication data (like credentials, token, session-id, etc.): Exploitation likelihood is *Likely* with *High* impact.

[unencrypted-communication@user-browser>direct-to-app-no-proxy@user-browser@juice-shop](#)

Unchecked

Unencrypted Communication named **To Reverse Proxy (preferred)** between **User Browser** and **Reverse Proxy** transferring authentication data (like credentials, token, session-id, etc.): Exploitation likelihood is *Likely* with *High* impact.

[unencrypted-communication@user-browser>to-reverse-proxy-preferred@user-browser@reverse-proxy](#)

Unchecked

Unencrypted Communication named **To App** between **Reverse Proxy** and **Juice Shop**: Exploitation likelihood is *Likely* with *Medium* impact.

[unencrypted-communication@reverse-proxy>to-app@reverse-proxy@juice-shop](#)

Unchecked

Container Base Image Backdooring: 1 / 1 Risk

Description (Tampering): [CWE 912](#)

When a technical asset is built using container technologies, Base Image Backdooring risks might arise where base images and other layers used contain vulnerable components or backdoors.

See for example:

<https://techcrunch.com/2018/06/15/tainted-crypto-mining-containers-pulled-from-docker-hub/>

Impact

If this risk is unmitigated, attackers might be able to deeply persist in the target system by executing code in deployed containers.

Detection Logic

In-scope technical assets running as containers.

Risk Rating

The risk rating depends on the sensitivity of the technical asset itself and of the data assets.

False Positives

Fully trusted (i.e. reviewed and cryptographically signed or similar) base images of containers can be considered as false positives after individual review.

Mitigation (Operations): Container Infrastructure Hardening

Apply hardening of all container infrastructures (see for example the *CIS-Benchmarks for Docker and Kubernetes* and the *Docker Bench for Security*). Use only trusted base images of the original vendors, verify digital signatures and apply image creation best practices. Also consider using Google's *Distroless* base images or otherwise very small base images. Regularly execute container image scans with tools checking the layers for vulnerable components.

ASVS Chapter: [V10 - Malicious Code Verification Requirements](#)

Cheat Sheet: [Docker Security Cheat Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS/CSVS applied?

Risk Findings

The risk **Container Base Image Backdooring** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Container Base Image Backdooring risk at **Juice Shop**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[container-baseimage-backdooring@juice-shop](#)

Unchecked

Cross-Site Request Forgery (CSRF): 2 / 2 Risks

Description (Spoofing): [CWE 352](#)

When a web application is accessed via web protocols Cross-Site Request Forgery (CSRF) risks might arise.

Impact

If this risk remains unmitigated, attackers might be able to trick logged-in victim users into unwanted actions within the web application by visiting an attacker controlled web site.

Detection Logic

In-scope web applications accessed via typical web access protocols.

Risk Rating

The risk rating depends on the integrity rating of the data sent across the communication link.

False Positives

Web applications passing the authentication state via custom headers instead of cookies can eventually be false positives. Also when the web application is not accessed via a browser-like component (i.e not by a human user initiating the request that gets passed through all components until it reaches the web application) this can be considered a false positive.

Mitigation (Development): CSRF Prevention

Try to use anti-CSRF tokens or the double-submit patterns (at least for logged-in requests). When your authentication scheme depends on cookies (like session or token cookies), consider marking them with the same-site flag. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

ASVS Chapter: [V4 - Access Control Verification Requirements](#)

Cheat Sheet: [Cross-Site Request Forgery Prevention Cheat Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Cross-Site Request Forgery (CSRF)** was found **2 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Cross-Site Request Forgery (CSRF) risk at Juice Shop via Direct To App (no proxy) from User Browser: Exploitation likelihood is *Very Likely* with *Low* impact.

[cross-site-request-forgery@juice-shop@user-browser>direct-to-app-no-proxy](#)

Unchecked

Cross-Site Request Forgery (CSRF) risk at Juice Shop via To App from Reverse Proxy: Exploitation likelihood is *Very Likely* with *Low* impact.

[cross-site-request-forgery@juice-shop@reverse-proxy>to-app](#)

Unchecked

Missing Build Infrastructure: 1 / 1 Risk

Description (Tampering): [CWE 1127](#)

The modeled architecture does not contain a build infrastructure (devops-client, sourcecode-repo, build-pipeline, etc.), which might be the risk of a model missing critical assets (and thus not seeing their risks). If the architecture contains custom-developed parts, the pipeline where code gets developed and built needs to be part of the model.

Impact

If this risk is unmitigated, attackers might be able to exploit risks unseen in this threat model due to critical build infrastructure components missing in the model.

Detection Logic

Models with in-scope custom-developed parts missing in-scope development (code creation) and build infrastructure components (devops-client, sourcecode-repo, build-pipeline, etc.).

Risk Rating

The risk rating depends on the highest sensitivity of the in-scope assets running custom-developed parts.

False Positives

Models not having any custom-developed parts can be considered as false positives after individual review.

Mitigation (Architecture): Build Pipeline Hardening

Include the build infrastructure in the model.

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Attack Surface Analysis Cheat Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Missing Build Infrastructure** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Missing Build Infrastructure in the threat model (referencing asset **Juice Shop** as an example): Exploitation likelihood is *Unlikely* with *Medium* impact.

[missing-build-infrastructure@juice-shop](#)

Unchecked

Missing Hardening: 1 / 1 Risk

Description (Tampering): [CWE 16](#)

Technical assets with a Relative Attacker Attractiveness (RAA) value of 55 % or higher should be explicitly hardened taking best practices and vendor hardening guides into account.

Impact

If this risk remains unmitigated, attackers might be able to easier attack high-value targets.

Detection Logic

In-scope technical assets with RAA values of 55 % or higher. Generally for high-value targets like datastores, application servers, identity providers and ERP systems this limit is reduced to 40 %

Risk Rating

The risk rating depends on the sensitivity of the data processed or stored in the technical asset.

False Positives

Usually no false positives.

Mitigation (Operations): System Hardening

Try to apply all hardening best practices (like CIS benchmarks, OWASP recommendations, vendor recommendations, DevSec Hardening Framework, DBSAT for Oracle databases, and others).

ASVS Chapter: [V14 - Configuration Verification Requirements](#)

Cheat Sheet: [Attack Surface Analysis Cheat Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Missing Hardening** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Missing Hardening risk at **Juice Shop**: Exploitation likelihood is *Likely* with *Low* impact.

[missing-hardening@juice-shop](#)

Unchecked

Missing Identity Store: 1 / 1 Risk

Description (Spoofing): [CWE 287](#)

The modeled architecture does not contain an identity store, which might be the risk of a model missing critical assets (and thus not seeing their risks).

Impact

If this risk is unmitigated, attackers might be able to exploit risks unseen in this threat model in the identity provider/store that is currently missing in the model.

Detection Logic

Models with authenticated data-flows authorized via enduser-identity missing an in-scope identity store.

Risk Rating

The risk rating depends on the sensitivity of the enduser-identity authorized technical assets and their data assets processed and stored.

False Positives

Models only offering data/services without any real authentication need can be considered as false positives after individual review.

Mitigation (Architecture): Identity Store

Include an identity store in the model if the application has a login.

ASVS Chapter: [V2 - Authentication Verification Requirements](#)

Cheat Sheet: [Authentication Cheat Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Missing Identity Store** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Missing Identity Store in the threat model (referencing asset **Reverse Proxy** as an example):
Exploitation likelihood is *Unlikely* with *Medium* impact.

[missing-identity-store@reverse-proxy](#)

Unchecked

Missing Two-Factor Authentication (2FA): 2 / 2 Risks

Description (Elevation of Privilege): [CWE 308](#)

Technical assets (especially multi-tenant systems) should authenticate incoming requests with two-factor (2FA) authentication when the asset processes or stores highly sensitive data (in terms of confidentiality, integrity, and availability) and is accessed by humans.

Impact

If this risk is unmitigated, attackers might be able to access or modify highly sensitive data without strong authentication.

Detection Logic

In-scope technical assets (except load-balancer, reverse-proxy, waf, ids, and ips) should authenticate incoming requests via two-factor authentication (2FA) when the asset processes or stores highly sensitive data (in terms of confidentiality, integrity, and availability) and is accessed by a client used by a human user.

Risk Rating

medium

False Positives

Technical assets which do not process requests regarding functionality or data linked to end-users (customers) can be considered as false positives after individual review.

Mitigation (Business Side): Authentication with Second Factor (2FA)

Apply an authentication method to the technical asset protecting highly sensitive data via two-factor authentication for human users.

ASVS Chapter: [V2 - Authentication Verification Requirements](#)

Cheat Sheet: [Multifactor Authentication Cheat Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Missing Two-Factor Authentication (2FA)** was found **2 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Missing Two-Factor Authentication covering communication link **Direct To App (no proxy)** from **User Browser to Juice Shop**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[missing-authentication-second-factor@user-browser>direct-to-app-no-proxy@user-browser@juice-shop](#)

Unchecked

Missing Two-Factor Authentication covering communication link **To App** from **User Browser** forwarded via **Reverse Proxy to Juice Shop**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[missing-authentication-second-factor@reverse-proxy>to-app@reverse-proxy@juice-shop](#)

Unchecked

Missing Vault (Secret Storage): 1 / 1 Risk

Description (Information Disclosure): [CWE 522](#)

In order to avoid the risk of secret leakage via config files (when attacked through vulnerabilities being able to read files like Path-Traversal and others), it is best practice to use a separate hardened process with proper authentication, authorization, and audit logging to access config secrets (like credentials, private keys, client certificates, etc.). This component is usually some kind of Vault.

Impact

If this risk is unmitigated, attackers might be able to easier steal config secrets (like credentials, private keys, client certificates, etc.) once a vulnerability to access files is present and exploited.

Detection Logic

Models without a Vault (Secret Storage).

Risk Rating

The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

False Positives

Models where no technical assets have any kind of sensitive config data to protect can be considered as false positives after individual review.

Mitigation (Architecture): Vault (Secret Storage)

Consider using a Vault (Secret Storage) to securely store and access config secrets (like credentials, private keys, client certificates, etc.).

ASVS Chapter: [V6 - Stored Cryptography Verification Requirements](#)

Cheat Sheet: [Cryptographic Storage Cheat Sheet](#)

Check

Is a Vault (Secret Storage) in place?

Risk Findings

The risk **Missing Vault (Secret Storage)** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Missing Vault (Secret Storage) in the threat model (referencing asset **Email/SMS Provider** as an example): Exploitation likelihood is *Unlikely* with *Medium* impact.

[missing-vault@email-sms-provider](#)

Unchecked

Server-Side Request Forgery (SSRF): 3 / 3 Risks

Description (Information Disclosure): [CWE 918](#)

When a server system (i.e. not a client) is accessing other server systems via typical web protocols Server-Side Request Forgery (SSRF) or Local-File-Inclusion (LFI) or Remote-File-Inclusion (RFI) risks might arise.

Impact

If this risk is unmitigated, attackers might be able to access sensitive services or files of network-reachable components by modifying outgoing calls of affected components.

Detection Logic

In-scope non-client systems accessing (using outgoing communication links) targets with either HTTP or HTTPS protocol.

Risk Rating

The risk rating (low or medium) depends on the sensitivity of the data assets receivable via web protocols from targets within the same network trust-boundary as well on the sensitivity of the data assets receivable via web protocols from the target asset itself. Also for cloud-based environments the exploitation impact is at least medium, as cloud backend services can be attacked via SSRF.

False Positives

Servers not sending outgoing web requests can be considered as false positives after review.

Mitigation (Development): SSRF Prevention

Try to avoid constructing the outgoing target URL with caller controllable values. Alternatively use a mapping (whitelist) when accessing outgoing URLs instead of creating them including caller controllable values. When a third-party product is used instead of custom developed software, check if the product applies the proper mitigation and ensure a reasonable patch-level.

ASVS Chapter: [V12 - File and Resources Verification Requirements](#)

Cheat Sheet: [Server Side Request Forgery Prevention Cheat Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Server-Side Request Forgery (SSRF)** was found **3 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Server-Side Request Forgery (SSRF) risk at **Juice Shop** server-side web-requesting the target **Email/SMS Provider** via **To Email/SMS Provider**: Exploitation likelihood is *Likely* with *Low* impact.

`server-side-request-forgery@juice-shop@email-sms-provider@juice-shop>to-email-sms-provider`

Unchecked

Server-Side Request Forgery (SSRF) risk at **Juice Shop** server-side web-requesting the target **Webhook Endpoint** via **To Webhook Endpoint**: Exploitation likelihood is *Likely* with *Low* impact.

`server-side-request-forgery@juice-shop@webhook-endpoint@juice-shop>to-webhook-endpoint`

Unchecked

Server-Side Request Forgery (SSRF) risk at **Reverse Proxy** server-side web-requesting the target **Juice Shop** via **To App**: Exploitation likelihood is *Likely* with *Low* impact.

`server-side-request-forgery@reverse-proxy@juice-shop@reverse-proxy>to-app`

Unchecked

Unencrypted Technical Assets: 1 / 1 Risk

Description (Information Disclosure): [CWE 311](#)

Due to the confidentiality rating of the technical asset itself and/or the processed data assets this technical asset must be encrypted. The risk rating depends on the sensitivity technical asset itself and of the data assets stored.

Impact

If this risk is unmitigated, attackers might be able to access unencrypted data when successfully compromising sensitive components.

Detection Logic

In-scope unencrypted technical assets (excluding reverse-proxy, load-balancer, waf, ids, ips and embedded components like library) storing data assets rated at least as confidential or critical. For technical assets storing data assets rated as strictly-confidential or mission-critical the encryption must be of type data-with-enduser-individual-key.

Risk Rating

Depending on the confidentiality rating of the stored data-assets either medium or high risk.

False Positives

When all sensitive data stored within the asset is already fully encrypted on document or data level.

Mitigation (Operations): Encryption of Technical Asset

Apply encryption to the technical asset.

ASVS Chapter: [V6 - Stored Cryptography Verification Requirements](#)

Cheat Sheet: [Cryptographic Storage Cheat Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Unencrypted Technical Assets** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Unencrypted Technical Asset named **Juice Shop**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[unencrypted-asset@juice-shop](#)

Unchecked

Missing Web Application Firewall (WAF): 1 / 1 Risk

Description (Tampering): [CWE 1008](#)

To have a first line of filtering defense, security architectures with web-services or web-applications should include a WAF in front of them. Even though a WAF is not a replacement for security (all components must be secure even without a WAF) it adds another layer of defense to the overall system by delaying some attacks and having easier attack alerting through it.

Impact

If this risk is unmitigated, attackers might be able to apply standard attack pattern tests at great speed without any filtering.

Detection Logic

In-scope web-services and/or web-applications accessed across a network trust boundary not having a Web Application Firewall (WAF) in front of them.

Risk Rating

The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

False Positives

Targets only accessible via WAFs or reverse proxies containing a WAF component (like ModSecurity) can be considered as false positives after individual review.

Mitigation (Operations): Web Application Firewall (WAF)

Consider placing a Web Application Firewall (WAF) in front of the web-services and/or web-applications. For cloud environments many cloud providers offer pre-configured WAFs. Even reverse proxies can be enhanced by a WAF component via ModSecurity plugins.

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Virtual Patching Cheat Sheet](#)

Check

Is a Web Application Firewall (WAF) in place?

Risk Findings

The risk **Missing Web Application Firewall (WAF)** was found **1 time** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Low Risk Severity

Missing Web Application Firewall (WAF) risk at **Juice Shop**: Exploitation likelihood is *Unlikely* with *Low* impact.

[missing-waf@juice-shop](#)

Unchecked

Unnecessary Data Transfer: 2 / 2 Risks

Description (Elevation of Privilege): [CWE 1008](#)

When a technical asset sends or receives data assets, which it neither processes or stores this is an indicator for unnecessarily transferred data (or for an incomplete model). When the unnecessarily transferred data assets are sensitive, this poses an unnecessary risk of an increased attack surface.

Impact

If this risk is unmitigated, attackers might be able to target unnecessarily transferred data.

Detection Logic

In-scope technical assets sending or receiving sensitive data assets which are neither processed nor stored by the technical asset are flagged with this risk. The risk rating (low or medium) depends on the confidentiality, integrity, and availability rating of the technical asset. Monitoring data is exempted from this risk.

Risk Rating

The risk assessment is depending on the confidentiality and integrity rating of the transferred data asset either low or medium.

False Positives

Technical assets missing the model entries of either processing or storing the mentioned data assets can be considered as false positives (incomplete models) after individual review. These should then be addressed by completing the model so that all necessary data assets are processed and/or stored by the technical asset involved.

Mitigation (Architecture): Attack Surface Reduction

Try to avoid sending or receiving sensitive data assets which are not required (i.e. neither processed or stored) by the involved technical asset.

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Attack Surface Analysis Cheat Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Unnecessary Data Transfer** was found **2 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Low Risk Severity

Unnecessary Data Transfer of Tokens & Sessions data at **User Browser** from/to **Juice Shop**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-data-transfer@tokens-sessions@user-browser@juice-shop](#)

Unchecked

Unnecessary Data Transfer of Tokens & Sessions data at **User Browser** from/to **Reverse Proxy**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-data-transfer@tokens-sessions@user-browser@reverse-proxy](#)

Unchecked

Unnecessary Technical Asset: 2 / 2 Risks

Description (Elevation of Privilege): [CWE 1008](#)

When a technical asset does not process or store any data assets, this is an indicator for an unnecessary technical asset (or for an incomplete model). This is also the case if the asset has no communication links (either outgoing or incoming).

Impact

If this risk is unmitigated, attackers might be able to target unnecessary technical assets.

Detection Logic

Technical assets not processing or storing any data assets.

Risk Rating

low

False Positives

Usually no false positives as this looks like an incomplete model.

Mitigation (Architecture): Attack Surface Reduction

Try to avoid using technical assets that do not process or store anything.

ASVS Chapter: [V1 - Architecture, Design and Threat Modeling Requirements](#)

Cheat Sheet: [Attack Surface Analysis Cheat Sheet](#)

Check

Are recommendations from the linked cheat sheet and referenced ASVS chapter applied?

Risk Findings

The risk **Unnecessary Technical Asset** was found **2 times** in the analyzed architecture to be potentially possible. Each spot should be checked individually by reviewing the implementation whether all controls have been applied properly in order to mitigate each risk.

Risk finding paragraphs are clickable and link to the corresponding chapter.

Low Risk Severity

Unnecessary Technical Asset named **Persistent Storage**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@persistent-storage](#)

Unchecked

Unnecessary Technical Asset named **User Browser**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@user-browser](#)

Unchecked

Identified Risks by Technical Asset

In total **23 potential risks** have been identified during the threat modeling process of which **0 are rated as critical, 0 as high, 5 as elevated, 13 as medium, and 5 as low.**

These risks are distributed across **4 in-scope technical assets**. The following sub-chapters of this section describe each identified risk grouped by technical asset. The RAA value of a technical asset is the calculated "Relative Attacker Attractiveness" value in percent.

Juice Shop: 13 / 13 Risks

Description

OWASP Juice Shop application (Node.js, v19.0.0).

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

Cross-Site Scripting (XSS) risk at **Juice Shop**: Exploitation likelihood is *Likely* with *Medium* impact.

[cross-site-scripting@juice-shop](#)

Unchecked

Missing Authentication covering communication link **To App** from **Reverse Proxy** to **Juice Shop**: Exploitation likelihood is *Likely* with *Medium* impact.

[missing-authentication@reverse-proxy>to-app@reverse-proxy@juice-shop](#)

Unchecked

Medium Risk Severity

Container Base Image Backdooring risk at **Juice Shop**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[container-baseimage-backdooring@juice-shop](#)

Unchecked

Missing Build Infrastructure in the threat model (referencing asset **Juice Shop** as an example): Exploitation likelihood is *Unlikely* with *Medium* impact.

[missing-build-infrastructure@juice-shop](#)

Unchecked

Missing Two-Factor Authentication covering communication link **Direct To App (no proxy)** from **User Browser** to **Juice Shop**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[missing-authentication-second-factor@user-browser>direct-to-app-no-proxy@user-browser@juice-shop](#)

Unchecked

Missing Two-Factor Authentication covering communication link **To App** from **User Browser** forwarded via **Reverse Proxy** to **Juice Shop**: Exploitation likelihood is *Unlikely* with *Medium* impact.

[missing-authentication-second-factor@reverse-proxy>to-app@reverse-proxy@juice-shop](#)

Unchecked

Unencrypted Technical Asset named **Juice Shop**: Exploitation likelihood is *Unlikely* with *Medium* impact.

unencrypted-asset@juice-shop

Unchecked

Cross-Site Request Forgery (CSRF) risk at **Juice Shop** via **Direct To App (no proxy)** from **User Browser**: Exploitation likelihood is *Very Likely* with *Low* impact.

cross-site-request-forgery@juice-shop@user-browser>direct-to-app-no-proxy

Unchecked

Cross-Site Request Forgery (CSRF) risk at **Juice Shop** via **To App** from **Reverse Proxy**: Exploitation likelihood is *Very Likely* with *Low* impact.

cross-site-request-forgery@juice-shop@reverse-proxy>to-app

Unchecked

Missing Hardening risk at **Juice Shop**: Exploitation likelihood is *Likely* with *Low* impact.

missing-hardening@juice-shop

Unchecked

Server-Side Request Forgery (SSRF) risk at **Juice Shop** server-side web-requesting the target **Email/SMS Provider** via **To Email/SMS Provider**: Exploitation likelihood is *Likely* with *Low* impact.

server-side-request-forgery@juice-shop@email-sms-provider@juice-shop>to-email-sms-provider

Unchecked

Server-Side Request Forgery (SSRF) risk at **Juice Shop** server-side web-requesting the target **Webhook Endpoint** via **To Webhook Endpoint**: Exploitation likelihood is *Likely* with *Low* impact.

server-side-request-forgery@juice-shop@webhook-endpoint@juice-shop>to-webhook-endpoint

Unchecked

Low Risk Severity

Missing Web Application Firewall (WAF) risk at **Juice Shop**: Exploitation likelihood is *Unlikely* with *Low* impact.

missing-waf@juice-shop

Unchecked

Asset Information

| | |
|-------------|-------------|
| ID: | juice-shop |
| Type: | process |
| Usage: | business |
| RAA: | 100 % |
| Size: | application |
| Technology: | web-server |

| | |
|-------------------|---|
| Tags: | app, nodejs |
| Internet: | false |
| Machine: | container |
| Encryption: | none |
| Multi-Tenant: | false |
| Redundant: | false |
| Custom-Developed: | true |
| Client by Human: | false |
| Data Processed: | Orders, Product Catalog, Tokens & Sessions, User Accounts |
| Data Stored: | Logs |
| Formats Accepted: | JSON |

Asset Rating

| | | |
|--------------------|---|-------------------------|
| Owner: | Lab Owner | |
| Confidentiality: | internal | (rated 2 in scale of 5) |
| Integrity: | important | (rated 3 in scale of 5) |
| Availability: | important | (rated 3 in scale of 5) |
| CIA-Justification: | Business-facing app with deliberate vulns for learning. | |

Outgoing Communication Links: 2

Target technical asset names are clickable and link to the corresponding chapter.

To Webhook Endpoint (outgoing)

Optional outbound webhooks.

| | |
|-----------------|------------------|
| Target: | Webhook Endpoint |
| Protocol: | https |
| Encrypted: | true |
| Authentication: | none |
| Authorization: | none |
| Read-Only: | false |
| Usage: | business |
| Tags: | egress |
| VPN: | false |
| IP-Filtered: | false |
| Data Sent: | Orders |
| Data Received: | none |

To Email/SMS Provider (outgoing)

Outbound notifications to provider.

| | |
|-----------------|-----------------------|
| Target: | Email/SMS Provider |
| Protocol: | https |
| Encrypted: | true |
| Authentication: | token |
| Authorization: | technical-user |
| Read-Only: | false |
| Usage: | business |
| Tags: | egress |
| VPN: | false |
| IP-Filtered: | false |
| Data Sent: | Orders, User Accounts |
| Data Received: | none |

Incoming Communication Links: 2

Source technical asset names are clickable and link to the corresponding chapter.

Direct To App (no proxy) (incoming)

Direct access to app (HTTP 3000).

| | |
|-----------------|------------------------------|
| Source: | User Browser |
| Protocol: | http |
| Encrypted: | false |
| Authentication: | session-id |
| Authorization: | enduser-identity-propagation |
| Read-Only: | false |
| Usage: | business |
| Tags: | direct |
| VPN: | false |
| IP-Filtered: | false |
| Data Received: | Tokens & Sessions |
| Data Sent: | Product Catalog |

To App (incoming)

Proxy to app (HTTP 3000).

| | |
|---------|---------------|
| Source: | Reverse Proxy |
|---------|---------------|

| | |
|-----------------|-------------------|
| Protocol: | http |
| Encrypted: | false |
| Authentication: | none |
| Authorization: | none |
| Read-Only: | false |
| Usage: | business |
| Tags: | none |
| VPN: | false |
| IP-Filtered: | false |
| Data Received: | Tokens & Sessions |
| Data Sent: | Product Catalog |

Reverse Proxy: 3 / 3 Risks

Description

Optional reverse proxy with TLS termination & security headers.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

Unencrypted Communication named **To App** between **Reverse Proxy** and **Juice Shop**:
Exploitation likelihood is *Likely* with *Medium* impact.

`unencrypted-communication@reverse-proxy>to-app@reverse-proxy@juice-shop`

Unchecked

Medium Risk Severity

Missing Identity Store in the threat model (referencing asset **Reverse Proxy** as an example):
Exploitation likelihood is *Unlikely* with *Medium* impact.

`missing-identity-store@reverse-proxy`

Unchecked

Server-Side Request Forgery (SSRF) risk at **Reverse Proxy** server-side web-requesting the target **Juice Shop** via **To App**: Exploitation likelihood is *Likely* with *Low* impact.

`server-side-request-forgery@reverse-proxy@juice-shop@reverse-proxy>to-app`

Unchecked

Asset Information

| | |
|---------------|-----------------|
| ID: | reverse-proxy |
| Type: | process |
| Usage: | business |
| RAA: | 13 % |
| Size: | application |
| Technology: | reverse-proxy |
| Tags: | optional, proxy |
| Internet: | false |
| Machine: | virtual |
| Encryption: | transparent |
| Multi-Tenant: | false |
| Redundant: | false |

Custom-Developed: false
Client by Human: false
Data Processed: Product Catalog, Tokens & Sessions
Data Stored: none
Formats Accepted: JSON

Asset Rating

Owner: Lab Owner
Confidentiality: internal (rated 2 in scale of 5)
Integrity: important (rated 3 in scale of 5)
Availability: important (rated 3 in scale of 5)
CIA-Justification: Controls ingress, adds TLS and headers.

Outgoing Communication Links: 1

Target technical asset names are clickable and link to the corresponding chapter.

To App (outgoing)

Proxy to app (HTTP 3000).

Target: Juice Shop
Protocol: http
Encrypted: false
Authentication: none
Authorization: none
Read-Only: false
Usage: business
Tags: none
VPN: false
IP-Filtered: false
Data Sent: Tokens & Sessions
Data Received: Product Catalog

Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

To Reverse Proxy (preferred) (incoming)

User to reverse proxy (HTTPS 443).

| | |
|-----------------|------------------------------|
| Source: | User Browser |
| Protocol: | http |
| Encrypted: | false |
| Authentication: | session-id |
| Authorization: | enduser-identity-propagation |
| Read-Only: | false |
| Usage: | business |
| Tags: | primary |
| VPN: | false |
| IP-Filtered: | false |
| Data Received: | Tokens & Sessions |
| Data Sent: | Product Catalog |

User Browser: 5 / 5 Risks

Description

End-user web browser.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Elevated Risk Severity

Unencrypted Communication named **Direct To App (no proxy)** between **User Browser** and **Juice Shop** transferring authentication data (like credentials, token, session-id, etc.): Exploitation likelihood is *Likely* with *High* impact.

`unencrypted-communication@user-browser>direct-to-app-no-proxy@user-browser@juice-shop`

Unchecked

Unencrypted Communication named **To Reverse Proxy (preferred)** between **User Browser** and **Reverse Proxy** transferring authentication data (like credentials, token, session-id, etc.): Exploitation likelihood is *Likely* with *High* impact.

`unencrypted-communication@user-browser>to-reverse-proxy-preferred@user-browser@reverse-proxy`

Unchecked

Low Risk Severity

Unnecessary Data Transfer of **Tokens & Sessions** data at **User Browser** from/to **Juice Shop**: Exploitation likelihood is *Unlikely* with *Low* impact.

`unnecessary-data-transfer@tokens-sessions@user-browser@juice-shop`

Unchecked

Unnecessary Data Transfer of **Tokens & Sessions** data at **User Browser** from/to **Reverse Proxy**: Exploitation likelihood is *Unlikely* with *Low* impact.

`unnecessary-data-transfer@tokens-sessions@user-browser@reverse-proxy`

Unchecked

Unnecessary Technical Asset named **User Browser**: Exploitation likelihood is *Unlikely* with *Low* impact.

`unnecessary-technical-asset@user-browser`

Unchecked

Asset Information

ID: user-browser
Type: external-entity

| | |
|-------------------|-------------|
| Usage: | business |
| RAA: | 32 % |
| Size: | system |
| Technology: | browser |
| Tags: | actor, user |
| Internet: | true |
| Machine: | virtual |
| Encryption: | none |
| Multi-Tenant: | false |
| Redundant: | false |
| Custom-Developed: | false |
| Client by Human: | true |
| Data Processed: | none |
| Data Stored: | none |
| Formats Accepted: | JSON |

Asset Rating

| | | |
|--------------------|----------------|-------------------------|
| Owner: | External Users | |
| Confidentiality: | public | (rated 1 in scale of 5) |
| Integrity: | operational | (rated 2 in scale of 5) |
| Availability: | operational | (rated 2 in scale of 5) |
| CIA-Justification: | UI client. | |

Outgoing Communication Links: 2

Target technical asset names are clickable and link to the corresponding chapter.

To Reverse Proxy (preferred) (outgoing)

User to reverse proxy (HTTPS 443).

| | |
|-----------------|------------------------------|
| Target: | Reverse Proxy |
| Protocol: | http |
| Encrypted: | false |
| Authentication: | session-id |
| Authorization: | enduser-identity-propagation |
| Read-Only: | false |
| Usage: | business |
| Tags: | primary |

VPN: false
IP-Filtered: false
Data Sent: Tokens & Sessions
Data Received: Product Catalog

Direct To App (no proxy) (outgoing)

Direct access to app (HTTP 3000).

Target: Juice Shop
Protocol: http
Encrypted: false
Authentication: session-id
Authorization: enduser-identity-propagation
Read-Only: false
Usage: business
Tags: direct
VPN: false
IP-Filtered: false
Data Sent: Tokens & Sessions
Data Received: Product Catalog

Persistent Storage: 1 / 1 Risk

Description

Host-mounted volume for logs/uploads.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Low Risk Severity

Unnecessary Technical Asset named **Persistent Storage**: Exploitation likelihood is *Unlikely* with *Low* impact.

[unnecessary-technical-asset@persistent-storage](#)

Unchecked

Asset Information

| | |
|-------------------|--------------------|
| ID: | persistent-storage |
| Type: | datastore |
| Usage: | devops |
| RAA: | 33 % |
| Size: | component |
| Technology: | file-server |
| Tags: | storage, volume |
| Internet: | false |
| Machine: | virtual |
| Encryption: | none |
| Multi-Tenant: | false |
| Redundant: | false |
| Custom-Developed: | false |
| Client by Human: | false |
| Data Processed: | none |
| Data Stored: | Logs |
| Formats Accepted: | File |

Asset Rating

| | | |
|------------------|-----------|-------------------------|
| Owner: | Lab Owner | |
| Confidentiality: | internal | (rated 2 in scale of 5) |

Integrity: important (rated 3 in scale of 5)
Availability: important (rated 3 in scale of 5)
CIA-Justification: Operational data; may contain sensitive info if misconfigured.

Email/SMS Provider: out-of-scope

Description

External Email/SMS API provider.

Identified Risks of Asset

Risk finding paragraphs are clickable and link to the corresponding chapter.

Medium Risk Severity

Missing Vault (Secret Storage) in the threat model (referencing asset **Email/SMS Provider** as an example): Exploitation likelihood is *Unlikely* with *Medium* impact.

[missing-vault@email-sms-provider](#)

Unchecked

Asset Information

| | |
|-------------------|-----------------------|
| ID: | email-sms-provider |
| Type: | external-entity |
| Usage: | business |
| RAA: | out-of-scope |
| Size: | system |
| Technology: | web-service-rest |
| Tags: | notifications, saas |
| Internet: | true |
| Machine: | virtual |
| Encryption: | none |
| Multi-Tenant: | true |
| Redundant: | true |
| Custom-Developed: | false |
| Client by Human: | false |
| Data Processed: | Orders, User Accounts |
| Data Stored: | none |
| Formats Accepted: | JSON |

Asset Rating

| | | |
|------------------|-------------|-------------------------|
| Owner: | Third Party | |
| Confidentiality: | internal | (rated 2 in scale of 5) |

Integrity: important (rated 3 in scale of 5)
Availability: important (rated 3 in scale of 5)
CIA-Justification: Handles notifications; sensitive addresses may be transmitted.

Asset Out-of-Scope Justification

Third-party service.

Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

To Email/SMS Provider (incoming)

Outbound notifications to provider.

| | |
|-----------------|-----------------------|
| Source: | Juice Shop |
| Protocol: | https |
| Encrypted: | true |
| Authentication: | token |
| Authorization: | technical-user |
| Read-Only: | false |
| Usage: | business |
| Tags: | egress |
| VPN: | false |
| IP-Filtered: | false |
| Data Received: | Orders, User Accounts |
| Data Sent: | none |

Webhook Endpoint: out-of-scope

Description

3rd-party webhook receiver (if configured).

Identified Risks of Asset

Asset was defined as out-of-scope.

Asset Information

| | |
|-------------------|------------------|
| ID: | webhook-endpoint |
| Type: | external-entity |
| Usage: | business |
| RAA: | out-of-scope |
| Size: | system |
| Technology: | web-service-rest |
| Tags: | saas, webhook |
| Internet: | true |
| Machine: | virtual |
| Encryption: | none |
| Multi-Tenant: | true |
| Redundant: | true |
| Custom-Developed: | false |
| Client by Human: | false |
| Data Processed: | Orders |
| Data Stored: | none |
| Formats Accepted: | JSON |

Asset Rating

| | | |
|--------------------|---|-------------------------|
| Owner: | Third Party | |
| Confidentiality: | internal | (rated 2 in scale of 5) |
| Integrity: | operational | (rated 2 in scale of 5) |
| Availability: | operational | (rated 2 in scale of 5) |
| CIA-Justification: | Potential egress path; validate destinations. | |

Asset Out-of-Scope Justification

Third-party sink.

Incoming Communication Links: 1

Source technical asset names are clickable and link to the corresponding chapter.

To Webhook Endpoint (incoming)
Optional outbound webhooks.

| | |
|-----------------|------------|
| Source: | Juice Shop |
| Protocol: | https |
| Encrypted: | true |
| Authentication: | none |
| Authorization: | none |
| Read-Only: | false |
| Usage: | business |
| Tags: | egress |
| VPN: | false |
| IP-Filtered: | false |
| Data Received: | Orders |
| Data Sent: | none |

Identified Data Breach Probabilities by Data Asset

In total **23 potential risks** have been identified during the threat modeling process of which **0 are rated as critical, 0 as high, 5 as elevated, 13 as medium, and 5 as low.**

These risks are distributed across **5 data assets**. The following sub-chapters of this section describe the derived data breach probabilities grouped by data asset.

Technical asset names and risk IDs are clickable and link to the corresponding chapter.

Logs: 15 / 15 Risks

App/access logs (may accidentally contain PII/secrets).

| | | |
|--------------------|---|-------------------------|
| ID: | logs | |
| Usage: | devops | |
| Quantity: | many | |
| Tags: | logs | |
| Origin: | application | |
| Owner: | Lab Owner | |
| Confidentiality: | internal | (rated 2 in scale of 5) |
| Integrity: | important | (rated 3 in scale of 5) |
| Availability: | important | (rated 3 in scale of 5) |
| CIA-Justification: | Operational value; ensure redaction to avoid leakage. | |
| Processed by: | none | |
| Stored by: | Juice Shop, Persistent Storage | |
| Sent via: | none | |
| Received via: | none | |
| Data Breach: | probable | |

Data Breach Risks: This data asset has data breach potential because of 15 remaining risks:

Probable: container-baseimage-backdooring@juice-shop

Possible: cross-site-scripting@juice-shop

Possible: missing-authentication@reverse-proxy>to-app@reverse-proxy@juice-shop

Possible: missing-authentication-second-factor@user-browser>direct-to-app-no-proxy@user-browser@juice-shop

Possible: missing-authentication-second-factor@reverse-proxy>to-app@reverse-proxy@juice-shop

Possible: server-side-request-forgery@juice-shop@email-sms-provider@juice-shop>to-email-sms-provider

Possible: server-side-request-forgery@juice-shop@webhook-endpoint@juice-shop>to-webhook-endpoint

Possible: unencrypted-communication@user-browser>direct-to-app-no-proxy@user-browser@juice-shop

Possible: unencrypted-communication@reverse-proxy>to-app@reverse-proxy@juice-shop

Improbable: cross-site-request-forgery@juice-shop@user-browser>direct-to-app-no-proxy

Improbable: cross-site-request-forgery@juice-shop@reverse-proxy>to-app

Improbable: missing-hardening@juice-shop

Improbable: missing-waf@juice-shop

Improbable: unencrypted-asset@juice-shop

Improbable: unnecessary-technical-asset@persistent-storage

Orders: 14 / 14 Risks

Order history, addresses, payment metadata (no PAN stored).

| | |
|--------------------|--|
| ID: | orders |
| Usage: | business |
| Quantity: | many |
| Tags: | pii |
| Origin: | application |
| Owner: | Lab Owner |
| Confidentiality: | confidential (rated 4 in scale of 5) |
| Integrity: | important (rated 3 in scale of 5) |
| Availability: | important (rated 3 in scale of 5) |
| CIA-Justification: | Contains personal data and business records. |
| Processed by: | Email/SMS Provider, Juice Shop, Webhook Endpoint |
| Stored by: | none |
| Sent via: | To Webhook Endpoint, To Email/SMS Provider |
| Received via: | none |
| Data Breach: | probable |

Data Breach Risks: This data asset has data breach potential because of 14 remaining risks:

Probable: container-baseimage-backdooring@juice-shop

Possible: cross-site-scripting@juice-shop

Possible: missing-authentication@reverse-proxy>to-app@reverse-proxy@juice-shop

Possible: missing-authentication-second-factor@user-browser>direct-to-app-no-proxy@user-browser@juice-shop

Possible: missing-authentication-second-factor@reverse-proxy>to-app@reverse-proxy@juice-shop

Possible: server-side-request-forgery@juice-shop@email-sms-provider@juice-shop>to-email-sms-provider

Possible: server-side-request-forgery@juice-shop@webhook-endpoint@juice-shop>to-webhook-endpoint

Possible: unencrypted-communication@user-browser>direct-to-app-no-proxy@user-browser@juice-shop

Possible: unencrypted-communication@reverse-proxy>to-app@reverse-proxy@juice-shop

Improbable: cross-site-request-forgery@juice-shop@user-browser>direct-to-app-no-proxy

Improbable: cross-site-request-forgery@juice-shop@reverse-proxy>to-app

Improbable: missing-hardening@juice-shop

Improbable: missing-waf@juice-shop

Improbable: unencrypted-asset@juice-shop

Product Catalog: 16 / 16 Risks

Public product info: names, prices, descriptions.

| | | |
|--------------------|--|-------------------------|
| ID: | product-catalog | |
| Usage: | business | |
| Quantity: | many | |
| Tags: | public | |
| Origin: | application | |
| Owner: | Lab Owner | |
| Confidentiality: | public | (rated 1 in scale of 5) |
| Integrity: | important | (rated 3 in scale of 5) |
| Availability: | important | (rated 3 in scale of 5) |
| CIA-Justification: | Integrity matters to avoid fraud/manipulation of prices. | |
| Processed by: | Juice Shop, Reverse Proxy | |
| Stored by: | none | |
| Sent via: | none | |
| Received via: | To Reverse Proxy (preferred), To App, Direct To App (no proxy) | |
| Data Breach: | probable | |
| Data Breach Risks: | This data asset has data breach potential because of 16 remaining risks: | |

Probable: container-baseimage-backdooring@juice-shop

Possible: cross-site-scripting@juice-shop

Possible: missing-authentication@reverse-proxy>to-app@reverse-proxy@juice-shop

Possible: missing-authentication-second-factor@user-browser>direct-to-app-no-proxy@user-browser@juice-shop

Possible: missing-authentication-second-factor@reverse-proxy>to-app@reverse-proxy@juice-shop

Possible: server-side-request-forgery@juice-shop@email-sms-provider@juice-shop>to-email-sms-provider

Possible: server-side-request-forgery@juice-shop@webhook-endpoint@juice-shop>to-webhook-endpoint

Possible: server-side-request-forgery@reverse-proxy@juice-shop@reverse-proxy>to-app

Possible: unencrypted-communication@user-browser>direct-to-app-no-proxy@user-browser@juice-shop

Possible: unencrypted-communication@reverse-proxy>to-app@reverse-proxy@juice-shop

Possible: unencrypted-communication@user-browser>to-reverse-proxy-preferred@user-browser@reverse-proxy

Improbable: cross-site-request-forgery@juice-shop@user-browser>direct-to-app-no-proxy

Improbable: cross-site-request-forgery@juice-shop@reverse-proxy>to-app

Improbable: missing-hardening@juice-shop

Improbable: missing-waf@juice-shop

Improbable: unencrypted-asset@juice-shop

Tokens & Sessions: 16 / 16 Risks

Session IDs, JWTs, CSRF tokens.

| | |
|--------------------|--|
| ID: | tokens-sessions |
| Usage: | business |
| Quantity: | many |
| Tags: | auth, tokens |
| Origin: | application |
| Owner: | Lab Owner |
| Confidentiality: | confidential (rated 4 in scale of 5) |
| Integrity: | important (rated 3 in scale of 5) |
| Availability: | important (rated 3 in scale of 5) |
| CIA-Justification: | Compromise leads to account takeover. |
| Processed by: | Juice Shop, Reverse Proxy |
| Stored by: | none |
| Sent via: | To Reverse Proxy (preferred), To App, Direct To App (no proxy) |
| Received via: | none |
| Data Breach: | probable |

Data Breach Risks: This data asset has data breach potential because of 16 remaining risks:

Probable: container-baseimage-backdooring@juice-shop

Possible: cross-site-scripting@juice-shop

Possible: missing-authentication@reverse-proxy>to-app@reverse-proxy@juice-shop

Possible: missing-authentication-second-factor@user-browser>direct-to-app-no-proxy@user-browser@juice-shop

Possible: missing-authentication-second-factor@reverse-proxy>to-app@reverse-proxy@juice-shop

Possible: server-side-request-forgery@juice-shop@email-sms-provider@juice-shop>to-email-sms-provider

Possible: server-side-request-forgery@juice-shop@webhook-endpoint@juice-shop>to-webhook-endpoint

Possible: server-side-request-forgery@reverse-proxy@juice-shop@reverse-proxy>to-app

Possible: unencrypted-communication@user-browser>direct-to-app-no-proxy@user-browser@juice-shop

Possible: unencrypted-communication@reverse-proxy>to-app@reverse-proxy@juice-shop

Possible: unencrypted-communication@user-browser>to-reverse-proxy-preferred@user-browser@reverse-proxy

Improbable: cross-site-request-forgery@juice-shop@user-browser>direct-to-app-no-proxy

Improbable: cross-site-request-forgery@juice-shop@reverse-proxy>to-app

Improbable: missing-hardening@juice-shop

Improbable: missing-waf@juice-shop

Improbable: unencrypted-asset@juice-shop

User Accounts: 14 / 14 Risks

Profiles, credential hashes, emails.

| | |
|--------------------|--|
| ID: | user-accounts |
| Usage: | business |
| Quantity: | many |
| Tags: | auth, pii |
| Origin: | user-supplied |
| Owner: | Lab Owner |
| Confidentiality: | confidential (rated 4 in scale of 5) |
| Integrity: | critical (rated 4 in scale of 5) |
| Availability: | important (rated 3 in scale of 5) |
| CIA-Justification: | PII and auth data require confidentiality; integrity critical to prevent takeover. |
| Processed by: | Email/SMS Provider, Juice Shop |
| Stored by: | none |
| Sent via: | To Email/SMS Provider |
| Received via: | none |
| Data Breach: | probable |
| Data Breach Risks: | This data asset has data breach potential because of 14 remaining risks: |

Probable: container-baseimage-backdooring@juice-shop

Possible: cross-site-scripting@juice-shop

Possible: missing-authentication@reverse-proxy>to-app@reverse-proxy@juice-shop

Possible: missing-authentication-second-factor@user-browser>direct-to-app-no-proxy@user-browser@juice-shop

Possible: missing-authentication-second-factor@reverse-proxy>to-app@reverse-proxy@juice-shop

Possible: server-side-request-forgery@juice-shop@email-sms-provider@juice-shop>to-email-sms-provider

Possible: server-side-request-forgery@juice-shop@webhook-endpoint@juice-shop>to-webhook-endpoint

Possible: unencrypted-communication@user-browser>direct-to-app-no-proxy@user-browser@juice-shop

Possible: unencrypted-communication@reverse-proxy>to-app@reverse-proxy@juice-shop

Improbable: cross-site-request-forgery@juice-shop@user-browser>direct-to-app-no-proxy

Improbable: cross-site-request-forgery@juice-shop@reverse-proxy>to-app

Improbable: missing-hardening@juice-shop

Improbable: missing-waf@juice-shop

Improbable: unencrypted-asset@juice-shop

Trust Boundaries

In total **3 trust boundaries** have been modeled during the threat modeling process.

Container Network

Docker bridge network.

ID: container-network
Type: network-dedicated-hoster
Tags: none
Assets inside: Juice Shop
Boundaries nested: none

Host

Host OS/VM running Docker.

ID: host
Type: network-dedicated-hoster
Tags: none
Assets inside: Persistent Storage, Reverse Proxy
Boundaries nested: Container Network

Internet

Public Internet zone.

ID: internet
Type: network-dedicated-hoster
Tags: none
Assets inside: Email/SMS Provider, User Browser, Webhook Endpoint
Boundaries nested: Host

Shared Runtimes

In total **1 shared runtime** has been modeled during the threat modeling process.

Docker Host

Docker daemon and bridge network.

| | |
|-----------------|-------------|
| ID: | docker-host |
| Tags: | docker |
| Assets running: | Juice Shop |

Risk Rules Checked by Threagile

Threagile Version: 1.0.0

Threagile Build Timestamp: 20240730113903

Threagile Execution Timestamp: 20250917101513

Model Filename: /app/work/labs/lab2/threagile-model.yaml

Model Hash (SHA256): a2df45e869f336c281bcd4793ebf59e1ab1895f8820aac7f84bed8a0a6f41557

Threagile (see <https://threagile.io> for more details) is an open-source toolkit for agile threat modeling, created by Christian Schneider (<https://christian-schneider.net>): It allows to model an architecture with its assets in an agile fashion as a YAML file directly inside the IDE. Upon execution of the Threagile toolkit all standard risk rules (as well as individual custom rules if present) are checked against the architecture model. At the time the Threagile toolkit was executed on the model input file the following risk rules were checked:

Accidental Secret Leak

accidental-secret-leak

STRIDE: Information Disclosure

Description: Sourcecode repositories (including their histories) as well as artifact registries can accidentally contain secrets like checked-in or packaged-in passwords, API tokens, certificates, crypto keys, etc.

Detection: In-scope sourcecode repositories and artifact registries.

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

Code Backdooring

code-backdooring

STRIDE: Tampering

Description: For each build-pipeline component Code Backdooring risks might arise where attackers compromise the build-pipeline in order to let backdoored artifacts be shipped into production. Aside from direct code backdooring this includes backdooring of dependencies and even of more lower-level build infrastructure, like backdooring compilers (similar to what the XcodeGhost malware did) or dependencies.

Detection: In-scope development relevant technical assets which are either accessed by out-of-scope unmanaged developer clients and/or are directly accessed by any kind of internet-located (non-VPN) component or are themselves directly located on the internet.

Rating: The risk rating depends on the confidentiality and integrity rating of the code being handled and deployed as well as the placement/calling of this technical asset on/from the internet.

Container Base Image Backdooring

container-baseimage-backdooring

STRIDE: Tampering

Description: When a technical asset is built using container technologies, Base Image Backdooring risks might arise where base images and other layers used contain vulnerable components or backdoors.

Detection: In-scope technical assets running as containers.

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets.

Container Platform Escape

container-platform-escape

STRIDE: Elevation of Privilege

Description: Container platforms are especially interesting targets for attackers as they host big parts of a containerized runtime infrastructure. When not configured and operated with security best practices in mind, attackers might exploit a vulnerability inside an container and escape towards the platform as highly privileged users. These scenarios might give attackers capabilities to attack every other container as owning the container platform (via container escape attacks) equals to owning every container.

Detection: In-scope container platforms.

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

Cross-Site Request Forgery (CSRF)

cross-site-request-forgery

STRIDE: Spoofing

Description: When a web application is accessed via web protocols Cross-Site Request Forgery (CSRF) risks might arise.

Detection: In-scope web applications accessed via typical web access protocols.

Rating: The risk rating depends on the integrity rating of the data sent across the communication link.

Cross-Site Scripting (XSS)

cross-site-scripting

STRIDE: Tampering

Description: For each web application Cross-Site Scripting (XSS) risks might arise. In terms of the overall risk level take other applications running on the same domain into account as well.

Detection: In-scope web applications.

Rating: The risk rating depends on the sensitivity of the data processed or stored in the web application.

DoS-risky Access Across Trust-Boundary

dos-risky-access-across-trust-boundary

STRIDE: Denial of Service

Description: Assets accessed across trust boundaries with critical or mission-critical availability rating are more prone to Denial-of-Service (DoS) risks.

Detection: In-scope technical assets (excluding load-balancer) with availability rating of critical or higher which have incoming data-flows across a network trust-boundary (excluding devops usage).

Rating: Matching technical assets with availability rating of critical or higher are at low risk. When the availability rating is mission-critical and neither a VPN nor IP filter for the incoming data-flow nor redundancy for the asset is applied, the risk-rating is considered medium.

Incomplete Model**incomplete-model**

STRIDE: Information Disclosure

Description: When the threat model contains unknown technologies or transfers data over unknown protocols, this is an indicator for an incomplete model.

Detection: All technical assets and communication links with technology type or protocol type specified as unknown.

Rating: low

LDAP-Injection**ldap-injection**

STRIDE: Tampering

Description: When an LDAP server is accessed LDAP-Injection risks might arise. The risk rating depends on the sensitivity of the LDAP server itself and of the data assets processed or stored.

Detection: In-scope clients accessing LDAP servers via typical LDAP access protocols.

Rating: The risk rating depends on the sensitivity of the LDAP server itself and of the data assets processed or stored.

Missing Authentication**missing-authentication**

STRIDE: Elevation of Privilege

Description: Technical assets (especially multi-tenant systems) should authenticate incoming requests when the asset processes or stores sensitive data.

Detection: In-scope technical assets (except load-balancer, reverse-proxy, service-registry, waf, ids, and ips and in-process calls) should authenticate incoming requests when the asset processes or stores sensitive data. This is especially the case for all multi-tenant assets (there even non-sensitive ones).

Rating: The risk rating (medium or high) depends on the sensitivity of the data sent across

the communication link. Monitoring callers are exempted from this risk.

Missing Two-Factor Authentication (2FA)

missing-authentication-second-factor

STRIDE: Elevation of Privilege

Description: Technical assets (especially multi-tenant systems) should authenticate incoming requests with two-factor (2FA) authentication when the asset processes or stores highly sensitive data (in terms of confidentiality, integrity, and availability) and is accessed by humans.

Detection: In-scope technical assets (except load-balancer, reverse-proxy, waf, ids, and ips) should authenticate incoming requests via two-factor authentication (2FA) when the asset processes or stores highly sensitive data (in terms of confidentiality, integrity, and availability) and is accessed by a client used by a human user.

Rating: medium

Missing Build Infrastructure

missing-build-infrastructure

STRIDE: Tampering

Description: The modeled architecture does not contain a build infrastructure (devops-client, sourcecode-repo, build-pipeline, etc.), which might be the risk of a model missing critical assets (and thus not seeing their risks). If the architecture contains custom-developed parts, the pipeline where code gets developed and built needs to be part of the model.

Detection: Models with in-scope custom-developed parts missing in-scope development (code creation) and build infrastructure components (devops-client, sourcecode-repo, build-pipeline, etc.).

Rating: The risk rating depends on the highest sensitivity of the in-scope assets running custom-developed parts.

Missing Cloud Hardening

missing-cloud-hardening

STRIDE: Tampering

Description: Cloud components should be hardened according to the cloud vendor best practices. This affects their configuration, auditing, and further areas.

Detection: In-scope cloud components (either residing in cloud trust boundaries or more specifically tagged with cloud provider types).

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

Missing File Validation

missing-file-validation

STRIDE: Spoofing

- Description:** When a technical asset accepts files, these input files should be strictly validated about filename and type.
- Detection:** In-scope technical assets with custom-developed code accepting file data formats.
- Rating:** The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

Missing Hardening

missing-hardening

- STRIDE:** Tampering
- Description:** Technical assets with a Relative Attacker Attractiveness (RAA) value of 55 % or higher should be explicitly hardened taking best practices and vendor hardening guides into account.
- Detection:** In-scope technical assets with RAA values of 55 % or higher. Generally for high-value targets like datastores, application servers, identity providers and ERP systems this limit is reduced to 40 %
- Rating:** The risk rating depends on the sensitivity of the data processed or stored in the technical asset.

Missing Identity Propagation

missing-identity-propagation

- STRIDE:** Elevation of Privilege
- Description:** Technical assets (especially multi-tenant systems), which usually process data for endusers should authorize every request based on the identity of the enduser when the data flow is authenticated (i.e. non-public). For DevOps usages at least a technical-user authorization is required.
- Detection:** In-scope service-like technical assets which usually process data based on enduser requests, if authenticated (i.e. non-public), should authorize incoming requests based on the propagated enduser identity when their rating is sensitive. This is especially the case for all multi-tenant assets (there even less-sensitive rated ones). DevOps usages are exempted from this risk.
- Rating:** The risk rating (medium or high) depends on the confidentiality, integrity, and availability rating of the technical asset.

Missing Identity Provider Isolation

missing-identity-provider-isolation

- STRIDE:** Elevation of Privilege
- Description:** Highly sensitive identity provider assets and their identity datastores should be isolated from other assets by their own network segmentation trust-boundary (execution-environment boundaries do not count as network isolation).
- Detection:** In-scope identity provider assets and their identity datastores when surrounded by other (not identity-related) assets (without a network trust-boundary in-between).

This risk is especially prevalent when other non-identity related assets are within the same execution environment (i.e. same database or same application server).

Rating: Default is high impact. The impact is increased to very-high when the asset missing the trust-boundary protection is rated as strictly-confidential or mission-critical.

Missing Identity Store

missing-identity-store

STRIDE: Spoofing

Description: The modeled architecture does not contain an identity store, which might be the risk of a model missing critical assets (and thus not seeing their risks).

Detection: Models with authenticated data-flows authorized via enduser-identity missing an in-scope identity store.

Rating: The risk rating depends on the sensitivity of the enduser-identity authorized technical assets and their data assets processed and stored.

Missing Network Segmentation

missing-network-segmentation

STRIDE: Elevation of Privilege

Description: Highly sensitive assets and/or datastores residing in the same network segment than other lower sensitive assets (like webserver or content management systems etc.) should be better protected by a network segmentation trust-boundary.

Detection: In-scope technical assets with high sensitivity and RAA values as well as datastores when surrounded by assets (without a network trust-boundary in-between) which are of type client-system, web-server, web-application, cms, web-service-rest, web-service-soap, build-pipeline, sourcecode-repository, monitoring, or similar and there is no direct connection between these (hence no requirement to be so close to each other).

Rating: Default is low risk. The risk is increased to medium when the asset missing the trust-boundary protection is rated as strictly-confidential or mission-critical.

Missing Vault (Secret Storage)

missing-vault

STRIDE: Information Disclosure

Description: In order to avoid the risk of secret leakage via config files (when attacked through vulnerabilities being able to read files like Path-Traversal and others), it is best practice to use a separate hardened process with proper authentication, authorization, and audit logging to access config secrets (like credentials, private keys, client certificates, etc.). This component is usually some kind of Vault.

Detection: Models without a Vault (Secret Storage).

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

Missing Vault Isolation

missing-vault-isolation

STRIDE: Elevation of Privilege

Description: Highly sensitive vault assets and their datastores should be isolated from other assets by their own network segmentation trust-boundary (execution-environment boundaries do not count as network isolation).

Detection: In-scope vault assets when surrounded by other (not vault-related) assets (without a network trust-boundary in-between). This risk is especially prevalent when other non-vault related assets are within the same execution environment (i.e. same database or same application server).

Rating: Default is medium impact. The impact is increased to high when the asset missing the trust-boundary protection is rated as strictly-confidential or mission-critical.

Missing Web Application Firewall (WAF)

missing-waf

STRIDE: Tampering

Description: To have a first line of filtering defense, security architectures with web-services or web-applications should include a WAF in front of them. Even though a WAF is not a replacement for security (all components must be secure even without a WAF) it adds another layer of defense to the overall system by delaying some attacks and having easier attack alerting through it.

Detection: In-scope web-services and/or web-applications accessed across a network trust boundary not having a Web Application Firewall (WAF) in front of them.

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

Mixed Targets on Shared Runtime

mixed-targets-on-shared-runtime

STRIDE: Elevation of Privilege

Description: Different attacker targets (like frontend and backend/datastore components) should not be running on the same shared (underlying) runtime.

Detection: Shared runtime running technical assets of different trust-boundaries is at risk. Also mixing backend/datastore with frontend components on the same shared runtime is considered a risk.

Rating: The risk rating (low or medium) depends on the confidentiality, integrity, and availability rating of the technical asset running on the shared runtime.

Path-Traversal

path-traversal

STRIDE: Information Disclosure

Description: When a filesystem is accessed Path-Traversal or Local-File-Inclusion (LFI) risks might arise. The risk rating depends on the sensitivity of the technical asset itself

and of the data assets processed or stored.

Detection: Filesystems accessed by in-scope callers.

Rating: The risk rating depends on the sensitivity of the data stored inside the technical asset.

Push instead of Pull Deployment

push-instead-of-pull-deployment

STRIDE: Tampering

Description: When comparing push-based vs. pull-based deployments from a security perspective, pull-based deployments improve the overall security of the deployment targets. Every exposed interface of a production system to accept a deployment increases the attack surface of the production system, thus a pull-based approach exposes less attack surface relevant interfaces.

Detection: Models with build pipeline components accessing in-scope targets of deployment (in a non-readonly way) which are not build-related components themselves.

Rating: The risk rating depends on the highest sensitivity of the deployment targets running custom-developed parts.

Search-Query Injection

search-query-injection

STRIDE: Tampering

Description: When a search engine server is accessed Search-Query Injection risks might arise.

Detection: In-scope clients accessing search engine servers via typical search access protocols.

Rating: The risk rating depends on the sensitivity of the search engine server itself and of the data assets processed or stored.

Server-Side Request Forgery (SSRF)

server-side-request-forgery

STRIDE: Information Disclosure

Description: When a server system (i.e. not a client) is accessing other server systems via typical web protocols Server-Side Request Forgery (SSRF) or Local-File-Inclusion (LFI) or Remote-File-Inclusion (RFI) risks might arise.

Detection: In-scope non-client systems accessing (using outgoing communication links) targets with either HTTP or HTTPS protocol.

Rating: The risk rating (low or medium) depends on the sensitivity of the data assets receivable via web protocols from targets within the same network trust-boundary as well on the sensitivity of the data assets receivable via web protocols from the target asset itself. Also for cloud-based environments the exploitation impact is at least medium, as cloud backend services can be attacked via SSRF.

Service Registry Poisoning

service-registry-poisoning**STRIDE:** Spoofing**Description:** When a service registry used for discovery of trusted service endpoints Service Registry Poisoning risks might arise.**Detection:** In-scope service registries.**Rating:** The risk rating depends on the sensitivity of the technical assets accessing the service registry as well as the data assets processed or stored.**SQL/NoSQL-Injection****sql-nosql-injection****STRIDE:** Tampering**Description:** When a database is accessed via database access protocols SQL/NoSQL-Injection risks might arise. The risk rating depends on the sensitivity technical asset itself and of the data assets processed or stored.**Detection:** Database accessed via typical database access protocols by in-scope clients.**Rating:** The risk rating depends on the sensitivity of the data stored inside the database.**Unchecked Deployment****unchecked-deployment****STRIDE:** Tampering**Description:** For each build-pipeline component Unchecked Deployment risks might arise when the build-pipeline does not include established DevSecOps best-practices. DevSecOps best-practices scan as part of CI/CD pipelines for vulnerabilities in source- or byte-code, dependencies, container layers, and dynamically against running test systems. There are several open-source and commercial tools existing in the categories DAST, SAST, and IAST.**Detection:** All development-relevant technical assets.**Rating:** The risk rating depends on the highest rating of the technical assets and data assets processed by deployment-receiving targets.**Unencrypted Technical Assets****unencrypted-asset****STRIDE:** Information Disclosure**Description:** Due to the confidentiality rating of the technical asset itself and/or the processed data assets this technical asset must be encrypted. The risk rating depends on the sensitivity technical asset itself and of the data assets stored.**Detection:** In-scope unencrypted technical assets (excluding reverse-proxy, load-balancer, waf, ids, ips and embedded components like library) storing data assets rated at least as confidential or critical. For technical assets storing data assets rated as strictly-confidential or mission-critical the encryption must be of type data-with-enduser-individual-key.

Rating: Depending on the confidentiality rating of the stored data-assets either medium or high risk.

Unencrypted Communication

unencrypted-communication

STRIDE: Information Disclosure

Description: Due to the confidentiality and/or integrity rating of the data assets transferred over the communication link this connection must be encrypted.

Detection: Unencrypted technical communication links of in-scope technical assets (excluding monitoring traffic as well as local-file-access and in-process-library-call) transferring sensitive data.

Rating: Depending on the confidentiality rating of the transferred data-assets either medium or high risk.

Unguarded Access From Internet

unguarded-access-from-internet

STRIDE: Elevation of Privilege

Description: Internet-exposed assets must be guarded by a protecting service, application, or reverse-proxy.

Detection: In-scope technical assets (excluding load-balancer) with confidentiality rating of confidential (or higher) or with integrity rating of critical (or higher) when accessed directly from the internet. All web-server, web-application, reverse-proxy, waf, and gateway assets are exempted from this risk when they do not consist of custom developed code and the data-flow only consists of HTTP or FTP protocols. Access from monitoring systems as well as VPN-protected connections are exempted.

Rating: The matching technical assets are at low risk. When either the confidentiality rating is strictly-confidential or the integrity rating is mission-critical, the risk-rating is considered medium. For assets with RAA values higher than 40 % the risk-rating increases.

Unguarded Direct Datastore Access

unguarded-direct-datastore-access

STRIDE: Elevation of Privilege

Description: Datastores accessed across trust boundaries must be guarded by some protecting service or application.

Detection: In-scope technical assets of type datastore (except identity-store-ldap when accessed from identity-provider and file-server when accessed via file transfer protocols) with confidentiality rating of confidential (or higher) or with integrity rating of critical (or higher) which have incoming data-flows from assets outside across a network trust-boundary. DevOps config and deployment access is excluded from this risk.

Rating: The matching technical assets are at low risk. When either the confidentiality rating is strictly-confidential or the integrity rating is mission-critical, the risk-rating is considered medium. For assets with RAA values higher than 40 % the risk-rating increases.

Unnecessary Communication Link

unnecessary-communication-link

STRIDE: Elevation of Privilege

Description: When a technical communication link does not send or receive any data assets, this is an indicator for an unnecessary communication link (or for an incomplete model).

Detection: In-scope technical assets' technical communication links not sending or receiving any data assets.

Rating: low

Unnecessary Data Asset

unnecessary-data-asset

STRIDE: Elevation of Privilege

Description: When a data asset is not processed or stored by any data assets and also not transferred by any communication links, this is an indicator for an unnecessary data asset (or for an incomplete model).

Detection: Modelled data assets not processed or stored by any data assets and also not transferred by any communication links.

Rating: low

Unnecessary Data Transfer

unnecessary-data-transfer

STRIDE: Elevation of Privilege

Description: When a technical asset sends or receives data assets, which it neither processes or stores this is an indicator for unnecessarily transferred data (or for an incomplete model). When the unnecessarily transferred data assets are sensitive, this poses an unnecessary risk of an increased attack surface.

Detection: In-scope technical assets sending or receiving sensitive data assets which are neither processed nor stored by the technical asset are flagged with this risk. The risk rating (low or medium) depends on the confidentiality, integrity, and availability rating of the technical asset. Monitoring data is exempted from this risk.

Rating: The risk assessment is depending on the confidentiality and integrity rating of the transferred data asset either low or medium.

Unnecessary Technical Asset

unnecessary-technical-asset

STRIDE: Elevation of Privilege

Description: When a technical asset does not process or store any data assets, this is an

indicator for an unnecessary technical asset (or for an incomplete model). This is also the case if the asset has no communication links (either outgoing or incoming).

Detection: Technical assets not processing or storing any data assets.

Rating: low

Untrusted Deserialization

untrusted-deserialization

STRIDE: Tampering

Description: When a technical asset accepts data in a specific serialized form (like Java or .NET serialization), Untrusted Deserialization risks might arise.

Detection: In-scope technical assets accepting serialization data formats (including EJB and RMI protocols).

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data assets processed and stored.

Wrong Communication Link Content

wrong-communication-link-content

STRIDE: Information Disclosure

Description: When a communication link is defined as readonly, but does not receive any data asset, or when it is defined as not readonly, but does not send any data asset, it is likely to be a model failure.

Detection: Communication links with inconsistent data assets being sent/received not matching their readonly flag or otherwise inconsistent protocols not matching the target technology type.

Rating: low

Wrong Trust Boundary Content

wrong-trust-boundary-content

STRIDE: Elevation of Privilege

Description: When a trust boundary of type network-policy-namespace-isolation contains non-container assets it is likely to be a model failure.

Detection: Trust boundaries which should only contain containers, but have different assets inside.

Rating: low

XML External Entity (XXE)

xml-external-entity

STRIDE: Information Disclosure

Description: When a technical asset accepts data in XML format, XML External Entity (XXE) risks might arise.

Detection: In-scope technical assets accepting XML data formats.

Rating: The risk rating depends on the sensitivity of the technical asset itself and of the data

assets processed and stored. Also for cloud-based environments the exploitation impact is at least medium, as cloud backend services can be attacked via SSRF (and XXE vulnerabilities are often also SSRF vulnerabilities).

Disclaimer

Student Name conducted this threat analysis using the open-source Threagile toolkit on the applications and systems that were modeled as of this report's date. Information security threats are continually changing, with new vulnerabilities discovered on a daily basis, and no application can ever be 100% secure no matter how much threat modeling is conducted. It is recommended to execute threat modeling and also penetration testing on a regular basis (for example yearly) to ensure a high ongoing level of security and constantly check for new attack vectors.

This report cannot and does not protect against personal or business loss as the result of use of the applications or systems described. Student Name and the Threagile toolkit offers no warranties, representations or legal certifications concerning the applications or systems it tests. All software includes defects: nothing in this document is intended to represent or warrant that threat modeling was complete and without error, nor does this document represent or warrant that the architecture analyzed is suitable to task, free of other defects than reported, fully compliant with any industry standards, or fully compatible with any operating system, hardware, or other application. Threat modeling tries to analyze the modeled architecture without having access to a real working system and thus cannot and does not test the implementation for defects and vulnerabilities. These kinds of checks would only be possible with a separate code review and penetration test against a working system and not via a threat model.

By using the resulting information you agree that Student Name and the Threagile toolkit shall be held harmless in any event.

This report is confidential and intended for internal, confidential use by the client. The recipient is obligated to ensure the highly confidential contents are kept secret. The recipient assumes responsibility for further distribution of this document.

In this particular project, a timebox approach was used to define the analysis effort. This means that the author allotted a prearranged amount of time to identify and document threats. Because of this, there is no guarantee that all possible threats and risks are discovered. Furthermore, the analysis applies to a snapshot of the current state of the modeled architecture (based on the architecture information provided by the customer) at the examination time.

Report Distribution

Distribution of this report (in full or in part like diagrams or risk findings) requires that this disclaimer as well as the chapter about the Threagile toolkit and method used is kept intact as part of the distributed report or referenced from the distributed parts.