

BUREAU OF INDIAN STANDARDS

IS 99999:2025

INDIAN STANDARD
SPECIFICATION FOR DOMESTIC ELECTRIC TOASTERS
(FIRST REVISION)

Adopted 15 January 2025

1 SCOPE

1.1 This standard specifies safety, performance, and construction requirements for electric toasters intended for domestic and similar use, operating on single-phase AC supply not exceeding 250 V.

2 TERMINOLOGY

2.1 Rated Voltage

The voltage assigned to the appliance by the manufacturer for normal operation.

2.2 Rated Power Input

The electrical wattage consumed by the heating elements during steady-state toasting.

3 GENERAL REQUIREMENTS

3.1 General Construction

Appliances shall be constructed to ensure personal safety during normal operation, surge conditions, and accidental tipping.
All external parts shall be free from sharp edges.

4 TESTING REQUIREMENTS

4.1 Electric Strength Test

The insulation of the heating element shall withstand an AC voltage of 1500 V for 60 seconds without electrical flashover or puncture.

4.2 Temperature Rise Limits

When tested at rated voltage for 5 consecutive toasting cycles, accessible surface temperatures shall not exceed the following limits:

TABLE:

Component	Maximum Temp Rise	Test Clause
Handle / Knob	30 K	Clause 4.2
Metallic Surface	60 K	Clause 4.2
Plastic Enclosure	65 K	Clause 4.2
Power Cord Outer Sheath	35 K	Clause 4.2

Annex A (Normative) Sampling and Conformity Assessment

A.1 Lot Inspection

A collection of toasters of identical design and rating manufactured in one production batch shall constitute a lot.

A.2 Acceptance Criteria

From each lot, a minimum of 5 samples shall be drawn at random and subjected to the electric strength test specified in Clause 4.1.

If zero samples fail, the lot conforms to the standard.