



Hebei InnoNew Material Technology Co., Ltd.

Add: No.79 Zhufeng Street, Shijiazhuang City, Hebei Province, China
InnoNew Tel/WhatsApp: +86 17736063980 Email: chris@innonew-material.com

Polycarboxylate Superplasticizer (PCE)

Items	Standard
Appearance	White powder
Solid content, %	≥ 98
Moisture, %	≤ 3
Bulk density, kg/m ³	600±50
pH value, 10% aqueous solution	6.0-9.0
Chloride content, %	≤ 0.02
Water reduction rate, %	≥ 25-40

advantages in technology and performance as following:

1. Low dosage, high rate of water reducing
2. Keep concrete good slump retention
3. Good compatibility with cement
4. Small shrinkage of concrete to keep the stability of volume and durability;
5. Environmental in production and usage. Base on above advantages.

Application:

The Polycarboxylate Superplasticizer needs to be mixed together with other dry powder materials. The added amount is 0.1-0.5% of the total material. The actual addition amount can be determined according to different debugging of products and applications.

Package:

25kg/bag, 13MT/20'FCL with pallets, 15MT/20'FCL without pallets

Storage:

It shall be stored in a cool and dry place. The opened packaging bags shall be sealed again to prevent moisture penetration. When stacked, they shall not exceed one pallet; The storage period shall not exceed one year.