

DATA SHEET&SPECIFICATION

For Monitoring IPDU

Model : CM-V-3P16A-36C39-3M	
Input	
Rated voltage	380-433Vac
Frequency	50/60 Hz
Input plug	IEC60309 industrial connector 16A 3phase
Cable length	3G*2.5mm ² *3meter
Input voltage range	380-433Vac
Power cord quantity	1
Max.Power Capacity	11.5kW
Max. input current	16A 3phase
Max. circuit current	16A
Output	
Rated voltage	220Vac ~250Vac
Overload protection	1P 16A Schneider Breaker
Max. Current	16A
Output Receptacles	36xC39
Physical parameter	
Dimensions (W*D*H) mm	1910*56*44.5mm
PDU Case material	Aluminum
Color	Black
Environment	
Working temperature	0 - 55 °C
Working humidity	5 - 95 %
Altitude	0-3000m
Storage temperature	-20 - 70 °C
Storage humidity	5 - 95 %
Conformity	
Standard warranty	1year
RoHS	Comply

Monitoring Functions & Multiple network service

1	Display	Hot-swappable meter	LCD, it displays the total input voltage, total current, total power etc.
		total voltage	Full scale:300V Accuracy:±1 % +2 character resolution ratio:0.1V Response Time:400ms
		Total current	Full scale:32A Accuracy: ±1 % +1 character resolution ratio:0.1A Response Time:400ms
		Total electric energy	A constant: 1600imp / kWh Level: 1 Resolution: 0.1kWh
		Temperature	resolution ratio: 0.1°C
		Humidity	resolution ratio: 0.1 %
2	monitoring function	the total load current monitoring	
		the total input voltage monitoring	
		the total load power monitoring	
		the total electricity consumption monitoring	
		the environmental temperature and humidity monitoring	
3	Setting Function	The total load current upper and lower limit settings	
		temperature and humidity upper and lower limit settings	
		address setting of email alarm	
		HTTP Network service settings	
		SNMP (V1 2 3) setting	
4	Alarm function	Network parameter settings (IP, gateway, mask, DNS)	
		The system alarm	When the total load current exceeds the rated value
			When temperature, humidity exceeds the upper and lower limits
		Customize the Alarms	When the total load current exceeds a threshold
			Temperature, humidity exceeds the upper and lower limits
		Alarm mode	Buzzer beep
			LCD digital flash
			Email is automatically sent to the system administrator
			SNMP Send alert status information.
			Serial Port Communication background send the alarm status information
5	Access method	WEB access control through IE;	
		SNMP (V1) via standard network management workstation access control	
		Telnet command line	
6	user management		Set the user name and password
7	cascading		Can be cascaded for two products