



Microsoft SQL Server

Deploying SQL Server 2016 PowerPivot and Power View in SharePoint 2016

Hands-On Lab for a Demo Environment

Summary: This white paper provides SharePoint administrators and architects detailed step-by-step instructions for deploying and configuring a Microsoft BI demo environment based on the Preview releases of SharePoint Server 2016, Office Online Server, and the SQL Server 2016 BI stack for SharePoint 2016. Following a brief introduction of important architecture changes and corresponding system dependencies, it outlines software and configuration requirements and a recommended deployment path to enable and verify BI capabilities in three main stages. This white paper also addresses known issues that exist in the SharePoint Server 2016 Beta 2, Office Online Server Preview and SQL Server 2016 CTP 3.1 releases and suggests appropriate workarounds. These workarounds will no longer be necessary in the final versions of the products. Check for an updated version of this white paper when deploying RTM releases.

Writer: Kay Unkroth

Technical Reviewers: Adam Saxton, Anne Zorner, Craig Guyer, Frank Weigel, Gregory Appel, Heidi Steen, Jason Haak, Kasper de Jonge, Kirk Stark, Klaus Sobel, Mike Plumley, Mike Taghizadeh, Patrick Wheeler, Riccardo Muti, Steve Hord

Published: December, 2015

Applies to: SQL Server 2016 CTP3.1, SharePoint 2016 Preview, Office Online Server Preview

Copyright

This document is provided “as-is”. Information and views expressed in this document, including URL and other Internet Web site references, may change without notice. You bear the risk of using it.

Some examples depicted herein are provided for illustration only and are fictitious. No real association or connection is intended or should be inferred.

This document does not provide you with any legal rights to any intellectual property in any Microsoft product. You may copy and use this document for your internal, reference purposes.

© 2015 Microsoft. All rights reserved.

Table of Contents

Introduction.....	5
Understanding the SQL BI Architecture for SharePoint 2016.....	6
Important Excel Online Dependencies and Restrictions	6
BI System Architecture for SharePoint 2016.....	7
Setting up a Demo Infrastructure	10
Step 1: Defining the VMs and their Roles	10
Step 2: Deploying the AD DS and DNS Environment and Joining the VMs.....	11
Deploy an AD DS Forest and DNS Zone.....	11
Create System, Administrator, and User Accounts	11
Step 3: Defining the Overall BI Deployment Sequence	12
Deploying a minimal Self-Service BI Environment	13
Step 1: Installing SQL Server Database Engine and Analysis Services in PowerPivot Mode	14
Install .NET Framework 3.5 as a SQL Server Setup Prerequisite:	14
Install SQL Server Database Engine Services and Analysis Services:	14
Configure Windows Firewall for Database Engine Services:.....	17
Configure Windows Firewall for Analysis Services:	20
Step 2: Installing SharePoint Server 2016 Beta 2	21
Install SharePoint Server 2016 Beta 2 Prerequisites:	22
Install a SharePoint Server 2016 Single Server Farm:.....	22
Configure the Single-Server Farm:.....	24
Add SharePoint Users to the BI Root Site:	25
Import user profiles into the SharePoint farm:.....	26
Step 3: Deploying Office Online Server Preview	28
Install Office Online Server Prerequisites	28
Install Office Online Server Preview	29
Create an Office Online Server Farm	30
Step 4: Configuring Excel Online for BI	31
Test Office Online Server to SSAS connectivity	31
Grant the Office Online Server Network Service Account Administrator Rights in Analysis Services	32
Connect Office Online Server to Analysis Services in PowerPivot Mode.....	33
Configure and enable Claims to Windows Token Service for Office Online Server	34
Register Office Online Server in the SharePoint Farm.....	35

Verify the Basic Excel Online Configuration for BI.....	35
Complementing Excel Online Capabilities for BI	36
Step 1: Adding PowerPivot Features to a SharePoint 2016 Farm	36
Install the PowerPivot Add-In File on the SharePoint Server.....	36
Deploy the PowerPivot Add-In in the SharePoint 2016 Farm	37
Grant SharePoint Services access to Analysis Services in PowerPivot Mode	38
Verify the Availability of PowerPivot Features in a SharePoint Site.....	38
Step 2: Enabling Workbooks as a Data Source.....	44
Configure SharePoint Authentication for Kerberos.....	45
Configure Kerberos Constrained Delegation between SharePoint and Office Online Server	45
Update the Analysis Services OLE DB Provider for Office Online Server Preview Only.....	47
Verify Workbooks as a Data Source in Excel Online	48
Step 3: Deploying the Management Dashboard Solution	48
Configure Office S2S Authentication between Office Online Server and SharePoint 2016.....	48
Update and Publish the Management Dashboard Workbooks in SharePoint 2016	52
Adding Self-Service Reporting	55
Step 1: Deploying SSRS in SharePoint integrated mode.....	55
Apply the Custom Server Role to SharePoint 2016	55
Install SSRS Add-in and Service in SharePoint-integrated Mode.....	56
Configure an SSRS service application	57
Step 2: Verifying SSRS in SharePoint-integrated Mode	58
Create a standalone Power View Report on top of a BISM connection	58
Create a standalone Power View Report on top of a workbook.....	59
Create a Power View Report embedded in a workbook.....	60
Conclusion.....	61
See Also	62

Introduction

There are many good reasons to upgrade BI-enabled SharePoint farms to Microsoft SharePoint Server 2016. New infrastructure advancements, specifically MinRole, help to facilitate performance and capacity planning, server deployment, and scale out in large environments. Other enhancements, such as advanced compliance capabilities and support for encrypted email communication, help to increase data protection and security in SharePoint farms, and there are numerous performance and reliability improvements stemming from the fact that SharePoint Server 2016 has its roots deep in the SharePoint Online codebase. For more information, see the SharePoint Server 2016 Beta 2 online documentation at [https://technet.microsoft.com/en-us/library/cc303422\(v=office.16\).aspx](https://technet.microsoft.com/en-us/library/cc303422(v=office.16).aspx).

More specifically for BI, Excel Services, now called Excel Online, features an improved architecture, unifying the Excel Services deployment for both workbook editing and BI scenarios. Previous releases required customers to exclude workbooks with PowerPivot data models from online editing experiences because the PowerPivot add-ins for SharePoint 2010 and SharePoint 2013 did not support Office Web Apps Server. The add-ins required Excel Services instances deployed directly in the SharePoint farms, which did not support online editing of workbooks. Furthermore, in SharePoint 2016, users soon can configure Scheduled Data Refresh for Excel workbooks that utilize Power Query connections to import data into a data model. This capability is not yet available in the Preview releases, but is going to ship with the final release of Office Online Server. Moreover, numerous popular Excel client features have found their way into Excel Online, such as search in filters, value field settings, freeze panes, print a selection, and support for comments.

The SQL Server 2016 BI stack for SharePoint 2016 also adds important enhancements. Thanks to the performance optimizations in SQL Server Analysis Services (SSAS), PowerPivot data models load faster and client queries also return quicker than with previous SSAS releases, contributing to an overall more responsive BI experience. SharePoint-integrated Reporting Services (SSRS) also offers noteworthy improvements with SQL Server 2016, such as new chart types, HTML5 rendering of reports, cross-browser printing, export to Microsoft PowerPoint, and an updated version of Report Builder.

Upgrading a BI-enabled SharePoint farm to SharePoint 2016 requires careful preparation, as many considerations have changed, due to the new architecture. Excel Services no longer ships with SharePoint 2016, making it a key requirement to deploy an Office Online Server environment along with the SharePoint 2016 farm. In BI-enabled SharePoint 2016 farms, Office Online Server must be able to act on behalf of the user when opening a workbook in the browser that uses another workbook as its data source. This PowerPivot functionality therefore requires Kerberos Constrained Delegation (KCD) between the Office Online servers that host Excel Online and the SharePoint front-end Web applications that host the site collections of the farm. KCD is not a requirement for SharePoint 2016 farms without the PowerPivot add-in.

This white paper provides you with detailed step-by-step instructions to deploy and configure a small BI demo environment to help you get familiar with the new architecture and its key components as quickly as possible. It also guides you past commonly encountered known issues in the Preview releases of SharePoint 2016, Office Online Server, and the SQL Server 2016 BI stack for SharePoint 2016. Due to these issues, it is recommended that you follow the deployment instructions in the sequence that this white paper outlines.

Understanding the SQL BI Architecture for SharePoint 2016

Even though the removal of Excel Services from the SharePoint codebase necessitated several design changes in the SQL Server BI stack for SharePoint 2016, farm administrators already familiar with the BI stack in SharePoint 2013 will find many similarities to their existing environments. The BI environment still relies on one or multiple server instances running Analysis Services in SharePoint/PowerPivot mode. Excel Online still maintains a corresponding BI server list that an administrator must configure so that Excel Online can load and query the data models embedded in the workbooks. SharePoint sites still provide users with the ability to upload and share their workbooks, reports, and other items. SharePoint content databases still store these workbooks and reports. Shared services, such as SharePoint-integrated Reporting Services, can still consume workbooks with data models as a data source. The main difference is that Excel Online must now be deployed on a separate dedicated computer running Office Online Server, as Figure 1 illustrates.




Figure 1 Server Deployments required for a BI-enabled SharePoint 2016 farm

Important Excel Online Dependencies and Restrictions

Under the covers, the SQL Server BI stack continues to rely on Excel Services SOAP APIs to communicate with the Excel Online service in Office Online Server, such as to load a data model and trigger a scheduled data refresh. Yet, due to the fact that Excel Online is now separate from the SharePoint farm, it is important to note the following system dependencies and restrictions when deploying and maintaining a BI environment based on SharePoint 2016:

- No workbook access for SharePoint managed accounts** Managed accounts, such as the farm account and the service accounts of shared services, cannot open Excel workbooks in Excel Online. This is an important limitation to keep in mind when testing PowerPivot functionality after an initial deployment. Make sure you use a regular SharePoint user account for testing and deployment verification.
- No workbook access from Central Administration** Opening workbooks from the SharePoint Central Administration web site in Excel Online is not possible. This affects the implementation

of the PowerPivot Management Dashboard, which is based on workbooks and Excel Services Web parts that previous releases hosted in the Central Administration web site. In SharePoint 2016, it is necessary to deploy the dashboard workbooks in a regular SharePoint site, as outlined later in this white paper.

- **Network Service Account only** Office Online Server does not support the configuration of a service account or unattended service account. Hence, Excel Online always uses the local Network Service account to connect to Analysis Services in PowerPivot mode as well as to organizational Multidimensional and Tabular databases.
- **Usage logging for the PowerPivot Management Dashboard requires PowerPivot Usage Processing Service and Office Service to Service (S2S) authentication** Excel Online cannot directly write SharePoint usage logs to track workbook and data model usage because the usage logging infrastructure is not available on the computer running Office Online Server. In order to gather this data for the Management Dashboard, the PowerPivot add-in for SharePoint 2016 includes a new component called PowerPivot Usage Processing Service. This service receives usage data from Excel Online and writes it into the SharePoint usage logs. In order to write it to SharePoint usage logs, trust must be established between Office Online Server and SharePoint Server 2016. The configuration of Office Service to Service (S2S) authentication establishes this trust, which has to be set up as a pre-requisite. The remaining processing of usage data is the same as in SharePoint 2013.
- **Workbooks as a data source require the PowerPivot Web Service and KCD** Given that Excel Online is external to the SharePoint farm, workbooks that access other workbooks as a data source require the PowerPivot Web Service on the SharePoint Front End Server. The PowerPivot Web Service only supports Windows authentication, so KCD must be configured between Excel Online and the SharePoint Web applications that host the sites and the PowerPivot Web Service. Also note that multi-forest topologies with single trust relationships are not supported because the Claims to Windows Token Service (C2WTS) cannot resolve accounts from remote forests if the required trust relationship is missing. If the domain controllers run Windows 2012 R2 and full trust relationships exist, then KCD can cross a single forest boundary. Multi-forest topologies are beyond the scope of this white paper. The demo environment relies on a single forest only.
- **Power View Reports embedded in Excel workbooks require SharePoint-integrated SSRS** While Excel Online can render workbooks in the browser, Power View reports embedded in these workbooks cannot be displayed unless the workbooks reside in a SharePoint farm with SharePoint-integrated Reporting Services installed. Excel Online relies on Reporting Services to render the Power View reports. Note also that Power View still has Silverlight dependencies.
- **Scheduled Data Refresh for workbook data models requires the PowerPivot add-in** Maintaining refresh schedules and triggering scheduled refreshes for workbook data models is the task of the PowerPivot System Services, which is part of the PowerPivot add-in for SharePoint 2016. If the add-in is not installed, workbooks cannot be scheduled for automatic refresh.

BI System Architecture for SharePoint 2016

As with previous releases, the SQL Server BI stack for SharePoint complements the capabilities of Excel Online so that users can interact with their workbook-based BI solutions in the browser, refresh their workbook data models on a scheduled basis, and consume these data models in new workbooks, SSRS

reports, and other solutions. However, due to the architectural changes regarding the Excel integration in SharePoint 2016, previous releases cannot support SharePoint 2016. SQL Server 2014 and earlier versions have no concept of Excel Online being in a separate Office Online Server deployment. Consequentially, SQL Server 2016 CTP3.1 or higher is the minimum software requirement to deploy PowerPivot and SSRS/Power View in a SharePoint 2016 farm.

Note that the SQL Server BI stack for SharePoint Server 2016 is only available with SQL Server 2016 CTP 3.1 and higher. While Multidimensional and Tabular SSAS instances can remain on previous SQL Server releases, previous versions do not support SharePoint Server 2016. Note also that while the SQL Server 2016 BI stack supports both, SharePoint 2013 and 2016, you must use separate PowerPivot add-ins. The PowerPivot add-in for SharePoint 2013 is available for download at <http://go.microsoft.com/fwlink/?LinkId=398152>. For SharePoint 2016, make sure you use the corresponding PowerPivot add-in at <http://go.microsoft.com/fwlink/?LinkId=716860>.

Figure 2 depicts the most important components in the system architecture of SQL Server BI for SharePoint 2016 in relationship to Excel Online hosted in Office Online Server.




Figure 2 System architecture for SQL Server BI based on SharePoint 2016 and Office Online Server

The SQL Server BI architecture for SharePoint 2016 includes the following key components and technologies:

- **Analysis Services Client Libraries** Enable service applications to load data models from workbooks via Excel Online and communicate with Analysis Services. In SharePoint 2016, it is important to use the client libraries that ship with the SQL Server 2016 PowerPivot for SharePoint add-in. Among other things, this add-in installs an SPClient component that enables the Analysis Services client libraries to communicate with Excel Online through the ECS API.
- **Analysis Services Service in PowerPivot Mode** Runs the VertiPaq engine to handle the data models received from Excel Online. Excel Online can load data models on the Analysis Services instance by using a Streaming Server Pool Module (SSPM). Having loaded a data model, the data is available for querying and refresh operations.
- **Excel Online** Loads Excel workbooks and renders them for display and interaction in the browser. If the workbook contains a data model, Excel Online streams the model to Analysis Services and then queries the data in order to update the workbook data. It is important to note that this action does not happen immediately when a user opens a workbook. Excel Online only streams the data model in response to a user action that requires an update of the workbook data, such as when a user interacts with PivotTables or PivotCharts via slicers.
- **PowerPivot Gallery** Implements custom content types and Microsoft Silverlight-enabled application pages for document libraries to visualize shared workbooks and SSRS/Power View reports interactively.
- **PowerPivot Management Dashboard** Facilitates centralized BI monitoring and management in a SharePoint environment.
- **PowerPivot Service Application Database** Stores schedule information for data refresh operations and usage data for the Management Dashboard workbooks.
- **PowerPivot System Service** Manages the application database, collects usage data, and performs automatic data refreshing for workbook data models.
- **PowerPivot Usage Processing Service** Enables Excel Online to submit usage data for a workbook and server statistics concerning the load and utilization of registered Analysis Services instances to the SharePoint 2016 usage logs. A SharePoint Timer job then moves the usage information into the PowerPivot Service Application Database.
- **PowerPivot Web Service** Exposes workbook data models via XML for Analysis (XML/A) as data sources to external applications, such as Excel or Report Builder. Client applications can access workbook data models in the same way as Tabular data models hosted on a dedicated Analysis Services instance in Tabular mode.
- **SharePoint Content Databases** Store the data, documents, workbook, and reports associated with SharePoint lists, libraries, and sites. Excel Online can retrieve the workbooks by using the Web Application Open Platform Interface (WOPI) protocol.
- **SharePoint Web Applications** Provide IIS sites and application pools, security identities, and isolation for front-end processes on a SharePoint server. A single web application can host multiple site collections and each site collection can have the PowerPivot feature activated or deactivated individually.
- **SSRS/Power View Service Application** Enables SSRS and Power View report creation and viewing in document libraries, subscription delivery of reports through email, and data alerting. Power View is a browser-based Silverlight application for interactive data exploration, visualization, and presentation.

Setting up a Demo Infrastructure

Deploying a small demo environment is a good way to get started with SQL Server BI in SharePoint 2016. Demo environments do not pose complicating challenges, such as production-level security or high-availability requirements, and do not require lengthy planning cycles. It is also an excellent idea to deploy the demo environment on virtual machines (VMs). VM checkpoints make it easy to return to a known good state, such as to repeat a failed installation or to undo an unsuccessful configuration step.

Step 1: Defining the VMs and their Roles

Given that Microsoft does not support installing Office Online Server on a computer already running SharePoint or SQL Server, a minimum BI demo environment for SharePoint 2016 requires three virtual machines to host Active Directory Domain Services (AD DS), SharePoint Server plus SQL Server, and Office Online Server. However, for performance reasons Microsoft highly recommends separating SharePoint Server and SQL Server, bringing the VM count up to four. It would also be a good idea to deploy SQL Server Database Engine and SQL Server Analysis Services on separate machines, but this white paper keeps both engines on the same VM to avoid redundant SQL Server Setup instructions.

Figure 3 shows the resulting infrastructure that this white paper uses for the demo environment with four virtual machines all hosted on the same physical computer running Microsoft Windows Server 2012 R2 and the Hyper-V server role. The fifth VM, WKSTA2016, does strictly speaking not belong to the server environment, but is required to create and work with workbooks using Microsoft Excel 2016.




Figure 3 A VM-based Demo Deployment SQL Server BI, SharePoint Server 2016, and Office Online Server

Note that you can also use Microsoft Azure virtual machines to deploy the demo environment. For details how to deploy AD DS, see Guidelines for Deploying Windows Server Active Directory on Azure Virtual Machines at <https://msdn.microsoft.com/en-us/library/azure/jj156090.aspx>.

Step 2: Deploying the AD DS and DNS Environment and Joining the VMs

In the demo environment for this white paper, all virtual machines run Windows Server 2012 R2 (even WKSTA2016). There are no special installation requirements. If you need installation instructions, refer to the Microsoft test lab guide for setting up a base configuration using Windows Server 2012 R2, available for download at <https://www.microsoft.com/en-us/download/details.aspx?id=39638>.

Deploy an AD DS Forest and DNS Zone

If you want to deploy your demo environment exactly as outlined in this white paper, log on to AD2012R2 as local administrator and run the following Windows PowerShell script:

```
# Install the AD-Domain-Services role on the domain controller AD2012R2
Install-WindowsFeature -Name AD-Domain-Services -IncludeManagementTools

# Establish a new forest
Install-ADDSForest -DomainName "lab.contoso.com"
    -DomainNetbiosName "Contosolab"
    -InstallDNS -SafeModeAdministratorPassword
        (ConvertTo-SecureString 'P@ssw0rd'
            -AsPlainText -Force)
    -Confirm:$false
```

This script deploys AD DS with a Fully Qualified Domain Name (FQDN) of *lab.contoso.com* and a corresponding NetBIOS domain name of *Contosolab*. Of course, if you use different names, make sure you use the correct information in the configuration instructions that follow.

Create System, Administrator, and User Accounts

As mentioned earlier in this white paper, system accounts, specifically SharePoint managed accounts, cannot open Excel workbooks in Excel Online. This implies that it is not possible to deploy and verify the demo environment by using only a single domain account. At the minimum, two accounts are necessary: one account for the SharePoint farm and its shared services and one account for the user verifying the BI features.

Table 1 lists the domain accounts that this white paper uses in the demo environment:

Account Name	Purpose
ContosoLab\SPFarm	The system account for the SharePoint farm and all its shared services. Given that there are no special security requirements, the demo environment does not use separate service accounts.
ContosoLab\SPUser	A domain account for a regular SharePoint user. This user does not have any administrative permissions in the SharePoint farm.
ContosoLab\SPAdmin	A domain admin account for SharePoint farm administration purposes. This account has full control over the SharePoint farm and its site collections.
ContosoLab\SPUpsSvc	A domain account for the User Profile Service Application to synchronize profile information with Active Directory. This account requires the Replicating Directory Changes permission in Active Directory. Because there are no special security requirements, the User Profile Service in the demo environment simply uses a domain admin account.

ContosoLab\SQLAdmin	A domain admin account for installing and configuring SQL Server Database Engine and Analysis Services. Using separate accounts for SharePoint and SQL Server administration helps to maintain a certain level of realism in the demo environment.
----------------------------	--

Table 1 System, administrator, and user accounts for deploying a SharePoint 2016-based demo environment for BI

After rebooting AD2012R2 and logging on as domain administrator, run the following Windows PowerShell script to create the suggested system, administrator, and user accounts:

```
# After the domain controller is rebooted, create user accounts
NEW-ADUSER SPFarm -Givenname SharePoint -Surname FarmAccount
    -AccountPassword (ConvertTo-SecureString "P@ssw0rd"
        -AsPlainText -Force)
    -DisplayName "Farm Account"
    -UserPrincipalName "spfarm@lab.contoso.com"
    -Enabled $True -PasswordNeverExpires:$true

NEW-ADUSER SPUser -Givenname SharePoint -Surname UserAccount
    -AccountPassword (ConvertTo-SecureString "P@ssw0rd"
        -AsPlainText -Force)
    -DisplayName "SharePoint User"
    -UserPrincipalName "spuser@lab.contoso.com"
    -Enabled $True -PasswordNeverExpires:$true

NEW-ADUSER SPAdmin -Givenname SharePoint -Surname AdminAccount
    -AccountPassword (ConvertTo-SecureString "P@ssw0rd"
        -AsPlainText -Force)
    -DisplayName "SharePoint Administrator"
    -UserPrincipalName "spadmin@lab.contoso.com"
    -Enabled $True -PasswordNeverExpires:$true

NEW-ADUSER SPUpssvc -Givenname SharePoint -Surname UPSAccount
    -AccountPassword (ConvertTo-SecureString "P@ssw0rd"
        -AsPlainText -Force)
    -DisplayName "SharePoint User Profile Import"
    -UserPrincipalName "spupssvc@lab.contoso.com"
    -Enabled $True -PasswordNeverExpires:$true

NEW-ADUSER SQLAdmin -Givenname SQL -Surname ServerAdmin
    -AccountPassword (ConvertTo-SecureString "P@ssw0rd"
        -AsPlainText -Force)
    -DisplayName "SQL Server Administrator"
    -UserPrincipalName "sqladmin@lab.contoso.com"
    -Enabled $True -PasswordNeverExpires:$true

# Add the SPAdmin and SQLAdmin accounts to the Domain Admins group
Add-ADGroupMember -Identity "Domain Admins" -Member "SPAdmin"
Add-ADGroupMember -Identity "Domain Admins" -Member "SPUpssvc"
Add-ADGroupMember -Identity "Domain Admins" -Member "SQLAdmin"
```

Step 3: Defining the Overall BI Deployment Sequence

With the basic Windows and AD DS infrastructure in place, the deployment of SQL Server, SharePoint Server, and Office Online Server can follow. Registering the Office Online Server deployment in SharePoint 2016 completes the steps to enable basic Excel Online capabilities according to the BI light-up story illustrated in Figure 4. The core BI features are not yet available until the server running Analysis Services in PowerPivot mode is registered in the Excel Online configuration.




Figure 4 The SQL Server BI Light-Up Story for SharePoint 2016

The remaining deployment steps for the PowerPivot add-in and SharePoint-integrated Reporting Services are interchangeable. However, it is strongly recommended to deploy the PowerPivot components before Reporting Services to avoid difficulties with the Preview releases. As outlined later in this white paper, Reporting Services requires the SharePoint server to be assigned the Custom server role, yet the PowerPivot Configuration Tool cannot deploy its SharePoint solution packages with this role due to a known issue in SharePoint 2016. Deploying the PowerPivot components first avoids having to switch server roles back and forth.

Deploying a minimal Self-Service BI Environment

A minimal self-service BI environment is an environment that provides core data exploration capabilities in Excel Online. In this environment, users can open workbooks in the browser and interact with the data in PivotTables or PivotCharts, such as by clicking on a slicer. This corresponds to the first two levels in the SQL Server BI Light-Up Story for SharePoint 2016. Advanced capabilities, such as Scheduled Data Refresh or Workbooks as a Data Source, are not yet available.

Deploying a minimal self-service BI environment involves the following steps:

1. **Installing the Database Engine and Analysis Services** SharePoint requires a database engine to host configuration and content databases and Excel Online requires an Analysis Services instance in PowerPivot mode to load and query data models. SharePoint 2016 does not require SQL Server 2016 for the database engine, and Excel Online might also work with SQL Server 2014 Analysis Services in PowerPivot mode, but it is highly recommended to use the latest SQL Server version.
2. **Installing a Single-Server SharePoint 2016 Farm** The SharePoint farm provides the main environment for users to collaborate and share their BI solutions.

3. **Deploying Office Online Server 2016** When a user opens a workbook in the browser, SharePoint redirects the browser to Office Online Server for rendering. To the user, it appears as if the workbooks are directly opened in SharePoint.
4. **Configuring Excel Online Server for BI** For Excel Online to be able to stream data models to Analysis Services, at least one SSAS server instance must be registered in the Excel Online configuration. This SSAS server must run in PowerPivot deployment mode. If the configuration includes multiple SSAS servers in PowerPivot mode, Excel Online performs load balancing automatically.

[Step 1: Installing SQL Server Database Engine and Analysis Services in PowerPivot Mode](#)

Starting with SQL Server 2016, the steps to install Analysis Services in PowerPivot mode are essentially the same as for Tabular or Multidimensional Mode. There is no longer a separate PowerPivot deployment path, which helps to provide a more intuitive setup experience. Among other things, it is now possible to deploy Analysis Services in PowerPivot mode using the default instance or an arbitrary instance name. However, due to an issue with the Preview releases, you must provide an instance name. Do not deploy Analysis Services in PowerPivot mode using the default instance yet.

The SQL Server 2016 Community Technology Preview (CTP) 3.1 is available for download in the Microsoft Evaluation Center at <http://www.microsoft.com/en-us/evalcenter/evaluate-sql-server-2016>.


[Install .NET Framework 3.5 as a SQL Server Setup Prerequisite:](#)

1. Log on to SQLDB2016 as SQLAdmin and then in **Server Manager**, click on **Add roles and features**.
2. On the **Before you begin** page, click **Next**.
3. On the **Select Installation type** page, accept the default selection for a **Role-based or feature-based installation** and click **Next**.
4. On the **Select destination server** page, make sure the local computer is selected, and then click **Next**.
5. On the **Select server roles** page, select **Application Server**, and then click **Next**.
6. On the **Select features** page, select **.NET Framework 3.5 Features** in addition to the default selection, and then click **Next**.
7. Click **Next** twice and then click **Install**.
8. Following the feature installation, click **Close** and then restart the computer to complete any pending update operations.


[Install SQL Server Database Engine Services and Analysis Services:](#)

1. Log on to SQLDB2016 again as SQLAdmin and start Setup.exe from the SQL Server 2016 CTP3.1 installation media. Click **Yes** if a **User Account Control** window is displayed.
2. In the **SQL Server Installation Center**, click **Installation** in the left-hand navigation area, and then click **New SQL Server stand-alone installation or add features to an existing installation**.
3. On the **Product Key** page, select an option to indicate whether you are installing a free edition of SQL Server, or a production version of the product that has a PID key. For a demo lab, accept the default **Specify a free edition** selection **Evaluation**.
4. On the **License Terms** page, review the license agreement and, if you agree, select the **I accept the license terms** check box, and then click **Next**.
5. On the **Product Updates** page, accept the default setting and click **Next**.


6. On the **Install Rule** page, verify that the rules are passed. Notice any warnings, such as for the **Windows Firewall** rule. Click **Next** to continue.
7. On the **Setup Role** page, select **SQL Server Feature Installation**, and then click **Next**.
8. On the Feature Selection page, select **Database Engine Services**, **Analysis Services**, and **Management Tools – Complete**. Take note of the directory paths, optionally change these paths if necessary, and then click **Next**.



9. The **Feature Rules** window will automatically advance if all rules pass. On the **Instance Configuration** page, make sure you select **Named instance**. The instance name is required. In prior releases installing Analysis Services in PowerPivot mode would automatically choose the instance name POWERPIVOT. This is no longer required. However, due to a known issue with CTP3.1, default instances are not yet supported. You can specify any valid instance name. This document suggests using **SHAREPOINT** as the instance name and ID. Click **Next** to continue.




10. On the **Server Configuration** page accept the default accounts for SQL Server services, and click **Next**.
11. On the **Database Engine Configuration** page, accept the default settings, and click on **Add Current User** to add SQLAdmin to the list of SQL Server administrators. Then click on **Add** to add the SPAdmin account as well. Click **Next** to continue.
12. On the **Analysis Services Configuration** page, under **Server Mode**, make sure you select **PowerPivot Mode**. Click on **Add Current User** to add SQLAdmin to the list of Analysis Services Server administrators, and then click **Next** to continue. The SPAdmin account does not require admin rights in Analysis Services.




13. On the **Ready to Install** page, click **Install**.
14. The **Installation Progress** page provides status so that you can monitor installation progress as Setup continues. If a **Computer restart required** dialog box is displayed, click **OK**, and then on the **Complete** page, click **Close**. Restart the server to complete the SQL Server installation.

Configure Windows Firewall for Database Engine Services:

1. Log on again to SQLDB2016 as SQLAdmin and then in **Server Manager**, under the **Tools** menu, select **Windows Firewall with Advanced Security**.
2. Select **Inbound Rules** and then in the right pane click on **New Rule**.
3. In **Rule Type**, click **Port** and then click **Next**.
4. In **Protocol and Ports**, select **UDP** and then under **Specific local ports** type **1434**. Click **Next**.



5. In **Action**, click **Allow the connection** and then click **Next**.
6. In **Profile**, clear any network locations that do not apply or accept the defaults and then click **Next**.
7. In **Name**, type a descriptive name for this rule (for example, **SQL Server Browser Service (udp-in) 1434**), and then click **Finish**.
8. Make sure **Inbound Rules** is still selected, and then in the right pane click on **New Rule** again.
9. In **Rule Type**, click **Program** and then click **Next**.
10. In **Program**, select **This program path**. Click **Browse**, and navigate to the instance of SQL Server that you want to access through the firewall, and then click **Open**. If you followed the installation instructions in this white paper, SQL Server is at **C:\Program Files\Microsoft SQL Server\MSSQL13.SHAREPOINT\MSSQL\Binn\Sqlservr.exe**. Click **Next**.



11. In **Action**, click **Allow the connection** and then click **Next**.
12. In **Profile**, clear any network locations that do not apply or accept the defaults and then click **Next**.
13. In **Name**, type a descriptive name for this rule (for example, **SQL Server Database Engine for SharePoint (dynamic port-in)**), and then click **Finish**.
14. On SP2016B2, logged on as SPAdmin, open Windows PowerShell and from the Windows PowerShell command prompt, run the following script to verify that the Database Engine is accessible:

```
# Open a connection to the SQL Server Database Engine
$sqlConnection = New-Object System.Data.SqlClient.SqlConnection
$sqlConnection.ConnectionString =
"Server=SQLDB2016\SHAREPOINT;Database=master;Integrated Security=True"
$sqlConnection.Open()

# Query the master database
$sqlCommand = New-Object System.Data.SqlClient.SqlCommand
$sqlCommand.CommandText = "SELECT name FROM [master].[sys].[databases]"
$sqlCommand.Connection = $sqlConnection


$sqlDataAdapter = New-Object System.Data.SqlClient.SqlDataAdapter
$sqlDataAdapter.SelectCommand = $sqlCommand

$dataSet = New-Object System.Data.DataSet
$sqlDataAdapter.Fill($dataSet)

# Close the SQL Server connection
$sqlConnection.Close()

# Dump out the results
```

\$dataset.Tables



```
Windows PowerShell
Copyright (C) 2013 Microsoft Corporation. All rights reserved.


PS C:\Users\SPAdmin> # Open a connection to the SQL Server Database Engine
PS C:\Users\SPAdmin> $sqlConnection = New-Object System.Data.SqlClient.SqlConnection
PS C:\Users\SPAdmin> $sqlConnection.ConnectionString = "Server=SQLDB2016\SHAREPOINT;Database=master;Integrated Security=True"
PS C:\Users\SPAdmin> $sqlConnection.Open()
PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin> # Query the master database
PS C:\Users\SPAdmin> $sqlCommand = New-Object System.Data.SqlClient.SqlCommand
PS C:\Users\SPAdmin> $sqlCommand.CommandText = "SELECT name FROM [master].[sys].[databases]"
PS C:\Users\SPAdmin> $sqlCommand.Connection = $sqlConnection
PS C:\Users\SPAdmin> $sqlDataAdapter = New-Object System.Data.SqlClient.SqlDataAdapter
PS C:\Users\SPAdmin> $sqlDataAdapter.SelectCommand = $sqlCommand
PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin> $dataSet = New-Object System.Data.DataSet
PS C:\Users\SPAdmin> $sqlDataAdapter.Fill($dataSet)
4
PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin> # Close the SQL Server connection
PS C:\Users\SPAdmin> $sqlConnection.Close()
PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin> # Dump out the results
PS C:\Users\SPAdmin> $dataSet.Tables

name
----
master
tempdb
model
msdb

PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin> _
```

Configure Windows Firewall for Analysis Services:

1. Select **Inbound Rules** again and click on **New Rule** one more time.
2. In **Rule Type**, click **Port** and then click **Next**.
3. In **Protocol and Ports**, select **TCP** and then under **Specific local ports** type **2382**. Click **Next**.



4. In **Action**, click **Allow the connection** and then click **Next**.
5. In **Profile**, clear any network locations that do not apply or accept the defaults and then click **Next**.
6. In **Name**, type a descriptive name for this rule (for example, **SQL Server Browser Service (tcp-in) 2382**), and then click **Finish**.
7. Make sure **Inbound Rules** is still selected, and then in the right pane click on **New Rule** again.
8. In **Rule Type**, click **Program** and then click **Next**.
9. In **Program**, select **This program path**. Click **Browse**, and navigate to the instance of Analysis Services that you want to access through the firewall, and then click **Open**. If you followed the installation instructions in this white paper, Analysis Services is at `%ProgramFiles%\Microsoft SQL Server\MSAS13.SHAREPOINT\OLAP\bin\msmdsrv.exe`. Click **Next**.
10. In **Action**, click **Allow the connection** and then click **Next**.
11. In **Profile**, clear any network locations that do not apply or accept the defaults, and then click **Next**.
12. In **Name**, type a descriptive name for this rule (for example, **SQL Server Analysis Services for SharePoint (dynamic port-in)**), and then click **Finish**. Note that Analysis Services connectivity will be tested in a later step as part of the Office Online Server deployment.

Step 2: Installing SharePoint Server 2016 Beta 2


During the SQL Server Database Engine installation, you specified SPAdmin as a SQL Server administrator so that you can use this account to carry out the deployment of the SharePoint farm. This includes installing prerequisites and SharePoint binaries as well as the provisioning of configuration and content

databases and the assignment of the Single Server role to the SharePoint server. Having deployed the initial farm, you must also provision and configure a minimum set of SharePoint shared services that the BI scenarios depend on.

SharePoint Server 2016 Beta 2 is available for download in the Microsoft Download Center at <http://www.microsoft.com/en-us/download/details.aspx?id=49961>.

Install SharePoint Server 2016 Beta 2 Prerequisites:


1. Log on to SP2016B2 as SPAdmin, download SharePoint Server 2016 Beta 2 from the Microsoft download site, and extract the files into an installation folder, such as C:\SP2016.
2. From the installation folder, run the **prerequisiteinstaller.exe** and if a **User Account Control** window is displayed, click **Yes**.
3. On the **Welcome to the Microsoft SharePoint 2016 Products Preparation Tool** page, click **Next**.
4. On the **License Terms for software products** page, review the license agreement and, if you agree, select the **I accept the terms of the License Agreement(s)** check box, and then click **Next**.
5. On the **Your system needs to restart to continue. Press Finish to restart your system.** page, click **Finish**.
6. After the restart, log on to SP2016B2 again as SPAdmin.
7. Prerequisiteinstaller.exe continues automatically. If a **User Account Control** window is displayed, click **Yes**.
8. On the **Installation Complete** page, click **Finish**.




Install a SharePoint Server 2016 Single Server Farm:

1. Log on to SP2016B2 as SPAdmin, and then start the **Setup.cmd** command file from the installation folder, such as C:\SP2016\Setup.cmd.

2. In the **SharePoint 2016 Preview** splash screen, click on **Install SharePoint Server**.
3. If a **User Account Control** window is displayed, click **Yes**.
4. On the **Enter your Product Key** page, enter your product key, and then click **Continue**. Note that PowerPivot for SharePoint 2016 requires Office 2016 SharePoint Server Premium Edition.
5. On the **Read the Microsoft Software License Terms** page, review the license agreement and, if you agree, select the **I accept the terms of this agreement** check box, and then click **Continue**.
6. On the **Choose a file location** page, accept the default paths or specify alternative file locations, and then click **Install Now**.
7. Following the installation, on the Run Configuration Wizard page, make sure the **Run the SharePoint Products Configuration Wizard now** check box is selected, and then click **Close**.
8. On the **Welcome to SharePoint Products** page, click **Next**.
9. In the **SharePoint Products Configuration Wizard** dialog box, informing you that a number of services will be restarted or reset, click **Yes**.
10. On the **Connect to a server farm** page, select **Create a new server farm**, and then click **Next**.
11. On the **Specify Configuration Database Settings** page, type the name of the Database Engine instance, such as **SQLDB2016\SHAREPOINT**, and under **Specify Database Access Account**, type the farm account name, such as **ContosoLab\SPFarm**, and the corresponding password. Click **Next**.




12. On the **Specify Farm Security Settings** page, enter and confirm a farm passphrase, such as **P@ssphr0se**, and then click **Next**.
13. On the **Specify Server Role** page, make sure you select **Single-Server Farm**, and then click **Next**.



14. On the **Configure SharePoint Central Administration Web Application** page, accept the default settings, and then click **Next**.
15. On the **Completing the SharePoint Products Configuration Wizard** page, review all the settings, and then click **Next** to start the configuration of the single-server farm.
16. On the **Configuration Successful** page, click **Finish**, and then in the SharePoint 2016 Preview splash screen, click **Exit**.

Configure the Single-Server Farm:


1. Logged on to SP2016B2 as SPAdmin, and having just finished the SharePoint farm setup, the **Initial Farm Configuration Wizard** is launched in the browser.
2. On the **Help Make SharePoint Better** page, select one of the options, and then click **OK**.
3. On the **Welcome** page, click **Start the Wizard**.
4. On the **Service Applications and Services** page, under **Service Account**, select **Use existing managed account**, and verify that **Contosolab\SPFarm** is selected.
5. Deselect all service applications, except **Application Management Service**, **Secure Store Service**, **User Profile Service Application**, **Claims to Windows Token Service**, **Distributed Cache**, and **Microsoft SharePoint Foundation Workflow Timer Service**. Click **Next**.
6. On the **Create Site Collection** page, in the **Title** textbox, type **BI Root Site**, and then click **OK**.



7. On the **This completes the Farm Configuration Wizard.** page, click **Finish**.

Add SharePoint Users to the BI Root Site:

1. Logged on to SP2016B2 as SPAdmin, in the browser, go to the BI Root Site, such as <http://sp2016b2/>.
2. Click on the settings icon in the top link bar and then click on **Site Settings**.
3. On the **Site Settings** page, click on **Site permissions**.
4. On the **Permissions** tab, click on **Grant Permissions**.
5. Under **Invite people**, type the name of the user you want to add, such as **SPUser** and verify that the name is resolved successfully.
6. Click on **Show Options** and verify that the user is added to the **BI Root Site Members [Edit]** group. Click on **Share**.



Import user profiles into the SharePoint farm:

1. Logged on to SP2016B2 as SPAdmin, and then on the Desktop, open **SharePoint 2016 Central Administration**. If a **User Account Control** window is displayed, click **Yes**.
2. On the Central Administration home page, click on **System Settings**, and then click on **Manage services on server**.
3. On the **Services on Server** page, verify that the **User Profile Service** is **Started**.
4. In the left navigation pane, click on **Application Management**, and on the **Application Management** page, under **Service Applications**, click on **Manage service applications**.
5. Select the **User Profile Service Application** and then on the ribbon click on **Manage**.
6. On the **Manage Profile Service: User Profile Service Application** page, under **Synchronization**, click on **Configure Synchronization Settings**.
7. On the **Configure Synchronization Settings** page, make sure that **Use SharePoint Active Directory Import** is selected and click **OK**.
8. Back on the **Manage Profile Service: User Profile Service Application** page, click on **Configure Synchronization Connections**.

9. Click on **Create New Connection** and provide the following information:

Parameter	Value
Connection Name	Contoso Lab
Type	Active Directory Import
Fully Qualified Domain Name	lab.contoso.com
Authentication Provider Type	Windows Authentication
Authentication Provider Instance	N/A
Account name	ContosoLab\SPUpsSvc
Password	P@ssw0rd
Confirm password	P@ssw0rd
Port	389

Note that the account you specify for the user profile import must have the Replicating Directory Changes permission in Active Directory.

10. Click on **Populate Containers**, and then expand the **contosolab** node.
11. Select the **Users** check box, and then click **OK**.
12. Click on **Application Management** again, and on the **Application Management** page, under **Service Applications**, click on **Manage service applications**, and then select the **User Profile Service Application** again and click on **Manage** one more time to navigate back to the **Profile Service Application** page.
13. Click on **Start Profile Synchronization**, then select **Start Full Synchronization**, and then click **OK**.
14. On the **Profile Service Application** page, verify that the import was successful, as indicated by the **Number of User Profiles**.

The screenshot shows the SharePoint Central Administration interface. The left navigation bar includes links for Central Administration, Application Management, System Settings, Monitoring, Backup and Restore, Security, Upgrade and Migration, General Application Settings, Apps, Office 365, Configuration Wizards, and Site Contents. The main content area is titled "Manage Profile Service: User Profile Service Application". It displays sections for People, Synchronization, Organizations, and My Site Settings. On the right, there is a detailed summary of Profile settings, including the number of user profiles (8), user properties (109), organization profiles (1), and organization properties (15). It also shows Audience settings with 1 audience, 0 uncompiled audiences, and an audience compilation status of Idle. The synchronization schedule is set to run every 5 minutes between 0 and 0. The last compilation time was on 11/7/2015 at 1:00 AM.

Profiles	
Number of User Profiles:	8
Number of User Properties:	109
Number of Organization Profiles:	1
Number of Organization Properties:	15

Audiences	
Number of Audiences:	1
Uncompiled Audiences:	0
Audience Compilation Status:	Idle

Audience Compilation Schedule	
Saturday at 01:00 AM	Ended at 11/7/2015 1:00 AM

Last Compilation Time	
11/7/2015 1:00 AM	

Profile Synchronization Settings	
Synchronization Schedule (Incremental)	every 5 minutes between 0 and 0
Profile Synchronization Status:	Idle

Step 3: Deploying Office Online Server Preview

As mentioned earlier in this white paper, Office Online Server Preview can't be installed on a SharePoint server, Active Directory domain controller, SQL server, or any other computer with existing applications. It is also not supported to install any other applications on the computer running Office Online Server. Make sure it is a dedicated deployment. Also make sure you deploy the prerequisites for Office Online Server, especially the Microsoft Identity Extensions for Office S2S authentication to work, as outlined in the following sections.

Office Online Server Preview is available for download in the Microsoft Download Center at <http://www.microsoft.com/en-us/download/details.aspx?id=49028>.


Install Office Online Server Prerequisites

1. Log on to WAC2016 as SPAdmin, and then in **Server Manager**, on the **Welcome to Server Manager** page, click on **Add roles and features**.
2. On the **Before you begin** page, click **Next**.
3. On the **Select Installation type** page, accept the default selection for a **Role-based or feature-based installation** and click **Next**.
4. On the **Select destination server** page, make sure the local computer is selected, and then click **Next**.
5. On the **Select server roles** page, select **Application Server** and **Web Server (IIS)**, and then in the **Add Roles and Features Wizard** dialog box, make sure the **Include management tools (if applicable)** check box is selected, click **Add Features**, and then click **Next**.

6. On the **Select features** page, in addition to the default selections, select **Ink and Handwriting Services** and **Windows Identity Foundation 3.5**, and then click **Next**.
7. On the **Application Server** page, note that the installation of Web Server (IIS) Support is recommended, and then click **Next**.
8. On the **Select role services** page, select **Web Server (IIS) Support**, and then in the **Add Roles and Features Wizard** dialog box, make sure the **Include management tools (if applicable)** check box is selected, click **Add Features**, and then click **Next**.
9. On the **Web Server Role (IIS)** page, click **Next**.
10. On the **Select role services** page, click **Next**, and then on the **Confirm installation selections** page, click **Install**.
11. Following the feature installation, click **Close** and then restart the computer to complete any pending update operations.
12. Log on to WAC2016 as SPAdmin, and then in **Server Manager**, click on **Add roles and features** again.
13. Click **Next** three times to reach the **Select server roles** page.
14. Expand **Web Server (IIS)**, expand **Web Server**, expand **Application Development**, and then select the **Server Side Includes** check box. Click **Next**.
15. On the **Select features** page, click **Next**.
16. On the **Confirm installation selections** page, click **Install**.
17. Following the feature installation, click **Close**.
18. Download and then run the installation package for Microsoft Identity Extensions at <http://download.microsoft.com/download/0/1/D/01D06854-CA0C-46F1-ADBA-EBF86010DCC6/MicrosoftIdentityExtensions-64.msi>.
19. On the **Please read the Microsoft Identity Extensions License Terms** page, review the license agreement and, if you agree, select the **I accept the terms of the License Agreement** check box, and then click **Install**. If a **User Account Control** window is displayed, click **Yes**.
20. On the **Completed the Microsoft Identity Extensions Setup Wizard** page, click **Finish**.
21. Download the **Update for Universal C Runtime in Windows** for your operating system, such as **All supported x64-based versions of Windows Server 2012 R2**, and then run the installer package.
22. In the **Windows Update Standalone Installer** dialog box, asking you if you want to install the updated, click **Yes**.
23. In the **Installation complete** dialog box, click **Close**.

Install Office Online Server Preview

1. Logged on to WAC2016 as SPAdmin, run **Setup.com** from the Office Online Server installation media. If a **User Account Control** window is displayed, click **Yes**.
2. On the **Read the Microsoft Software License Terms** page, review the license agreement and, if you agree, select the **I accept the terms of this agreement** check box, and then click **Continue**.
3. On the **Choose a file location** page, accept the default paths or specify alternative file locations, and then click **Install Now**.



4. On the final Office Online Server page, informing that the installation was successful, click **Close**.

Create an Office Online Server Farm

1. Logged on to WAC2016 as SPAdmin, right-click on the Windows PowerShell icon in the taskbar, and then click on **Run as Administrator**. If a **User Account Control** window is displayed, click **Yes**.
2. In Windows PowerShell, run the following command (if you use different computer names, replace `http://WAC2016` accordingly):

```
New-OfficeWebAppsFarm -InternalURL http://WAC2016.lab.contoso.com  
-AllowHttp -ClipartEnabled  
-TranslationEnabled -EditingEnabled  
-ExcelWorkbookSizeMax 2000  
-AllowHttpSecureStoreConnections  
-Verbose
```

Note that if `New-OfficeWebAppsFarm` is unavailable, you must run the `Import-Module OfficeWebApps` command to load the Office Online Server cmdlets.

3. Confirm the message that you should only set EditingEnabled to TRUE if licenses permit online editing with Y for Yes.
4. It is recommended that you copy & paste the output into a document to keep a reference of the Office Online Server configuration.
5. Note also that the **New-OfficeWebAppsFarm** cmdlet creates a new firewall rule called **Microsoft Office Web Apps** to open TCP ports 80, 443, and 809 for inbound traffic.

Step 4: Configuring Excel Online for BI

Configuring Excel Online for BI is a three-step process. First, ensure that the Analysis Services server instance in PowerPivot mode is accessible over the network. Second, register the server instance in the Excel Online configuration. Third, do not forget to grant Excel Online permission in Analysis Services to actually be able to load and query data models. In PowerPivot mode, you can grant this permission by adding the Excel Online service account to the list of SSAS server administrators. Remember that Office Online Server only uses the Network Service account, which corresponds to the computer account of the Office Online server in the Active Directory domain. Make sure you use the SQL Server 2016 Management Tools. Previous versions do not support adding computer accounts through the graphical user interface.

Also do not forget to register Excel Online in SharePoint so that users can open workbooks in the browser, and enable the Claims to Windows Token Service (C2WTS) so that Excel Online can resolve SharePoint identities into Windows identities. This section includes a Windows PowerShell script to register Excel Online. The SPAdmin user account from which you installed SharePoint Server 2016 is automatically granted the appropriate permissions to run Windows PowerShell cmdlets. If the user account you are using has not been added to run a Windows PowerShell cmdlet, you can use the Add-SPShellAdmin cmdlet to add the account. For additional information, see the Permissions section of the topic Use Windows PowerShell to administer SharePoint Server 2016 Beta 2, at [https://technet.microsoft.com/EN-US/library/ee806878\(v=office.16\).aspx#section3](https://technet.microsoft.com/EN-US/library/ee806878(v=office.16).aspx#section3).

Test Office Online Server to SSAS connectivity

1. Log on to WAC2016 as SQLAdmin (SQLAdmin is currently the only account with server administrator rights in Analysis Services), and start Windows PowerShell.
2. Run the following script to current list of server administrators in Analysis Services:


```
# Open a connection to Analysis Services
$ssasConnection = New-Object System.Data.OleDb.OleDbConnection
$ssasConnection.ConnectionString = "Provider=MSOLAP;Data
Source=SQLDB2016\SHAREPOINT"
$ssasConnection.Open()

# Retrieve the definition for the global Administrators group in SSAS
$guid = New-Object System.Guid "3444B255-171E-4cb9-AD98-19E57888A75F"
$restrictionList = @($null, $null, $null, $null, $null, $null, $null, $null,
"Administrators")
$schemaTable = $ssasConnection.GetOleDbSchemaTable($guid, $restrictionList);
[xml]$admins = $schemaTable.METADATA

# Close the SQL Server connection
$ssasConnection.Close()

# Dump out the members of the Administrators group
$admins.Role.Members.Member
```

- Verify that the ContosoLab\SQLAdmin account is returned, which indicates that Analysis Services can be accessed and queried successfully.



```

Windows PowerShell
Copyright (C) 2013 Microsoft Corporation. All rights reserved.

PS C:\Users\SPAdmin> # Open a connection to Analysis Services
PS C:\Users\SPAdmin> $ssasConnection = New-Object System.Data.OleDb.OleDbConnection
PS C:\Users\SPAdmin> $ssasConnection.ConnectionString = "Provider=MSOLAP;Data Source=SQLDB2016\SHAREPOINT"
PS C:\Users\SPAdmin> $ssasConnection.Open()
PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin> # Retrieve the definition for the global Administrators group in SSAS
PS C:\Users\SPAdmin> $guid = New-Object System.Guid "3444B255-171E-4cb9-AD98-19E57888A75F"
PS C:\Users\SPAdmin> $restrictionList = @($null, $null, $null, $null, $null, $null, $null, "Administrators")
PS C:\Users\SPAdmin> $schemaTable = $ssasConnection.GetOleDbSchemaTable($guid, $restrictionList);
PS C:\Users\SPAdmin> [xml]$admins = $schemaTable.METADATA
PS C:\Users\SPAdmin> # Close the SQL Server connection
PS C:\Users\SPAdmin> $ssasConnection.Close()
PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin> # Dump out the members of the Administrators group
PS C:\Users\SPAdmin> $admins.Role.Members.Member


Sid                               Name
---                               ---
S-1-5-21-576692669-1620830494-3657325270-1114  contosolab\SQLAdmin

PS C:\Users\SPAdmin>

```

Grant the Office Online Server Network Service Account Administrator Rights in Analysis Services

- Log on to SQLDB2016 as SQLAdmin and start SQL Server Management Studio.
- Connect to the **SQLDB2016\SHAREPOINT** instance of Analysis Services, and then right-click the instance name in **Object Explorer** and then click **Properties**.
- Click **Security** in the **Select a Page** pane, and then click **Add**.
- In the **Select Users or Groups** dialog, click **Locations**, and then select **Entire directory** and click **OK**.
- Click **Object Types**, select the **Computers** check box, and then click **OK**.
- In the **Enter the object names to select** textbox, type the name of the computer, such as **WAC2016**, and then click **Check Names** to verify the computer account is found.
- Click **OK** twice to apply the changes and close the **Analysis Server Properties** dialog box.



Connect Office Online Server to Analysis Services in PowerPivot Mode

1. If you are still logged on to WAC2016 as SQLAdmin, log off, and then log on as SPAdmin.
2. Right-click on the Windows PowerShell icon in the taskbar, and then click on **Run as Administrator**. If a **User Account Control** window is displayed, click **Yes**.
3. From the Windows PowerShell command prompt, run the following command:

```
# Register the Analysis Services server in Office Online Server
New-OfficeWebAppsExcelBIServer -ServerId SQLDB2016\SHAREPOINT
```

Note that if `New-OfficeWebAppsExcelBIServer` is unavailable, you must run the `Import-Module OfficeWebApps` command to load the Office Online Server cmdlets.

```

Administrator: Windows PowerShell
Windows PowerShell
Copyright (C) 2013 Microsoft Corporation. All rights reserved.

PS C:\Windows\system32> New-OfficeWebAppsExcelBIserver -ServerId SQLDB2016\SHAREPOINT

ServerId
-----
[SQLDB2016\SHAREPOINT]

PS C:\Windows\system32>

```

Configure and enable Claims to Windows Token Service for Office Online Server

- From the Windows PowerShell command prompt, run the following command to open the configuration file of the Claims to Windows Token Service (C2WTS) in Notepad.exe:
- Notepad "C:\Program Files\windows Identity Foundation\v3.5\c2wtshost.exe.config"**
- Remove the comment tags (<!-- and -->) from the NT AUTHORITY\Network Service line and save the changes.

```

c2wtshost.exe.config - Notepad
File Edit Format View Help
<?xml version="1.0"?>

<configuration>
  <configSections>
    <section name="windowsTokenService" type="Microsoft.IdentityModel.WindowsTokenService.Configuration.WindowsTokenServiceSection, Microsoft.IdentityMod
  </configSections>

  <startup>
    <supportedRuntime version="v4.0"/>
    <supportedRuntime version="v2.0.50727"/>
  </startup>

  <windowsTokenService>
    <!--
      By default no callers are allowed to use the Windows Identity Foundation Claims To NT Token Service.
      Add the identities you wish to allow below.
    -->
    <allowedCallers>
      <clear/>
      <add value="NT AUTHORITY\Network Service" />
      <!-- <add value="NT AUTHORITY\Local Service" /> -->
      <!-- <add value="NT AUTHORITY\System" /> -->
      <!-- <add value="NT AUTHORITY\Authenticated Users" /> -->
    </allowedCallers>
  </windowsTokenService>
</configuration>

```

- From the Windows PowerShell command prompt, run the following commands to configure the Claims to Windows Token Service for automatic startup and start the service:

```

Set-Service -Name C2WTS -startuptype "automatic"
Start-Service -Name C2WTS

```

Register Office Online Server in the SharePoint Farm

1. Log on to SP2016B2 as SPAdmin, right-click on the SharePoint 2016 Management Shell, and then click **Run as administrator**. If a **User Account Control** window is displayed, click **Yes**.
2. From a Windows PowerShell command prompt, run the following commands to update the SharePoint farm properties for Excel Services SOAP API support, which provides among other things the basis for Analysis Services client libraries to communicate with Excel Online:

```
$farm = Get-SPFarm  
$farm.Properties.Add("WopiLegacySoapSupport",  
"http://WAC2016.lab.contoso.com/x/_vti_bin/ExcelServiceInternal.asmx");  
$farm.Update();
```


3. From a Windows PowerShell command prompt, run the following commands to register a new WOPI Binding for the Office Online Server and allow authentication over HTTP connections:

```
New-SPWOPIBinding -ServerName WAC2016.lab.contoso.com -AllowHTTP  
Set-SPWOPIZone internal-http  
$config = (Get-SPSecurityTokenServiceConfig)  
$config.AllowOAuthOverHttp = $true  
$config.Update()
```

4. Close the SharePoint 2016 Management Shell.

Verify the Basic Excel Online Configuration for BI

1. Log on to SP2016B2 as SPUser, and then in the browser, visit the BI Root Site at <http://sp2016b2>.
2. Open the **Documents** library and then click on **Upload**. Upload an Excel workbook with a PowerPivot data model.
3. Following the upload, click on the workbook to open it in the browser. Note that the workbook renders in Excel Online.
4. Interact with the data by clicking on a slicer to ensure Excel Online loads the data model on the Analysis Services instance.
5. Log on to SQLDB2016 as SQLAdmin and start **Microsoft SQL Server Management Studio**.
6. In the **Connect to Server** dialog box, under **Server type**, select **Analysis Server**, und under **Server name**, type **SQLDB2016\SHAREPOINT**. Click **Connect**.
7. Expand the **Databases** node and verify that the workbooks data model is listed.



Complementing Excel Online Capabilities for BI

Even though the basic Excel Online configuration for BI does not yet unlock the richness of PowerPivot and Reporting Services capabilities, it does represent a significant milestone because Excel Online is the only service with the ability to load workbook data models. Any other service application wanting to access such data models must first ask Excel Online to load them. This step is usually transparent to the application because the Analysis Services client libraries handle the Excel Online communication, but it implies that Excel Online must be able to communicate with Analysis Service for any application to consume a workbook data model. Having loaded a requested data model, Excel Online returns the chosen SSAS server and data model name to the caller so that the client library can establish a direct SSAS connection to this model. In PowerPivot mode, establishing a direct connection requires SSAS server admin rights, so the service accounts of the SharePoint service applications must be added to the SSAS administrator list.

Step 1: Adding PowerPivot Features to a SharePoint 2016 Farm

The successful verification of the basic Excel Online configuration for BI in the previous step indicates that the BI environment ready for the deployment of the PowerPivot add-in. The PowerPivot add-in for SharePoint 2016 is available for download as part of the SQL Server 2016 CTP3.1 Feature Pack in the Microsoft Download Center at <http://go.microsoft.com/fwlink/?LinkId=716860>.

Install the PowerPivot Add-In File on the SharePoint Server

1. Log on to SP2016B2 as SPAdmin and download the PowerPivot for SharePoint 2016 add-in installation package (spPowerPivot16.msi) from the SQL Server 2016 Feature Pack.
2. Run **spPowerPivot16.msi** and then on the **Welcome** page, click **Next**.


3. On the **License Agreement** page, review the license agreement and, if you agree, select the **I accept the terms in the license agreement** check box, and then click **Next**.
4. On the **Feature Selection** page, make sure all of the features are selected, and then click **Next**.
5. On the **Ready to Install the Program** page, click **Install**.
6. If a **User Account Control** window is displayed, click **Yes**.
7. On the **Completing the SQL Server 2016 PowerPivot for SharePoint installation** page, click **Finish**.

Deploy the PowerPivot Add-In in the SharePoint 2016 Farm

1. Logged on to SP2016B2 as SPAdmin, run the PowerPivot for SharePoint 2016 Configuration tool. If a **User Account Control** window is displayed, click **Yes**.
2. In the **PowerPivot Configuration Tool** dialog box, select **Configure or Repair PowerPivot for SharePoint**, and then click **OK**.
3. On the **Parameters** tab, assuming you followed the instructions in this white paper, provide the following information:

Parameter	Value
Default Account Username	contosolab\SPFarm
Default Account Password	P@ssw0rd
Database Server	SQLDB2016\SHAREPOINT
Passphrase	P@ssphr0se
Confirm Passphrase	P@ssphr0se

4. Click **Validate**, and then in the **Test Validation** dialog box informing you that the validation succeeded for all actions, click **OK**.
5. Click **run** to start the PowerPivot deployment and farm configuration steps, and confirm the actions by clicking **Yes** in the **Warning** dialog box.
6. In the **Task Configuration** dialog box, informing you that the selected tasks completed successfully, click **OK**.
7. In the **PowerPivot Configuration Tool**, click **Exit**.



Grant SharePoint Services access to Analysis Services in PowerPivot Mode

1. Log on to SQLDB2016 as SQLAdmin and start SQL Server Management Studio.
2. Connect to the **SQLDB2016\SHAREPOINT** instance of Analysis Services, and then right-click the instance name in **Object Explorer** and then click **Properties**.
3. Click **Security** in the **Select a Page** pane, and then click **Add**.
4. In the **Select Users or Groups** dialog, click **Locations**, and then select **Entire directory** and click **OK**.
5. In the **Enter the object names to select** textbox, type the name of the SharePoint farm/services account, such as **ContosoLab\SPFarm**, and then click **Check Names** to verify the account is found.
6. Click **OK** twice to apply the changes and close the **Analysis Server Properties** dialog box.

Verify the Availability of PowerPivot Features in a SharePoint Site

1. Logged on to SP2016B2 as SPAdmin, in the browser, visit the BI Root Site at <http://sp2016b2>.
2. Click on the cogwheel at the top right corner of your site's home page, and then click on **Site settings**.
3. Under **Site Collection Administration**, click on **Site collection features**.
4. On the **Site Settings – Site Collection Features** page, make sure that the **PowerPivot Feature Integration for Site Collections** is **Active**.

Note that the PowerPivot Configuration Tool automatically deployed the PowerPivot Web app solution in the Web application of the <http://sp2016b2> site collection and activated the

PowerPivot feature. Additional Web applications and site collections require manual steps to deploy the Web app solution by using Central Administration and feature activation using the **Site Settings – Site Collection Features** page.


The screenshot shows the SharePoint Site Collection Features page. The URL in the address bar is http://sp2016b2/_layouts/15/start.aspx#?page=SiteCollectionFeatures. The page title is "Site Collection Features". The "PowerPivot Feature Integration for Site Collections" feature is listed and marked as "Active". Other features shown include Document Sets, In Place Records Management, Library and Folder Based Retention, Limited-access user permission lockdown mode, Open Documents in Client Applications by Default, PerformancePoint Services Site Collection Features, Project Server Approval Content Type, Project Web App Permission for Excel Web App Refresh, Project Web App Ribbon, Project Web App Settings, Project Web App PMO Settings, and Publishing Approval Workflow. Most features have "Activate" buttons next to them, except for the ones that are already active.

5. Log on to SP2016B2 as SPUser, and then in the browser, visit the BI Root Site at <http://sp2016b2>.
6. Click on **Site Contents** and then click on **add an app**.
7. On the **Site Contents – Your Apps** page, click on **PowerPivot Gallery**.
8. In the **Adding PowerPivot Gallery** dialog box, type a name for the new repository, such as **PowerPivot Gallery**, and then click **Create**.
9. Click on the new link to the Power Pivot Gallery library that appears in the navigation Quick Launch pane for the current site and upload a sample workbook by clicking on **Files** and then on **Upload Document**.

Note that the PowerPivot Gallery requires Silverlight. If Silverlight is not yet installed on your computer, click on the **Install Microsoft Silverlight** link that the PowerPivot Gallery provides and

follow the installation instructions. Note also that browsers without support for Silverlight, such as Microsoft Edge or Google Chrome, cannot be used to display the contents of a PowerPivot Gallery.

10. Verify that the PowerPivot Gallery displays the uploaded document. After a short period of time, refresh the gallery view and verify that the PowerPivot Gallery displays the individual worksheets as thumbnails.



11. Click on the Refresh Schedule button, which looks like a calendar, at the top right corner of your PowerPivot Gallery page.
12. On the **Manage Data Refresh** page, under **Data Refresh**, select the **Enable** check box.
13. Specify the desired **Schedule Details** and then select the **Also refresh as soon as possible** check box.
14. Under **Credentials**, select **Connect using the following Windows user credentials**, and then type in the credentials required to access the data source, such as the SPUser account, and then click **OK**.

Manage Data Refresh: Olympics

Warning: this page is not encrypted for secure communication. User names, passwords, and any other information will be sent in clear text. For more information, contact your administrator.

Data Refresh

Specify if you would like to turn Data Refresh on or off. [Click here](#) to learn more about this page.

Enable

Schedule Details

Define the frequency (daily, weekly, monthly or once) and the timing details for the refresh schedule.

Daily Every day(s)
 Weekly Every weekday
 Monthly On the following days:
 Once Sunday Monday Tuesday Wednesday
 Thursday Friday Saturday

Also refresh as soon as possible

Earliest Start Time

Specify the earliest start time that the data refresh will begin

After business hours
 Specific earliest start time:
 12 : 00 am pm

E-mail Notifications

Specify e-mail address of the users to be notified in the event of data refresh failures.

Credentials

Provide the credentials that will be used to refresh data on your behalf.

Use the data refresh account configured by the administrator
 Connect using the following Windows user credentials

User Name:
 Password:
 Confirm Password:

Connect using the credentials saved in Secure Store Service (SSS) to log on to the data source. Enter the ID used to look up the credentials in the SSS ID box

15. After a minute, click on the Refresh Schedule button again. Note that the **Data Refresh History** page is displayed with the status of the recent refresh operation. Verify that the initial data refresh completed successfully.

The screenshot shows a SharePoint interface for the PowerPivot Gallery. The URL in the address bar is http://sp2016b2/_layouts/15/PowerPivot/View1.aspx. The page title is "PowerPivot Gallery". The left navigation bar includes links for Home, Documents, Recent, PowerPivot Gallery, Site Contents, and Recycle Bin. The main content area is titled "Data Refresh History: Olympics". It displays a table with the following data:


Schedule Information		
Name:	Olympics.xlsx	
Schedule Last Updated By:	SharePoint User	
Schedule Last Updated:	11/17/2015 1:33:45 PM	
Current Status:	Succeeded	
Last Successful Refresh:	11/17/2015 1:34:03 PM	
Next Scheduled Refresh:	11/18/2015 Configure Schedule ...	

Below this is a table titled "History" with columns: Started, Duration, and Comments. It contains one entry:

Started	Duration	Comments
11/17/2015 1:31:58 PM	00:00:05	

16. Click on **Site Contents** and then click again on **add an app**.
17. On the **Site Contents – Your Apps** page, click on **Document Library**.
18. In the **Adding Document Library** dialog box, type a name for the new repository, such as **Data Connection Library**, and then click **Create**.
19. Open the new **Data Connection Library**, and then on the **Library** tab, click on **Library Settings**.
20. Click on **Advanced Settings**, and then in the **Settings – Advanced Settings** page, under **Allow management of content types?**, select **Yes**.
21. Click **OK**.
22. On the **Data Connection Library : Settings** page, under **Content Types**, click on **Add from existing site content types**.
23. Under **Available Site Content Types**, select **BI Semantic Model Connection**, click **Add**, and then click **OK**.
24. Click on the **Data Connection Library** in the left navigation Quick Launch pane to open the **Data Connection Library** again.
25. Click **New** and then click **BI Semantic Model Connection**.
26. Under **File Name**, type a descriptive name, such as **Olympics Workbook Connection**, and optionally provide a **Description**.
27. Under **Workbook URL or Server Name**, type the workbook URL, such as **<http://sp2016b2/PowerPivot%20Gallery/Olympics.xlsx>** and then click **OK**.
28. If you are notified that it is not possible to connect to the server or database, select the **Save the link file without connection validation** check box, and then click **OK** to save the file anyway. The connection test is performed under the identity of the PowerPivot service application, which does not have the permissions to load the referenced workbook.

Note that if you have Tabular Analysis Services databases in your environment, you can also register these databases in the Data Connection Library by using BISM connection files.



29. On the workstation with Excel 2016, WKSTA2016, log on as SPUser, and then in the browser, visit the BI Root Site at <http://sp2016b2>.
30. Open the **Data Connection Library** and then click on the ellipsis for the **Olympics Workbook Connection** file, click on the ellipsis in the context menu again to display more options, and then click on **Launch Excel**.
31. When you are asked to open or save an odc file, click **Open**.
32. Note that Excel is launched. In the **Microsoft Excel Security Notice**, click **Enable**.
33. In the **Data Link Properties** dialog box, accept the defaults, and click **OK**.
34. Verify that Excel automatically adds an empty PivotTable to the worksheet and displays the PivotTable Fields with the fields from the data model. You now can query the Data Model that was created and uploaded with the first Excel workbook. The new workbook does not contain a data model; it is linked to the first workbook that already exists in SharePoint.
35. Build a new report by selecting appropriate measures and fields. For example, you could try to recreate a PivotTable from the original workbook.
36. Make sure you also add a slicer for easy interaction with the data. On the **Analyze** tab, click on **Insert Slicer**. In the **Insert Slicer** dialog box, select an appropriate field and then click **OK**.
37. Click on a value in the slicer and notice that data in the PivotTable changes according to your selection.
38. Save the workbook with an appropriate name in a document library of your choice, such as <http://sp2016b2/PowerPivot%20Gallery>.
39. Close Excel.

40. Open the workbook in the browser and try to interact with the data by clicking on the slicer. If a **Query and Refresh Data** dialog box is displayed asking you if you want to refresh the workbook, click **Yes**.
41. Note that an **External Data Refresh Failed** dialog box is displayed informing you that the **PowerPivot Linked Data** connection could not be established. This error occurs because Excel Online cannot yet act on behalf of the user to retrieve the source workbook, which requires Kerberos Constrained Delegation to be enabled between Excel Online and SharePoint servers. Click **OK**.

The screenshot shows an Excel Online interface with a PivotTable Fields pane on the right. The PivotTable Fields pane lists various fields under categories like CountryRegions, Editions, and Medals. A specific field, 'Medal Count', is checked. A 'Continent' slicer is applied to the data, showing options for Africa and Asia. A modal dialog box titled 'External Data Refresh Failed' is displayed in the center, stating: 'An error occurred during an attempt to establish a connection to the external data source. The following connections failed to refresh: PowerPivot Linked Data'. It includes a link 'Learn more about data refresh' and an 'OK' button.

Step 2: Enabling Workbooks as a Data Source


Workbooks as a Data Source, also known as consuming a workbook's data model from another workbook or application similar to an Analysis Services database, requires some extra configuration steps because Excel Online must access the source workbook that contains the data model on behalf of the user. In other words, you must configure KCD. Moreover, due to a known issue in the Analysis Services client libraries that ship with Excel Online Preview, the following section also shows you how to update the client libraries so that the server uses the latest version of the Analysis Services OLE DB Provider. The Analysis Services OLE DB Provider (ENU\x64\SQL_AS_OLEDB.msi) is available for download in the SQL Server 2016 CTP 3.1 Feature Pack at <http://go.microsoft.com/fwlink/?LinkId=398150>.

Configure SharePoint Authentication for Kerberos

1. Log on to SP2016B2 as SPAdmin, and then on the Desktop, open **SharePoint 2016 Central Administration**. If a **User Account Control** window is displayed, click **Yes**.
2. Under **Application Management**, click on **Manage web applications**.
3. Select the Web application that hosts your site collection, such as **SharePoint – 80**, and then click on **Authentication Providers**.
4. In the **Authentication Providers** dialog box, under **Zone**, click on **Default**.
5. On the **Authentication Providers** page, under **Claims Authentication Types**, make sure the check boxes **Enable Windows Authentication** and **Integrated Windows authentication** are selected, and then in the listbox select **Negotiate (Kerberos)**.
6. Click **OK** and wait until the **Authentication Providers** page is closed.
7. Close Central Administration.

Configure Kerberos Constrained Delegation between SharePoint and Office Online Server

1. On all server machines, log on with an account that has local administrator permissions, start Windows PowerShell, and then run the following command: **ipconfig /all**. In the output, verify that the **DNS Suffix Search List** contains the correct DNS domain name for your environment, such as **lab.contoso.com**. This is a requirement for Kerberos authentication to work. Correct any inconsistencies in the DNS properties of your network adapter for both the IPv6 and IPv4 protocol.
2. Continuing on SP2016B2 only, logged as SPAdmin, switch to Server Manager.
3. Click on **Add roles and features**.
4. On the **Before you begin** page, click **Next**.
5. On the **Select Installation type** page, accept the default selection for a **Role-based or feature-based installation** and click **Next**.
6. On the **Select destination server** page, make sure the local computer is selected, and then click **Next**.
7. On the **Select server roles** page, click **Next**.
8. On the **Select features** page, expand **Remote Server Administration Tools**, expand **Role Administration Tools**, expand **AD DS and AD LDS Tools**, and then select **Active Directory Module for Windows PowerShell**.
9. Click **Next** and then click **Install**.
10. Following the feature installation, click **Close**.
11. Right-click the clock in the Taskbar and then click **Task Manager**.
12. In **Task Manager**, click on **More Details**, and then switch to the **Details** tab.
13. In the **Name** column, select a row for the **w3wp.exe**, which is the **IIS Worker Process**. Note the service identity under User name, such as **SPFarm**, which is the service account that the application pool for SharePoint Web Services uses. Alternatively, you can use SharePoint Central Administration to determine the service account for the Web Applications that host your site collections.



14. Open a new Windows PowerShell window and run the following script (replace computer and service account names if necessary):

```
# Get the Office Online server account in Active Directory.
$allowedPrincipals = @()
$allowedPrincipals += Get-ADComputer -Identity WAC2016

# Set the delegation property on the application pool identity.
Set-ADUser SPFarm -PrincipalsAllowedToDelegateToAccount $allowedPrincipals

# Set the Service Principal Names for the application pool identity.
SetSPN -S HTTP/SP2016B2 ContosoLab\SPFarm
SetSPN -S HTTP/SP2016B2.lab.contoso.com ContosoLab\SPFarm

# List the principals allowed to delegate
Get-ADUser SPFarm -Properties PrincipalsAllowedToDelegateToAccount

# List the Service Principal Names.
SetSPN -T WAC2016
SetSPN -T ContosoLab\SPFarm
```

15. In the script output, make sure that the **WAC2016** computer account is listed under **PrincipalsAllowedToDelegateToAccount** and that the following Service Principal Names have been configured:

Account Name	SPNs
WAC2016	HOST/WAC2016 HOST/WAC2016.lab.contoso.com
ContosoLab\SPFarm	HTTP/SP2016B2.lab.contoso.com HTTP/SP2016B2

```

Windows PowerShell
Copyright (C) 2013 Microsoft Corporation. All rights reserved.

PS C:\Users\SPAdmin> # Get the Office Online server account in Active Directory.
PS C:\Users\SPAdmin> $allowedPrincipals = @()
PS C:\Users\SPAdmin> $allowedPrincipals += Get-ADComputer -Identity WAC2016
PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin> # Set the delegation property on the application pool identity.
PS C:\Users\SPAdmin> Set-ADUser SPFarm -PrincipalsAllowedToDelegateToAccount $allowedPrincipals
PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin> # Set the Service Principal Names for the application pool identity.
PS C:\Users\SPAdmin> SetSPN -S HTTP/SP2016B2 ContosoLab\SPFarm
Checking domain DC=lab,DC=contoso,DC=com

Registering ServicePrincipalNames for CN=SPFarm,CN=Users,DC=lab,DC=contoso,DC=com
    HTTP/SP2016B2
Updated object
PS C:\Users\SPAdmin> SetSPN -S HTTP/SP2016B2.lab.contoso.com ContosoLab\SPFarm
Checking domain DC=lab,DC=contoso,DC=com

Registering ServicePrincipalNames for CN=SPFarm,CN=Users,DC=lab,DC=contoso,DC=com
    HTTP/SP2016B2.lab.contoso.com
Updated object
PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin> # List the principals allowed to delegate
PS C:\Users\SPAdmin> Get-ADUser SPFarm -Properties PrincipalsAllowedToDelegateToAccount

DistinguishedName : CN=SPFarm,CN=Users,DC=lab,DC=contoso,DC=com
Enabled : True
GivenName : SharePoint
Name : SPFarm
ObjectClass : user
ObjectGUID : c7ef7668-73cc-4274-9fb8-e5c6a5424bf2
PrincipalsAllowedToDelegateToAccount : {CN=WAC2016,CN=Computers,DC=lab,DC=contoso,DC=com}
SamAccountName : SPFarm
SID : S-1-5-21-576692669-1620830494-3657325270-1111
Surname : FarmAccount
UserPrincipalName : spfarm@lab.contoso.com

PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin> # List the Service Principal Names.
PS C:\Users\SPAdmin> SetSPN -L WAC2016
Registered ServicePrincipalNames for CN=WAC2016,CN=Computers,DC=lab,DC=contoso,DC=com:
    TERMSRV/WAC2016
    TERMSRV/WAC2016.lab.contoso.com
    WSMAN/WAC2016
    WSMAN/WAC2016.lab.contoso.com
    RestrictedKrbHost/WAC2016
    HOST/WAC2016
    RestrictedKrbHost/WAC2016.lab.contoso.com
    HOST/WAC2016.lab.contoso.com
PS C:\Users\SPAdmin> SetSPN -L ContosoLab\SPFarm
Registered ServicePrincipalNames for CN=SPFarm,CN=Users,DC=lab,DC=contoso,DC=com:
    HTTP/SP2016B2.lab.contoso.com
    HTTP/SP2016B2
PS C:\Users\SPAdmin>

```

Update the Analysis Services OLE DB Provider for Office Online Server Preview Only

1. Log on to WAC2016 as SPAdmin, and download the latest version of the Analysis Services OLE DB Provider from the SQL Server 2016 CTP3.1 Feature Pack (ENU\X64\SQL_AS_OLEDB.msi) and run the installer package. Note that the provider version must be CTP3.1 or higher.
2. On the **Welcome** page, click **Next**.
3. On the **License Agreement** page, review the license agreement and, if you agree, select the **I accept the terms in the license agreement** radio button, and then click **Next**.
4. On the **Ready to Install the Program** page, click **Install**. If a **User Account Control** window is displayed, click **Yes**.
5. Following the successful installation, click **Finish**.
6. Copy the following lines into a text file and name it MSOLAP.5.Update.reg.

[Windows Registry Editor Version 5.00](#)

```
[HKEY_CLASSES_ROOT\MSOLAP.5]
@="MSOLAP 13.0 OLE DB Provider"
```

```
[HKEY_CLASSES_ROOT\MSOLAP.5\CLSID]
```

- `@="{FBE7F3BD-C550-490E-B38C-A8661E420070}"`
7. Double-click the MSOLAP.5.Update.reg file and if a **User Account Control** window is displayed, click **Yes**.
 8. In the **Registry Editor** dialog box, informing you that you are about to change registry settings, click **Yes**.
 9. In the **Registry Editor** dialog box, informing you that the changes have been applied successfully, click **OK**.

Verify Workbooks as a Data Source in Excel Online

1. Back on WKSTA2016, logged on as SPUser, and then in the browser, visit the BI Root Site at <http://sp2016b2>.
2. Open the document library, such as <http://sp2016b2/PowerPivot%20Gallery>, where you previously saved the workbook, such as *LinkedWorkbook.xlsx*, which uses another workbook as a data source by means of a BISM connection file.
3. Open the workbook in the browser and try to interact with the data by clicking on a slicer. If a **Query and Refresh Data** dialog box is displayed asking you if you want to refresh the workbook, click **Yes**.
4. Note that you can now interact with the data, which verifies that Workbooks as a Data Source is functioning.

Step 3: Deploying the Management Dashboard Solution


The deployment of the Management Dashboard workbooks is an optional step as this solution does not target regular SharePoint users. SharePoint administrators, on the other hand, will find the Management Dashboard workbooks useful as they provide valuable information about the utilization of server resources and workbook data models in the farm.

Enabling the Management Dashboard solution in SharePoint 2016 requires the configuration of Office S2S authentication so that Excel Online can submit data to the PowerPivot Usage Processing Service. It also requires updating the Management Dashboard workbooks to point them to the right data sources prior to uploading these workbooks to a SharePoint site. Remember that these workbooks contain farm-wide usage information. In production environments, it would be inadvisable to grant regular SharePoint users access to these workbooks, yet these considerations do not apply to this white paper's demo environment.

Configure Office S2S Authentication between Office Online Server and SharePoint 2016

1. Log on to WAC2016 as SPAdmin, and then in **Server Manager**, open the **Tools** menu and select **Internet Information Services (IIS) Manager**.
2. In the **Connections** pane, select the computer object. If an **Internet Information Services (IIS) Manager** dialog box is displayed, click **No**.
3. In the features pane of the server object, double-click on **Server Certificates**.
4. In the **Actions** pane, select **Create Self-Signed Certificate**.
5. Type a meaningful name under **Specify a friendly name for the certificate**, such as *Office S2S Authentication Certificate*, and make sure **Personal** is selected as the certificate store. Click **OK**.
6. Right-click the Windows icon in the taskbar, click **Run**, and type **certlm.msc** and click **OK** to open the **Manage Computer Certificates** tool. If a **User Account Control** window is displayed, click **Yes**.

7. Expand the **Personal** node and then select **Certificates**.
8. Right-click the newly created certificate, select **All Tasks**, and click on **Manage Private Keys**.
9. Click **Add**, click **Locations**, select the local computer, click **OK**, then type **NETWORK SERVICE**, click **Check Names**, and then click **OK** to add the Network Service account to the list of accounts with permissions.
10. Make sure the Network Service account has full permissions to the private keys and click **OK**.
11. Right-click the certificate again, and then, under **All Tasks**, click on **Export**.
12. On the **Welcome to the Certificate Export Wizard** page, click **Next**.
13. On the **Export Private Key** page, make sure **No, do not export the private key** is selected, and then click **Next**.
14. On the **Export File Format** page, select **Base-64 encoded X509 (.CER)**, and then click **Next**.
15. On the **File to Export** page, type a meaningful name, such as **Office S2S Authentication Certificate**, and click **Next**.
16. On the **Completing the Certificate Export Wizard** page, under **File Name**, notice the path where the certificate will be saved, and then click **Finish**.
17. In the **Certificate Export Wizard** dialog box informing you that the export was successful, click **OK**.
18. Right-click the Windows PowerShell icon in the taskbar and then click on **Run as Administrator**. If a **User Account Control** window is displayed, click **Yes**.
19. Copy the exported certificate to the SharePoint server, such as by using the command **copy "C:\Windows\System32\Office S2S Authentication Certificate.cer" \\sp2016b2\c\$**.
20. Register the self-signed certificate with Office Online Server by using the following command:
Set-OfficeWebAppsFarm -S2ScertificateName "Office S2S Authentication Certificate" -Force.




21. Log on to SP2016 as SPAdmin, and then right-click the Windows icon in the taskbar, click **Run**, and type **certlm.msc** and click **OK** to open the Manage Computer Certificates tool. If a **User Account Control** window is displayed, click **Yes**.
22. Expand the **Trusted Root Certification Authorities** node and then select **Certificates**.
23. Right-click on **Certificates**, select **All Tasks**, and click on **Import**.
24. On the **Welcome to the Certificate Import Wizard** page, click **Next**.
25. On the **File to Import** page, click on **Browse** and select the previously exported certificate, such as **C:\Office S2S Authentication Certificate.cer**, and click **Next**.
26. On the **Certificate Store** page, under **Place all certificates in the following store**, make sure **Trusted Root Certification Authorities** is selected, and then click **Next**.
27. On the **Completing the Certificate Import Wizard** page, click **Finish**.
28. In the **Certificate Import Wizard** dialog box informing you that the import was successful, click **OK** and then close the Manage Computer Certificates tool.
29. On the Desktop, right-click the **SharePoint 2016 Management Shell** and click **Run as administrator**. If a **User Account Control** window is displayed, click **Yes**.
30. From a Windows PowerShell command prompt, run the following commands to register the certificate for all the sites under **http://sp2016b2** (change the \$SP_SITE_URL and \$CERT_PATH parameters as necessary):

```
$SP_SITE_URL = "http://sp2016b2"
$CERT_PATH = Get-PfxCertificate "C:\Office S2S Authentication Certificate.cer"

# Register the Excel Online components that authenticate using S2S as trusted token issuers
$wac = New-SPTrustedSecurityTokenIssuer -Name OOS_ECS -Certificate $CERT_PATH -RegisteredIssuerName 67e3df25-268a-4324-a550-0de1c7f97287@bd2372e4-0a11-495c-9541-8377c6def195
$sspm = New-SPTrustedSecurityTokenIssuer -Name OOS_SSPM -Certificate $CERT_PATH -RegisteredIssuerName 67e3df25-268a-4324-a550-0de1c7f97287@ffab2d74-c6ae-4375-819a-8555d49b699a

# Grant full control to the corresponding application identities.
$app_wac = Get-SPAppPrincipal -Site $SP_SITE_URL -NameIdentifier $wac.NameId
$app_sppm = Get-SPAppPrincipal -Site $SP_SITE_URL -NameIdentifier $sspm.NameId
$site=Get-SPSite $SP_SITE_URL
Set-SPAppPrincipalPermission -AppPrincipal $app_wac -Site $site.RootWeb -Scope sitesubscription -Right fullcontrol -EnableAppOnlyPolicy
Set-SPAppPrincipalPermission -AppPrincipal $app_sppm -Site $site.RootWeb -Scope sitesubscription -Right fullcontrol -EnableAppOnlyPolicy

# Restart IIS, and then wait for SharePoint to come back online.
IISReset
```



```

Administrator: SharePoint 2016 Management Shell
PS C:\Users\SPAdmin> $SP_SITE_URL = "http://sp2016b2"
PS C:\Users\SPAdmin> $CERT_PATH = Get-PfxCertificate "C:\Office S2S Authentication Certificate.cer"
PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin> # Register the Excel Online components that authenticate using S2S as trusted token issuers
PS C:\Users\SPAdmin> $wac = New-SPTrustedSecurityTokenIssuer -Name OOS_ECS -Certificate $CERT_PATH -RegisteredIssuerName 67e3df25-268a-4324-a550-0de1c7f97287@bd2372e4-0a11-495c-9541-8377c6def195
PS C:\Users\SPAdmin> $sspm = New-SPTrustedSecurityTokenIssuer -Name OOS_SSPM -Certificate $CERT_PATH -RegisteredIssuerName 67e3df25-268a-4324-a550-0de1c7f97287@ffab2d74-c6ae-4375-819a-8555d49b699a
PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin> # Grant full control to the corresponding application identities.
PS C:\Users\SPAdmin> $app_wac = Get-SPAppPrincipal -Site $SP_SITE_URL -NameIdentifier $wac.NameId
PS C:\Users\SPAdmin> $app_sspm = Get-SPAppPrincipal -Site $SP_SITE_URL -NameIdentifier $sspm.NameId
PS C:\Users\SPAdmin> $site=Get-SPSite $SP_SITE_URL
PS C:\Users\SPAdmin> Set-SPAppPrincipalPermission -AppPrincipal $app_wac -Site $site.RootWeb -Scope sitesubscription -Right fullcontrol -EnableAppOnlyPolicy
PS C:\Users\SPAdmin> Set-SPAppPrincipalPermission -AppPrincipal $app_sspm -Site $site.RootWeb -Scope sitesubscription -Right fullcontrol -EnableAppOnlyPolicy
PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin>
PS C:\Users\SPAdmin> # Restart IIS, and then wait for SharePoint to come back online.
PS C:\Users\SPAdmin> IISReset

Attempting stop...
Internet services successfully stopped
Attempting start...
Internet services successfully restarted

```

31. Back on WAC2016, logged on as SPAdmin, in the browser, visit the BI Root Site at <http://sp2016b2> to verify that the SharePoint farm is back online and available. Then right-click the **Windows PowerShell** icon in the taskbar and click **Run as Administrator**. If a **User Account Control** window is displayed, click **Yes**.
32. Type **IISReset** and press Enter to restart Office Online Server.
33. On WKSTA2016, log on as SPUser, and then in the browser, visit the BI Root Site at <http://sp2016b2>.
34. Open a document library, such as <http://sp2016b2/PowerPivot%20Gallery>, and then open a workbook in the browser.
35. Interact with the data by clicking on a slicer. If a **Query and Refresh Data** dialog box is displayed asking you if you want to refresh the workbook, click **Yes**. Explore the data some more to generate activity.
36. Back on SP2016B2, logged on as SPAdmin, open the SharePoint Logs folder in Windows Explorer (by default C:\Program Files\Common Files\Microsoft Shared\Web Server Extensions\16\LOGS\). Check that there are subfolders such as AnalysisServicesConnections and AnalysisServicesLoads, and that these folders contain one or multiple .usage files.
37. On the Desktop, open **SharePoint 2016 Central Administration**. If a **User Account Control** window is displayed, click **Yes**.
38. In the left pane, click on **Monitoring**, and then under **Timer Jobs**, click on **Review job definitions**.
39. Scroll through the pages until you find the **PowerPivot Health Statistics Collector Timer Job**. Click on this timer job to display the corresponding **Edit Timer Job** page. Click **Run Now**.

40. Log on to SQLDB2016 as SQLAdmin and start SQL Server Management Studio.
 41. Connect to the **SQLDB2016\SHAREPOINT** instance of the Database Engine, expand **Databases**, expand the database of the PowerPivot service application, which typically starts with **DefaultPowerPivotServiceApplicationDB...**, expand **Tables**, and then right-click on the **Usage.Documents** table, and click **Select Top 1000 Rows**.
 42. In the **Results**, verify that you have at least 1 entry corresponding to the workbook you just interacted with on WKSTA2016.

The screenshot shows the SSMS interface with the following details:

- Title Bar:** SQLQuery3.sql - SQLDB2016\SHAREPOINT.DefaultPowerPivotServiceApplicationDB-afaa4e02-3d54-4d0d-add0-62a98ee91725 (contosolab\SQLAdmin (52)) - Microsoft SQL Server Management Studio
- Object Explorer:** Shows the database structure for SQLDB2016\SHAREPOINT, including Databases, Tables, Views, and Security.
- SQL Query Editor:** Contains a T-SQL script to select top 1000 SPFileID records from the Usage.Document table.
- Results Window:** Displays the execution results with two rows of data.
- Status Bar:** Shows "Query executed successfully" and "2 rows".

SPSiteID	Url	SiteID
3-55A9-4A4D-A303-06FE43FC08E9	http://sp2016b2/Shared Documents/Olympics.xlsx	NUL
4-5F1A-4FB3-88ED-7075570EBB8E	http://sp2016b2/PowerPivot Gallery/Olympics.xlsx	NUL

Update and Publish the Management Dashboard Workbooks in SharePoint 2016

1. If you are logged on to WKSTA2016 as SPUser, log off, and then log on again as SPAdmin.
 2. Start Internet Explorer and open the Central Administration web site.
 3. On the home page, under **General Application Settings**, click on **PowerPivot Management Dashboard**.
 4. Click on the workbook link **PowerPivot Management Data**, and then in the **Open Document** dialog box, select **Edit**, and click **OK**.
 5. If Excel displays a read-only warning, click on **Edit Workbook**.
 6. If Excel displays a security warning, click on **Enable Content**, and if a **Security Warning** dialog box is displayed, click **Yes**.
 7. On the ribbon, click on **PowerPivot** (if the **PowerPivot** tab is not displayed, click on **File**, **Options**, **Add-ins**, and then under **Manage** select **COM Add-ins** and click **Go**, and then select **Microsoft Power Pivot for Excel** and click **OK**).

8. Click on **Manage** and then in the **PowerPivot for Excel** window, click on **Existing Connections** (if **Existing Connections** is not displayed on the ribbon, then click on **Get External Data** and then on **Existing Connections**).
9. Select the connection called **PowerPivotConnectionString** and click **Edit**.
10. In the **Edit Connection** dialog box, under **Server name**, type the name of the database instance, such as **SQLDB2016\SHAREPOINT**.
11. Under Database name, select the database of the PowerPivot service application, which typically starts with **DefaultPowerPivotServiceApplicationDB...**
12. Click **Save** and then **Close**.
13. Switch to the **Date** table, and then on the **Design** ribbon, click on **Table Properties**.
14. In the top right corner, under **Switch to**, select **Query Editor**, and then replace the entire **Sql statement** with the following query: **SELECT * FROM [Usage].[vDate]**
15. Click **Save**, and then on the **Home** tab, click on the triangle under **Refresh**, and then click on **Refresh All**.


The screenshot shows the Microsoft Excel interface with the title bar "Power Pivot for Excel - PowerPivot Management Data.xlsx". The ribbon has tabs like File, Home, Design, Advanced, etc. The Home tab is selected. On the left, there's a Power Pivot ribbon tab with options like Manage, Measures, KPIs, Add to Data Model, and Data Sources. The main worksheet contains a table with columns: Date, Year, Month, Week, Day, DayOfWeek, MonthName_English, MonthName_German, and MonthName_French. The table data starts from row 1 with values like 1/1/2009, 2009, 1, 1, 1, 5, January, Januar, janvier. A modal dialog box titled "Data Refresh" is open, showing "Data Refresh Progress" with a success message: "Success" (12 Total, 0 Cancelled, 12 Success, 0 Error). It lists details for various work items: DataSources, Documents, Health, Servers, Time, Users, Connections, Date, DocumentVersions, Loads, Requests, and Unloads, all marked as successful. At the bottom of the dialog are "Stop Refresh" and "Close" buttons.

16. Click **Close** and then close the PowerPivot window.
17. In the Excel client window, click on **File** and then click on **Save As**. Save this workbook in a document library of your choice, such as **[http://sp2016b2/Shared Documents](http://sp2016b2/Shared%20Documents)**, and then close the file Excel.

Note that it is best to save the source workbook for the PowerPivot Management Dashboard in a protected location because this workbook contains farm-wide usage data that should not be

disclosed to every SharePoint site user. In a lab environment with no special security requirements, it is sufficient to save this workbook in any standard document library.

18. Switch back to Central Administration, and then on the **PowerPivot Management Dashboard** page, click on **Server Health**. In the **Open Document** dialog box, select **Edit**, and click **OK**.
19. If Excel displays a read-only warning, click on **Edit Workbook**.
20. If Excel displays a security warning, click on **Enable Content**, and if a **Security Warning dialog box** is displayed, click **Yes**.
21. On the ribbon, switch to the **Data** tab, and then click on **Get External Data**, click on **From Other Sources**, and then click on **From Analysis Services**.
22. Under **Server name**, type the URL to the source workbook you just uploaded to a document library, such as [http://sp2016b2/Shared Documents/PowerPivot Management Data.xlsx](http://sp2016b2/Shared%20Documents/PowerPivot%20Management%20Data.xlsx).
23. Click **Next** and then click **Finish**, and then in the **Import Data** dialog box, select the option **Only Create Connection**, and click **OK**.
24. On the **Data** tab, click on **Connections**.
25. In the **Workbook Connections** dialog box, select the connection you just created (the connection that is *not* called **Data**), and click on **Properties**.
26. Switch to the **Definition** tab and copy the entire **Connection string** into the clipboard.
27. Click **Cancel** and then with the new connection still selected in the **Workbook Connections** dialog box, click **Remove** to delete this connection. Click **OK** to confirm the deletion.
28. Select the **Data** connection and click on **Properties**.
29. In the **Connection Properties** dialog box, switch to the **Definition** tab and then replace the entire connection string with the connection string you just copied into the clipboard.
30. In the **Command text** box, delete the **Sandbox** command and type in **Model**.
31. Click **OK** and then click **Close**.
32. In the Excel client window, click on **File** and then click on **Save As**. Save this workbook in a document library of your choice, such as [http://sp2016b2/PowerPivot Gallery](http://sp2016b2/PowerPivot%20Gallery), and then close the Excel file.
33. Switch back to Central Administration, and then on the **PowerPivot Management Dashboard** page click on **Workbook Activity**. Repeat the steps you just performed for the **Server Health** workbook. If you still have the connection string in the clipboard, you can skip the creation of a temporary connection to the uploaded source workbook with the PowerPivot Management Data.
34. Switch back to the browser, open the document library where you uploaded the source workbook, such as [http://sp2016b2/Shared Documents](http://sp2016b2/Shared%20Documents), and configure a daily refresh schedule as explained earlier in this document in order to keep the PowerPivot Management Dashboard data updated on a regular basis.



Adding Self-Service Reporting

The deployment of SharePoint-integrated Reporting Services adds the remaining capabilities of the SQL Server BI stack to SharePoint 2016. In the demo environment, SharePoint users can then create paginated SSRS and Power View reports based on workbook data models. Subscription delivery of reports through email and data alerting are not available because the demo environment does not include email connectivity. Refer to the topic [Configure E-mail for a Reporting Services Service Application](#) at <https://msdn.microsoft.com/en-us/library/hh231673.aspx> if you want to enable this capability after adding a messaging server to the demo environment.

Step 1: Deploying SSRS in SharePoint integrated mode

While the deployment steps of installing the SSRS binaries and configuring a service application are very similar to previous SQL Server releases, keep in mind that only SQL Server 2016 Reporting Services is supported in SharePoint 2016. Remember also to assign the Custom server role to the SharePoint server where you plan to run the Reporting Services service application. The deployment succeeds even if you skip this step, but during the next SharePoint maintenance window, MinRole will stop the SSRS service because it detects that SSRS in SharePoint-integrated mode does not indicate support for any of the other SharePoint server roles. The SSRS service application only supports the Custom role.

Apply the Custom Server Role to SharePoint 2016


1. Log on to SP2016B2 as SPAdmin, and then on the Desktop, right-click the **SharePoint 2016 Management Shell** and click **Run as administrator**. If a **User Account Control** window is displayed, click **Yes**.

- From the Window PowerShell command prompt, run the following command (make sure you specify the correct name for your SharePoint server):

```
Set-SPServer SP2016B2 -Role Custom
```

- Wait until the server role conversion timer job has successfully applied the changes. Use the following command to verify the server's assigned role:

```
Get-SPServer SP2016B2
```




```
Administrator: SharePoint 2016 Management Shell
PS C:\Users\SPAdmin> Set-SPServer SP2016B2 -Role Custom
A server role conversion timer job has been successfully scheduled for server 'SP2016B2'.
You can run 'Get-SPTimerJob db34e87b-c781-45b4-83d2-159a7a4b4c05' to query its status.
PS C:\Users\SPAdmin> Get-SPServer SP2016B2
Address          Role          Status
SP2016B2        SingleServerFarm  Online

PS C:\Users\SPAdmin> Get-SPServer SP2016B2
Address          Role          Status
SP2016B2        Custom        Online

PS C:\Users\SPAdmin> _
```

Install SSRS Add-in and Service in SharePoint-integrated Mode


- Logged on to SP2016B2 as SPAdmin, start **Setup.exe** from the SQL Server 2016 CTP3.1 installation media. Click **Yes** if a **User Account Control** window is displayed.
- In the **SQL Server Installation Center**, click **Installation** in the left-hand navigation area, and then click **New SQL Server stand-alone installation or add features to an existing installation**.
- On the **Product Key** page, select an option to indicate whether you are installing a free edition of SQL Server, or a production version of the product that has a PID key. For a demo lab, accept the default **Specify a free edition** selection **Evaluation**.
- On the **License Terms** page, review the license agreement and, if you agree, select the **I accept the license terms** check box, and then click **Next**.
- On the **Product Updates** page, accept the default setting and click **Next**.
- On the **Install Rule** page, verify that the rules are passed. Notice any warnings, such as for the **Windows Firewall** rule. Click **Next** to continue.
- On the **Setup Role** page, select **SQL Server Feature Installation**, and then click **Next**.
- On the **Feature Selection** page, select **Reporting Services - SharePoint** and **Reporting Services Add-in for SharePoint Products**, and then click **Next**.



9. On the **Reporting Services Configuration** page, accept the default option **Install only**, and click **Next**.
10. On the **Ready to Install** page, click **Install**.
11. The **Installation Progress** page provides status so that you can monitor installation progress as Setup continues. On the **Complete** page, click **Close**, and then close **SQL Server Installation Center**.

Configure an SSRS service application

1. Logged on to SP2016B2 as SPAdmin, on the Desktop, open **SharePoint 2016 Central Administration**. If a **User Account Control** window is displayed, click **Yes**.
2. On the Central Administration home page, under **Application Management**, click on **Manage service applications**.
3. Click **New** and select **SQL Server Reporting Services Service Application**.
4. On the **Create SQL Server Reporting Services Service Application** page, under **Name**, type a unique name for the service application, such as **Reporting Services Service Application**.
5. Under **Application Pool**, select **Use existing application pool**, and from the corresponding list box, select **SharePoint Web Services Default**.
6. In the **Database server** textbox, provide the name of your database server instance, such as **SQLDB2016\SHAREPOINT**.
7. Under **Web Application Association**, select the check box **SharePoint - 80 (<http://sp2016b2/>)**.
8. Click **OK** to create the Reporting Services service application.
9. On the **Create SQL Server Reporting Services Service Application** page, informing you that the service application has been successfully created, click **OK**.




Step 2: Verifying SSRS in SharePoint-integrated Mode

In the demo environment, SSRS and Power View can only consume workbook data models because Tabular or Multidimensional Analysis Services server instances are not available. In production environments, make sure you also test against these types of SSAS instances. Adding Tabular or Multidimensional instances to the demo environment is beyond the scope of this white paper.

Create a standalone Power View Report on top of a BISM connection


1. Log on to WKSTA2016 as SPUser, and then in the browser, visit the BI Root Site at <http://sp2016b2>.
2. Open the **Data Connection Library** and then click on the BISM connection you created earlier.
3. Note that with SSRS in SharePoint-integrated mode installed in the farm, the BISM connection no longer launches the Excel by default. The installation changed the default behavior to launch Power View instead.
4. Create a report, such as by selecting **Country/Region** under **CountryRegions** and **Medal Count** under **Medals**.
5. Under **CountryRegions** drag **Continent** to the **TILE BY** field.
6. In the ribbon, click on **Column** to change the data display and resize the tiles and chart to cover the full report canvas.

7. Click **File** and select **Save**, and then in the **Save As** dialog box, provide a meaningful name, and click **Save**.
8. Close the browser when you are finished creating the report.



Create a standalone Power View Report on top of a workbook


1. Logged on to WKSTA2016 as SPUser, open the browser and visit the BI Root Site at <http://sp2016b2>.
2. Open the **PowerPivot Gallery** and then click on the **Create Power View Report** button, which is displayed in the top right corner of every workbook that contains a data model.
3. In the Power View window that opens, create and save another report similar to the one created in the previous procedure.



Create a Power View Report embedded in a workbook

1. Logged on to WKSTA2016 as SPUser, open the browser and visit the BI Root Site at <http://sp2016b2>.
2. Open the **PowerPivot Gallery** and then open the workbook that contains a data model.
3. In Excel Online, click on **Edit Workbook**, and then select **Edit in Excel**.
4. If Excel displays a read-only warning, click on **Edit Workbook**.
5. If Excel displays a security warning, click on **Enable Content**, and if a **Security Warning dialog box** is displayed, click **Yes**.
6. Click on **File**, select **Options**, and then select **Add-ins**.
7. Under **Manage**, select **COM Add-ins** and click **Go**.
8. In the **COM Add-ins** dialog box, select **Microsoft Power View for Excel** and click **OK**.
9. Switch to the **Data** tab, click **Existing Connections** (click on **Get External Data** if this option is not immediately displayed), switch to the **Tables** tab, and then select the data model under **This Workbook Data Model**, and click **Open**.
10. In the **Import Data** dialog box, select **Power View Report**, and click **OK**.
11. Create a Power View Report similar to the reports in the previous sections. The steps in the Power View user interface are essentially identical. The difference is that the report is stored directly in the workbook.
12. Save your changes and close Excel.

13. Open the workbook in the browser. Note that the Power View report is displayed within the Excel Online rendering context.



Conclusion

Deploying the full SQL Server BI stack for SharePoint 2016 is a significant undertaking, best tackled in multiple stages using a structured approach. Following the installation of the necessary Windows and AD DS infrastructure, the first stage revolves around establishing a basic BI environment without advanced PowerPivot or SSRS/Power View capabilities. It is imperative to configure SharePoint Server, Office Online Server, and Analysis Services correctly so that users can open workbooks in the browser and Excel Online can load and query data models as users interact with the workbook data.

Having established that the basic BI environment works reliably, additional BI capabilities can be added. A good next step is to deploy the PowerPivot add-in for SharePoint 2016. PowerPivot adds important features, such as the PowerPivot Gallery, Scheduled Data Refresh, and Workbooks as a Data Source. The add-in also adds support for BISM connection files to the SharePoint farm and gives SharePoint administrators the option to deploy the PowerPivot Management Dashboard solution.

A fully BI-enabled SharePoint 2016 farm also includes SharePoint-integrated Reporting Services so that users can create and share SSRS and Power View reports based on workbook data models as well as

Tabular or Multidimensional databases. SharePoint-integrated Reporting Services also adds subscription delivery of reports through email and data alerting to the SharePoint 2016 environment.

While the PowerPivot and Power View feature set is largely the same as in previous releases, there are important improvements and enhancements in SharePoint Server 2016, Office Online Server, and in the SQL Server 2016 BI stack, namely in the areas of usability, performance, reliability, and security. Excel Online now supports workbook editing and BI scenarios in a unified deployment, Scheduled Data Refresh support for Excel workbooks that utilize Power Query connections is going to be available with the final releases, and workbook data models load faster and client queries return quicker than with previous releases thanks to the performance optimizations in SQL Server 2016 Analysis Services. SQL Server 2016 Reporting Services, to complete the list, also offers noteworthy improvements with new chart types, HTML5 rendering of paginated reports, cross-browser printing, export to Microsoft PowerPivot, and a new Report Builder. In short, there are many good reasons to deploy or upgrade to SharePoint Server 2016, Office Online Server, and the SQL Server 2016 BI stack.

See Also

- SQL Server Web site <http://www.microsoft.com/sqlserver/>
 - SQL Server TechCenter <http://technet.microsoft.com/en-us/sqlserver/>
 - SQL Server DevCenter <http://msdn.microsoft.com/en-us/sqlserver/>
-
- AD DS Deployment Cmdlets in Windows PowerShell [https://technet.microsoft.com/en-us/library/hh974720\(v=wps.630\).aspx](https://technet.microsoft.com/en-us/library/hh974720(v=wps.630).aspx)
 - Install SQL Server 2016 from the Installation Wizard (Setup) <https://msdn.microsoft.com/en-us/library/ms143219.aspx>
 - Configure the Windows Firewall to Allow SQL Server Access <https://msdn.microsoft.com/en-us/library/cc646023.aspx>
 - What's new in SharePoint Server 2016 Installation and Deployment
<http://blogs.technet.com/b/wbaer/archive/2015/05/12/what-s-new-in-sharepoint-server-2016-installation-and-deployment.aspx>
 - Deploy Office Online Server Preview [https://technet.microsoft.com/en-us/library/jj219455\(v=office.16\).aspx](https://technet.microsoft.com/en-us/library/jj219455(v=office.16).aspx)
 - Configure server-to-server authentication between Office Online Server Preview and SharePoint Server 2016 Beta 2 [https://technet.microsoft.com/EN-US/library/mt346470\(v=office.16\).aspx](https://technet.microsoft.com/EN-US/library/mt346470(v=office.16).aspx)

Did this paper help you? Please give us your feedback. Tell us on a scale of 1 (poor) to 5 (excellent), how would you rate this paper and why have you given it this rating? For example:

- Are you rating it high due to having good examples, excellent screen shots, clear writing, or another reason?

- Are you rating it low due to poor examples, fuzzy screen shots, or unclear writing?

This feedback will help us improve the quality of white papers we release.

[Send feedback.](#)