Playground Modular Global

ref. 0956.8

ASSEMBLY INSTRUCTIONS

Assembly video on YouTube:
youtu.be/Mpiky4LYkB0



Product size: **4,10 × 3,14 × 2,22 m**
Four-wall tower with a floor, curved slide, climber and spiral slide
Modular snap-fit system, no screws: takes other Playground Modular parts
Age: 3 years and up
Assembly by an adult; a second person makes fitting the walls easier.
7 steps · keep this manual for future reference.

BEFORE YOU START

Read carefully

Caution

Give this toy to the child only after it has been **assembled by an adult**, and always use it under **adult supervision**.

Assembly rules

- Assemble in this order: **a blue wall** and **a yellow wall**, the **other yellow wall**, the **floor**, the **other blue wall** and finally the **slide**, the **climber** and the **spiral slide**.
- Every joint must go fully in: if the part sits crooked, lift it and fit it again.
- Assemble on level ground: on uneven ground the joints do not line up.

Tools

- No tools needed: every part snaps together

This playground has no screws.

PARTS LIST

Playground Modular Global parts



LARGE BLUE WALL 2×
No. 1 · ref. 956501



LARGE YELLOW WALL 2×
No. 2 · ref. 956502



FLOOR 1×
No. 3 · ref. 956508



CURVED SLIDE 1×
No. 4 · ref. 957606



CLIMBER 1×
No. 5 · ref. 957605



SPIRAL SLIDE 1×
No. 6 · ref. 956509

PRODUCT ASSEMBLY

Step by step

In each step, the arrows show where the part goes, the **black numbers** give the order and the **yellow letters** point to the details explained under the picture.

1 STEP 1 OF 7
Blue wall and yellow wall



A Large blue wall

B Large yellow wall



Joint between the walls

A The yellow wall's tabs go into the blue wall's slots

Set out the 4 walls: **2 large blue walls** and **2 large yellow walls**.

Stand a **blue wall** up and bring a **yellow wall** against it, forming a corner.

Line up the tabs on the side of the yellow wall with the slots of the blue wall and lower the yellow wall until the tabs are fully in.

CAUTION
The walls are 2.22 m high: with a second person holding them, fitting is easier and the wall will not tip over.

PARTS FOR THIS STEP



1× Large blue wall ref. 956501




1× Large yellow wall ref. 956502



How it looks at the end of step 1

STEP 2 OF 7

2 Other yellow wall




A Large yellow wall

Fit the other **yellow wall** on the other side of the blue wall the same way, parallel to the first one.

PARTS FOR THIS STEP




1× Large yellow wall
ref. 956502




How it looks at the end of step 2

STEP 3 OF 7

3 Platform



A Platform



Floor hooks in the wall slots

A The floor's hooks go into the yellow wall's slots

Fit the **floor** between the two yellow walls, from the side that is still open.

The hooks at the ends of the floor go into the slots of the yellow walls; the floor sits level, at the height of the wall openings.

PARTS FOR THIS STEP



1× Platform
ref. 956508



How it looks at the end of step 3

STEP 4 OF 7

4 Other blue wall



A Large blue wall

Close the tower with the other **blue wall**: the tabs of both yellow walls go into its slots.

Check that the 4 walls are lined up at the top and that the floor is level.

PARTS FOR THIS STEP



1× Large blue wall
ref. 956501



How it looks at the end of step 4

STEP 5 OF 7

5 Curved slide



A Curved slide



Slide end in the wall opening

A The top end goes into the wall opening and rests on the floor

The **curved slide** fits in the opening of one of the yellow walls, at floor height.

With the slide tilted, fit one side of its top end into the wall opening.

Press the other side until it snaps in: the end rests on the floor and the slide sits straight.

PARTS FOR THIS STEP




1× Curved slide
ref. 957606




How it looks at the end of step 5

STEP 6 OF 7

6 Climber



A Climber



Climber end in the wall opening

A The top end goes into the wall opening and rests on the floor

Repeat the fitting with the **climber**, in the opening of one of the blue walls: tilt it, fit one side and press the other in.

PARTS FOR THIS STEP



1× Climber
ref. 957605




How it looks at the end of step 6

STEP 7 OF 7

7 Spiral slide



A Spiral slide



Spiral slide end in the wall opening

A The top end goes into the wall opening and rests on the floor

Repeat with the **spiral slide**, in the opening of the other blue wall: tilt it, fit one side and press the other in.

> The snap-fit system is modular: other Playground Modular parts can be added in the wall openings.

PARTS FOR THIS STEP

1× Spiral slide
ref. 956509



How it looks at the end of step 7


FASTENING DETAILS

How each part is held



Walls

The tabs on the sides of the yellow walls go into the slots of the blue walls. Lower the wall until the joint is fully in.



Platform

The hooks at the ends of the floor go into the slots of the yellow walls.



Slide, climber and spiral slide

The top end goes into the wall opening, at floor height: tilt the part, fit one side and press the other in.




Assembly complete

Check the product visually, making sure every part is fitted and firmly fastened. **Only then let children use it.**

Maximum weight 100 kg per platform. Check that the 4 walls are fully fitted, the floor is level and the slide, the climber and the spiral slide are firm in their openings.

INSTALLATION DETAILS

Location and safety area



Area reserved for installation and slide landing (top view): 7.58 × 7.15 m. Product size: 4.10 × 3.14 × 2.22 m.

To keep users safe, minimum spaces and free distances must be respected.

Circulation area: at least 1.20 m wide around the equipment, so users can run freely; at least 1.50 m where the path changes direction, so strollers and wheelchairs can get in and turn.

Fall space: neighboring static equipment with overlapping fall spaces must be at least 1.50 m apart for a fall height of up to 600 mm, and 2.50 m for higher falls. Maximum fall height of this product: **930 mm**.

Slide landing area: at least 1000 mm from the sides of the run-out section and 2000 mm (type 01 run-out) or 1000 mm (type 02 run-out) from the end of the run-out section.

Ground: an even, continuous, stable surface that is non-slip in any weather, with no obstacles and a cross slope of no more than 2%. Use on grass, sand, carpet or another soft, level surface.

Location: first check for chemicals and loose material (rubble, sharp objects). Choose an airy place with morning sun, sheltered from drafts; do not install it in basements or garages. Never use it near stairs, roads, swimming pools, water or slippery places. If the area is fenced, the gates must open outwards and be at least 1 m wide.

Footprint: the assembled playground takes up about 4.10 × 3.14 m of ground; the free areas above apply all around it.

To avoid accidents, the child should wear shoes. This product is not intended for commercial use.

INSPECTION AND MAINTENANCE

Keep the playground safe

Visual inspection — daily

- Cleanliness
- Free distances between the ground and the equipment
- Ground surface finish and exposed foundations
- Sharp edges and missing components
- Excessive wear and structural integrity

Operational inspection — every 1 to 3 months

Pay special attention to the structural integrity of the product, besides the items of the visual inspection.

Main inspection — yearly

- Structure: bending, deformation and cracks
- Finish: cracks, chips, broken or open joints
- Missing, bent, broken, loose or worn parts
- Edges, pinch points, access points and protective surfaces
- Walls fully fitted, floor level and slide, climber and spiral slide firm in their openings

Maintenance

- Tighten the joining parts and clean (do not use paints, solvents or other chemicals)
- Keep the free spaces and drain holes clean
- Replace fasteners and faulty or worn parts

As per NBR 16071-7:2012. Any change that affects safety only after consulting the manufacturer.

XALINGO S/A INDÚSTRIA E COMÉRCIO
BR 471, km 147 – Santa Cruz do Sul – RS – Brasil – CEP 96835-642
CNPJ 95.425.534/0001-76

SAC
(51) 3719-9800 · sac@xalingo.com.br
www.xalingo.com.br

Playground Modular Global · ref. 0956.8
Keep this manual for future reference.