Size of diffused data

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s



Spatial efficiency (size of txs on ledger / size of non-tx persisted data)

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s



Time for transaction to reach an EB

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s

Δ_hdr = 1000 ms



Δ_hdr = 1500 ms



Δ_hdr = 2000 ms



Time for transaction to reach the ledger

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s

Δ_hdr = 1000 ms



Δ_hdr = 1500 ms



Δ_hdr = 2000 ms



Number of EB references (0 = not used, 2+ = duplicated)

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s



Transactions reaching the ledger

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s

Δ_hdr = 1000 ms



Δ_hdr = 1500 ms



Δ_hdr = 2000 ms



Network

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s




1-Second Peak CPU
topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s
L_diff = 1 slots
L_diff = 3 slots
L_diff = 5 slots
L_diff = 7 slots
L_vote = 1 slots
L_vote = 2 slots
L_vote = 3 slots
L_vote = 4 slots
1-Second peak CPU [vCPU·s/s]
0.0
0.3
0.6
0.9
1.2
Δ_hdr = 1000 ms
Δ_hdr = 1500 ms
Δ_hdr = 2000 ms

Mean CPU

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s



Arrival delay for EB

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s

Δ_hdr = 1000 ms



Δ_hdr = 1500 ms



Δ_hdr = 2000 ms



Arrival delay for RB

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s

Δ_hdr = 1000 ms



Δ_hdr = 1500 ms



Δ_hdr = 2000 ms



Arrival delay for TX

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s







Arrival delay for VT

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s

Δ_hdr = 1000 ms



Δ_hdr = 1500 ms



Δ_hdr = 2000 ms



Mean nodal ingress

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s

Δ_hdr = 1000 ms



Δ_hdr = 1500 ms



Δ_hdr = 2000 ms



Peak nodal ingress

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s







Peak CPU load among all nodes

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s

Δ_hdr = 1000 ms



Δ_hdr = 1500 ms



Δ_hdr = 2000 ms



Mean CPU load among all nodes

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s

Δ_hdr = 1000 ms



Δ_hdr = 1500 ms



Δ_hdr = 2000 ms



Size of transactions in EBs

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s







Size of transactions in RBs

topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s








Disposition of transactions
topology-v2, 10 Mb/s, 4 vCPU/node, 12 MB/EB, 1500 B/Tx, 0.200 TxMB/s
L_diff = 1 slots
L_diff = 3 slots
L_diff = 5 slots
L_diff = 7 slots
L_vote = 1 slots
L_vote = 2 slots
L_vote = 3 slots
L_vote = 4 slots
Total size of transactions [MB]
0
250
500
750
1000
Block
RB
EB later not certified
EB later certified
EB now certified
Δ_hdr = 1000 ms
Δ_hdr = 1500 ms
Δ_hdr = 2000 ms
VariedZ