
InsightSolver API client

Release 0.1.21

Noé Aubin-Cadot

May 08, 2025

CONTENTS:

1	Introduction	1
1.1	About InsightSolver	1
1.2	Access Options	1
1.3	The InsightSolver API client	1
1.4	Who Should Use This Documentation?	1
1.5	Accessing the API	1
2	Installation	2
2.1	Prerequisites	2
2.2	Installation Steps	2
2.3	Testing the Installation	3
3	Usage	4
3.1	Quick Start Example	4
3.2	Advanced usage	6
4	Modules	15
4.1	insightsolver module	15
4.2	api_utilities module	15
4.3	visualization module	25
5	Help	30
5.1	1. Technical Documentation	30
5.2	2. Frequently Asked Questions (FAQ)	30
5.3	3. GitHub Issues	30
5.4	4. Contact Support	30
6	License	31
	Python Module Index	32
	Index	33

INTRODUCTION

Welcome to the technical documentation for the **InsightSolver API Client**.

1.1 About InsightSolver

InsightSolver is a SaaS (Software as a Service) solution designed for advanced rule mining and data insights. Powered by a centralized rule-mining engine, it enables organizations to uncover hidden patterns and generate actionable insights for data-driven decision-making.

1.2 Access Options

InsightSolver can be accessed through the following options:

- The **API Client**, designed for seamless integration with Python applications and data workflows.
- The **Web App** (not yet available), which will provide an intuitive and interactive interface for exploring rule-mining results, visualization, and analysis.

This documentation specifically covers the API Client. The Web App will have its own documentation once available.

1.3 The InsightSolver API client

The InsightSolver API Client offers a Python-based interface for direct interaction with our rule-mining engine. Designed for data engineers, scientists, and developers, this client integrates InsightSolver's functionalities into custom workflows, applications, and automated pipelines. The API client allows users to configure rule-mining parameters, send encrypted data to the server and retrieve results efficiently.

1.4 Who Should Use This Documentation?

This documentation is for:

- Developers integrating our rule-mining API.
- Engineers needing setup guides and technical references.
- Users looking for examples of effective API use.

1.5 Accessing the API

The API client requires a valid `.json` service key. This key authenticates your identity and ensures secure communication with the InsightSolver API server. If you do not yet have a service key, please contact support@insightsolver.com for assistance.

INSTALLATION

This guide provides instructions to install and set up the InsightSolver API client on your local machine.

2.1 Prerequisites

- **Python 3.9 or higher:** Ensure Python is installed on your system. You can check your Python version with:

```
python --version
```

- **pip:** Python's package installer, which is typically included with Python 3 installations.

2.2 Installation Steps

You can install the InsightSolver API client in different ways, depending on your setup:

A. Install directly using pip (100% CLI)

If you have git installed and don't need a local copy of the repository, run:

```
pip install git+https://github.com/insightsolver/insightsolver.git
```

B. Clone the repository and install locally (100% CLI)

If you have git installed and want to also keep a local copy of the repository, run:

```
git clone https://github.com/insightsolver/insightsolver.git
cd insightsolver
pip install .
```

C. Download via browser and install (50% GUI + 50% CLI)

If you don't have git installed, follow these steps:

- Open a browser and go to <https://github.com/insightsolver/insightsolver>.
- Click on the green button <> Code v and select Download ZIP.
- Extract the ZIP file to a folder on your machine.
- Open a terminal and navigate to the extracted folder using:

```
cd path/to/unzipped-folder
```

- Then install the package with:

```
pip install .
```

2.3 Testing the Installation

To verify that the installation was successful, you can run a quick test in Python to ensure all dependencies are correctly installed and functioning.

1. Open a terminal and start a Python interpreter by typing:

```
python
```

2. Once inside the Python shell, try importing the `InsightSolver` class with the following command:

```
from insightsolver import InsightSolver
```

3. If the installation was successful, there should be no errors, and the Python shell should return to the prompt. If you encounter an *ImportError*, ensure that you have installed the package in the correct environment.
4. Exit the Python shell by typing:

```
quit()
```

If you encounter any errors or need assistance, please refer to the [Help section](#).

The following sections provide examples on how to use the InsightSolver API client.

3.1 Quick Start Example

This section provides a quick example of how to use the InsightSolver API client. Before running the example script, please ensure that:

1. You have completed the steps in the *Installation Guide*.
2. You have obtained a valid service key.

The following example demonstrates how to the basic usage of the InsightSolver API client, showing how to initialize the solver and generate insights using the InsightSolver API.

```
# Import some data
import pandas as pd
df = pd.read_csv('kaggle_titanic_train.csv') # Dataset here: https://www.kaggle.com/competitions/titanic/data

# Specify the name of the target variable
target_name = 'Survived' # We are interested in whether the passengers survived or not

# Specify the target goal
target_goal = 1 # We are searching rules that describe survivors

# Choose how features should be interpreted
columns_types = {
    'Survived' : 'binary',
    'Pclass'   : 'continuous', # Could be 'multiclass' (i.e. unordered) or
    ↪ 'continuous' (i.e. ordered)
    'Name'     : 'ignore',
    'Sex'      : 'binary',
    'Age'      : 'continuous',
    'SibSp'    : 'continuous', # Could be 'multiclass' (i.e. unordered) or
    ↪ 'continuous' (i.e. ordered)
    'Parch'    : 'continuous', # Could be 'multiclass' (i.e. unordered) or
    ↪ 'continuous' (i.e. ordered)
    'Ticket'   : 'ignore',
    'Fare'     : 'continuous',
    'Cabin'    : 'ignore',
    'Embarked' : 'multiclass',
```

(continues on next page)

(continued from previous page)

```

    }

# Import the class InsightSolver from the module insightsolver
from insightsolver import InsightSolver

# Create an instance of the class InsightSolver
solver = InsightSolver(
    df          = df,          # A dataset
    target_name  = target_name, # Name of the target variable
    target_goal  = target_goal, # Target goal
    columns_types = columns_types, # Columns types
)

# Specify the service key
service_key = 'name_of_your_service_key.json'

# Fit the solver
solver.fit(
    service_key = service_key, # Use your API service key here
)

# Print the rule mining results
solver.print(mode='dense')
"""
              contribution variable          rule      nans
i p_value coverage lift
0 2e-67   19.1%   2.47
      86.2%   Sex      female
      13.8%  Pclass    [1, 2]
1 6e-13    6.3%   2.19
      52.7%   Age      [0.42, 15.0] exclude
      47.3%  SibSp     [0, 2]
2 3e-20   12.2%   2.06
      81.4%  Pclass    [1, 1]
      11.3%   Fare    [7.925, 512.3292]
      7.3%   Age      [4.0, 42.0] exclude
"""

```

In this specific example, the InsightSolver API gives us three rules in which we find more survivors of the Titanic:

- (i=0) : **Women in 1st or 2nd class.** This group covers 19.1% of the passengers and has a survival gain of +147% compared to the population of the Titanic.
- (i=1) : **Children (which we know the age) with not too many siblings.** This group covers 6.3% of the passengers and has a survival gain of +117% compared to the population of the Titanic.
- (i=2) : **Rich 1st class that are not too old (which we know the age).** This group covers 12.2% of the passengers and has a survival gain of +106% compared to the population of the Titanic.

Note that there could be a survivor bias in the two rules i=1 and i=2 because we know the age of the survivors more than we know the age of the non-survivors of the Titanic. We could also use `target_goal = 0` to look for passengers that did not survive the Titanic:

```
# Specify the target goal
target_goal = 0 # We are searching rules that describe non-survivors

# Create an instance of the class InsightSolver
solver = InsightSolver(
    df = df, # A dataset
    target_name = target_name, # Name of the target variable
    target_goal = target_goal, # Target goal
    columns_types = columns_types, # Columns types
)

# Fit the solver
solver.fit(
    service_key = service_key,
)

# Print the rule mining results
solver.print(mode='dense')
```

```

"""
                                contribution variable          rule      nans
i p_value coverage lift
0 7e-55    42.6%    1.46
                                78.8%    Sex          male
                                10.9%    Fare    [0.0, 26.0]
                                10.3%    Parch    [0, 0]
1 1e-12    12.9%    1.45
                                63.6%    Fare    [7.8875, 15.1]
                                36.4%    Age     [19.0, 26.0] include
"""

```

In this specific example, the InsightSolver API gives us two rules in which we find more non-survivors of the Titanic:

- (i=0) : **Poor males without a family**. This group covers 42.6% of the passengers and has a non-survival gain of +46% compared to the population of the Titanic.
- (i=1) : **Poor young adults (include missing ages)**. This group covers 12.9% of the passengers and has a non-survival gain of +45% compared to the population of the Titanic.

Note that there could be a survivor bias in the rule i=1 because we know the age of the non-survivors less than we know the age of the survivors of the Titanic. In conclusion, using the InsightSolver API, we know that *Rose DeWitt Bukater* (young rich female, 1st class, with her family) had a higher chance to survive the Titanic than *Jack Dawson* (3rd class young male without a family). For more technical details about the API, please refer to the [detailed documentation](#).

3.2 Advanced usage

This section provides a deeper look at how to use the InsightSolver API client.

Let's revisit the *Titanic* demo. Once the solver is fitted, we can do more than simply print the results. This becomes particularly important when integrating the InsightSolver API client into a Python pipeline.

3.2.1 Conventions

In InsightSolver, the parameter `target_goal` specifies the target modality of the target variable for which rules should capture a large number of 1's. By convention:

- A data point is considered a 1 if it matches the target modality specified by `target_goal`.
- A data point is considered a 0 otherwise.

It is important to note that these 0's and 1's are conventions used internally by InsightSolver and should not be confused with the actual values or modalities of the target variable in the dataset.

For instance, consider the Titanic dataset used in the *Titanic* example:

- Dataset: `kaggle_titanic_train.csv`.
- Target variable: `target_name='Survived'`.
- Target modalities: 0 (non-survivor), 1 (survivor).
- Target goals: either `target_goal=0` (looking for non-survivors) either `target_goal=1` (looking for survivors).

Here, the modalities 0 and 1 are specific to the Titanic dataset and represent whether a passenger survived or not.

- Total passengers: 891 rows.
- Non-survivors (Survived=0): 549 rows.
- Survivors (Survived=1): 342 rows.

Case 1: Looking for Survivors (`target_goal=1`)

When the goal is to identify survivors:

- `M=891`: Total population.
- `M0=549`: Number of 0's, representing non-survivors (Survived=0).
- `M1=342`: Number of 1's, representing survivors (Survived=1).

Case 2: Looking for Non-Survivors (`target_goal=0`)

When the goal is to identify non-survivors:

- `M=891`: Total population.
- `M0=342`: Number of 0's, representing survivors (Survived=1).
- `M1=549`: Number of 1's, representing non-survivors (Survived=0).

InsightSolver operates under the principle of capturing 1's and rejecting 0's, regardless of the specific meaning of these values in a given dataset.

3.2.2 Attributes of the solver

The solver object includes several relevant attributes, which are described exhaustively [here](#). For now, let's take a brief look at the most important ones:

- `M`: The total number of points in the population.
- `M0`: The number of points classified as 0 in the population.
- `M1`: The number of points classified as 1 in the population.
- `rule_mining_results`: A dictionary containing the results of the rule mining process. Below, we'll explore methods to access and parse specific aspects of these results.

- **benchmark_scores**: A dictionary containing the best scores obtained on shuffled data. This is useful to compare the scores of the rules found in the real data against the scores of the rules found in random data.

3.2.3 Counting the number of rules

To obtain the number of rules found by the solver, we can use the `ruleset_count` method:

```
solver.ruleset_count() # 3

# 3 rules are found by the solver
```

Each rule in the solver is indexed by an integer, conventionally denoted as `i`.

3.2.4 Getting the index of the rules

To retrieve the range of rule indices, we can use the `get_range_i` method:

```
solver.get_range_i() # [0, 1, 2]
```

This shows that the index `i` can take the values 0, 1 or 2. Knowing this range is useful when iterating over individual rules in the solver.

3.2.5 Exhaustive dictionary of a given rule

Let's take a closer look at the rule at position `i=0`. We can retrieve an exhaustive dictionary of the rule at position `i=0` as follows:

```
solver.i_to_rule(i=0)

# {
#   "m": 170,
#   "m0": 9,
#   "m1": 161,
#   "coverage": 0.19079685746352412,
#   "m1/M1": 0.47076023391812866,
#   "mu_rule": 0.9470588235294117,
#   "mu_pop": 0.3838383838383838,
#   "sigma_pop": 0.48659245426485753,
#   "lift": 2.4673374613003096,
#   "p_value": 1.925558554763681e-67,
#   "F_score": 0.62890625,
#   "Z_score": 16.767366956025956,
#   "rule_S": {
#     "Sex": "female",
#     "Pclass": [
#       1,
#       2
#     ]
#   },
#   "complexity_S": 2,
#   "F1_pop": 0.5547445255474452,
#   "G_bad_class": 0.17059483726150393,
#   "G_information": 0.24588549145241542,
#   "G_gini": 0.14958927829841417,
```

(continues on next page)

(continued from previous page)

```

#   "p_value_ratio_S": {
#       "Pclass": 5.359920512293736e-08,
#       "Name": 1.0,
#       "Sex": 5.022554571114061e-46,
#       "Age": 1.0,
#       "SibSp": 1.0,
#       "Parch": 1.0,
#       "Ticket": 1.0,
#       "Fare": 1.0,
#       "Cabin": 1.0,
#       "Embarked": 1.0
#   },
#   "F_score_ratio_S": {
#       "Pclass": 1.2812499999999998,
#       "Name": 1.0,
#       "Sex": 0.9302417652027029,
#       "Age": 1.0,
#       "SibSp": 1.0,
#       "Parch": 1.0,
#       "Ticket": 1.0,
#       "Fare": 1.0,
#       "Cabin": 1.0,
#       "Embarked": 1.0
#   },
#   "subrules_S": [
#       {
#           "M": 891,
#           "M0": 549,
#           "M1": 342,
#           "mu_pop": 0.3838383838383838,
#           "sigma_pop": 0.48659245426485753,
#           "F1_pop": 0.5547445255474452,
#           "m": 314,
#           "m0": 81,
#           "m1": 233,
#           "coverage": 0.35241301907968575,
#           "m1/M1": 0.6812865497076024,
#           "mu_rule": 0.7420382165605095,
#           "lift": 1.9332048273550118,
#           "mc": 577,
#           "m0c": 468,
#           "m1c": 109,
#           "p_value": 3.592513266469419e-60,
#           "F_score": 0.7103658536585366,
#           "Z_score": 16.20063097451895,
#           "G_bad_class": 0.17059483726150393,
#           "G_information": 0.21766010666061436,
#           "G_gini": 0.13964795747285225,
#           "complexity": 1,
#           "subrule_S": {
#               "Sex": "female"
#           },
#       }
#   ]

```

(continues on next page)

(continued from previous page)

```

#         "var_name": "Sex",
#         "var_rule": "female",
#         "p_value_ratio": 5.022554571114061e-46,
#         "shuffling_scores": {
#             "p_value": {
#                 "cohen_d": 75.86463627446636,
#                 "effect_size": "6. huge",
#                 "wy_ratio": 0.0
#             },
#             "Z_score": {
#                 "cohen_d": 37.71820414056423,
#                 "effect_size": "6. huge",
#                 "wy_ratio": 0.0
#             },
#             "F_score": {
#                 "cohen_d": 51.16755087975539,
#                 "effect_size": "6. huge",
#                 "wy_ratio": 0.0
#             }
#         },
#     },
#     {
#         "M": 891,
#         "M0": 549,
#         "M1": 342,
#         "mu_pop": 0.3838383838383838,
#         "sigma_pop": 0.48659245426485753,
#         "F1_pop": 0.5547445255474452,
#         "m": 170,
#         "m0": 9,
#         "m1": 161,
#         "coverage": 0.19079685746352412,
#         "m1/M1": 0.47076023391812866,
#         "mu_rule": 0.9470588235294117,
#         "lift": 2.4673374613003096,
#         "mc": 721,
#         "m0c": 540,
#         "m1c": 181,
#         "p_value": 1.925558554763681e-67,
#         "F_score": 0.62890625,
#         "Z_score": 16.767366956025956,
#         "G_bad_class": 0.17059483726150393,
#         "G_information": 0.24588549145241542,
#         "G_gini": 0.14958927829841417,
#         "complexity": 2,
#         "subrule_S": {
#             "Sex": "female",
#             "Pclass": [
#                 1,
#                 2
#             ]
#         },
#     },

```

(continues on next page)

(continued from previous page)

```

#         "var_name": "Pclass",
#         "var_rule": [
#             1,
#             2
#         ],
#         "p_value_ratio": 5.359920512293736e-08,
#         "shuffling_scores": {
#             "p_value": {
#                 "cohen_d": 85.9832032893128,
#                 "effect_size": "6. huge",
#                 "wy_ratio": 0.0
#             },
#             "Z_score": {
#                 "cohen_d": 39.52974355288319,
#                 "effect_size": "6. huge",
#                 "wy_ratio": 0.0
#             },
#             "F_score": {
#                 "cohen_d": 23.36359433204899,
#                 "effect_size": "6. huge",
#                 "wy_ratio": 0.0
#             }
#         }
#     }
# ],
#     "feature_contributions_S": {
#         "rule_S": {
#             "Sex": "female",
#             "Pclass": "[1, 2]"
#         },
#         "p_value_contribution": {
#             "Sex": 0.8616919700920942,
#             "Pclass": 0.13830802990790583
#         },
#         "F_score_contribution": {
#             "Sex": 1.0,
#             "Pclass": 0.0
#         },
#         "Z_score_contribution": {
#             "Sex": 0.9417181496074654,
#             "Pclass": 0.05828185039253464
#         },
#         "G_bad_class_contribution": {
#             "Sex": 1.0,
#             "Pclass": 0.0
#         },
#         "G_information_contribution": {
#             "Sex": 0.857675593215252,
#             "Pclass": 0.142324406784748
#         },
#         "G_gini_contribution": {
#             "Sex": 0.9099458875412633,

```

(continues on next page)

(continued from previous page)

```
#         "Pclass": 0.0900541124587367
#     }
# },
#     "shuffling_scores": {
#         "p_value": {
#             "cohen_d": 85.9832032893128,
#             "effect_size": "6. huge",
#             "wy_ratio": 0.0
#         },
#         "Z_score": {
#             "cohen_d": 39.52974355288319,
#             "effect_size": "6. huge",
#             "wy_ratio": 0.0
#         },
#         "F_score": {
#             "cohen_d": 23.36359433204899,
#             "effect_size": "6. huge",
#             "wy_ratio": 0.0
#         }
#     }
# }
```

This dictionary contains detailed information and statistics about the rule at position $i=0$. Here are some of the key entries:

- "m": 170: This is the number of points captured by the rule. The rule contains 170 points in total.
- "m0": 9: This is the number of 0 captured by the rule. The rule contains 9 non-survivors.
- "m1": 161: This is the number of 1 captured by the rule. The rule contains 161 survivors.
- "coverage": 0.19079685746352412: This is the coverage of the rule, i.e. the ratio m/M . The rule covers 19.1% of the population.
- "m1/M1": 0.47076023391812866: This is the sensitivity of the rule, i.e. the capture rate of 1. The rule captures 47.1% of the survivors.
- "mu_rule": 0.9470588235294117: This is the average of the target variable in the rule, i.e. the ratio $m1/m$. Here we have a survival rate of 94.7% in the rule.
- "mu_pop": 0.3838383838383838: This is the average of the target variable in the population, i.e. the ratio $M1/M$. Here we have a survival rate of 38.4% in the population.
- "sigma_pop": 0.48659245426485753: This is the standard deviation of the target variable in the population.
- "lift": 2.4673374613003096: This is the lift of the rule, i.e. the ratio μ_rule/μ_pop .
- "p_value": 1.925558554763681e-67: This is the p-value (according to the hypergeometric probability law, not the chi-squared) of the rule.
- "F_score": 0.62890625: This is the F1-score of the rule.
- "Z_score": 16.767366956025956: This is the Z-score of the rule.
- "rule_S": {"Sex": "female", "Pclass": [1,2]}: The rule reads *Females in first or second class*.
- "complexity_S": 2: The complexity of the rule is 2, i.e. two variables are involved in the rule ("Sex" and "Pclass").

- "F1_pop": 0.5547445255474452: This is the F1-score of the population.
- "G_bad_class": 0.17059483726150393: This is the bad classification gain of the rule.
- "G_information": 0.24588549145241542: This is the information gain of the rule.
- "G_gini": 0.14958927829841417: This is the Gini gain of the rule.
- "shuffling_scores": This contains the scores that measure how strong is the rule compared to what would be found in shuffled data.

3.2.6 DataFrame of subrules

We can retrieve a DataFrame of the subrules for the rule at position `i=0` as follow:

```
solver.i_to_subrules_dataframe(i=0)
```

#	p_value_ratio	variable	rule	complexity	p_value	F_score	...	m0c	m1c
→	G_bad_class	G_information	G_gini		subrule_S				
# 0	5.022555e-46	Sex	female	1	3.592513e-60	0.710366	...	468	109
→	0.170595	0.217660	0.139648	{'Sex': 'female'}					
# 1	5.359921e-08	Pclass	[1, 2]	2	1.925559e-67	0.628906	...	540	181
→	0.170595	0.245885	0.149589	{'Sex': 'female'...					

The DataFrame of subrules begins with a rule of complexity 1 (e.g. {"Sex": "female"}) and progresses to higher complexities, such as complexity 2 (e.g. {"Sex": "female", "Pclass": [1, 2]}). As we can observe, increasing the complexity from 1 to 2 improves the p-values and the information gain but degrades the F1-score.

The purpose of the subrules DataFrame is to assist in deciding the optimal level of rule complexity based on various metrics.

3.2.7 DataFrame of features contributions

We can retrieve a DataFrame showing the contributions of the features for the rule at position `i=0` as follows:

```
solver.i_to_feature_contributions_S(i=0)
```

#	p_value	F_score	Z_score	G_bad_class	G_information	G_gini
# feature_name						
# Sex	0.861692	1.0	0.941718	1.0	0.857676	0.909946
# Pclass	0.138308	0.0	0.058282	0.0	0.142324	0.090054

As we can observe, the variable "Sex" provides the largest contribution. The variable "Pclass" adds a slight positive contribution to both the p-value and the information gain, as including it in the rule improves these metrics. However, the contribution of "Pclass" is zero for the F-score. This indicates that it does not enhance the F-score (in fact, it degrades it, but by convention, contributions are kept nonnegative).

3.2.8 Printing modes

Earlier in *Titanic* we saw the dense printing mode. There are three printing modes:

- full: A full print of the results.
- light: A lighter version of the full print.
- dense: A very compact version of the print.

3.2.9 Column types

The columns of a Pandas DataFrame are associated with a type known as a *dtype*, such as `int64`, `float64`, `object`, and so on. In addition to these, InsightSolver introduces a complementary layer of types called *btype*.

While *dtypes* describe the encoding of the data (e.g., integers or floats), *btypes* define how the data should be interpreted when mining for rules. These *btypes* include:

- **binary**: The variable is treated as a binary categorical variable, and rule mining will focus on finding subsets.
- **multiclass**: The variable is treated as a multiclass categorical variable, and rule mining will aim to find subsets.
- **continuous**: The variable is treated as an ordered variable, and rule mining will focus on identifying meaningful intervals.
- **ignore**: The variable is excluded from rule mining.

The *btypes* of the columns are automatically detected in InsightSolver, so its not mandatory to explicitly specify a *btype* for each variable. However, if the user wishes to specify the *btype* for some or all variables, this can be done using the `columns_types` dictionary (a key is a column name, a value is a *btype*). The `columns_types` dictionary can be passed as a parameter of the `solver`.

MODULES

4.1 insightsolver module

- *Organization:* InsightSolver
- *Project Name:* InsightSolver
- *Module Name:* insightsolver
- *File Name:* __init__.py
- *Author:* Noé Aubin-Cadot
- *Email:* noe.aubin-cadot@insightsolver.com
- *Last Updated:* 2025-04-24
- *First Created:* 2024-09-16

4.1.1 Description

The Python module *insightsolver* is an API client of the InsightSolver SaaS which is designed to generate advanced rule mining and data insights.

4.1.2 License

Exclusive Use License - see [LICENSE](#) for details.

4.2 api_utilities module

- *Organization:* InsightSolver
- *Project Name:* InsightSolver
- *Module Name:* insightsolver
- *File Name:* api_utilities.py
- *Author:* Noé Aubin-Cadot
- *Email:* noe.aubin-cadot@insightsolver.com
- *Last Updated:* 2025-05-08
- *First Created:* 2024-09-16

4.2.1 Description

This file provides essential utility functions to secure and streamline client-server communication within the API. It includes functions for data compression, encryption, decryption, and transformations of data structures, all designed to facilitate efficient and protected message exchange between the client and server.

While all communications are secured via HTTPS, this file goes a step further by adding an additional layer of encryption, using RSA-4096 and ECDSA-SECP521R1 for secure key exchange and AES-256 for data encryption. These functions are particularly useful for scenarios requiring enhanced data privacy and integrity.

4.2.2 Functions provided

- `hash_string`: Computes the hash of a string.
- `convert_bytes_to_base64_string`: Convert bytes to a base64 string.
- `convert_base64_string_to_bytes`: Convert a base64 string to bytes.
- `compress_string`: Compress a string using gzip.
- `decompress_string`: Decompress a gzip-compressed string.
- `compress_and_encrypt_string`: Compress and encrypt a string for secure transmission.
- `decrypt_and_decompress_string`: Decrypt an encrypted string.
- `encode_obj`: Takes an object and encode it to a new object compatible with json serialization.
- `convert_dict_to_json_string`: Convert a dict to a json string.
- `decode_obj`: Inverse operation from `encode_obj`.
- `convert_json_string_to_dict`: Convert a json string to a dict.
- `transform_dict`: Convert a dictionary for easier client-server communication.
- `untransform_dict`: Reverse the dictionary transformation to restore the original data format.
- `generate_keys`: Generate RSA and ECDSA private and public keys.
- `compute_credits_from_df`: Compute the amount of credits consumed for a given DataFrame.
- `request_cloud_credits_infos`: Request the server for informations about the credits available.
- `request_cloud_public_keys`: Request the server for public keys.
- `request_cloud_computation`: Request the server for computation.
- `search_best_ruleset_from_API_dict`: Make the API call.

4.2.3 License

Exclusive Use License - see [LICENSE](#) for details.

`insightsolver.api_utilities.hash_string(string)`

A function to compute the hash of a string using hashlib.

`insightsolver.api_utilities.convert_bytes_to_base64_string(data: bytes) → str`

Convert a bytes object to a base64-encoded string.

4.2.4 Parameters

data

[bytes] The byte data to encode.

4.2.5 Returns

str

The base64-encoded string.

`insightsolver.api_utilities.convert_base64_string_to_bytes(string: str) → bytes`

Convert a base64-encoded string to a bytes object.

4.2.6 Parameters

string

[str] The base64-encoded string.

4.2.7 Returns

bytes

The decoded byte data.

`insightsolver.api_utilities.compress_string(original_string: str) → str`

Compress a string using gzip and then encode it to base64.

4.2.8 Parameters

original_string

[str] The original string to be compressed.

4.2.9 Returns

str

The compressed string.

4.2.10 Example

```
original_string = "This is a test string"
compressed_string = compress_string(original_string)
print(compressed_string) # Example output: 'H4sIAA01/2YC/
→wvJyCxWAKJEhZLU4hKF4pKizLx0AG3zTmsVAAAA'
```

`insightsolver.api_utilities.decompress_string(compressed_string: str) → str`

Decompress a base64-encoded string that was previously compressed using gzip.

This function takes a base64-encoded string, decodes it, and then decompresses the resulting data using gzip to return the original string.

4.2.11 Parameters

compressed_string

[str] The base64-encoded string that contains the compressed data.

4.2.12 Returns

str

The original uncompressed string.

4.2.13 Example

```
compressed_string = 'H4sIAA01/2YC/wvJyCxWAKJEhZLU4hKF4pKizLx0AG3zTmsVAAAA'
original_string = decompress_string(compressed_string)
print(original_string) # 'This is a test string'
```

```
insightsolver.api_utilities.compress_and_encrypt_string(original_string: str, symmetric_key: bytes)
→ tuple[str, str]
```

Compress and encrypt a string using AES-256-GCM.

This function compresses the given string using gzip and then encrypts it using AES-256 in GCM mode. A nonce is used in the encryption process for AES-GCM, and the result is base64-encoded for easy transfer over networks.

Security: - AES-256 encryption - GCM (Galois/Counter Mode) with authentication

4.2.14 Parameters

original_string

[str] The original string to be compressed and encrypted.

symmetric_key

[bytes] The 32-byte symmetric key used for encryption.

4.2.15 Returns

tuple[str, str]

A tuple containing the base64-encoded encrypted compressed string and the base64-encoded nonce used.

4.2.16 Example

```
transformed_string, nonce_string = compress_and_encrypt_string(
    original_string = "Secret data",
    symmetric_key   = token_bytes(32),
)
print(transformed_string, nonce_string) # 'Base64_encoded_result', nonce_string
```

```
insightsolver.api_utilities.decrypt_and_decompress_string(transformed_string: str, symmetric_key:
    bytes, nonce: bytes) → str
```

Decrypt and decompress a string using AES-256-GCM.

This function takes a base64-encoded encrypted string, decrypts it using AES-256 in GCM mode with the provided symmetric key and nonce, and then decompresses the result using gzip.

Security: - AES-256 encryption - GCM (Galois/Counter Mode) with authentication

4.2.17 Parameters

transformed_string

[str] The base64-encoded string that contains the encrypted and compressed data.

symmetric_key

[bytes] The 32-byte symmetric key used for decryption.

nonce

[bytes] The nonce used for AES-GCM during encryption.

4.2.18 Returns

str

The original uncompressed and decrypted string.

4.2.19 Raises

Exception

If the decryption fails.

4.2.20 Example

```
original_string = decrypt_and_decompress_string(
    transformed_string = encrypted_compressed_string,
    symmetric_key       = token_bytes(32),
    nonce               = nonce
)
print(original_string) # 'Secret data'
```

`insightsolver.api_utilities.encode_obj(obj)`

This function takes an object and encode it to a new object compatible with json serialization.

`insightsolver.api_utilities.convert_dict_to_json_string(d: dict) → str`

This function converts a dict to a json string.

`insightsolver.api_utilities.decode_obj(obj)`

This function does the inverse operation from the function `encode_obj`.

`insightsolver.api_utilities.convert_json_string_to_dict(string: str) → dict`

This function takes a json string and converts it to a dict.

`insightsolver.api_utilities.transform_dict(d_original: dict, do_compress_data: bool = False, symmetric_key: bytes | None = None, json_format: str = 'json') → dict`

Transform the contents of a dictionary by optionally compressing and encrypting its data.

This function takes a dictionary and converts it to a string. Depending on the options provided, it can compress the data using gzip, encrypt it using AES-256, or both. The resulting string is returned in a transformed dictionary format for easier transmission or storage.

4.2.21 Parameters

d_original

[dict] The original dictionary that needs to be transformed.

do_compress_data

[bool, optional] Whether or not to compress the dictionary data (default is False).

symmetric_key

[bytes, optional] A symmetric key. Typically generated using `from secrets import token_bytes; symmetric_key = token_bytes(32)`. If provided, the data will be encrypted (default is None).

json_format

[str, optional] The format to convert the dictionary to a string. Can be 'json' or 'json_extended' (default is 'json').

4.2.22 Returns

dict

A dictionary containing the transformed string, the transformations applied, and the json format.

4.2.23 Example

```
d_original = {'A':1, 'B':2, 'C':3}
from secrets import token_bytes
symmetric_key = token_bytes(32) # b'\x1a\xef&\x0bR\xe1\x95\xfa\x90\x10r\x93\x1a\xaeN\
→xc2\xba\x80\xf1\x1a\x0fG\xf4(\x0e#\xd4\xaf\x81q\xf4'
d_transformed = transform_dict(
    d_original      = d_original,
    do_compress_data = True,
    symmetric_key    = symmetric_key,
    json_format      = 'json',
)
print(d_transformed)
# {
#     'transformations': 'encrypted_gzip_base64',
#     'json_format': 'json',
#     'transformed_string':
→'q30qPkK19Z3sENnfk77t4CnpzWKV+gdHLLSpNNgU3DjdmEbLcZWj+AjZyFmUquuUmh6obZmTh8k=',
#     'nonce_string': '7PpTvoc0Ksx8whRy',
# }
```

`insightsolver.api_utilities.untransform_dict(d_transformed: dict, symmetric_key: bytes | None = None, verbose: bool = False) → dict`

Decompress and decrypt the contents of a transformed dictionary.

This function takes a dictionary that has been transformed (e.g., compressed, encrypted), and restores its original contents by reversing the transformations. Depending on the transformation type, it may decrypt and/or decompress the data.

4.2.24 Parameters

d_transformed

[dict] The transformed dictionary containing the compressed/encrypted string, the transformations applied, and the json format used.

symmetric_key

[bytes, optional] A symmetric key. Typically generated using `from secrets import token_bytes; symmetric_key = token_bytes(32)`. If provided, the data will be decrypted using this key (default is None).

verbose

[bool, optional] If True, additional debug information will be printed (default is False).

4.2.25 Returns**dict**

The original dictionary with its content restored.

4.2.26 Raises**Exception**

If an invalid transformation type or JSON format is provided.

4.2.27 Example

```
d_transformed = {
    'transformations' : 'encrypted_gzip_base64',
    'json_format' : 'json',
    'transformed_string' :
    ↪ 'q30qPkK19Z3sENnfk77t4CnpzWKV+gdHLLSpNNgU3DjdmEbLcZWj+AjZyFmUquuUmh6obZmTh8k='
    'nonce_string' : '7PpTvoc0Ksx8whRy',
}
d_untransformed = untransform_dict(
    d_transformed = d_transformed,
    symmetric_key = symmetric_key, # b'\x1a\xef&\x0bR\xe1\x95\xfa\x90\x10r\x93\
    ↪ \x1a\xaeN\xc2\xba\x80\xf1\x1a\x0fG\xf4(\x0e#\xd4\xaf\x81q\xf4'
)
print(d_untransformed) # {'A': 1, 'B': 2, 'C': 3}
```

insightsolver.api_utilities.generate_keys()

This function generates RSA and ECDSA private and public keys. The generated keys:

- rsa_private_key
- ecdsa_private_key
- rsa_public_key_pem_bytes
- ecdsa_public_key_pem_bytes

4.2.28 Returns**tuple**

A tuple containing four elements:

- rsa_private_key: The generated RSA private key.
- ecdsa_private_key: The generated ECDSA private key.
- rsa_public_key_pem_bytes: The RSA public key serialized in PEM format.
- ecdsa_public_key_pem_bytes: The ECDSA public key serialized in PEM format.

insightsolver.api_utilities.generate_url_headers(*computing_source: str, input_file_service_key: str | None = None*) → Tuple[str, Dict[str, Any] | None]

This function generates the url and the headers for the POST request.

4.2.29 Parameters

computing_source

[str] Where the server is.

input_file_service_key

[optional] The client's service key, needed if the server is remote. Default is *None*.

`insightsolver.api_utilities.compute_credits_from_df(df: DataFrame) → int`

This function computes the number of credits consumed by a rule mining via the API. This number is based on the size of the DataFrame sent to the API.

4.2.30 Parameters

df

[pd.DataFrame] Input DataFrame whose size is used to compute credits.

4.2.31 Returns

int

The computed number of credits consumed.

`insightsolver.api_utilities.request_cloud_credits_infos(computing_source: str, d_out_credits_infos: dict, input_file_service_key: str | None = None, user_email: str | None = None, timeout: int = 60) → dict`

Send a dict that specifies which infos about the credits are asked for.

4.2.32 Parameters

computing_source

[str] Where the server is.

d_out_credits_infos

[dict] A dictionary containing the infos about the credits that are asked for. The dictionary format is:

- **private_key_id**: private_key_id of the service_key.
- **user_email**: Email of the user.
- **do_compute_credits_available**: A boolean that specifies where the number of credits available is requested.
- **do_compute_df_credits_infos**: A boolean that specifies if a DataFrame containing all credits transactions is asked for.

input_file_service_key

[optional] The client's service key, needed if the server is remote. Default is *None*.

timeout

[int, optional] The timeout duration for the request, in seconds. Default is 60 seconds, as this operation is typically fast and does not involve computation.

`insightsolver.api_utilities.request_cloud_public_keys(computing_source: str, d_client_public_keys: dict, input_file_service_key: str | None = None, timeout: int = 60) → dict`

Send the client's public keys to the server and receive the server's public keys in response.

This function establishes a secure connection to the specified server (`computing_source`) and sends the client's public keys (`d_client_public_keys`). The server responds with its own set of public keys, which are returned in a dictionary format.

4.2.33 Parameters

computing_source

[str] Where the server is.

d_client_public_keys

[dict] A dictionary containing the client's public keys to be sent to the server. The dictionary format is:

- `alice_rsa_public_key_pem_base64`: Client's RSA public key, encoded in base64.
- `alice_ecdsa_public_key_pem_base64`: Client's ECDSA public key, encoded in base64.

input_file_service_key

[optional] The client's service key, needed if the server is remote. Default is *None*.

timeout

[int, optional] The timeout duration for the request, in seconds. Default is 60 seconds, as this operation is typically fast and does not involve computation.

4.2.34 Returns

dict

A dictionary containing the server's public keys and a unique session identifier. The dictionary format is as follows:

- `session_id`: A unique identifier for the session.
- `bob_rsa_public_key_pem_base64`: Server's RSA public key, encoded in base64.
- `bob_ecdsa_public_key_pem_base64`: Server's ECDSA public key, encoded in base64.

4.2.35 Example

```
# Client's public keys
d_client_public_keys = {
    'alice_rsa_public_key_pem_base64': '<base64-encoded RSA public key>',
    'alice_ecdsa_public_key_pem_base64': '<base64-encoded ECDSA public key>',
}

# Request server public keys
d_server_public_keys = request_cloud_public_keys(
    computing_source='https://server-address.com',
    d_client_public_keys=d_client_public_keys,
    input_file_service_key='client_service_key'
)

# Access the session ID and server's public keys
session_id = d_server_public_keys['session_id']
bob_rsa_public_key = d_server_public_keys['bob_rsa_public_key_pem_base64']
bob_ecdsa_public_key = d_server_public_keys['bob_ecdsa_public_key_pem_base64']
```

4.2.36 Raises

Exception

If the request fails or the server does not return the expected keys.

```
insightsolver.api_utilities.request_cloud_computation(computing_source: str, d_out_transformed:  
                                                    dict, input_file_service_key: str | None =  
                                                    None, timeout: int = 600, verbose: bool =  
                                                    False) → dict
```

Send the transformed dict to the server for it to compute the rule mining.

4.2.37 Parameters

computing_source

[str] The computing source.

d_out_transformed

[dict] The transformed dict to send to the server.

input_file_service_key

[str, optional] The client's service key, needed if the server is remote. Default is *None*.

timeout

[int, optional] Timeout for the request, in seconds. Default is 600 seconds, as computation may take longer.

4.2.38 Returns

dict

The dict that contains the rule mining results.

```
insightsolver.api_utilities.search_best_ruleset_from_API_dict(d_out_original: dict,  
                                                            input_file_service_key: str | None =  
                                                            None, user_email: str | None =  
                                                            None, computing_source: str =  
                                                            'remote_cloud_function',  
                                                            do_compress_data: bool = True,  
                                                            do_compute_memory_usage: bool  
                                                            = True, verbose: bool = False) →  
dict
```

Search for the best ruleset where the computation is done from the server.

4.2.39 Parameters

d_out_original: dict

The original dict, pre-transformation, that contains the necessary data for the server to do rule mining.

input_file_service_key: str, optional

The service key of the client.

user_email: str, optional

Email of the user (only for use inside a Google Cloud Run container).

computing_source: str, optional

The computing source.

do_compress_data: bool, optional

If we want to compress the data to reduce transmission size.

If we want to compute the memory usage.

Verbosity.

dict

The dict that contain the output of the rule mining from the server.

- *Organization*: InsightSolver
- *Project Name*: InsightSolver
- *Module Name*: insightsolver
- *File Name*: visualization.py
- *Author*: Noé Aubin-Cadot
- *Email*: noe.aubin-cadot@insightsolver.com
- *Last Updated*: 2025-04-25
- *First Created*: 2025-04-24

This file contains some visualization functions, some of which are integrated as a method of the InsightSolver class.

- `classify_variable_as_continuous_or_categorical`
- `compute_feature_label`
- `show_feature_distributions_of_S`
- `generate_insightsolver_banner`
- `show_feature_contributions_of_i`
- `show_all_feature_contributions`
- `show_all_feature_contributions_and_distributions`

Exclusive Use License - see [LICENSE](#) for details.

This function is meant to classify a series as continuous or categorical. This is used to decide which plot to do with it.

4.3.4 Parameters

s: pd.Series

Series that needs to be classified.

unique_ratio_threshold: float

Threshold on the *unique_ratio*.

4.3.5 Returns

categorical_or_continuous: str

The classification of the Series.

`insightsolver.visualization.compute_feature_label(solver, feature_name: str, S: dict) → [<class 'str'>, <class 'str'>]`

This function computes the label of a feature in a rule S.

4.3.6 Parameters

solver: InsightSolver

The solver.

feature_name: str

The name of the feature.

S: dict

The rule S.

4.3.7 Returns

feature_label: str

The label of the feature.

feature_relationship: str

The relationship of the feature to the constraints.

`insightsolver.visualization.show_feature_distributions_of_S(solver, S: dict, padding_y: int = 5, do_show_kde: bool = False, do_show_vertical_lines: bool = False) → None`

This function generates bar plots of the distributions of the points in the specified rule S.

4.3.8 Parameters

solver

[InsightSolver] The solver object.

S

[dict] The rule S that we wish to visualize.

padding_y: int

The padding used for the ylim.

do_show_kde: bool

Boolean to show the KDE of the continuous features.

`insightsolver.visualization.generate_insightsolver_banner(solver, i: int, loss: float | None = None)`

This function returns an image containing the parameters for p-value, purity, lift, coverage, size and loss value of a specified rule.

4.3.9 Parameters

solver: InsightSolver

The solver.

i: int

Index of the rule.

loss: float

Some loss to show in the banner.

4.3.10 Returns

image: Image

Image of the banner (with the values).

`insightsolver.visualization.show_feature_contributions_of_i(solver, i: int, a: float = 0.5, b: float = 1, fig_width: float = 12, language: str = 'en', do_grid: bool = True, do_title: bool = False, do_banner: bool = True, loss: float | None = None) → None`

This function returns a horizontal bar plots of the feature contributions of a specified rule S.

4.3.11 Parameters

solver: InsightSolver

The fitted solver that contains the identified rules.

i: int

The index of the rule to show.

a: float

Height per bar.

b: float

Added height to the figure.

fig_width: float

Width of the figure

language: str

Language of the figure ('fr' or 'en').

do_grid: bool

If we want to show a vertical grid behind the horizontal bars.

do_title: bool

If we want to show a title.

do_banner: bool

If we want to show the banner.

loss: float

If we want to show a loss.

```

insightsolver.visualization.show_all_feature_contributions(solver, a: float = 0.5, b: float = 1,
                                                           fig_width: float = 12, language: str =
                                                           'en', do_grid: bool = True, do_title:
                                                           bool = False, do_banner: bool = True)
                                                           → None

```

This function generates a horizontal bar plot of the feature contributions for each rule found in a solver.

4.3.12 Parameters

solver: InsightSolver

The fitted solver that contains the identified rules.

a: float

Height per bar.

b: float

Added height to the figure.

fig_width: float

Width of the figure

language: str

Language of the figure ('fr' or 'en').

do_grid: bool

If we want to show a vertical grid behind the horizontal bars.

do_title: bool

If we want to show a title.

do_banner: bool

If we want to show the banner.

```

insightsolver.visualization.show_feature_contributions_and_distributions_of_i(solver, i: int,
                                                                               do_banner:
                                                                               bool = True,
                                                                               loss: float |
                                                                               None = None)
                                                                               → None

```

This function returns a bar plot of the feature contributions and a distribution of the points in the rule i.

4.3.13 Parameters

solver: InsightSolver

The fitted solver that contains the identified rules.

i: int

The index of the rule to show.

do_banner: bool

If we want to show the banner.

loss: float

If we want to show a loss.

```

insightsolver.visualization.show_all_feature_contributions_and_distributions(solver,
                                                                               do_banner:
                                                                               bool = True) →
                                                                               None

```

This function generates the feature contributions and feature distributions for all rules found in a fitted solver.

4.3.14 Parameters

solver: `InsightSolver`

The fitted solver that contains the identified rules.

do_banner: `bool`

If we want to show the banner.

If you need assistance with the InsightSolver API client, please follow the resources below in the suggested order:

5.1 1. Technical Documentation

The technical documentation provides detailed guidance on installation, usage, and troubleshooting. Start here if you are encountering issues.

- **Installation Guide:** Refer to the *Installation Guide* for step-by-step instructions.
- **Quickstart Usage Example:** Check out the *Quickstart Example* for a simple and practical example to get started quickly. This example demonstrates how to use the InsightSolver API client and may inspire you to adapt it to your specific needs.
- **API Reference:** Explore the *API Reference* for detailed information on available methods and parameters.

5.2 2. Frequently Asked Questions (FAQ)

The FAQ section addresses common questions and issues.

- **How do I install the API client?**
Please see the *Installation Guide*.
- **What should I do if I encounter a connection error?**
Ensure your service key is valid, and check that your network permits outgoing connections.

5.3 3. GitHub Issues

For reporting bugs or exploring existing issues, visit our [GitHub Issues](#) page.

5.4 4. Contact Support

If the above resources do not resolve your issue, you can contact us directly at:

- **Email:** support@insightsolver.com

LICENSE

Exclusive Use License:

This script is provided under an exclusive use license.
The holder of this license is authorized to use the script for internal purposes only. Any modification, distribution, or sharing of the script or parts thereof is strictly prohibited without prior written consent from the author.

This script is provided "as is", without warranty of any kind, express or implied, including but not limited to the warranties of merchantability, fitness for a particular purpose, or non-infringement.

PYTHON MODULE INDEX

i

`insightsolver`, [15](#)
`insightsolver.api_utilities`, [15](#)
`insightsolver.visualization`, [25](#)

C

`classify_variable_as_continuous_or_categorical()` (in module `insightsolver.visualization`), 25
`compress_and_encrypt_string()` (in module `insightsolver.api_utilities`), 18
`compress_string()` (in module `insightsolver.api_utilities`), 17
`compute_credits_from_df()` (in module `insightsolver.api_utilities`), 22
`compute_feature_label()` (in module `insightsolver.visualization`), 26
`convert_base64_string_to_bytes()` (in module `insightsolver.api_utilities`), 17
`convert_bytes_to_base64_string()` (in module `insightsolver.api_utilities`), 16
`convert_dict_to_json_string()` (in module `insightsolver.api_utilities`), 19
`convert_json_string_to_dict()` (in module `insightsolver.api_utilities`), 19

D

`decode_obj()` (in module `insightsolver.api_utilities`), 19
`decompress_string()` (in module `insightsolver.api_utilities`), 17
`decrypt_and_decompress_string()` (in module `insightsolver.api_utilities`), 18

E

`encode_obj()` (in module `insightsolver.api_utilities`), 19

G

`generate_insightsolver_banner()` (in module `insightsolver.visualization`), 26
`generate_keys()` (in module `insightsolver.api_utilities`), 21
`generate_url_headers()` (in module `insightsolver.api_utilities`), 21

H

`hash_string()` (in module `insightsolver.api_utilities`), 16

I

`insightsolver`
 module, 15
`insightsolver.api_utilities`
 module, 15
`insightsolver.visualization`
 module, 25

M

module
 `insightsolver`, 15
 `insightsolver.api_utilities`, 15
 `insightsolver.visualization`, 25

R

`request_cloud_computation()` (in module `insightsolver.api_utilities`), 24
`request_cloud_credits_infos()` (in module `insightsolver.api_utilities`), 22
`request_cloud_public_keys()` (in module `insightsolver.api_utilities`), 22

S

`search_best_ruleset_from_API_dict()` (in module `insightsolver.api_utilities`), 24
`show_all_feature_contributions()` (in module `insightsolver.visualization`), 27
`show_all_feature_contributions_and_distributions()` (in module `insightsolver.visualization`), 28
`show_feature_contributions_and_distributions_of_i()` (in module `insightsolver.visualization`), 28
`show_feature_contributions_of_i()` (in module `insightsolver.visualization`), 27
`show_feature_distributions_of_S()` (in module `insightsolver.visualization`), 26

T

`transform_dict()` (in module `insightsolver.api_utilities`), 19

U

`untransform_dict()` (*in module insight-solver.api_utilities*), [20](#)