

02393 C++ Programming Exercises

Week 6, October 3, 2016

Hand-in via codejudge, before October 10, 5pm

A class for fractions of integers The goal of the exercise of this week is to implement a class of fractions of integers supporting some basic operations like addition and multiplication. You can use the following interface for the class as a starting point and modify it at will:

```
class fraction {  
  
private:  
    // Internal representation of a fraction as two integers  
    int numerator;  
    int denominator;  
  
public:  
    // Class constructor  
    fraction(int n, int d);  
  
    // Methods to update the fraction  
    void add(fraction f);  
    void mult(fraction f);  
    void div(fraction f);  
  
    // Display method  
    void display(void);  
  
};
```

The main idea above is that a fraction $\frac{a}{b}$ is represented by two integers (the numerator a and the denominator b) and several methods are provided to support arithmetic operations on fractions. For example:

`fraction(int n, int m)` constructs the fraction $\frac{n}{m}$;

`void add(fraction f)` updates a fraction by adding fraction f to it.

`void mult(fraction f)` updates a fraction by multiplying it by fraction f .

`void div(fraction f)` updates a fraction by dividing it by fraction f .

Your program should read a sequence of simple expressions from `cin` of any of the following forms:

- `a / b + c / d`
- `a / b * c / d`
- `a / b div c / d`

and provide the result as a shortened fraction. For example, if the input is

```
1 / 4 + 1 / 2
1 / 2 * 3 / 4
```

your program should provide the following output to `cout`

```
3 / 4
3 / 8
```

This is because

$$\frac{1}{4} + \frac{1}{2} = \frac{1 \cdot 2 + 1 \cdot 4}{4 \cdot 2} = \frac{6}{8} = \frac{3}{4}$$

and

$$\frac{1}{2} \cdot \frac{3}{4} = \frac{1 \cdot 3}{2 \cdot 4} = \frac{3}{8}$$

Hint for reading the input: you can use the normal `cin` to read first an `int` (the enumerator of the first fraction), then a `string` (the / sign), then another `int` for the denominator, and so on. There is no requirement for your program in case of ill-formed inputs.

Extra Challenge (nothing to hand in) The suggested internal representation poses some limits on the actual domain of integral numbers that the fraction class can cover. For example, the largest number would be $\frac{\text{INT_MAX}}{1}$ and the smallest positive fraction would be $\frac{1}{\text{INT_MAX}}$. A possible remedy to mitigate this would be to exploit the fact that every integer can be represented by a product of prime numbers (see e.g. https://en.wikipedia.org/wiki/Fundamental_theorem_of_arithmetic). This was indeed what we exploited in assignment 2. For example

$$137200 = 2 \cdot 2 \cdot 2 \cdot 2 \cdot 5 \cdot 5 \cdot 7 \cdot 7 \cdot 7$$

To avoid repeating the same prime number many times, we could equivalently represent 137200 with exponentiation of prime numbers:

$$137200 = 2^4 \cdot 5^2 \cdot 7^3$$

We could thus represent all the exponents in an array of exponents, where the i -th element of the array represents how many times the i -th prime number occurs.¹ So the representation of 137200 would be

array index	0	1	2	3	4	5	...
array	4	0	2	3	0	0	...
corresponding prime number	2	3	5	7	11	13	...

Arithmetic operations can also exploit such representation. For instance, the multiplication of two numbers in such representation can be obtained by adding

¹Formally, the factorization of a natural number $n > 0$ consists of the (uniquely determined) exponents k_1, k_2, \dots such that $n = p_1^{k_1} \cdot p_2^{k_2} \cdot \dots$ where p_1, p_2, \dots are the prime numbers.

the corresponding exponents. For instance, multiplying the factorizations of 12 and 10 would be done as follows

primes	2	3	5
12	2	1	0
10	1	0	1
Adding exponents gives:			
120	3	1	1

Division can be obtained in a similar manner, by subtracting the exponents. Addition may be more involved.

The challenge is to implement the class of fractions with this representation technique.