

# Използване на OpenMP. Част 3.

*Курс „Паралелно програмиране“*



ИНСТИТУТ за СЪВРЕМЕННИ  
ФИЗИЧЕСКИ ИЗСЛЕДВАНИЯ

Стоян Мишев

Locks

Shared, private, firstprivate, lastprivate

Примери


Изпълнява се нишката, която държи lock. Останалите изчакват докато се освободи.

```
omp_init_lock()
```

```
omp_set_lock()
```

```
omp_unset_lock()
```

```
omp_destroy_lock()
```



```
#pragma omp parallel for
for(i=0;i<NBUCKETS; i++){
    omp_init_lock(&hist_locks[i]);    hist[i] = 0;
}
#pragma omp parallel for
for(i=0;i<NVALS; i++){
    ival = (int) sample(arr[i]);
    omp_set_lock(&hist_locks[ival]);
    hist[ival]++;
    omp_unset_lock(&hist_locks[ival]);
}

for(i=0;i<NBUCKETS; i++)
    omp_destroy_lock(&hist_locks[i]);
```

`omp_set_num_threads()`

`omp_get_num_threads()`

`omp_get_thread_num()`

`omp_get_max_threads()`

`omp_in_parallel()`


`omp_set_dynamic()`

`omp_get_dynamic()`

`omp_num_procs()`

```
#include <omp.h>
void main()
{ int num_threads;
  omp_set_dynamic( 0 );
  omp_set_num_threads( omp_num_procs() );
#pragma omp parallel
  { int id=omp_get_thread_num();
#pragma omp single
    num_threads = omp_get_num_threads();
    do_lots_of_stuff(id);
  }
}
```

```
double A[10];  
int main() {  
    int index[10];  
    #pragma omp parallel  
        work(index);  
    printf("%d\n", index[0]);  
}
```



```
extern double A[10];  
void work(int *index) {  
    double temp[10];  
    static int count;  
    ...  
}
```



shared

private

firstprivate

lastprivate


default(private|shared|none)

---

```
void wrong() {  
    int tmp = 0;  
    #pragma omp parallel for private(tmp)  
    for (int j = 0; j < 1000; ++j)  
        tmp += j;  
    printf("%d\n", tmp);  
}
```

```
void wrong() {  
    int tmp = 0;  
    #pragma omp parallel for private(tmp)  
    for (int j = 0; j < 1000; ++j)  
        tmp += j;  
    printf("%d\n", tmp);  
}  
  
incr = 0;  
#pragma omp parallel for firstprivate(incr)  
for (i = 0; i <= MAX; i++) {  
    if ((i%2)==0) incr++;  
    A[i] = incr;  
}
```

```
void sq2(int n, double *lastterm)
{
    double x; int i;
    #pragma omp parallel for lastprivate(x)
    for (i = 0; i < n; i++){
        x = a[i]*a[i] + b[i]*b[i];
        b[i] = sqrt(x);
    }
    *lastterm = x;
}
```



```
#include <omp.h>
# define NPOINTS 1000
# define MXITR 1000
void testpoint(void);
struct d_complex{
    double r;   double i;
};
struct d_complex c;
int numoutside = 0;

int main(){
    int i, j;
    double area, error, eps = 1.0e-5;
#pragma omp parallel for default(shared) private(c,eps)
    for (i=0; i<NPOINTS; i++) {
        for (j=0; j<NPOINTS; j++) {
            c.r = -2.0+2.5*(double)(i)/(double)(NPOINTS)+eps;
            c.i = 1.125*(double)(j)/(double)(NPOINTS)+eps;
            testpoint();
        }
    }
    area=2.0*2.5*1.125*(double)(NPOINTS*NPOINTS-
numoutside)/(double)(NPOINTS*NPOINTS);
    error=area/(double)NPOINTS;
}
```

```
void testpoint(void){
    struct d_complex z;
    int iter;
    double temp;

    z=c;
    for (iter=0; iter<MXITR; iter++){
        temp = (z.r*z.r)-(z.i*z.i)+c.r;
        z.i = z.r*z.i*2+c.i;
        z.r = temp;
        if ((z.r*z.r+z.i*z.i)>4.0) {
            numoutside++;
            break;
        }
    }
}
```

```
#include <omp.h>
# define NPOINTS 1000
# define MXITR 1000
struct d_complex{
    double r;   double i;
};
void testpoint(struct d_complex);
struct d_complex c;
int numoutside = 0;

int main(){
    int i, j;
    double area, error, eps = 1.0e-5;
    #pragma omp parallel for default(shared) private(c, j) \
        firstprivate(eps)
    for (i=0; i<NPOINTS; i++) {
        for (j=0; j<NPOINTS; j++) {
            c.r = -2.0+2.5*(double)(i)/(double)(NPOINTS)+eps;
            c.i = 1.125*(double)(j)/(double)(NPOINTS)+eps;
            testpoint(c);
        }
    }
    area=2.0*2.5*1.125*(double)(NPOINTS*NPOINTS-numoutside)/(double)(NPOINTS*NPOINTS);
    error=area/(double)NPOINTS;
```

```
void testpoint(struct d_complex c){
    struct d_complex z;
    int iter;
    double temp;

    z=c;
    for (iter=0; iter<MXITR; iter++){
        temp = (z.r*z.r)-(z.i*z.i)+c.r;
        z.i = z.r*z.i*2+c.i;
        z.r = temp;
        if ((z.r*z.r+z.i*z.i)>4.0) {
            #pragma omp atomic
            numoutside++;
            break;
        }
    }
}
```

```
#include <omp.h>
static long num_steps = 100000;
double step;
void main ()
{ int i; double x, pi, sum = 0.0;
#pragma omp parallel for private(x) reduction(+:sum)
  step = 1.0/(double) num_steps;

  for (i=0;i< num_steps; i++){
    x = (i+0.5)*step;
    sum = sum + 4.0/(1.0+x*x);
  }
  pi = step * sum;
}
```



от *Introduction to OpenMP 11 part 2 Module 6* до *Introduction to OpenMP 13 Discussion 5*