

Използване на OpenMP. Част 2. for, barrier, section, master, single

Курс „Паралелно програмиране“



Стоян Мишев

$$\int_0^1 \frac{4}{1+x^2} dx = \pi$$

Loop
Section
Single
Task

Нишките изпълняват итерации с различен номер.

```
#pragma omp parallel  
  
{  
  #pragma omp for  
  for (l=0; l<N; l++){  
    NEAT_STUFF(l);  
  }  
}
```

Нишките изпълняват итерации с различен номер.

```
#pragma omp parallel
{
    #pragma omp for
    for (l=0; l<N; l++){
        NEAT_STUFF(l);
    }
}
```

```
double res[MAX]; int i;
#pragma omp parallel for
for (i=0; i<MAX; i++){
    res[i] = huge();
}
```

Съкратен запис:

```
1  int i = 0;
2  omp_set_num_threads(4);
3
4  printf("Total number of threads allocated in the
        serial section %d \n", omp_get_num_threads() );
5  #pragma omp parallel
6  {
7      #pragma omp for
8      for( i = 0; i < omp_get_num_threads(); i++) {
9          printf("This is run by thread %d, Total threads
                in the parallel section %d\n",
                omp_get_thread_num(), omp_get_num_threads());
10     }
11 }
```

<code>schedule(static [,chunk])</code>	Deal-out blocks of iterations of size "chunk" to each thread.
<code>schedule(dynamic[,chunk])</code>	Each thread grabs "chunk" iterations off a queue until all iterations have been handled.
<code>schedule(guided[,chunk])</code>	Threads dynamically grab blocks of iterations. The size of the block starts large and shrinks down to size "chunk" as the calculation proceeds.
<code>schedule(runtime)</code>	Schedule and chunk size taken from the OMP_SCHEDULE environment variable (or the runtime library).
<code>schedule(auto)</code>	Schedule is left up to the runtime to choose (does not have to be any of the above).


```
double ave=0.0, A[MAX]; int i;  
#pragma omp parallel for reduction (+:ave)  
    for (i=0;i<MAX; i++){  
        ave + = A[i];  
    }  
ave = ave/MAX;
```

```
double ave=0.0, A[MAX]; int i;  
#pragma omp parallel for reduction (+:ave)  
    for (i=0;i<MAX; i++){  
        ave + = A[i];  
    }  
ave = ave/MAX;
```

Operator	Initial Value
+	0
*	1
-	0
min	Largest pos num
max	Most neg num

```
#include <omp.h>
static long num_steps = 100000;    double step;
void main ()
{   int i;  double x, pi, sum = 0.0;
    step = 1.0/(double) num_steps;
    #pragma omp parallel
    {
        double x;
        #pragma omp for reduction(+:sum)
        for (i=0;i<num_steps; i++){
            x = (i+0.5)*step;
            sum = sum + 4.0/(1.0+x*x);
        }
    }
    pi = step * sum;
}
```

```
#include <omp.h>
static long num_steps = 100000;    double step;
void main ()
{   int i;  double x, pi, sum = 0.0;
    step = 1.0/(double) num_steps;
    #pragma omp parallel
    {
        double x;
        #pragma omp for reduction(+:sum)
        for (i=0;i<num_steps; i++){
            x = (i+0.5)*step;
            sum = sum + 4.0/(1.0+x*x);
        }
    }
    pi = step * sum;
}
```

Threads	1 st SPMD	1 st SPMD Padded	SPMD Critical	Pi Loop
1	1.86	1.86	1.87	1.91
2	1.03	1.01	1.01	1.02
3	1.08	0.69	0.68	0.80
4	0.97	0.53	0.53	0.68

```
#pragma omp parallel shared (A, B, C) private(id)
{
    id=omp_get_thread_num();
    A[id] = big_calc(id);
#pragma omp barrier
#pragma omp for
    for(i=0;i<N;i++){C[i]=big_calc3(i,A);}
#pragma omp for nowait
    for(i=0;i<N;i++){ B[i]=big_calc2(C, i); }
    A[id] = big_calc4(id);
}
```

Нишките изпълняват код от различни `section`

```
#pragma omp parallel
{
    #pragma omp sections
    {
        #pragma omp section
        x_calculation();
        #pragma omp section
        y_calculation();
        #pragma omp section
        z_calculation();
    }
}
```

```
1  int a = 6;
2  int b = 3;
3  omp_set_num_threads(4);
4  #pragma omp parallel
5  {
6      #pragma omp sections
7      {
8          #pragma omp section
9          {
10             printf("Sum = %d on thread %d \n", a + b,
11                    omp_get_thread_num());
12         }
13         #pragma omp section
14         {
15             printf("Difference = %d on thread %d \n", a - b,
16                    omp_get_thread_num());
17         }
18     }
19 }
```

Когато искаме някоя част от кода да се изпълни само от една нишка използваме `master` или `single`. При `single` нишката, която първа достигне до кода, го изпълнява, докото при `master` точно нишката с `id=0` изпълнява кода (, а останалите - не). Няма скрит `barrier` след `master`, но има скрит `barrier` след `single`.

```
#pragma omp parallel
{
    do_many_things();
#pragma omp master
    { exchange_boundaries(); }
#pragma omp barrier
    do_many_other_things();
}
```



```
1  int i = 0, N = 8;
2  omp_set_num_threads(N);
3  int *a, *b, *c;
4  #pragma omp parallel
5  {
6      #pragma omp master
7      {
8          a = malloc(N * sizeof(int));
9          b = malloc(N * sizeof(int));
10         c = malloc(N * sizeof(int));
11         srand(time(NULL));
12     }
13     #pragma omp for
14     for( i = 0; i < N; i++) {
15         a[i] = rand() % 10;
16         b[i] = rand() % 10;
17     }
18     #pragma omp for
19     for( i = 0; i < N; i++) {
20         c[i] = a[i] * b[i];
21     }
22     #pragma omp for
23     for( i = 0; i < N ; i++) {
24         printf("A[%d] * B[%d] = %d \n", i, i, c[i]);
25     }
```

```
#pragma omp parallel
{
    do_many_things();
#pragma omp single
    {  exchange_boundaries();  }
    do_many_other_things();
}
```

```
1  int i = 0, N = 8;
2  omp_set_num_threads(N);
3  int *a, *b, *c;
4  #pragma omp parallel
5  {
6      #pragma omp single
7      {
8          a = malloc(N * sizeof(int));
9          b = malloc(N * sizeof(int));
10         c = malloc(N * sizeof(int));
11         srand(time(NULL));
12     }
13     #pragma omp for
14     for( i = 0; i < N; i++) {
15         a[i] = rand() % 10;
16         b[i] = rand() % 10;
17     }
18     #pragma omp for
19     for( i = 0; i < N; i++) {
20         c[i] = a[i] * b[i];
21     }
22     #pragma omp for
23     for( i = 0; i < N ; i++) {
24         printf("A[%d] * B[%d] = %d \n", i, i, c[i]);
25     }
```

<https://www.youtube.com/watch?list=PLLbPZJxtMs4ZHSamRRYCtvowRS0qIwC-I>

От “Introduction to OpenMP 08 Discussion 3 ”
до “Introduction to OpenMP 11 part 1 Module 6”.