### Designing the speed limit

Speed limits may be reduced depending on the size of the reduction by one or a combination of the following:

- a speed limit sign
- a speed limit of intermediate value or a buffer zone
- a speed limit AHEAD sign.

Speed limit reductions must be implemented as provided in Table 5.6.

***Table 5.6: Method for reducing speed limit***

| Speed limit reduction | Method for reducing speed limit | Recommended applications | Alternative applications |
|---|---|---|---|
| 10 | Speed limit sign | 60 – 50<br>50 – 40<br>40 – 30 | |
| 20 | Speed limit sign<br>or<br>Speed limit AHEAD*<br>(alternative) | 100 – 80<br>80 – 60<br>60 – 40 | 100 – 80 AHEAD – 80*<br>80 – 60 AHEAD – 60*<br>60 – 40 AHEAD – 40* |
| 30 | Speed limit AHEAD<br>or<br>Speed limit sign<br>or<br>Speed limit signs<br>(alternative) | 110 – 80 AHEAD – 80<br>110 – 80<br>90 – 60 AHEAD – 60<br>90 – 60<br>70 – 40 AHEAD – 40<br>70 – 40 | 110 – 100 – 80<br>90 – 80 – 60<br>70 – 60 – 40 |
| 40 | Speed limit AHEAD<br>or<br>Speed limit signs | 100 – 80 – 60<br>100 – 60 AHEAD – 60<br>80 – 60 – 40<br>80 – 40 AHEAD – 40 | |
| 50 | Speed limit signs<br>and/or<br>Speed limit AHEAD | 110 – 80 – 60<br>110 – 80 AHEAD – 80 – 60<br>100 – 80 – 50<br>100 – 80 – 50 AHEAD – 50<br>90 – 60 – 40<br>90 – 60 AHEAD – 60 – 40 | 110 – 80 – 60 AHEAD – 60<br><br>100 – 80 AHEAD – 80 – 50 |
| 60 | Speed limit signs<br>and/or<br>Speed limit AHEAD | 110 – 80 – 60 – 50<br>110 – 80 AHEAD – 80 – 50<br>110 – 80 – 50 AHEAD – 50<br>100 – 80 – 60 – 40<br>100 – 60 AHEAD – 60 – 40<br>100 – 80 – 40 AHEAD – 40 | 110 – 80 – 50 |
| 70 | Speed limit signs<br>and/or<br>Speed limit AHEAD | 110 – 80 – 60 – 40<br>110 – 80 AHEAD – 80 – 60 – 40<br>110 – 80 – 40 AHEAD – 40 | 110 – 80 – 60 – 40 AHEAD – 40*<br>110 – 80 – 60 AHEAD – 60 – 40* |

*May be used where additional advance warning of speed limit reduction is required