

Item (Generic / Site Specific)		Risk Event	Consequence	Pre-treatment Risk			Treatment	Residual Risk				
				L	C	RR		L	C	RR		
3.2.	2	3	G	Traffic control points during night time hours having poor visibility due to artificial illumination resulting in serious injury or fatality.	Serious injuries to Traffic Controllers operating at Traffic Control points.	C	4	H12	All Traffic Control points during night time hours must be at existing street lighting or portable lighting towers must be installed. Traffic Controllers operating during night time hours must use night wands to direct traffic. Traffic Controllers must always be aware of their proposed escape routes and be aware of incoming vehicles and hazards.	D	4	M8
3.2.	2	4	G	Insufficient illumination of temporary cross over points or lateral shift locations causing road users to crash through the proposed Temporary Traffic Management setups resulting in property damage.	Property damage to Traffic Management devices and road user vehicles.	C	3	M9	Signs and devices to be installed through temporary shifts which must be retro-reflective. Temporary lighting towers should also be utilised at locations where the existing lighting is insufficient. Drive throughs must be completed periodically during the works to ensure the setups are safe.	D	3	L6
3.2.	2	5	G	Sun glare at dawn or dusk on East/West facing road alignments causing poor visibility to advanced warning signs and other devices resulting in serious injury or fatality to personnel and property damage.	Serious injury or fatality to personnel.	C	4	H12	Immediately after setup is complete a site visit must be conducted to determine the eligibility of signs and devices on approach to worksite. Signs may be angled or positioned/adjusted as per the tolerances to accommodate for poor visibility due to sun glare. Where the signs and devices cannot be adjusted, the works may be postponed to a time not affected by sun glare.	D	4	M8
3.2.	2	6	G		Property damage to Traffic Management devices and road user vehicles.	C	3	M9		D	3	L6
3.2.	2	7	G	Crests and curves causing reduced visibility of the worksite and implemented traffic control resulting in serious injury or fatality to personnel and property damage.	Serious injury or fatality to personnel.	C	4	H12	Traffic Management Assessor or Project Delivery Supervisor must provide details where on-site geometry or furniture may impact on signage positions. Sign locations can be staggered to assist driver’s visibility, in accordance with the tolerances provided. To accommodate reduced sight distances from curves and crests, Site Supervisor can move or angle signage. Site Supervisor to record changes in the daily diary as required.	D	4	M8
3.2.	2	8	G		Property damage to Traffic Management devices and road user vehicles.	C	3	M9		D	3	L6