

Item (Generic / Site Specific)		Risk Event	Consequence	Pre-treatment Risk			Treatment	Residual Risk		
				L	C	RR		L	C	RR
3.2. 19		Heavy and Wide Vehicle Network Impacts								
3.2. 19	1 G	Restrictions placed on traffic lane widths and corner geometries by temporary traffic management impacting heavy haulage traffic routes resulting in adverse public reaction and property damage.	Adverse public reaction and property damage to road infrastructure or trucks.	C	3	M9	Notification is required to Heavy Vehicle Services prior to works commencement. Details of temporary lane widths are required. Where corner geometry or lane widths cannot accommodate heavy vehicles, detours or provisions to escort trucks are required. Where large or oversized trucks are moving through the site, accredited Traffic Management Personnel are required to ensure there is sufficient carriageway width. Workers and plant will be required to clear the worksite during heavy vehicle escorts. Temporary alignment swept paths may be provided to assess if a heavy vehicle network is affected by the works. Traffic Management Personnel on site must manage UHF Chanel 40 and communicate with heavy vehicle operators and pilots as required.	D	3	L6
3.2. 19	2 G	Restrictions on lane widths causing wide loads approaching the site to not be able to pass TM setups resulting in damaged equipment, serious injuries, or fatality.	Damage equipment.	C	3	M9	Traffic Management Personnel to allow oversize vehicles passage at the earliest suitable time. Traffic Management Personnel and Heavy Vehicle truck drivers will remain in constant communication over UHF channel 40. Traffic Management Personnel to act as a spotter for workers close to the trafficable lane to stand down until the vehicle has past and to move any signs or delineation to allow the oversized vehicle to pass safely.	D	3	L6
3.2. 19	3 G		Serious injuries, or fatality.	C	4	H12		D	4	M8
3.2. 19	4 G	Heavy vehicles unable / failing to slow or stop as per the proposed Temporary Traffic Management setups causing them to collide with worksite resulting in serious injury or fatality.	Serious injury or fatality.	C	4	H12	End of queue protection to be applied as per the advice in this Traffic Management Plan and MRWA CoP. Sign spacing may be increased on-site as per the tolerances provided to accommodate vehicle stopping distances. Traffic Controllers to have suitable escape routes and must face the approaching traffic at all times.	D	4	M8