

Item (Generic / Site Specific)		Risk Event	Consequence	Pre-treatment Risk			Treatment	Residual Risk			
				L	C	RR		L	C	RR	
3.2. 20		Works on High Speed & Volume Roads / Proposed Temporary Speed Zones / Works off Road Setups									
3.2. 20	1 G	Traffic management light vehicle used as shadow vehicle on high speed / volume highway or freeway in the metropolitan area causing unsafe work environments for TCs and workers resulting in serious injury or fatality.	Serious injury or fatality.	C	4	H12	A TMA shall be used where meeting the requirements listed within this document, Main Roads Code of Practice and in the Requirements for use of Truck Mounted Attenuators document. TMA to be deployed and positioned to protect workers or TCs when operating with the live lane or when works occur on the Freeway.	D	4	M8	
3.2. 20	2 G	Traffic not adhering to proposed temporary speed zones causing an increased potential for conflicts between workers and motorists resulting in serious injury or fatality.	Serious injury or fatality.	C	4	H12	Police intervention is required to enforce implemented speed zones where excessive speeding occurs. This plan outlines the requirements for speed compliance by using speed sign repeaters, narrowing lane widths and close space delineation. Speed zones will follow the minimum and maximum lengths provided in AGTTM Part 3 Table 5.5. A site-specific variation to the AGTTM Part 3 standard is required where speed zone lengths exceed those specified in the standards.	D	4	M8	
3.2. 20	3 G	Traffic speed on affected routes in traffic lanes adjacent to the worksite creating hazardous worksites and unsafe worksite access.	Potential injury or fatality to road users, project personnel or sub-contractors.	B	4	V16	Temporary speeds zones will reduce risk to motorists, workers and work plant. This TMP and associated drawings outline the requirements for temporary speed zones and follow the requirements per the AGTTM and MRWA CoP standards.	D	4	M8	
3.2. 20	4 G	Workers within 1.2m of live traffic lanes with an existing or temporary speed greater than 40km/h causing an increase in severity of crashes resulting in serious injury or fatality.	Serious injury or fatality.	B	4	V16	A temporary 40km/h speed zone shall be implemented on the approach to the worksite where workers are within 1.2m. Spotters may be used on site to warn of approaching vehicles. Worker clearzones and escape routes to be maintained at all times.	D	4	M8	