

Item (Generic / Site Specific)		Risk Event	Consequence	Pre-treatment Risk			Treatment	Residual Risk			
				L	C	RR		L	C	RR	
3.2.	20	5 G	Workers within 3m of live traffic lanes with an existing or temporary speed greater than 60km/h causing an increase in severity of crashes resulting in serious injury or fatality.	Serious injury or fatality.	B	4	V16	A temporary 60km/h speed zone shall be implemented on the approach to the worksite where workers are between 1.2m and 3m. A temporary 40km/h speed zone shall be implemented on the approach to the worksite where workers are within 1.2m. Spotters may be used on site to warn of approaching vehicles. Worker clearzones and escape routes to be maintained at all times and instructed prior to the start of the shift.	D	4	M8
3.2.	20	6 G	TM implemented or removed on high speed roads causing an increased severity in crashes resulting in serious injuries or fatality.	Serious injury or fatality.	C	4	H12	Traffic Management vehicle to shadow workers implementing signs at all times and a TMA is required as per the MRWA CoP and Requirements for use of Truck Mounted Attenuators documents. Temporary speed zones to be implemented to reduce the speed of adjacent live traffic lanes on the shadow vehicle VMS screen. A spotter is to watch for any vehicles that may pose a threat to the workers on foot.	D	4	M8
3.2.		21	Variations to AGTTM, AS 1742.3 and Main Roads Code of Practice								
3.2.	21	1 G	No speed reinstatement on some Mobile Works Convoys due to lack of lead vehicle causing vehicles to be unsure of end of temporary speed zone. AGTTM Part 4 Mobile Works Section 3.8.4 Mobile Temporary Speed Zone requires 'For works where a lead vehicle is not required, the speed zone must be placed between the work vehicle and the shadow vehicle'.	Adverse public reaction.	B	3	H12	There is only 20-40m between the shadow vehicle and work vehicle which is to display the temporary speed sign and termination speed sign which may cause conflicting messages to road users. Road users may increase speed between the shadow vehicle and work vehicle increasing risk to the work vehicle. In the metropolitan area the number of repeater speed signs is frequent. For rural areas, where an on-site risk assessment identifies insufficient repeaters or significant impacts to road users, an additional lead vehicle should be implemented.	C	3	M9