

Where applicable, the MRWA Traffic Management Code of Practice further expands volumes based on speed and duration of works which may be used as follows:

Freeways and Controlled Access Highways:

Table 12: Variation to Traffic Volumes – MRWA Code of practice Table 20

Between ramps			Within 200m of an entry ramp*		
40 km/h	60 km/h	80 km/h	40 km/h	60 km/h	80 km/h
1200	1400	1600	700	900	1100

**Applies from the start of the end of the gore area and start of the continuity or lane line. This does not apply where the entry-ramp becomes an additional lane.*

Where single lane operation (reversible flow) is used the following table outlines the recommended capacity based on the length of reversible flow. This should be used when determining the proposed work times and lengths must be calculated from the STOP HERE WHEN DIRECTED / STOPHERE ON RED SIGNAL sign position in each direction:

Table 13: Maximum Length of Operation under Shuttle Flow – MRWA CoP Table 15

Traffic Volume in both Directions (vph)	Length of Single Lane Section (m)
Residential Street	60
701 – 800	70
601 – 700	100
501 – 600	150
401 – 500	250
351 – 400	400
301 – 350	600
*251 -300	800
*201 – 250	1200
*151 – 200	1600
*<150	2200

** These shuttle lengths must only be used subject to a risk assessment approved by the Road Infrastructure Manager*

The Traffic Management Assessor or Delivery Supervisor must determine the impact on lane capacity using historical traffic data prior to the implementation of any Traffic Management. Traffic volumes for each work location must be assessed with the requirements detailed the tables above and the MRWA risk tables listed in section 3 of this document to ensure the predicted Level of Service (LoS) is acceptable.

Allowable work times should be determined and communicated with workers and Traffic Management Implementors. Refer to the Tables above, and Main Roads Code of Practice for more information on Traffic Management at worksites and traffic analysis. Where the works may occur significant impacts to the Main Roads Network prior notifications and approvals may be required. Where possible, traffic flow should be maintained at all times.