

4.5.1 Truck Mounted Attenuators

A TMA must be provided where all the criteria is met in any of the below scenarios:

Table 20: Main Roads Requirements for the use of Truck Mounted Attenuators Code of Practice

Scenario 1 – Works on a Freeway in a Live Traffic Lane (Including TM set up and pack up)

Criteria	Yes/No
1 The works occur on a Freeway (includes mobile works).	
2 The work area is within a traffic lane.	
3 The work area has not been separated or protected by a full road closure or road safety barrier.	

Scenario 2 – Work on Freeway not Within Live Traffic Lane (including TM set up and pack up)

Criteria	Yes/No
1 The works occur on a Freeway (includes mobile works).	
2 Work area is within 3m of the traffic lane.	
3 The works will take longer than 20 minutes (even if mobile).	
4 The work area has not been separated or protected by a full road closure or road safety barrier.	

Scenario 3 – Frequently Changing Work Area on Freeway

Criteria	Yes/No
1 Activities that involve slow moving vehicles* and/or a frequently changing work area that occurs on more than 1km total length of the named road (e.g. litter collection).	
2 The activity occurs on a Freeway.	
3 Work area is within 3m of the traffic lane.	
4 The work area has not been separated or protected by a full road closure or road safety barrier.	

*Vehicles travelling more than 20km/h below the speed limit.

Scenario 4 – Works on High-speed Grade Separated Roads

Criteria	Yes/No
1 The posted speed limit prior to road works is 90km/h or more.	
2 The road is a grade separated road with 20,000 vpd or more.	
3 The work area is within a traffic lane (includes mobile works).	
4 The work area has not been separated or protected by a full road closure or road safety barrier.	

Scenario 5 – Works on High-speed Multi-lane Roads in the Metropolitan Area

Criteria	Yes/No
1 The posted speed limit prior to road works is 90km/h or more (including sections reduced due to traffic signals).	
2 The road is a multi-lane road in the metropolitan area with 15,000 vpd or more.	
3 The work area is within a traffic lane (includes mobile works).	
4 The work area has not been separated or protected by a full road closure or road safety barrier.	

Truck Mounted Attenuators (TMA) are required to replace the shadow vehicle in mobile convoys under the following environments:

- Roads with a speed limit of 80km/h or more and 3,000 vpd or more.
- When conducting longitudinal road marking on state roads with a speed limit 80km/h or more.