

Temporary line markings will consist of raised retro reflective markers. Temporary reflective pavement markers will be of the type manufactured with butyl adhesive base that allows easy and quick placement on the road surface.

The markers will be fitted with retro-reflective tape on either one or both sides and shall be 100mm wide by 50mm high. The road surface is to have markers applied in accordance with the manufacturer's recommendations. Inspection of all temporary pavement markers are required daily and any loss or displacement made good immediately.

The following table details further requirements for temporary RRPMS:

Table 22: Details for Temporary RRPM Installation

Temporary RRPM's				
Posted Speed	Pavement Marking	Length of one Patch		More than two Patches within a 100m section of road
		Less than 20m	Less than 20m	
40 – 60	Dividing Line	N	Y	N
	Lane Line	N	Y	N
	Edge Line	N	Y	N
70 – 80	Dividing Line	Y	Y	Y
	Lane Line	N	Y	N
	Edge Line	N	Y	N
90 – 100	Dividing Line	Y	Y	Y
	Lane Line	N	Y	Y
	Edge Line	N	Y	Y
110	Dividing Line	Y	Y	Y
	Lane Line	N	Y	Y
	Edge Line	N	Y	Y

Table 23: Details for Raised Reflective Pavement Markers – AS 1742.2 2009 Table 5.3

Application	RRPM Colour
Dividing lines	Yellow
Lane lines (excluding tram lane lines)	White
Right hand edge line, divided road	Yellow
Left hand edge line, divided road	Red
Left hand edge line, 2-way road	Red
Tram lane lines	Yellow
Small ¹ channelizing island outline, painted or raised – all sides	White
Median island outline, painted or raised – all sides	Yellow
Roadway diverge outline, including expressway exit nose and approach end of large island: - Left² side - Right² side	Yellow Red
Step out markings at expressway exit ramps	Green

¹ A small island should generally be regarded as one with no side, including approach and departure marking, longer than 12 metres

² Left or right when viewed in the direction of travel.

Substitution to the RRPM colours in the above table is not supported by Main Roads.