

The typical Temporary Traffic Management requirements for working in gaps of traffic may include a lookout person and a work vehicle fitted with a vehicle mounted warning device. This practice may only be used where all the following criteria can be met:

Table 24: AGTTM Part 5 Section 4.2.2 Table 4.1: Work Between Gaps in Traffic Criteria

Criteria		Yes/No
1.	The work area is within a traffic lane	
2.	The works can be undertaken safely with road workers entering and exiting the road in gaps in traffic.	
3.	Traffic is not impeded in any way.	
4.	The road surface can remain trafficable without hazard to traffic	
5.	A lookout person is available to warning workers on foot to vacate the roadway before the arrival of approaching traffic (refer to TGS for sight distance to vehicle mounted warning device table)	
6.	A vehicle mounted warning device is displayed on the work vehicle and not obscured when the vehicle can be parked adjacent to the worker location.	
7.	Work vehicles and equipment are parked clear of moving traffic lanes.	

Equipment or materials which are brought onto the work area should be unloaded from the non-traffic side of a stationary work vehicle, or the rear of a stationary work vehicle with a lookout person or shadow vehicle in place.

The works vehicles placement should consider the impact on vulnerable road users including cyclists. The worker must always have a clear exit path from the road and ensure that this is not blocked by the placement of the work vehicle. **Criteria 5** the lookout person may be dispensed with if the work task takes 10 seconds or less to complete and the sight distance of approaching traffic to the vehicle mounted warning device is a minimum distance as per the Table 25 below. The worker must be required to be aware of the approaching vehicles within the distance if no lookout person is required. Where a lookout person is used on site, they must be positioned adjacent to the worker so that they can view approaching traffic in time to warn the worker. Enough time must be provided to allow the worker to vacate the live traffic lanes prior to the vehicle approaching. Recommended lookout person sight distance is shown in the Table 25 below (maximum distance of 3.5m between road workers' location and their escape path):

Table 25: AGTTM Part 5 Section 4.2.5 Table 4.3: Sight Distance for Lookout Person

Speed (km/h)	Distance (m)
≤ 45	80
46 – 55	100
56 – 65	120
66 – 75	140
76 – 85	160
86 – 95	180
96 – 110	200
>110	220

Work between gaps of traffic is not recommended on multi-lane roads where traffic volumes exceed 100vph/pl unless significant gaps are being created by upstream traffic control devices such as intersection traffic signals. The below

Table 26 outlines the minimum sight distance requirements for the vehicle mounted warning device (distances are based on a travel length within 20 seconds):