

**Table 27: AGTTM Part 5 Section 4.3.2 Table 4.4: Short-term Works in Traffic
Within 1.2m or Partially in Lane**

Criteria	Yes/No
1 The work area is within 1.2m of a traffic lane or partially within a traffic lane.	
2 Works take 5 minutes or less.	
3 A lookout person is available to warn workers on foot to vacate the roadway before the arrival of approaching traffic which is not altering path to pass the worksite.	
4 A vehicle mounted warning device is displayed on the work vehicles and not obscured.	
5 There is a minimum sight distance from approaching road users to the vehicle mounted warning device of: 150m if the speed is 60km/h or less. 250m if the speed is more than 60km/h.	
6 Works do not reduce the overall lane width to a centreline to less than 3.5m or if the volume is less than 50vpd, less than 3.3m.	
7 Works do not reduce any traffic lane width adjacent to a barrier line to less than that needed to allow vehicles to proceed without crossing the line.	

**Table 28: AGTTM Part 5 Section 4.3.2 Table 4.4: Short-term Works in Traffic
Between 1.2m and 3.0m of Traffic**

Criteria	Yes/No
1 The work area is between 1.2m and 3.0m of moving traffic.	
2 Works take 20 minutes or less.	
3 A lookout person is available to warn workers on foot to vacate the roadway before the arrival of approaching traffic.	
4 A vehicle mounted warning device is displayed on the work vehicles and not obscured.	
5 There is a minimum sight distance from approaching road users to the vehicle mounted warning device of: 150m if the speed is 60km/h or less. 250m if the speed is more than 60km/h.	

Where two or more locations within a space of 2km or less require work to be undertaken, the methods listed in Frequently Changing Work Area below must apply. The works vehicles placement should consider the impact on vulnerable road users including cyclists. Equipment or materials which are brought onto the work area should be unloaded from the non-traffic side of a stationary work vehicle, or the rear of a stationary work vehicle with a lookout person or shadow vehicle in place.

The work vehicle must be located adjacent to, or on approach (within 40m) to the worksite in the primary direction of travel to the works if undertaking works in a single location. Where this is not achievable, due to site constraints, this practice must not be used.

The lookout person must be positioned adjacent to the worker so that they can view approaching traffic in time to warn the worker. Enough time must be provided to allow the worker to vacate the live traffic lanes prior to the vehicle approaching. At all times during the works, the lookout person and the worker must be within a reasonable proximity (no more than 40m) of the vehicle with a vehicle mounted warning device. Recommended lookout person sight distance is shown in the table below (maximum distance of 3.5m between road workers' location and their escape path):