

#### 4.8.1.7 Works off Road – Shoulder, Medians, Verges and Footpaths with Large Plant Items

This practice may be used where the works are completely off the road and involve large items of plant. This works must be contained within the shoulder, median, verge or footpath and must not encroach into live traffic lanes. Refer to AGTTM Part 5 Section 5.2 – Shoulders, Medians, Verges and Large Plant Items Only and **0922-01531-STLI-013**.

This practice is best suited to the following tasks (does not include all tasks):

- Mowing, tilling, seeding, weed spraying.
- Minor tree clearing.
- Herbicide spraying.
- Road edge guidepost installation/repairs.

The typical Temporary Traffic Management requirements for this works may include advanced warning signs and a vehicle mounted warning device on the works vehicle.

This practice may only be used where all the criteria is met in the tables below:

**Table 40: AGTTM Part 5 Section 5.2.2 Table 5.3: Works on Shoulders, Medians, Verges and Footpaths Large Items of Plant**

| Criteria                                                                                                                                                                                                                                                                     | Yes/No |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| 1 The work area is outside of traffic lanes.                                                                                                                                                                                                                                 |        |
| 2 No workers on foot are required.                                                                                                                                                                                                                                           |        |
| 3 Clearance from the work area to the edge of the traffic lane is: <ul style="list-style-type: none"> <li>• Greater than 1.2m where the speed limit is more than 80km/h.</li> <li>• May be less than 1.2m where speed limit is 80km/h or less (no plant in lanes)</li> </ul> |        |
| 4 A vehicle mounted warning device is displayed on each large plant item, is not obscured and meets the recommended sight distance requirements table below.                                                                                                                 |        |

**Table 41: AGTTM Part 5 Section 5.2.2 Table 5.4: Sight Distance to the Vehicle Mounted Warning Device**

| Speed (km/h) | Distance (m) |
|--------------|--------------|
| ≤ 45         | 80           |
| 46 – 55      | 100          |
| 56 – 65      | 120          |
| 66 – 75      | 140          |
| 76 – 85      | 160          |
| 86 – 95      | 180          |
| 96 – 105     | 200          |
| > 105        | 220          |

The advanced warning signs must be displayed up to 2km in advance of each work location or item of moving plant. A maximum distance of 2km between advance warning signs for opposing directions of travel must not be exceeded at any time by progressively changing their location as the work location changes. The start of the work area in relation to the advanced or intermediate warning signs in a mobile convoy must be within distances specified below:

**Table 42: AGTTM Part 5 Section 2.4.2 Table 2.3: Sign Spacing**

| Speed (km/h) | Distance (m)              |
|--------------|---------------------------|
| ≤ 55         | 15                        |
| 56 – 65      | 45                        |
| > 66         | Equal to the speed (km/h) |

The required advanced warning signs, to be erected by workers, should be done so in a manner that does not expose workers to oncoming traffic. Install signs so that the nearest edge is clear of the travelled path of vehicles and so that the signs are clearly visible to all oncoming vehicles.