

5. SITE ASSESSMENT

5.1 Provision to Address Environmental Conditions

5.1.1.1 Adverse Weather

The weather may influence the effectiveness of the traffic control detailed in the Traffic Management Advice and Traffic Guidance Schemes. Where significant impacts occur on site the following contingency plans should be used.

Note: any adjustments to the plan outside the tolerances provided in AGTTM shall be risk assessed and approved by someone holding a WTM or AWTM accreditation. Major changes will require Road Infrastructure Manager approval.

5.1.1.2 Rain

In the event of rain, Traffic controllers must perform an on-site assessment and sign spacing and tapers may require extending by 25% to account for increased stopping distances. Placement of “Slippery When Wet” signs as required and all changes recorded in the daily diary.

Where rain occurs, Traffic Controllers shall audit the site. Where signs and / or devices are not clearly visible, Traffic Controllers shall adjust signage to improve visibility or if necessary, provide additional signage and delineation. If the wet surfaces are affecting the stopping distance, Traffic Controllers shall adjust spacing between signs to provide increased reaction time for drivers. In cases where it is determined that the rain is heavy and the risk unacceptable; all work shall cease until rain has cleared. The daily diary is to capture all the changes made by the traffic controllers.

5.1.1.3 Floods

Should works be affected by flooding to the extent that the worksite becomes impassable or risk is considered unacceptable, all work shall cease immediately and Traffic Controllers (and other personnel if necessary) shall be deployed immediately to close the site and direct traffic around the flooded area (under the direction of the Delivery Supervisor or traffic manager). Emergency services and the Road Infrastructure Manager shall be notified immediately and Traffic Controllers shall remain onsite until emergency services and the Road Infrastructure Manager personnel arrive and take control of the site.

5.1.1.4 Other Adverse Weather (strong winds, thunder storms, etc.)

Where strong or damaging winds may impact signage placement, signs are to be weighted to ensure they do not fall over. Regular site checks to be conducted to ensure all signage integrity. Where significant impacts are expected prior to the works commencing, the works should be delayed or suspended.

5.1.2 Sun Glare

Where sun glare is adversely affecting a driver’s ability to sight signs and / or traffic control devices, Traffic Controllers shall adjust sign locations and provide additional delineation and traffic control devices necessary to address the risk from glare. Additionally, in the event that sunrise and sunset causes glare, traffic controllers will assist in maintaining low traffic speeds. The daily diary is to capture all the changes made by the traffic controllers.