

5.1.3 Fog/Dust/Smoke

Where fog, dust or smoke is identified as adversely affecting a driver's ability to sight signage and / or traffic control devices, sign locations may need to be adjusted and additional delineation and/or traffic control devices provided to address the risk. All changes are to be noted in the daily diary.

Should works be affected by fog, dust or smoke to the extent that risk is considered unacceptable, all work shall cease immediately and Traffic Controllers (and other personnel if necessary) shall be deployed immediately to close the site.

5.1.4 Road Geometry, Terrain, Vegetation and Structures

The Traffic Management Assessor or Delivery Supervisor must ensure that the Traffic Guidance Schemes and advice provided accommodates geometric design of the road on approach, through and departing the worksite. This should include roadside furniture, curves, bends, crests, through terrain, vegetation and structures.

Should the sight distance of traffic management devices, the traffic management personnel on site be affected, adjustments as necessary may be made and recorded in the daily diary. Where the adjustments exceed those given in section 7.3.2 of this Traffic Management Plan, an accredited AWTM person is required to approve the changes prior to work commencing.

The following requirements from Section 6.17.1 of the MRWA Code of Practice must be adhered to:

- Merge tapers should not start or end:
 - Within 50 metres of the controlled leg of an intersection (both approach and departure sides) on a Category 2 road.
 - If site constraints make it unavoidable to place a taper within this zone, a generic risk assessment has been included in this TMP. However, this option should only be considered after all other alternatives have been exhausted.
 - Within 100 metres of an intersection (both approach and departure sides) located on a ramp to/from a Category 3 road.
 - Within 100 metres of a ramp (on or off) on a Category 3 road.
- Merge tapers on an uncontrolled leg of an intersection on a Category 2 road should not start or end within 50 metres of the intersection (both approach and departure sides).
 - *If site constraints require a taper within this distance, a risk assessment has been provided in this TMP. This must only be used after all other alternatives have been considered.*
- Merge tapers must not be implemented through or across an intersection or ramp.

5.2 Existing Traffic and Advertising Signage

Covering is required for existing traffic signs that are contrary to the temporary traffic control and are within the traffic control zone. These include but are not limited to the posted speed limit signs within the section of road under temporary speed restriction. The Traffic Management Assessor or Delivery Supervisor should identify signs to be covered within the temporary traffic management setup. Where signs are identified on site as contradictory by the Traffic Management Implementor any adjustments made must be noted in the Daily Dairy.

Existing advertisement signs must not distract from the temporary traffic management setups.