

- turn around procedures must be conducted in a safe and legal manner
- Traffic Management Implementer must face the traffic when placing devices
- all workers must know their escape route at all times
- the vehicle mounted warning device must be operating and the hazard/arrow board used as required
- all workers must wear correct PPE
- a look out person/spotter must be used for all activities where required in accordance with AGTTM Part 5
- full co-ordination of any ITS infrastructure which may assist the Traffic Guidance Schemes installation
- the locations and types of devices are recorded in the diary
- the Traffic Guidance Schemes is implemented as approved and a copy is available on site.

If it is considered too dangerous due to speed or volume to install the Traffic Guidance Schemes using the protections defined in AGTTM Part 5, then consideration needs to be given to adopting a mobile convoy (refer AGTTM Part 4) or other controls e.g. manual traffic control to hold traffic during installation under its own Traffic Guidance Schemes (refer AGTTM Part 3). A different installation sequence may need to be adopted to address any site-specific circumstances and can be approved by Traffic Management Designer or other authorised person.

7.2.3 Installation Process

The general procedure for setting up a site is to:

1. locate the work area using GPS, landmarks, side streets, chainage
2. install devices as outlined in the Traffic Guidance Schemes for side streets first
3. install devices as outlined in the Traffic Guidance Schemes for the non-working lane (un-affected direction)
4. install devices as outlined in the Traffic Guidance Schemes for the working lane (affected direction) to complete installation.
5. conduct a drive through inspection after all devices are in place and before work commences

All sign spacings and taper lengths will be noted on the Traffic Guidance Schemes and should be in accordance with AGTTM Part 3.

7.2.4 Placement of Signs and Devices (*AGTTM Part 6 Field Staff – Implementation and Operation*)

The scenarios in AGTTM Part 6 Field Staff – Implementation and Operation Section 6.4 are designed to encourage workers to review the safest installation process. Many factors can influence the appropriate sequence for installation including but not limited to road geometry, hills, crests, curves, surface condition, lane widths, shoulder width, traffic volumes, peak traffic flows, road user travel speed, road user make up (e.g. % of heavy vehicles or cyclists), lighting and time of day, and weather.

If the Traffic Management Plan does not contain specific advice on the installation order for Traffic Guidance Schemes, AGTTM Part 6, Section 6.4 gives several scenarios for the typical installation with diagrams and steps to facilitate safe installation. These diagrams can be referred to when Traffic Management Implementer's are preparing for installation. The scenarios include:

- Two-way road - lane closure
- Two-way road (lateral shift)
- Two-way road - lane closure with side roads
- Multi-lane un-divided road - lane closure
- Multi-lane divided road - left or right lane closure