

7.3.4 Delineation and Edge Clearance

Cones shall be used for delineation unless another treatment is specified in the Traffic Management Plan or on the Traffic Guidance Schemes. All cones shall be at least 700 millimetres in height (and be fitted with Class 1 reflective banner for night works) and constructed from fluorescent orange or red material that is resilient to impact and will not damage vehicles when hit at low speed. Cones shall be designed to be stable under reasonably expected wind conditions and air turbulence from passing traffic.

The base of the cones will be secured so that they are not dislodged by traffic. Cones will be inspected at intervals necessary to ensure any misalignment or displacement is identified and corrected prior to this causing disruption to traffic.

Where specified, temporary frangible or otherwise non-hazardous delineator posts or bollards may be used for edge protection and taper delineation. Posts or bollards shall have a maximum dimension of 60 millimetres when measured along the longest side of a square or rectangular section or across the diameter of a circular section. Base design shall permit easy fixing to either sealed or unsealed surfaces and not intrude into traffic lanes greater than 50 millimetres from the face of the post or bollard.

All posts or bollards shall be erected in accordance with the Traffic Guidance Schemes. Posts and bollards shall be a minimum of 1000 mm. high, capable of being fixed to the road pavement by a suitable road adhesive or by fastening bolts or spikes. Fixing shall be in accordance with manufacturer's recommendations. All posts or bollards will be inspected daily and where displaced or missing made good immediately. All delineator posts are to be completely removed at the completion of all stages of construction and prior to the placement of asphalt surfacing. If adhesive is used to affix the posts this shall be completely removed from the road surface so that a flush surface is obtained.

The spacing between delineation devices should be as detailed in AGTTM Part 3: Static Worksites Table 4.2. These are maximum measurements and can be reduced (e.g on curves at night). If there is a risk that road users may take a wrong turn or take the wrong path, the spacing may be reduced to a minimum of 1m.

Cone and other delineation spacing will be as per the table below:

Table 50: 'Through' spacing of traffic cones, bollards and post-mounted delineators – AGTTM Part 3 Table

4.2		
Purpose and usage	Speed (km/h)	Recommended maximum spacing (m)
For traffic cones and bollards**		
All purposes	<55	4
	56 - 75	12
	>76	18
Protecting freshly painted lines	56 – 75	24
	>76	60
For post-mounted delineators		
All purposes	<75	24
	>76	60

*****Consider whether cyclists are using the road shoulder or bike lane and whether an appropriate alternative facility be provided before installing traffic cones or bollards in the area. Where possible, place bollards to maintain a safe cycling facility.***