

A		B		C		D		E		F		G		H	
SCENARIO IA:												IMPLEMENTATION PROCEDURES		NOTES	
FLASHING CORNERS TM VEHICLE TC WITH SIGN LI DISTANCE L2 DISTANCE ADVANCED WARNING INTERMEDIATE SIGNAGE TAPER/BUFFER/WORKSITE TERMINATION SIGNS COLD SIDE LIVE SIDE DRIVER TO BE USED AS SPOTTER TO WATCH FOR ERRANT VEHICLES												SCENARIO IA: 1. EACH SIGN IS TO BE INSTALLED AS PER TGS-IW-002 SCENARIO I. 2. THIS SCENARIO IS TO BE USED ON DUAL CARRIAGEWAYS WITH A POSTED SPEED LESS THAN 80KM/H AND WHERE THERE IS ENOUGH ROOM IN THE VERGE/MEDIAN TO PARK THE TM VEHICLE. 3. VEHICLE TO ENTER AND EXIT THE ROAD WAY BETWEEN GAPS IN TRAFFIC TO INSTALL SIGNS IN A CONTINUOUS LINE. 4. VEHICLE TO RESET AT START OF SIGNAGE INSTALLATION FOR SIGNAGE ON THE OTHER SIDE OF THE ROAD.		DOCUMENTATION ON-SITE VARIATIONS MUST BE APPROVED BY THE TRAFFIC MANAGEMENT SUPERVISOR, THAN AN ON-SITE VARIATION MADE AND CHANGES RECORDED IN THE DAILY DAIRY. FOR MORE INFORMATION REFER TO SECTION 9.3 OF THE TMP. 1. TM VEHICLE SHALL BE ANY OF THE FOLLOWING: 1.1. TRAFFIC MANAGEMENT UTE 1.2. UTE WITH ARROW BOARD 1.3. CONE TRUCK 1.4. MR TRUCK 1.5. HR TRUCK 1.6. TRUCK MOUNTED ATTENUATOR 2. THIS DRAWING IS FOR IMPLEMENTATION ONLY AND MUST BE USED IN CONJUNCTION WITH AN APPROVED TRAFFIC MANAGEMENT LAYOUT TGS. 3. THIS DRAWING IS TO BE USED AS A GUIDELINE FOR THE TYPICAL SIGNAGE INSTALLATION AND MAY CHANGE DEPENDING SITE REQUIREMENTS. 4. THIS SCENARIO IS TO BE USED ON ROADS WITH A POSTED SPEED LESS THAN 80km/h. 5. A SHADOW VEHICLE MAY NOT BE REQUIRED SUBJECT TO A ON SITE RISK ASSESSMENT. WHERE A HAZARD IS IDENTIFIED WHICH REQUIRES THE USE OF A SHADOW VEHICLE, THE BELOW SCENARIOS MUST BE USED. 6. TC RETRIEVING SIGNS MUST DO SO FROM THE COLD SIDE OF THE VEHICLE. THE VEHICLE MUST BE PARKED OFF THE ROAD AT ALL TIMES. 7. DRIVER OF TM VEHICLE MUST ACT AS SPOTTER TO WARN OF ERRANT VEHICLES. 8. MUST NOT BE USED WHERE A TMA IS REQUIRED TO SHADOW THE WORKS OPERATION, REFER TO SCENARIO 3.	
SCENARIO IA:															
FLASHING CORNERS TM VEHICLE TC WITH SIGN LI DISTANCE L2 DISTANCE ADVANCED WARNING INTERMEDIATE SIGNAGE TAPER/BUFFER/WORKSITE TERMINATION SIGNS COLD SIDE LIVE SIDE DRIVER TO BE USED AS SPOTTER TO WATCH FOR ERRANT VEHICLES															
SCENARIO IB:															
FLASHING CORNERS TM VEHICLE TC WITH SIGN LI DISTANCE L2 DISTANCE ADVANCED WARNING INTERMEDIATE SIGNAGE BUFFER & WORKSITE TERMINATION SIGNS COLD SIDE LIVE SIDE DRIVER TO BE USED AS SPOTTER TO WATCH FOR ERRANT VEHICLES															
SCENARIO IB:															
L3 SIGNAGE INTERMEDIATE SIGNS INTERMEDIATE SIGNS L3 SIGNAGE TC WITH SIGN LI DISTANCE L2 DISTANCE ADVANCED WARNING INTERMEDIATE SIGNAGE BUFFER & WORKSITE TERMINATION SIGNS COLD SIDE LIVE SIDE DRIVER TO BE USED AS SPOTTER TO WATCH FOR ERRANT VEHICLES															
A		B		C		D		E		F		G		H	