

A		B		C		D		E		F		G		H		NOTES	
SCENARIO 2A:												IMPLEMENTATION PROCEDURES				DOCUMENTATION	
												SCENARIO 2A:				ON-SITE VARIATIONS MUST BE APPROVED BY THE TRAFFIC MANAGEMENT SUPERVISOR, THAN AN ON-SITE VARIATION MADE AND CHANGES RECORDED IN THE DAILY DAIRY. FOR MORE INFORMATION REFER TO SECTION 9.3 OF THE TMP.	
DRIVER TO BE USED AS SPOTTER TO WATCH FOR ERRANT VEHICLES												1. EACH SIGN IS TO BE INSTALLED AS PER TGS-IW-002 SCENARIO 2.				1. TM VEHICLE SHALL BE ANY OF THE FOLLOWING:	
												2. THIS SCENARIO IS TO BE USED ON DUAL CARRIAGEWAYS WITH A POSTED SPEED 80km/h OR GREATER AND WHERE THERE IS ENOUGH ROOM IN THE VERGE/MEDIAN TO PARK THE TM VEHICLE.				1.1. TRAFFIC MANAGEMENT UTE	
												3. VEHICLE TO ENTER AND EXIT THE ROAD WAY BETWEEN GAPS IN TRAFFIC TO ACT AS SHADOW VEHICLE FOR SIGN INSTALLATION AND TO MAINTAIN 2M FOR TC SIGN RETRIEVAL.				1.2. UTE WITH ARROW BOARD	
												4. VEHICLE TO RESET AT START OF SIGNAGE INSTALLATION FOR SIGNAGE ON THE OTHER SIDE OF THE ROAD.				1.3. CONE TRUCK	
																1.4. MR TRUCK	
																1.5. HR TRUCK	
																1.6. TRUCK MOUNTED ATTENUATOR	
																2. THIS DRAWING IS FOR IMPLEMENTATION ONLY AND MUST BE USED IN CONJUNCTION WITH AN APPROVED TRAFFIC MANAGEMENT LAYOUT TGS.	
																3. THIS DRAWING IS TO BE USED AS A GUIDELINE FOR THE TYPICAL SIGNAGE INSTALLATION AND MAY CHANGE DEPENDING SITE REQUIREMENTS.	
																4. THIS SCENARIO IS TO BE USED ON ROADS WITH A POSTED SPEED 80km/h OR GREATER AND A VERGE/SHOULDER WIDE ENOUGH WHERE THE TCS UNLOADING SIGNS CAN MAINTAIN 2M FROM LIVE TRAFFIC LANES. WHERE THIS CANNOT BE MAINTAINED REFER TO THE SCENARIO BELOW.	
																5. TC RETRIEVING SIGNS MUST DO SO FROM THE COLD SIDE OF THE VEHICLE. THE VEHICLE MUST BE PARKED OFF THE ROAD WHILE THE SINGS ARE UNLOADED.	
																6. ONCE THE SIGN IS UNLOADED FROM THE VEHICLE, TC TO POSITION 20-40M AHEAD OF VEHICLE AS IT PULLS INTO THE LANE.	
																7. TM VEHICLE TO BE USED AS SHADOW VEHICLE DURING THE SIGNAGE INSTALLATION. ARROW BOARD ON TM VEHICLE TO BE SWITCHED TO FLASHING ARROW PRIOR TO ENTERING LANE.	
																8. DRIVER OF TM VEHICLE MUST ACT AS SPOTTER TO WARN OF ERRANT VEHICLES.	
																9. MUST NOT BE USED WHERE A TMA IS REQUIRED TO SHADOW THE WORKS OPERATION, REFER TO SCENARIO 3.	
SCENARIO 2A:												SCENARIO 2B:				FOR IMPLEMENTATION ONLY	
												1. EACH SIGN IS TO BE INSTALLED AS PER TGS-IW-002 SCENARIO 2.				LEGEND	
DRIVER TO BE USED AS SPOTTER TO WATCH FOR ERRANT VEHICLES												2. THIS SCENARIO IS TO BE USED ON TWO WAY ROADS WITH A POSTED SPEED 80km/h AND GREATER AND WHERE THERE IS ENOUGH ROOM IN THE VERGE TO PARK THE TM VEHICLE.				EXISTING ROAD	
												3. VEHICLE TO ENTER AND EXIT THE ROAD WAY BETWEEN GAPS IN TRAFFIC TO ACT AS SHADOW VEHICLE FOR SIGN INSTALLATION AND TO MAINTAIN 2M FOR TC SIGN RETRIEVAL.				TC MOVEMENTS	
												4. VEHICLE TO FIND A SUITABLE PLACE TO LEGALLY TURN AROUND TO INSTALL SIGNS IN THE OPPOSING DIRECTION.				TM VEHICLE MOVEMENTS	
SCENARIO 2B:																METROPOLITAN REGIONS TRAFFIC MANAGEMENT BRANCH WATERLOO CRESCENT TELEPHONE (08) 138 138 EAST PERTH 6004	
																DATE OF DRAWING 2025 JULY	
DRIVER TO BE USED AS SPOTTER TO WATCH FOR ERRANT VEHICLES																SCALE -	
																LOCAL GOVERNMENT AUTHORITY -	
																POSTED SPEED -	
																ROAD AUTHORITY MAIN ROADS WA	
																WORKSITE SPEED -	
																CHECKED BY TYLER HARTLEY	
																SIGNATURE Tyler Hartley	
																ACCREDITATION RTM-0066	
																SIGNATURE Michael Reed	
																DESIGNED BY MICHAEL REED	
																ACCREDITATION AWTM-23-11536-02	
																GENERIC TRAFFIC GUIDANCE SCHEME IMPLEMENTATION WORK SETUPS CONTINUOUS SIGNAGE IMPLEMENTATION TGS-IW-002 SCENARIO 2	
																DRAWING NO 0922-01531-IW-008B	
																REVISION 6	
A		B		C		D		E		F		G		H			