

FLASHING ARROW BOARD
FLASHING CORNERS

VARIABLE MESSAGE BOARD
DISPLAY 1
80
AHEAD

DISPLAY 2
T ↑ ↑

ADVANCED WARNING VEHICLE

CONVOY DISTANCE SPACING
(REFER TABLE)

FLASHING ARROW BOARD
FLASHING ARROW

VARIABLE MESSAGE BOARD
DISPLAY 1
80
AHEAD

SHADOW VEHICLE

40M

WORK VEHICLE

CONVOY DISTANCE SPACING
(REFER TABLE)

FLASHING ARROW BOARD
FLASHING ARROW

VARIABLE MESSAGE BOARD
DISPLAY 1
END
80

LEAD VEHICLE

LEAD VEHICLE OPTIONAL
SUBJECT TO AWTM RISK
ASSESSMENT

SCENARIO 2:

FLASHING ARROW BOARD
FLASHING CORNERS

VARIABLE MESSAGE BOARD
DISPLAY 1
80
AHEAD

ADVANCED WARNING VEHICLE

CONVOY DISTANCE SPACING
(REFER TABLE)

SHUNT DISTANCE

FLASHING ARROW BOARD
FLASHING ARROW

VARIABLE MESSAGE BOARD
DISPLAY 2
ROAD PLANT AHEAD

WORK VEHICLE

CONVOY DISTANCE SPACING
(REFER TABLE)

FLASHING ARROW BOARD
FLASHING ARROW

VARIABLE MESSAGE BOARD
DISPLAY 1
80

LEAD VEHICLE

CONVOY DISTANCE SPACING
(REFER TABLE)

LEAD VEHICLE OPTIONAL
SUBJECT TO AWTM RISK
ASSESSMENT

A	B	C	D	E	F
---	---	---	---	---	---

WHERE WORKSITE CLEARANCES CANNOT BE ACHIEVED, ANOTHER MOBILE SCENARIO OR A STATIC SETUP MAY BE REQUIRED.

MOBILE CONVOY IS INDICATIVE ONLY AND WORKS CAN BE IN EITHER THE FAR LEFT OR FAR RIGHT LANE AND NUMBER OF LANES MAY VARY. WHERE WORKS ARE IN THE RIGHT LANE, LANE STATUS AND ARROW BOARDS TO BE CHANGED ACCORDINGLY. FOR WORKS IN THE MIDDLE LANES REFER TO TGS-TMC-MS2-006.

WHERE THERE IS INSUFFICIENT ROOM IN THE SHOULDER, VERGE OR MEDIAN FOR ADVANCED WARNING VEHICLE REFER TO TGS-TMC-MS2-007.

THIS DRAWING IS FOR LARGE PLANT ITEMS ONLY AND THERE MUST BE NO WORKERS ON FOOT. THIS SCENARIO IS TO BE USED FOR CLASS 2 MOBILE WORKS, WHERE MOBILE CONVOY TRAVELS GREATER THAN 20km/h OF TRAFFIC SPEED.

THE VEHICLE CONVOY MUST BE MOBILE AT ALL TIMES AND MUST NOT STOP IF WITHIN LIVE TRAFFIC LANES.

PRIOR TO THE IMPLEMENTATION OF ANY MOBILE CONVOYS, A RISK ASSESSMENT IS REQUIRED TO DETERMINE IF THE WORKS CAN BE COMPLETED SAFELY. REFER TO THE TMP FOR RISK CONSIDERATIONS.

WHERE THERE IS POOR SIGHT DISTANCE DUE TO CURVE OR CREST IN THE ROAD THE ADVANCED WARNING VEHICLE MUST STOP PRIOR TO THE REDUCED SIGHT DISTANCE LOCATION WHILE THE REST OF THE CONVOY TRAVEL THROUGH. WHERE THERE IS SIGNIFICANT SECTIONS OF POOR SIGHT DISTANCE AN ADDITIONAL SHADOW VEHICLE MAY BE USED.

ALL DRIVERS WITHIN MOBILE CONVOY MUST BE ALERT AND AWARE OF APPROACHING VEHICLES AT ALL TIMES.

ALL VEHICLES WITHIN MOBILE CONVOY MUST HAVE CLEAR COMMUNICATION METHODS USING TWO-WAY RADIO DEVICES.

VEHICLE LOCATIONS MUST CONSIDER THE IMPACT ON VULNERABLE ROAD USERS AND CYCLISTS.

FOR WORKS AROUND ON / OFF RAMPS, MAJOR SIDE ROADS OR SIGNALISED INTERSECTIONS A STATIC SETUP SHOULD BE CONSIDERED TO MANAGE VEHICLES PROPERLY. UPON RISK ASSESSMENT, THIS DRAWING MAY BE USED AND SHADOW VEHICLE DISTANCES REDUCED TO PREVENT VEHICLES ENTERING / EXITING THE ROAD IN BETWEEN THE CONVOY VEHICLES.

REFER TO MANUFACTURING ADVICE FOR SHUNT DISTANCES ON TRUCK MOUNTED ATTENUATORS.

WHEN A MOBILE CONVOY CONTAINS MORE THAN ONE WORK VEHICLE, EACH VEHICLE MUST BE 40M APART AS A MAXIMUM. WHERE THIS IS NOT PRACTICABLE, EACH WORK VEHICLE MUST BE TREATED AS A SEPARATE MOBILE OPERATION WITH THEIR OWN WORK CONVOY. EACH WORK VEHICLE MUST ADHERE TO THE CLEARANCES TO LIVE TRAFFIC LANE TABLE.

NUMBER OF LANES AND CONFIGURATION OF ROAD ARE INDICATIVE ONLY.

LEGEND	
	EXISTING ROAD



DATE OF DRAWING 2025 JULY	SCALE -
LOCAL GOVERNMENT AUTHORITY -	POSTED SPEED -
ROAD AUTHORITY MAIN ROADS WA	WORKSITE SPEED 80KM/H
CHECKED BY TYLER HARTLEY	SIGNATURE 
ACCREDITATION RTM-0066	
DESIGNED BY MICHAEL REED	SIGNATURE 
ACCREDITATION AWTM-23-11536-02	

GENERIC TRAFFIC GUIDANCE SCHEME CLASS 2 - MOBILE SCENARIOS SINGLE LANE CLOSURE 80km/H WORK VEHICLE GREATER THAN 3.0m		
DRAWING NO 0922-01531-MS2-005	REVISION 6	