

Criteria	Lane width (m)
Curve with radius <100 m	In addition to the curve widening of 0.5 m per lane, consider the swept path of long vehicles (for example, buses, trams)
Two-way residential street	Minimum of 5.5 (sum both ways)
Shuttle flow operation	
Shuttle flow with active control (by traffic controllers or PTCDs)	Minimum 3.0*
Shuttle flow, without active control on residential streets, includes no control or the use of GIVE WAY and ONE WAY signs (see Section 5.4.4).	Minimum 3.0* and Maximum 3.5 to ensure vehicles take turns using a single lane

* Temporary minimum lane widths are not to be greater than existing lane widths. This minimum temporary lane width does not apply to curves of radius 250 m or less, or locations where there are fixed vertical obstructions such as fences or safety barriers within 30 cm of the edge of the lane on one or both sides. Where these conditions apply, consider widths wider than those listed previously to accommodate large vehicles. The speed to be used when considering lane width requirements is the speed limit (permanent or reduced) which is applicable to that length of road.

Addition

When selecting lane widths, especially when travel paths are confined on each side by physical barriers and / or hazards (for example excavations or safety barriers) for a significant distance, it is important to consider any impact of breakdowns and congestion for emergency vehicle access and on traffic flow. This is generally only applicable for major link roads, arterial roads or highways where maintaining traffic flow and emergency vehicle access is critical.

The following considerations may impact the selection of lane widths:

- how will traffic get past a broken-down vehicle
- how will emergency vehicles get past a broken-down vehicle or through a congested road environment
- the length of the constraint may dictate the mitigations required, as short, localised constraints may not be a large issue under normal conditions
- where possible the minimum distance between physical constraints on each side of the carriageway should allow vehicles to move off to the side to allow emergency vehicles to pass