

PART 2 – DEPARTURES AND ADDITIONAL INFORMATION TO THE AGTTM**16. Traffic Management Planning**

- (1) The guidance on Traffic Management Planning is in Part 2 of the AGTTM which has been incorporated into this Code under Clause 5.
- (2) Departure from and Additional information to Table 2.1 in Part 2 of the AGTTM For ‘Road Safety Act (Traffic Management Regulations) 2009’ **substitute** ‘Road Safety (Traffic Management) Regulations 2019’.

The list of Victorian legislation also includes:

- **Road Safety Act 1986;**
- **Occupational Health and Safety Act 2004;**
- Road Safety Road Rules 2017.

- (3) **Additional information** to section 4.8.2 of Part 2 of the AGTTM

When considering the emergency arrangements, emergency contact details should also be included.

17. Static Worksites

- (1) The guidance on Static Workplaces is in Part 3 of the AGTTM which has been incorporated into this Code under Clause 5.
- (2) **Additional information** to sections 3.11, 4.11 and 5.14 of Part 3 of the AGTTM
In relation to the issues to consider for public transport, the impact on rail infrastructure also needs to be considered and the required duties met. For more detail see Clause 12.

- (3) **Additional information** to section 5.3.1 of Part 3 of the AGTTM

Safety barriers should be considered for all long term works in accordance with the hierarchy of safety control. Any decision not to use them should be fully documented. When considering using safety barriers at a worksite, the type, shape, protection, performance and test characteristics of the safety barrier (as stated by the manufacturer) should be considered, especially:

- strength of materials used to manufacture the safety barrier;
- performance test level of the safety barrier;
- maximum deflection at test level loading;
- connection details of individual units to ensure that when joined together they act appropriately;
- base or footing requirements and whether they need horizontal support or ‘anchoring’ into the existing pavement;
- anchorage terminal treatments and protection; and
- minimum length of safety barrier.

If the hazard assessment indicates that it is not possible to obtain sufficient clearance from the work area to the traffic lanes or behind a safety barrier a method of using temporary speed-limits during works may be considered.

- (4) **Additional information** to section 5.3.3 of Part 3 of the AGTTM

Where safety barriers are used on heavily trafficked roads (generally volumes higher than 20,000 vehicles per day), consideration should be given to the erection of visibility screens. These screens are designed to ‘hide’ activities from road users to avoid creating a distraction and generally comprise flexible mesh fabric or shade cloth placed over a debris protection screen.

Where it is proposed to erect a visibility screen, consideration should be given to:

- the effect of a screen on the stopping sight distance along the road (e.g. roads with small radius curves);