

- 3 closing one lane to be used for sign placement, and/or
 - 4 use of a variable message sign (VMS).
- Signs and sign support structures should be kept away from the edge of the roadway as outlined in AGTTM Part 6.
 - Sign supports on the outside of curves and other vulnerable places should be avoided or the sign support should be protected. Signs used at roadwork sites should be frangible and not require protecting with additional devices such as road safety barriers.
 - The Lane Status sign must be used where one or more lanes of a multiway roadway are closed to assist with providing advance warning. These signs must not to be used instead of signage of the closure. They should be used in conjunction with closure signage.
 - Signs must not encroach on footpaths or bicycle lanes unless the path is wide enough to accommodate them. Consider vulnerable road users with impaired vision, mobility or cognitive limitations. A delineation device (e.g. a traffic cone) should be placed at the base of signs on footpaths or bicycle lanes. If the width of the footpath/cycle path is insufficient, then an appropriate TGS must be determined to manage the path users.
 - Avoid placement that could direct road users into incorrect or dangerous situations.
 - Signs or their supports must not obstruct visibility of other devices (e.g. signals, other signs, etc.), should not obstruct the view between different road users, or create a hazard for pedestrians or cyclists. Signs on narrow medians along the roadway might have reduced visibility. Increase the height of signs or consider using a VMS to improve visibility due to obstructions (e.g. parked cars).
 - Signs must not be used where their legibility and effectiveness are compromised by contamination and/or marks and abrasions. Signs must be kept clean, especially in dusty or muddy conditions.
 - Signs that conflict with the works must be removed or covered. Consider weather conditions (e.g. wind, rain) when choosing a suitable covering. It is essential that all signs at the worksite or varied travel route accurately represent the prevailing conditions at all times. Covering, altering or replacing signs may need to be approved by a RIM. Ensure that permanent signs are not damaged when doing so. Restore these signs when works are completed.
 - Covering signs may be difficult due to height or size of the sign. When covering signs that are high, ensure this is done in a safe manner. All